wiFred

WiFi throttle for model railroads using the wiThrottle protocol

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME
0.2-WIP	2-7-2021	Converting to asciidoc	HR

Contents

List of Figures

List of Tables

Abstract

This document describes the usage and configuration of the wiFred - a very simple wireless throttle for model railroads to connect to wiThrottle servers like JMRI. It also contains schematics and BOMs for the device - for both LiPo battery versions in active development - as well as programming instructions and assembly tips, and also an overview of options for the server side of things.

The most recent version of this document can be found at https://newheiko.github.io/wiFred, https://github.com/-newHeiko/wiFred/raw/master/documentation/docu.pdf and https://github.com/newHeiko/wiFred/blob/-master/documentation/docu.adoc.

If you want to know more about the development history of the wiFred, skip ahead to section [?] - otherwise read on with section Section 1.

1 Quickstart Guide

1.1 Finish assembly (blank enclosure)

1. Use drilling jig to drill holes into housing

2. Make cutout for micro USB connector

3. Use PCB to drill holes for LEDs next to micro USB connector (D101, D102)

4. Install LEDs — long pin (positive) into square pad

   - Red LEDs at D101 and D301 with 3mm spacers
   - Green LEDs at D102, D302 and D303 with 3mm spacers
   - White LEDs at D304 and D305 — you can choose if you want them on top or bottom and how long they should stick out of housing

5. Install potentiometer and loco selection switches

6. Install direction selection switch and connect pins to PCB with short wires or cutoffs from LEDs

7. Make cut-outs in housing fit slide switches and flashlight LEDs

8. If pushbuttons are not installed: Place them on PCB, screw PCB into housing so they fit into the holes and solder them to the PCB

9. Connect battery to P101 - BATT-connector

10. Arrange battery so it fits between direction selection switch and PCB screws and glue into back housing

---

Warning
Make sure red wire is connected to + and black wire connected to GND. Reversing the connection may destroy the wiFred.

Warning
Make sure nothing pinches the battery. LiIon batteries are susceptible to mechanical damage.

1.2   Finish assembly (laser engraved enclosure)

1. Make cutout for micro USB connector

2. Install LEDs — long pin (positive) into square pad

   • Red LEDs at D101 and D301 with 3mm spacers
   • Green LEDs at D102, D302 and D303 with 3mm spacers
   • White LEDs at D304 and D305 — you can choose if you want them on top or bottom and how long they should stick out of housing

3. Install potentiometer and loco selection switches

4. Install direction selection switch and connect pins to PCB with short wires or cutoffs from LEDs

5. Drill holes in enclosure - 3mm for LEDs, 3.5mm for push buttons, 6.5mm for direction switch, 8mm for potentiometer, 1.5mm for slide switches

6. Carefully file slide switch slots to match switch handles

7. If pushbuttons are not installed: Place them on PCB, screw PCB into housing so they fit into the holes and solder them to the PCB

8. Connect battery to P101 - BATT-connector

9. Arrange battery so it fits between direction selection switch and PCB screws and glue into back housing

---

Warning

Make sure red wire is connected to + and black wire connected to GND. Reversing the connection may destroy the wiFred.

Warning

Make sure nothing pinches the battery. LiIon batteries are susceptible to mechanical damage.

1.3 First startup

1. Charge device with a micro USB charger until charging LED switches to green

2. Turn on device with charger still connected (calibrates low battery threshold)

3. Wait for red LED on top to stop flashing and stay lit

4. Use any WiFi device to search for and connect to network wiFred-configXXXX

5. Connect to http://config.local and configure device

More information can be found at https://newHeiko.github.io/wiFred.

Red LED	Green LED (Left)	Green LED (Right)	Status
Slow Blinking (0.5 Hz)	Off	Off	Trying to connect to WiFi network
Fast Blinking (2 Hz)	Off	Off	Successful WiFi connection, trying to connect to wiThrottle server and acquire locos
Off	Off	On	Regular operation, forward direction
Off	On	Off	Regular operation, reverse direction
Off	Flashing	On	Emergency stop, forward direction. Also happens when switching direction with speed potentiometer not at zero
Off	On	Flashing	Emergency stop, reverse direction. Also happens when switching direction with speed potentiometer not at zero
Off	Off	Blinking	Battery low, regular operation, forward direction
Off	Blinking	Off	Battery low, regular operation, reverse direction
Off	Flashing	Blinking	Battery low, Emergency stop, forward direction
Off	Blinking	Flashing	Battery low, Emergency stop, reverse direction
Short flashes	Off	Off	Throttle in low-power mode
Off	Off	Off	Battery empty or no battery inserted
On	Off	Off	No connection to existing WiFi network. Created internal configuration WiFi network
On	On	On	Configuration mode enabled while connected to existing WiFi network. All locos emergency stop to avoid runaways. Push SHIFT + ESTOP again to exit configuration mode
To recover from an emergency stop, turn speed potentiometer to zero to re-gain control.			

Table 1: LED patterns and their meaning on the wiFred

2 Usage

2.1 Operating locos

Figure 1: Controls and features of the wiFred throttle

Figure 1 shows the controls of the wireless throttle. They consist of the following: - Four loco selection switches (loco 1 on the left, loco 4 on the right, move towards speed potentiometer to enable)

- Speed potentiometer (Counter-clockwise endstop: Stop, clockwise endstop: Full speed)

- Direction switch — move right for forward movement, left for reverse movement

- Black function keys F0 to F8

- Yellow shift key to trigger F9-F16 and turn on flashlight function

- Red emergency stop key

- Two green direction indicator LEDs next to speed potentiometer

- Red status LED next to speed potentiometer

- Red charging indicator LED at lower end of device — lit while charging

- Green fully charged indicator LED at lower end of device — lit when fully charged as long as charger still connected

As soon as any of the loco selection switches is moved into the "enabled" position, the throttle will boot up and try to connect to a wireless network. When all four loco selection switches are "disabled", the throttle will disconnect from the wireless network after a grace period of five seconds. The device will then go into low power mode, in which the battery will last for more than a year.

If no connection to the network configured into the device can be established within 60 seconds, the throttle will create it's own wireless network named **wiFred-config** plus four hex digits taken from the MAC address of the throttle WiFi interface, for example **wiFred-config0CAC**, to enable configuration as described in [?].

Four different locos with long DCC addresses can be assigned to the four loco selection switches. Commands derived from the speed potentiometer, the direction switch and the function keys will be transmitted to all selected locos (near) simultaneously, with a certain translation table enabling some locos to go backwards when others go forwards and also limiting function keys to some of the four locos only — this is described in more detail in [?] and [?].

Pushing the red emergency stop key will cause the throttle to send an emergency stop signal to all four locos attached. After an emergency stop, turn the speed potentiometer to zero to re-enable control of the locos.

Pushing the red emergency stop key while holding down the shift key will place the device into configuration mode (as well as issueing an emergency stop to all attached locos). See [?] for more details on how to access the throttle to do the configuration.

Any change in the loco selection switches will cause the throttle to send an emergency stop command to all attached locos. This makes sure that any loco that is deselected will stop on the layout and avoids newly selected locos suddenly taking off at speed. The same is true for a change in the direction switch, to avoid high-speed reverse maneuvers. Turn the speed potentiometer to zero to re-enable control of the locos.

When the battery is low, the device will not re-activate before charging the batteries, but continue operating for approximately an hour if active. When the battery is empty, it will disconnect and enter low power mode. Expected runtime is around 20 hours of full time operations, more if the throttle is placed in low power mode when the locos are not running.

During startup and operation, the LEDs will show the patterns explained in Table 1.

2.2 Charging the wiFred

The wiFred can be charged through the Micro-USB connector at the lower end of the device. Maximum charging current is approximately 400 mA and the device does not communicate with the USB host, so technically there is no guarantee that charging from a USB cable will work, but most chargers, computer ports or power banks do not check the current before powering up.

As long as the battery is being charged, the red charging indicator LED will be lit. When the battery is fully charged, the green charged indicator LED will be lit as long as the charger is still connected. Expected charging time is around five to six hours for a full charge.

Even while charging, the device can still be operated (particularly helpful with a power bank) but since the operating current will come out of the battery, the battery will never be fully charged.

If both charging status LEDs light up when a charging cable is connected, probably the internal connection to the battery is faulty.

3 Hardware description

The wiFred hardware is centered around an ESP8266 for the WiFi connection. The ESP8266 communicates through it's serial port with an ATMega 328P microcontroller which manages the power, controls the LEDs, reads the loco selection switches, speed potentiometer, direction switch and pushbutton switches for functions and emergency stop. The communication goes through a 2x3 pin header which enables the user to connect a programming cable to the same serial port if removing the jumpers.

Optionally, two white 5 mm-LEDs protruding from the top of the PCB can be installed to serve as a flashlight. They are driven by a constant-current source directly from the battery and enabled when pushing the yellow SHIFT key.

The wiFred is powered by a single cell LiPo battery. The ATMega 328P is connected directly to the LiPo cell, going into sleep mode when no loco selection switch is active, thereby reducing the power consumption to less than 1 mA. The ESP8266 is powered by a low-drop linear voltage regulator with an output voltage of 3 V which is disabled by the ATMega 328P when the device goes into standby.

The schematic is split into several pages and can be found in figures [2](#schematicPage1){reference-type="ref" reference="schematicPage1"} to [5](#schematicPage4){reference-type="ref" reference="schematicPage4"}. It has been created with kicad and is available on the github repository at **http://github.com/newHeiko/-wiFred** along with the PCB design.

\centering ![Master schematic sheet with battery connector, charging circuit and power supply[]{label="schematicPage1"}](imag
width="\textwidth"}

\centering ![Schematic sheet including ESP8266 for WiFi connection with bootloader enabling jumper
and connection to programming cable[]{label="schematicPage2"}](images/wfred-wifi-Wifi_connection){#schematicPage2
width="\textwidth"}

\centering ![Schematic sheet including ATMega 328P along with crystal and in system programming
header[]{label="schematicPage3"}](images/wfred-controller_rev2-Controller){#schematicPage3 width="\textwidth"}

\centering ![Schematic sheet including pushbutton switches, loco selection switches, direction switch,
speed potentiometer and flashlight LEDs with controller[]{label="schematicPage4"}](images/User_interface_rev2-
User_Interface){#schematicPage4 width="\textwidth"}

4   Hints for building the wiFred

The PCB has holes in the center of the LED footprints to enable transferring their positions to a Stra-puBox housing with a sharp needle or to drill pilot holes with a 1 mm drill. For all other holes, there is a drill jig available which also allows the drilling of pilot holes for the pushbutton switches, the direction control switch and the speed potentiometer. Figure [7](#transferHoles){reference-type="ref" reference="transferHoles"} shows the process and it's results. Holes for the pushbutton switches should be drilled at 3.5 mm diameter. Holes for the LEDs should be drilled at 3 mm diameter and holes for the speed potentiometer at 8 mm, for the direction switch at 6.5 mm diameter. The cutouts for the loco selection switches are best drilled at 5 mm or 5.5 mm and extended to fit when the PCB is assembled with a sharp hobby knife and a file.

\centering ![Using the original PCB and the drilling jig to transfer the positions of the holes to the housing
— better results will be achieved when the PCBs are screwed in position[]{label="transferHoles"}](images/_DSC0124
"fig:"){#transferHoles width="0.49 \textwidth"} ![Using the original PCB and the drilling jig to transfer
the positions of the holes to the housing — better results will be achieved when the PCBs are screwed in
position[]{label="transferHoles"}](images/_DSC0128 "fig:"){#transferHoles width="0.49 \textwidth"}

The remaining assembly is a basic exercise in installing all the components to the PCB, listed in table [\[wiFredBOM\]](#wiFredBOM){reference-type="ref" reference="wiFredBOM"}. From assembling the prototypes, the suggested order of installing the components is as follows:

1. IC101, IC102, IC201 (note: Rotate PCB so Designator is right side up, then Pin 1 is on top left) and IC301

2. X201 and D201

3. USB connector CON101

4. Capacitors and Resistors in 0805 size (first those on the same side as the items before) [\[0805de-vices\]]{#0805devices label="0805devices"}

5. U401

6. Capacitors and Resistors not installed in step [\[0805devices\]](#0805devices){reference-type="ref" reference="0805devices"} — that is R403, R404, R405, C401, C402 and C403

7. Pushbutton switches SW305 to SW312 and SW314 to SW316 — taking care to put the red one at SW312 and the yellow one at SW311

8. Pin headers K401, K402 and P401 (correct alignment of K401 and K402 can be assured by adding a jumper before soldering)

9. Pin headers P101 and P201

10. Loco selection switches SW301 to SW304

11. LEDs D101, D102 and D301 to D303 with 3mm spacers to the PCB — making sure the Anode (long pin) is aligned with the square pad on all of them

12. LEDs D304 and D305 — making sure the Anode (long pin) is aligned with the square pad on both, they can be installed on top or bottom of the PCB as desired

13. Direction switch SW313 (screwed into the PCB with an 8 mm hex nut first, then attached to it's pads using the cutoffs from D301, D302 and D303) and Speed potentiometer RV301 (screwed into the PCB with a 10 mm hex nut first)

\vspace{0.5em} \centering Designator Package Designation ---------------------------- ----------------------- ----------------------------- ---------------------------- C102,C101 C_0805_HandSoldering 4u7 C105,C103, C302 C_0805_HandSoldering 1u C206,C205 C_0805_HandSoldering 22p C401,C203, C202,C201, C207 C_0805_HandSoldering 100n C402,C301 C_0805_HandSoldering 22u C403 C_0805_HandSoldering 100u CON101 USB_Micro-B_Molex-105017-0001 USB-MICRO-B D101 LED_D3.0mm LED - red D102 LED_D3.0mm LED - green D201 SOT-23_Handsoldering BAR43 D301 LED_D3.0mm STOP - red D302 LED_D3.0mm FORWARD - green D303 LED_D3.0mm REVERSE - green D303,D302, D301,D101, D102 LED Spacer 3mm D304 LED_D5.0mm_Horicontal_FLIPPED_O1.27mm LED white D305 LED_D5.0mm_Horicontal_O1.27mm LED white IC101 SOT95P270X145-5N MCP73831T-2ACI_OT IC102 SOT95P275X110-5N NCV8161BSN300T1G IC201 TQFP-32_7x7mm_Pitch0.8mm ATMEGA328P-A IC301 SOT-23-6_Handsoldering MIC2860-2PYD6 K401 Pin_Header_Straight_1x03_Pitch2.54mm UART_ESP K402 Pin_Header_Straight_1x03_Pitch2.54mm UART_AVR P1 PCB 124mm x 35mm x 1.6mm P101 Pin_Header_Angled_1x02_Pitch2.54mm BATT P201 Pin_Header_Straight_2x03_Pitch2.54mm_SMD ISP P401 Pin_Header_Straight_1x02_Pitch2.54mm ESP_BOOTLOAD R101,R102 C_0805_HandSoldering 680R R103 C_0805_HandSoldering 2k2 R301 C_0805_HandSoldering 4k7 R304,R303, R302,R204 C_0805_HandSoldering 220R R305 C_0805_HandSoldering 15k R405,R404, R403,R201, R104 C_0805_HandSoldering 10k RV301 P160KNPD 10k lin P160KNPD-4FC20B10K SW301 OS102011MS2Q LOCO1 SW302 OS102011MS2Q LOCO2 SW303 OS102011MS2Q LOCO3 SW304 OS102011MS2Q LOCO4 SW305 SW_SPST_PTS645 F0 SW306 SW_SPST_PTS645 F1 SW307 SW_SPST_PTS645 F2 SW308 SW_SPST_PTS645 F3 SW309 SW_SPST_PTS645 F4 SW310 SW_SPST_PTS645 F5 SW311 SW_SPST_PTS645 SHIFT SW312 SW_SPST_PTS645 ESTOP SW313 100SP1T1B1M1QEH DIRECTION SW314 SW_SPST_PTS645

F6 SW315 SW_SPST_PTS645 F7 SW316 SW_SPST_PTS645 F8 U401 ESP-12E_SMD ESP-12E
X201 Crystal_SMD_TXC_7M-4pin_3.2x2.5mm_HandSoldering 14.7456MHz

: List of components for the wiFred PCB[]{label="wiFredBOM"}

To form a complete BOM, also include the parts listed in table [\[wiFredBOMextra\]](#wiFredBOMextra){reference-type="ref" reference="wiFredBOMextra"} which are not soldered to the PCB but used in assembly later on.

\vspace{0.5em} \centering Designator Package Designation -------------- ---------------------------- ---------- --------------- B1 Battery Lithium battery 1700mAh H1a Housing black Strapubox 2090 or H1b Housing white Strapubox 2090 J1,J2 Jumper K1a Potentiometer Knob silver 24mm or K1b Potentiometer Knob black 24mm P1 PCB 124mm x 35mm x 1.6mm S1,S2, S3,S4 Mounting Screws 2,9mm x 6,5mm

: List of components for the wiFred excluding electronic parts to solder to PCB[]{label="wiFredBOMextra"}

After assembling the PCB with all the components, the holes and cutouts in the enclosure most likely will have to be reworked / extended to actually fit the PCB, then the PCB can be screwed into the enclosure with four screws. Afterwards the battery should be connected to P101 making sure the orientation is correct as shown in figure [8](#battConnection){reference-type="ref" reference="battConnection"} and printed on the PCB, then the battery should be glued to the bottom of the enclosure with double-sided tape so it does not collide with any parts on the PCB, particularly P101 and SW313. Finally, both the ATMega 328P and the ESP8266 will need to be programmed as described in the next section.

\centering ![Connection of battery to P101 — black wire is GND, red wire is positive[]{label="battConnection"}](images/_DSC(width="0.8 \textwidth"}

5 Programming instructions

The ATMega 328P is programmed using the regular AVR ISP connection on P201. Pin 1 — GND — is towards the PCB edge, as shown in figure [9](#progAVR){reference-type="ref" reference="progAVR"}. An ISP dongle with either automatic voltage selection or 3.3 V supply voltage should be used to avoid placing too high voltage on the ESP8266, which can only support 3.3 V power. The firmware for the ATMega 328P can be found in the **software/avr-firmware**-subdirectory of the github repository with both a precompiled hexfile and all source code including a Makefile to recompile as needed. After writing the firmware file and the eeprom file, also the fuse bits need to be set properly as detailed in the **main.c**-file.

\centering ![Programming connection for ATMega 328P — Pin 1 on purple cable[]{label="progAVR"}](images/_DSC0146){#pr width="0.8 \textwidth"}

The ESP8266 is programmed using the Arduino IDE connected via a serial or USB-to-serial port to the K401 header as shown in figure [10](#progESP){reference-type="ref" reference="progESP"}. The serial port needs to be at 3.3 V-levels like from an FTDI232-device run at 3.3 V. To program the ESP8266, first

the ATMega 328P has to be programmed, a battery has to be connected and reasonably charged and one of the loco selection switches needs to be moved to the "enabled" position

\centering ![Programming connection for ESP8266 — GND on orange wire, then TXD of programming cable (RXD of ESP8266), then RXD of programming cable (TXD of ESP8266) — also note the jumper on P401[]{label="progESP"}](images/_DSC0138){#progESP width="0.8 \textwidth"}

All files in the **software/esp-firmware**-subdirectory of the github repository need to be placed in a folder, then the main sketch **arduino_main_sketch.ino.ino** needs to be opened with the Arduino IDE. Settings for the Arduino IDE can be found inside the main file, programming the device should work using the **Upload**-button in the **Sketch**-menu.

To put the ESP8266 into programming mode, a jumper needs to be placed across the P401 header before powering up the ESP8266 by enabling one of the loco selection switches to start the device in programming mode. The red STOP LED should start flashing and the bootloader should show some results on the serial port and during download the LED on the ESP8266 module should flash as well.

After programming, two jumpers need to be placed between the K401 and K402 pin headers to re-enable communication between the ESP8266 and the ATMega 328P as shown in figure [11](#serialJumpers){reference-type="ref" reference="serialJumpers"}.

\centering ![Communication jumpers for connecting the ESP8266 and the ATMega 328P[]{label="serialJumpers"}](images/_DS width="0.8 \textwidth"}

\clearpage wiFred Wireless throttle configuration {#config}

Before using the device, it must be configured. At the very least, the General Configuration page [13](#throttleConfMainPage){reference-type="ref" reference="throttleConfMainPage"} has to be submitted once to be saved to non-volatile memory. If no valid configuration is detected at startup, the device will start with a default configuration with no locos enabled and no WiFi settings, so it won't be able to connect to any WiFi network.

After entering any kind of text (names, numbers...) into text fields, the corresponding "Save" button has to be pressed to submit the changes to the wiFred.

Entering configuration mode

```
There are two ways to enter configuration mode:

1.  Power up the throttle/select a loco when the configured WiFi network
    is not in range (or when there is no valid configuration -- the
    first startup of a new throttle will fall into this category)

2.  Press SHIFT and ESTOP together when the throttle is connected

In the first case, the throttle will create a wireless network named
*wiFred-config* plus four hex digits taken from the MAC address of the
throttle WiFi interface, for example *wiFred-config0CAC* and announce
its presence under the name *config.local* as well as creating a captive
portal. Any WiFi device with a web browser can connect to that network
and open a web browser to point to *http://192.168.4.1* or
```

http://config.local. This has been tested with Mozilla Firefox and
Opera on Linux with Avahi (a Zeroconf implementation) and Safari on iOS
13.

In the second case, the throttle will only announce its presence under
the name *config.local* using the Bonjour/Zeroconf-protocol. Any device
on the same WiFi network with Bonjour/Zeroconf can use a web browser to
access the configuration at *http://config.local*. See
section~[3.6](#configurationComputer){reference-type="ref"
reference="configurationComputer"} for an explanation what is required
to have your device read Bonjour/Zeroconf announcements. This has been
tested with Mozilla Firefox and Opera on Linux with Avahi (a Zeroconf
implementation).

If the IP address or the name of the throttle during normal operation is
known, the configuration pages can also be accessed by pointing a web
browser to it at any time while it is connected. Note that this is
mostly untested and therefore not recommended while the throttle is
running locos.

\centering
![Screenshot of wiThrottle screen showing one throttle
connected[]{label="withrottleScreenshot"}](images/withrottle_Screenshot){# ↩
    withrottleScreenshot
width="0.8 \textwidth"}

Throttle configuration

Figure~[13](#throttleConfMainPage){reference-type="ref"
reference="throttleConfMainPage"} shows the first page you will see when
you point a web browser at your wiFred throttle. It is divided into
multiple sections explained in the following chapters.

\centering
![Screenshot of wiFred main configuration
page[]{label="throttleConfMainPage"}](images/wiFred_configuration_page){# ↩
    throttleConfMainPage
width="0.8 \textwidth"}

General configuration {#throttle_GeneralConf}

In the "General configuration" section there is only one configuration
option: The throttle name. This is a free-form identification string of
the throttle. It shows up in the wiThrottle window of JMRI as shown in
figure~[12](#withrottleScreenshot){reference-type="ref"
reference="withrottleScreenshot"} and can be used to identify the

throttle during configuration. The wiFred also announces its presence on
the WiFi network through Bonjour/Zeroconf using a sanitized version of
the name, i.e. a throttle called "Heiko Prototype 2-2" will announce its
presence as *heikoprototype22.local* when not in configuration mode.

WiFi configuration

The "WiFi configuration" section shows a list of configured WiFi
networks. The wiFred will connect to any network in this list, more or
less randomly choosing one if multiple configured networks are in range.

Existing entries can be removed by clicking on the "Remove SSID" button
in the line of the network that shall be removed.

New entries can be added either by manually entering the SSID and
PSK[^1] if required and clicking the "Manually add network" button or by
clicking on the "Scan for networks" link which takes the user to the
page shown in figure~[14](#throttleConfWiFiPage){reference-type="ref"
reference="throttleConfWiFiPage"}.

\centering
![Screenshot of wiFred "Scan for
WiFi"-page[]{label="throttleConfWiFiPage"}](images/wiFred_wifi-scan_page) ↩
    {#throttleConfWiFiPage
width="0.8 \textwidth"}

This page will take a few seconds to load, since the scan for networks
has to be completed first. It shows all the networks found during the
scan. Networks can be added to the list by clicking the "Add network"
button, after entering the PSK[^2] in the field next to it.

Note that the wiFred does not support WPS and it won't accept multiple
networks with the same SSID but different PSKs. More details regarding
the network requirements can be found in
section~[3](#serverSetup){reference-type="ref" reference="serverSetup"}.

The new WiFi configuration will not be activated until the wiFred is
restarted, either through a power-cycle or by clicking on the "Restart
wiFred to enable new WiFi-settings" link on the configuration page.

Loco server configuration

Following the WiFi configuration, the section "Loco server
configuration" allows configuring the wiThrottle server to which the
wiFred shall connect. The default setting -- automatically detect server
-- works well if there is only one wiThrottle server on the network. It
will connect to any server announcing its presence on port 12090 through

```
Zeroconf/Bonjour, the result of the Zeroconf/Bonjour-search will be
shown here when the wiFred has automatically discovered a server.

### Loco configuration {#throttle_LocoConf}

Following the "Loco server configuration", there are four identical
sections assigned to the four different locomotives which can be
controlled with this throttle. Each section consists of the following
settings:

DCC address: Can be a short address between 1 and 127 (also used for
consists) or a long address between 0 and 10239. Note: Short addresses
between 1 and 127 are not the same as long addresses between 1 and 127.
If this is set to -1, the corresponding loco is disabled.

Long address?: Checkbox to change the behaviour of the DCC address input
field described above.

Reverse?: If checked, the corresponding loco will invert it's travel
direction. Mainly intended for back-to-back consists without decoder
reconfiguration.

Function mapping: Link to the function mapping subpage for the
corresponding loco, as described in
section~[2.2.5](#throttle_FunctionConf){reference-type="ref"
reference="throttle_FunctionConf"}. Clicking this link will lose all
information entered on the current page and take the web browser to a
different subpage.

**Reminder: Changes are saved using the "Save loco config" button which
may look different in different web browsers (firefox shown).**

### DCC function configuration {#throttle_FunctionConf}

By default, if a function key is pressed, the throttle will send the
appropriate commands to every loco under control. Under certain
circumstances, this may not be desired -- the obvious example being a
loco in the middle of a multi-unit consist, which should not have lights
or ditchlights. So this page -- shown in
figure~[15](#throttleConfigFunctionPage){reference-type="ref"
reference="throttleConfigFunctionPage"} -- offers the option to chose
between three different settings for every function on each of the four
locomotives (one page per locomotive):

\centering
![Screenshot of wiFred function handling config
page[]{label="throttleConfigFunctionPage"}](images/wiFred_function_page){# ←
```

```
    throttleConfigFunctionPage
width="0.8 \textwidth"}
```

Always Off: When the loco is enabled by moving the selection switch to
the "selected" position, the current status of the function is queried.
If the function is on, a function key press will be simulated to turn it
off. No other function key events will be sent to this loco for this
function.

Throttle controlled: When the first loco is enabled by moving the
selection switch to the "selected" position, the current status of the
function is queried and saved. When selecting the next loco, the status
is queried. If it does not match the first loco, the function status is
changed by simulating a function key press. Afterwards, key presses are
handed through to the loco.

Always On: Similar to the "Always Off" setting, but the throttle will
attempt to enable the function when the locomotive is selected and
ignore any further function key presses. This will probably not work
with so-called momentary functions that are only active as long as the
function key is pressed.

**Reminder: Changes are saved using the "Save function configuration"
button which may look different in different web browsers (firefox
shown).**

wiFred status

The "wiFred status" section shows the current battery voltage, as
measured by the wiFred. This is updated on reloading the page, not
continuosly.

wiFred system

The "wiFred system" section consists of two links:

-   Reset wiFred to factory defaults -- which leads to a confirmation
    page shown in~[16](#throttleConfResetPage){reference-type="ref"
    reference="throttleConfResetPage"} to reset all configuration data
    to factory defaults as on a new wiFred.

-   Update wiFred firmware -- which leads to a firmware update page
    shown in~[17](#throttleConfUpdatePage){reference-type="ref"
    reference="throttleConfUpdatePage"} to update the wiFred firmware of
    the ESP8266. Find the .bin-file from the arduino build folder, click
    on "Choose file", navigate to the .bin-file and finally initiate the
    update with a click on "Update" -- which will take a while.

```
\centering
![Screenshot of wiFred configuration reset
page[]{label="throttleConfResetPage"}](images/wiFred_reset_page){# ←↩
    throttleConfResetPage
width="0.8 \textwidth"}

\centering
![Screenshot of wiFred firmware update
page[]{label="throttleConfUpdatePage"}](images/wiFred_update_page){# ←↩
    throttleConfUpdatePage
width="0.8 \textwidth"}

\clearpage
Options for server setup {#serverSetup}
========================

Figure~[18](#runningTrains){reference-type="ref"
reference="runningTrains"} shows the connections between the devices
required to run trains using the wiFred.

\centering
![Overview of devices required to run trains with the
wiFred[]{label="runningTrains"}](images/runningTrains){#runningTrains
width="0.99 \textwidth"}

The symbols in figure~[18](#runningTrains){reference-type="ref"
reference="runningTrains"} symbolize the following parts:

1.  An IEEE 802.11b/g/n 2.4 GHz WiFi access point described in detail in
    section~[3.3](#serverWiFi){reference-type="ref"
    reference="serverWiFi"} [\[indexWiFi\]]{#indexWiFi
    label="indexWiFi"}

2.  A PC or laptop computer with Windows, Linux or MacOS to run the JMRI
    server described in detail in
    section~[3.4](#serverJMRI){reference-type="ref"
    reference="serverJMRI"} [\[indexJMRIserver\]]{#indexJMRIserver
    label="indexJMRIserver"}

3.  A way to connect the JMRI server to the model railroading layout
    described in detail in
    section~[3.5](#serverLayoutConn){reference-type="ref"
    reference="serverLayoutConn"} [\[indexLocoBuffer\]]{#indexLocoBuffer
    label="indexLocoBuffer"}

4.  A device with a web browser connected to the same network as the
```

```
    wiFred to configure it -- can be the same physical device
    as~[\[indexJMRIserver\]](#indexJMRIserver){reference-type="ref"
    reference="indexJMRIserver"} if requirements in
    section~[3.6](#configurationComputer){reference-type="ref"
    reference="configurationComputer"} are met
    [\[indexConfigurationComputer\]]{#indexConfigurationComputer
    label="indexConfigurationComputer"}
```

Multiple options for every step or combining these steps are described
in the following sections.

Basically, if a layout is set up to run trains with a smartphone running
wiThrottle or EngineDriver, a wiFred should work with no changes to the
layout configuration.

If a layout is set up in a way that trains can be run from a JMRI screen
throttle on a computer, only a WiFi connection to the JMRI computer
needs to be added.

Out-of-the-box server-side options

A pretty much out-of-the-box solution is provided by Steve Todd
at~[@raspiImage] which auto-detects multiple options to interface to a
DCC layout and has been tested in the JMRI 4.16 version to work with the
wiFred, connecting to a Z21 black through both an RRCircuits
LocoBuffer~USB and a Digitrax~PR3 via Loconet.

Although untested so far, adding a Digitrax~LNWI~[@digitrax] to a
Digitrax system or an MRC~Prodigy~WiFi~[@mrc] to an MRC system should
allow the wiFred to run locos out-of-the-box as well.

Step by step instructions for a Windows computer

Tested on Windows 7 64Bit

Requirements: WiFi 2.4GHz

Installation:

1. Install HostedNetworkStarter from
    https://www.nirsoft.net/utils/wifi_hotspot_starter.html

2. Install DHCP server from https://www.dhcpserver.de/cms/download/ --
    download and extract all the files from the zip file to somewhere on
    your harddrive, for example C:\\DHCPServer

3. Install a JDK, version 8 and 11 have been tested. For example,
    https://adoptopenjdk.net/releases.html Version OpenJDK 11 (LTS), JVM
    HotSpot. Choose the 64bit version for most modern hardware, 32bit
    only if you are running a 32bit operating system. Easiest option:
    MSI file, download and install.

4. Install JMRI from https://www.jmri.org -- versions tested to run
    with the wiFred include 4.14, 4.16, 4.18 and 4.20. Most recent
    production version recommended.

Configuration:

1. Start HostedNetworkStarter from the start menu, enter a Network Name
    and Network Key, then hit the Start button. Note the "Hosted Network
    Connection Name" for the next step

2. Start the DHCP server wizard from C:\\DHCPServer\\dhcpwiz.exe,
    select the network with the name that's the same as the "Hosted
    Network Connection Name" from the step before, hit "Next" a few
    times (deselecting all additional supported protocols), Write INI
    file, Start Service and Configure Firewall Exceptions

3. Start JMRI using the DecoderPro icon on the desktop, setup your
    layout connection, test if you can run a loco with a JMRI throttle

4. Within JMRI, start the WiThrottle Server from the Actions menu. If a
    firewall popup comes up, allow all.

5. Within JMRI, edit the Preferences from the Edit menu, choose
    WiThrottle on the left pane, click the "Start automatically with
    application" checkbox. All the Allowed Controls can be disabled.

Running:

1. Start HostedNetworkStarter from the start menu, enter a Network Name
    and Network Key, then hit the Start button.

2. Start JMRI using the DecoderPro icon on the desktop

WiFi access point requirements {#serverWiFi}

IEEE802.11bg 2.4GHz DHCP server comm between clients

Linux: hostapd (tested: netbook, Raspberry Pi 3 in a PiTop) Windows:
link to \... Hardware.

```
JMRI server requirements {#serverJMRI}
------------------------

Any PC.

Layout connection options {#serverLayoutConn}
------------------------

Loconet: LocoBufferUSB Digitrax PR3 / PR4

Tested: Intellibox, Z21 black, DCS 51 Zephyr xtra

Should work: Anything JMRI can control trains on, even SPROG as command
station plus boosters\...

Computer or smartphone to configure wiFred {#configurationComputer}
------------------------------------------

Webbrowser, Zeroconf. Avahi. Bonjour (iTunes?). MacOS out of the box?
iOS? Android?

For initial configuration of the wiFred, most of the devices mentioned
above can be omitted. As shown in
figure~[19](#confWifred){reference-type="ref" reference="confWifred"},
only a WiFi capable device with a web browser is required.

\centering
![For initial configuration, the requirements are very
small[]{label="confWifred"}](images/configuringWifred){#confWifred
width="0.5 \textwidth"}

\clearpage
wiFred Wireless throttle prototype {#oldThrottle}
=================================

Quickstart Guide
----------------

Follow these steps for a new throttle (see later chapters for more
explanation or if you run into trouble)

-3. Use PCB to determine positions of holes and cutouts in housing

-2. Make said cutouts and glue little pieces of 3mm thick plastic or
    wood underneath PCB screw holes
```

```
-1. Solder components to PCB

0.  Flash firmware to ESP8266 and to ATMega~328P

1.  Test fit PCB into housing, removing plastic parts of housing as
    required

2.  Fit PCB into housing, insert three screws to fix PCB to housing

3.  Make sure communication jumpers are set correctly, close housing and
    fix back cover with two screws

4.  Add throttle knob

5.  Insert batteries

6.  Using any WiFi client (laptop, smartphone, tablet\...), find and
    connect to network *wiFred-configXXXX*

7.  Using any web browser, navigate to *http://192.168.4.1*

8.  Enter your WiFi configuration (and a throttle ID if you like --
    highly recommended to easier tell them apart) **and hit the
    *Submit*-Button**

9.  Click on 'Loco configuration subpage'

10. Enter your wiThrottle server settings

11. For every loco you want to control with this throttle, enter the
    appropriate details below

12. Finish by **hitting the *Submit*-Button**

13. Configure function settings for each loco on the respective sub
    pages if required

14. Restart the throttle by navigating back to the main configuration
    page and clicking on 'Restart system to enable new WiFi settings'

Your throttle should now be ready to use and connect to your wiThrottle
server on startup. Refer to the chapters below if it does not or contact
the author of this document.

Usage
-----
```

```
\centering
![Controls and features of the wiFred-throttle -- prototype
version[]{label="oldThrottleControls"}](images/throttle_Front "fig:"){# ↩
    oldThrottleControls
height="100mm"} ![Controls and features of the wiFred-throttle --
prototype
version[]{label="oldThrottleControls"}](images/throttle_Back "fig:"){# ↩
    oldThrottleControls
height="100mm"} ![Controls and features of the wiFred-throttle --
prototype
version[]{label="oldThrottleControls"}](images/throttle_Back_openBattery " ↩
    fig:"){#oldThrottleControls
height="100mm"}
```

Figure~[22](#oldThrottleControls){reference-type="ref"
reference="oldThrottleControls"} shows the controls of the wireless
throttle. They consist of the following:

-   Four loco selection switches (loco 1 on the left, loco 4 on the
    right, move towards speed potentiometer to enable)

-   Speed potentiometer (Counter-clockwise endstop: Stop, clockwise
    endstop: Full speed)

-   Direction switch -- move right for forward movement, left for
    reverse movement

-   Black function keys F0 to F4

-   Two yellow shift keys to trigger F5-F8 (SHIFT1, lower key), F9-F12
    (SHIFT2, upper key) and F13-F16 (both shift keys)

-   Red emergency stop key

-   Two green direction indicator LEDs

-   One red status LED

-   Battery compartment (on the rear) for two AA cells, 1.2 V to 1.5 V
    nominal voltage

As soon as a pair of batteries is inserted into the battery compartment
as the symbols inside the battery compartment show, the throttle will
boot up and try to connect to a wireless network. The throttle will not
be damaged if batteries are inserted wrongly, but it will not work
either. Use NiMH- or primary AA cells with 1.2 V to 1.5 V nominal
voltage, low self discharge NiMH cells like Eneloop~or similar are

recommended. Do not insert 3 V or 3.6 V AA size lithium batteries as
this may damage the throttle.

If no connection to the network configured into the device can be
established within 60 seconds, the throttle will create it's own
wireless network named *wiFred-config* plus four hex digits taken from
the MAC address of the throttle WiFi interface, for example
wiFred-config0CAC, to enable configuration as described in
section~[2](#config){reference-type="ref" reference="config"}.

Four different locos with long DCC addresses can be assigned to the four
loco selection switches. Commands derived from the speed potentiometer,
the direction switch and the function keys will be transmitted to all
selected locos (near) simultaneously, with a certain translation table
enabling some locos to go backwards when others go forwards and also
limiting function keys to some of the four locos only -- this is
described in more detail in
sections~[2.2.4](#throttle_LocoConf){reference-type="ref"
reference="throttle_LocoConf"}
and~[2.2.5](#throttle_FunctionConf){reference-type="ref"
reference="throttle_FunctionConf"}.

Pushing the red emergency stop key will cause the throttle to send an
emergency stop signal to all four locos attached. After an emergency
stop, turn the speed potentiometer to zero to re-enable control of the
locos.

Pushing the red emergency stop key while holding down either of the
shift keys will place the device into configuration mode (as well as
issueing an emergency stop to all attached locos). See
section~[2](#config){reference-type="ref" reference="config"} for more
details on how to access the throttle to do the configuration.

Any change in the loco selection switches will cause the throttle to
send an emergency stop command to all attached locos. This makes sure
that any loco that is deselected will stop on the layout and avoids
newly selected locos suddenly taking off at speed. The same is true for
a change in the direction switch, to avoid high-speed reverse maneuvers.
Turn the speed potentiometer to zero to re-enable control of the locos.

When all four loco selection switches are set to the disabled state, the
throttle will send an emergency stop command to all four locos attached
and -- after a wait time of 30 seconds -- it will disconnect from the
network and go into low power mode. To reconnect, re-enable any loco
selection switch.

The same happens when the batteries are empty, but the throttle will not

reactivate before changing the batteries. Expected runtime with a pair
of 2500 mAh-NiMH-batteries is around 8-10 hours of full time operations,
more if the throttle is placed in low power mode when the locos are not
running.

During startup and operation, the LEDs will show the patterns explained
in table~[\[ledTable\]](#ledTable){reference-type="ref"
reference="ledTable"}.

Hardware description

The wiFred hardware is centered around an ESP8266 for the WiFi
connection. The ESP8266 also reads the loco selection switches and the
battery voltage and communicates through it's serial port with an
ATMega~328P microcontroller which controls the LEDs, reads the speed
potentiometer, direction switch and pushbutton switches for functions
and emergency stop. The communication goes through a 2x3 pin header
which enables the user to connect a programming cable to the same serial
port if removing the jumpers.

The wiFred is powered by two AA size battery cells connected to a
step-up converter creating 3.3V for the entire device.

The schematic is split into several pages and can be found in
figures~[23](#oldSchematicPage1){reference-type="ref"
reference="oldSchematicPage1"}
to~[26](#oldSchematicPage4){reference-type="ref"
reference="oldSchematicPage4"}. It has been created with kicad and is
available on the github repository at
http://github.com/newHeiko/wiFred along with the PCB design.

\centering
![Master schematic sheet with batteries and power
supply[]{label="oldSchematicPage1"}](images/old_wfred_rev2){# ↩
    oldSchematicPage1
width="\textwidth"}

\centering
![Schematic sheet including ESP8266 for WiFi connection with bootloader
enabling jumper and connection to programming
cable[]{label="oldSchematicPage2"}](images/old_wfred-wifi-Wifi_connection) ↩
    {#oldSchematicPage2
width="\textwidth"}

\centering
![Schematic sheet including ATMega 328P along with crystal and in system

```
programming
header[]{label="oldSchematicPage3"}](images/old_wfred-controller_rev2- ←
    Controller){#oldSchematicPage3
width="\textwidth"}

\centering
![Schematic sheet including pushbutton switches, loco selection
switches, direction switch and speed
potentiometer[]{label="oldSchematicPage4"}](images/old_User_interface_rev2 ←
    -User_Interface){#oldSchematicPage4
width="\textwidth"}

Hints for building the wiFred
-----------------------------

The PCB has holes in the center of the pushbutton switch footprints and
LED footprints to enable transferring their positions to a StrapuBox
housing with a sharp needle or similar, and the position of the loco
selection switches can also be transferred to the housing by marking it
through the non-copper holes at their ends.
Figure~[28](#oldTransferHoles){reference-type="ref"
reference="oldTransferHoles"} shows the process and it's results. Holes
for the pushbutton switches should be drilled at 3.5mm diameter and
countersunk from the inside. Holes for the LEDs should be drilled at
3mm diameter and holes for the speed potentiometer and direction switch
at 6.5mm or 7mm diameter and countersunk. The cutouts for the loco
selection switches are best created when the PCB is assembled and
carefully cut out with a sharp hobby knife and a file until they fit.

\centering
![Using the PCB to transfer the positions of the holes to the
housing[]{label="oldTransferHoles"}](images/_DSC8652 "fig:"){# ←
    oldTransferHoles
width="0.49 \textwidth"} ![Using the PCB to transfer the positions of
the holes to the
housing[]{label="oldTransferHoles"}](images/_DSC8653 "fig:"){# ←
    oldTransferHoles
width="0.49 \textwidth"}

The remaining assembly is a basic exercise in installing all the
components to the PCB, listed in
table~[\[oldWiFredBOM\]](#oldWiFredBOM){reference-type="ref"
reference="oldWiFredBOM"}. From assembling the prototypes, the suggested
order of installing the components is as follows:

\vspace{0.5em}
\centering
```

```
Designator                         Package  ↩
                                        Designation
-------------------------------  ↩
    ----------------------------------------------------  ↩
    --------------------------
B101                               KEYSTONE1013  ↩
                                        BATT\_HOLDER
C206,C205                          C\_0805\_HandSoldering  ↩
                                    22p
C301,C105, C104,C102, C101         C\_0805\_HandSoldering  ↩
                                    22u/25V
C401,C204, C203,C202, C201,C103    C\_0805\_HandSoldering  ↩
                                    100n
C402                               C\_0805\_HandSoldering  ↩
                                    22u
D301                               LED\_D3.0mm  ↩
                                        STOP - red
D302                               LED\_D3.0mm  ↩
                                        FORWARD - green
D303                               LED\_D3.0mm  ↩
                                        REVERSE - green
IC201                              TQFP-32\_7x7mm\_Pitch0.8mm  ↩
                                  ATMEGA328P-A
K401                               Pin\_Header\_Straight\_1x03\_Pitch2.54  ↩
    mm               UART\_ESP
K402                               Pin\_Header\_Straight\_1x03\_Pitch2.54  ↩
    mm               UART\_AVR
L101                               L\_2424\_HandSoldering  ↩
                                    22u
P201                               Pin\_Header\_Straight\_2x03\_Pitch2.54  ↩
    mm\_SMD          ISP
P401                               Pin\_Header\_Straight\_1x02\_Pitch2.54  ↩
    mm               ESP\_BOOTLOAD
R301                               C\_0805\_HandSoldering  ↩
                                    4k7
R304,R303, R302                    C\_0805\_HandSoldering  ↩
                                    470R
R401                               C\_0805\_HandSoldering  ↩
                                    100k
R402                               C\_0805\_HandSoldering  ↩
                                    47k
R405,R404, R403,R201               C\_0805\_HandSoldering  ↩
                                    10k
RV301                              P160KNPD  ↩
                                        10k lin P160KNPD-4  ↩
    FC20B10K
SW301                              OS102011MS2Q  ↩
```

```
                                                    LOCO1
  SW302                                OS102011MS2Q  ←
                                                    LOCO2
  SW303                                OS102011MS2Q  ←
                                                    LOCO3
  SW304                                OS102011MS2Q  ←
                                                    LOCO4
  SW305                                KSC621G  ←
                                                       F0
  SW306                                KSC621G  ←
                                                       F1
  SW307                                KSC621G  ←
                                                       F2
  SW308                                KSC621G  ←
                                                       F3
  SW309                                KSC621G  ←
                                                       F4
  SW310                                KSC621G  ←
                                                    SHIFT2
  SW311                                KSC621G  ←
                                                    SHIFT
  SW312                                KSC621G  ←
                                                    ESTOP
  SW313                                100SP1T1B1M1QEH  ←
                                         DIRECTION
  U101                                 TSSOP-8\_4.4x3mm\_Pitch0.65mm  ←
                             L6920D
  U401                                 ESP-12E\_SMD  ←
                                                    ESP-12E
  X201                                 Crystal\_SMD\_TXC\_7M-4pin\_3.2x2.5mm\ ←
     _HandSoldering    14.7456MHz
                                       Housing StrapuBox 6090
                                       Two Jumpers, 2.54mm
                                       Potentiometer Knob, 21mm
                                       Three fastening screws, 2.9
                                          mm dia x 6.5mm
```

  : List of components for the wiFred[]{label="oldWiFredBOM"}

1. IC201 and U101 (note: Rotate PCB so Designator is right side up,
    then Pin 1 is on top left)

2. X201

3. Capacitors and Resistors in 0805 size (only those on the same side
    as the items before) [\[old0805devices\]]{#old0805devices
    label="old0805devices"}

4. U401

5. LEDs D301 to D303

6. Pushbutton switches SW305 to SW312

7. Loco selection switches SW301 to SW304

8. L101

9. Capacitors and Resistors not installed in
    step~[\[old0805devices\]](#old0805devices){reference-type="ref"
    reference="old0805devices"}

10. Pin header P201

11. Pin headers K401, K402 and P401 (correct alignment of K401 and K402
    can be assured by adding a jumper before soldering)

12. Direction switch SW313 (screwed into the PCB with an 8 mm hex nut
    first, then attached to it's pads using the cutoffs from D301, D302
    and D303) and Speed potentiometer RV301 (screwed into the PCB with a
    10 mm hex nut first and slightly shortening the pins before
    soldering)

13. Battery holder B101

After assembling the PCB with all the components and drilling and
cutting the holes and cutouts into the housing, there are few steps
left. First, a few protrusions inside the housing need to be removed so
the PCB fits properly.
Figure~[30](#breakProtrusions){reference-type="ref"
reference="breakProtrusions"} shows how they can be removed easily,
remains may be cut off with a hobby knife. Second, new PCB mounting pads
need to be installed as shown in
figure~[31](#mountingPads){reference-type="ref"
reference="mountingPads"}. For the prototype, Forex PVC foam was used,
cut with a pair of scissors and glued to the housing with superglue,
making sure not to be in the way of any components on the PCB, but any
kind of easily worked upon material with a thickness of 3 mm can be
used, as long as it will take self-driving screws (prototype uses 2.9 mm
by 6.5 mm DIN~7981 screws). Third, the two shift keys need yellow paint
on the top and the emergency stop key needs red paint -- either any kind
of paint or a paint marker like Edding~751 will do. Finally, both the
ESP8266 and the ATMega~328P will need to be programmed as described in
the next section.

```
\centering
![Removing protrusions inside the housing so the PCB
fits[]{label="breakProtrusions"}](images/_DSC8654 "fig:"){# ←
    breakProtrusions
width="0.49 \textwidth"} ![Removing protrusions inside the housing so
the PCB
fits[]{label="breakProtrusions"}](images/_DSC8655 "fig:"){# ←
    breakProtrusions
width="0.49 \textwidth"}

\centering
![New PCB mounting pads made from 3mm thick Forex
PVC[]{label="mountingPads"}](images/_DSC8658){#mountingPads
width="0.8 \textwidth"}

Programming instructions
------------------------

The ESP8266 is programmed using the Arduino IDE connected via a serial
or USB-to-serial port to the K401 header as shown in
figure~[32](#oldProgESP){reference-type="ref" reference="oldProgESP"}.
The serial port needs to be at 3.3V-levels like from an FTDI232-device
run at 3.3V.

\centering
![Programming connection for ESP8266 -- GND on orange wire, then TXD of
programming cable (RXD of ESP8266), then RXD of programming cable (TXD
of ESP8266)[]{label="oldProgESP"}](images/_DSC8637){#oldProgESP
width="0.8 \textwidth"}

\centering
![Programming connection for ATMega~328P -- Pin 1 on purple
cable[]{label="oldProgAVR"}](images/_DSC8638){#oldProgAVR
width="0.8 \textwidth"}

All files in the *software/esp-firmware*-subdirectory of the github
repository need to be placed in a folder, then the main sketch
*arduino\_main\_sketch.ino.ino* needs to be opened with the Arduino IDE.
Settings for the Arduino IDE can be found inside the main file,
programming the device should work using the *Upload*-button in the
*Sketch*-menu.

To put the ESP8266 into programming mode, a jumper needs to be placed
across the P401 header before inserting batteries to start the device in
programming mode. The bootloader should show some results on the serial
port and during download the LED on the ESP8266 module should flash.
```

The ATMega~328P is programmed using the regular AVR ISP connection on
P201. Pin 1 -- GND -- is towards the PCB edge, as shown in
figure~[33](#oldProgAVR){reference-type="ref" reference="oldProgAVR"}.
An ISP dongle with either automatic voltage selection or 3.3V supply
voltage should be used to avoid placing too high voltage on the ESP8266,
which can only support 3.3V power. The firmware for the ATMega~328P can
be found in the *software/avr-firmware*-subdirectory of the github
repository with both a precompiled hexfile and all source code including
a Makefile to recompile as needed. After writing the firmware file, also
the fuse bits need to be set properly as detailed in the *main.c*-file.

After programming, two jumpers need to be placed between the K401 and
K402 pin headers to re-enable communication between the ESP8266 and the
ATMega~328P.

\clearpage
Background for wiFred development {#background}
================================

As of the writing of this document, JMRI~[@jmri] has a long track record
of offering a server for using smartphones as wireless model railroad
throttles, along with apps like withrottle~[@withrottleApp][^3] and
EngineDriver~[@EngineDriver]. This server will enable WiFi throttles to
control locos any model railroading layout to which JMRI can build a
connection~[@jmrihardwaresupport]. In addition, Digitrax~[@digitrax] and
MRC~[@mrc] offer specific hardware solutions to enable the connection of
the abovementioned smartphone apps to their DCC systems through a WiFi
network.

The Fremo~[@fremo] is a European modular model railroading club whose
unique requirements on it's DCC throttles led to the creation of the
throttles FRED and FREDI~[@fred] -- a series of LocoNet-throttles which
started their life as hobbyist projects with large numbers in
circulation but were also commercially available from
Uhlenbrock~[@uhlenbrock].

Specification wishlist

In modular railroading events, particularly of the
Fremo-americaN-group~[@fremo], multiple people have evaluated the
smartphone throttle solutions and found them lacking a nice, haptical
feedback. But the idea of wireless control without locking into a
specific vendor and their necessarily expensive equipment found great
approval. So a wishlist was compiled to define the requirements for a
wireless throttle:

- Same form factor as the FRED~[@fred] with similar controls

- Option to control at least two, better four locomotives for
  double/triple traction (similar to the double FRED)

- Battery runtime of at least six hours

- Exchangeable batteries, so when the battery runs down, they can be
  quickly exchanged for a charged set or cheap primary cells

- Easy configuration, but not too easy to prevent operators from
  accidentally selecting other locomotives

- As little change to the existing Fremo Loconet~network as possible

- Use of withrottle protocol, so the server side of the communication
  can be assumed to work and does not have to be developed as well

Development history

The first prototype versions of the wiFred were built to run from two AA
cells, either dry batteries or rechargeable NiMH cells. As described in
section~[4](#oldThrottle){reference-type="ref" reference="oldThrottle"},
this led to some special adaptations of the housing to fit all
components. Even then, experience with the prototypes showed the battery
compartment cover did not really fit and easily broke when trying to
open and close the battery compartment. So the next versions were built
around an integrated lithium battery, losing the ability to exchange
empty batteries, but with increased runtime and proper fit into the
housing. Recharging of the second generation is done through a Micro USB
connector, so a powerbank can extend the runtime of the device when the
internal battery is exhausted. Also, the loco selection switches act as
more of a power switch than they did with the first prototypes, reducing
power consumption to a negligible amount when all locos are deselected.

Wireless clock

During the development of this wiFred another topic came up in the
americaN group of the Fremo, namely wireless clocks with adjustable
clock rate for Timetable & Trainorder operations. This led to the
spinoff of the wiClock project[@wiClock].

\clearpage
99

[^1]: Pre-Shared Key, often just called password

[^2]: Pre-Shared Key, often just called password

[^3]: withrottle is also the name JMRI uses for the protocol and the
    server.