

An empirical study of fixation for strategies in the Iterated Prisoner's Dilemma

Marc Harper

Vincent Knight

Abstract

The Iterated Prisoner's Dilemma is a well established framework for the study of emergent behaviour. In this paper an extensive numerical study of the evolutionary dynamics of this framework are presented.

Fixation probabilities for Moran processes are obtained for 172 different strategies. This is done in both a standard 200 turn interaction and a noisy setting.

To the authors knowledge this is the largest such study. It allows for insights about the behaviour and performance of strategies with regard to their survival in an evolutionary setting.

1 Introduction

Since the formulation of the Moran Process in [11], this model of evolutionary population dynamics has been used to gain insights about the evolutionary stability of strategies in a number of settings. Similarly since the first Iterated Prisoner's Dilemma (IPD) tournament described in [3] the Prisoner's dilemma has been used to understand the evolution of cooperative behaviour in complex systems.

The analytical models of a Moran process are based on the relative fitness between two strategies and take this to be a fixed value r [13]. This is a valid model for simple strategies of the Prisoner's Dilemma such as to *always cooperate* or *always defect*. This manuscript provides a detailed numerical analysis of **164** complex and adaptive strategies for the IPD. In this case the relative fitness of a strategy is dependent on the population distribution.

Further deviations from the analytical model occur when interactions between players are subject to uncertainty. This is referred to as noise and has been considered in the IPD setting in [5, 12, 17].

This work provides answers to the following questions:

1. What strategies are good invaders?
2. What strategies are good at resisting invasion?
3. How does the population size affect these findings?

Figure 1 shows a diagrammatic representation of the Moran process. This process is a stochastic birth death process on a finite population in which the population size stays constant over time. Individuals are **selected** according to a given fitness landscape. Once selected, a given individual is reproduced and similarly another individual is chosen to be removed from the population. In some settings mutation is also considered but without mutation (the case considered in this work) this process will arrive at an absorbing state where the population is entirely made up of a single individual. The probability with which a given strategy is the survivor is called the fixation probability. A more detailed analytic description of this is given in Section 3.




Figure 1: A diagrammatic representation of a Moran process

The Moran process was initially introduced in [11] in a genetic setting. It has since been used in a variety of settings including the understanding of the spread of cooperative behaviour. However, as stated before, these mainly consider non sophisticated strategies. Some work has looked at evolutionary stability of strategies within the Prisoner's Dilemma [9]

but this is not done in the more widely used setting of the Moran process but in terms of infinite population stability. In [4] Moran processes are looked at in a theoretic framework for a small subset of strategies. In [8] machine learning techniques are used to train a strategy capable of resisting invasion and also invade any memory one strategy. Recent work [6] has investigated the effect of memory length on strategy performance and the emergence of cooperation but this is not done in Moran process context and only considers specific cases of memory 2 strategies.

The contribution of this work is a detailed and extensive analysis of absorption probabilities for 164 strategies. These strategies and the numerical simulations are from [15] which is an open source research library written for the study of the IPD. The strategies and simulation frameworks are automatically tested in accordance to best research software practice. The large number of strategies are available thanks to the open source nature of the project with over 40 contributions made by different programmers. Thus by considering Moran processes with population size greater than 2 we are taking in to account the effect of complex population dynamics. By considering sophisticated strategies we are taking in to effect the reputation of a strategy during each interaction.

Section 2 will explain the methodological approach used, Section 3 will validate the methodology by comparing simulated results to analytical results. The main results of this manuscript are presented in Section 4 which will present a detailed analysis of all the data generated. Finally, Section 5 will conclude and offer future avenues for the work presented here.

2 Methodology

To carry out this large numerical experiment 164 strategies are used from [15]. These include 161 default strategies in the library at the time (excluding strategies classified as having a long run time and those that make use of the length of the game) as well as the following 3 finite state machine machine strategies [2]:

Appendix A shows all the players in question. More information about each player can be obtained in the documentation for [15]. There are 43 stochastic and 121 deterministic strategies. Their memory depth is shown in Table 1.

Memory Depth	0	1	2	3	4	5	6	9	10	11	12	16	20	40	200	∞
Count	3	31	12	8	2	6	1	1	5	1	1	2	2	2	1	86

Table 1: Memory depth

All strategies are paired and these pairs are used in 1000 repetitions of a Moran process assuming a starting population of $(N/2, N/2)$. This is repeated for even N between 2 and 14. The fixation probability is then estimated for each value of N .


Note that due to the high computational cost of these experiments, for any given interaction between two players within the Moran process the outcome is sampled from a pre computed cache of 1000 match outcomes. This is carried out using an software written for the purpose of this work. This has been implemented in [15] ensuring that it can be used to either reproduce the work or carry out further work.

Figure 2 shows the distribution of the number of outcomes between all strategy pairs. Tables 2 shows that 95% of the stochastic matches have less than 788 unique outcomes whilst the maximum number is 971. This ensures that using a set of cached results from 1000 precomputed matches is sufficient for the analysis taking place here.


Outcome count		Outcome count	
count	13530.00	count	4753.00
mean	85.98	mean	242.90
std	192.58	std	260.04
min	1.00	min	2.00
25%	1.00	25%	28.00
50%	1.00	50%	139.00
75%	36.00	75%	394.00
95%	595.00	95%	788.00
max	971.00	max	971.00

(a) All matches
(b) Stochastic matches

Table 2: Summary statistics for the number of different match outcomes used as the cached results



(a) All matches



(b) Stochastic matches

Figure 2: The distribution of the number of unique outcomes used as the cached results

Section 3 will validate the methodology used here against known theoretic results.

3 Validation

As described in [13] Consider the payoff matrix:

$$M = \begin{pmatrix} a, b \\ c, d \end{pmatrix} \quad (1)$$

The expected payoffs of i players of the first type in a population with $N - i$ players of the second type are given by:

$$F_i = \frac{a(i-1) + b(N-i)}{N-1} \quad (2)$$

$$G_i = \frac{ci + d(N-i-1)}{N-1} \quad (3)$$

With an intensity of selection ω the fitness of both strategies is given by:

$$f_i = 1 - \omega + \omega F_i \quad (4)$$

$$g_i = 1 - \omega + \omega G_i \quad (5)$$

The transitions within the birth death process that underpins the Moran process are then given by:

$$p_{i,i+1} = \frac{if_i}{if_i + (N-i)g_i} \frac{N-i}{N} \quad (6)$$

$$p_{i,i-1} = \frac{(N-i)g_i}{if_i + (N-i)g_i} \frac{i}{N} \quad (7)$$

$$p_{ii} = 1 - p_{i,i+1} - p_{i,i-1} \quad (8)$$


Using this it is a known result that the fixation probability of the first strategy in a population of i individuals of the first type (and $N - i$ individuals of the second. We have:

$$x_i = \frac{1 + \sum_{j=1}^{i-1} \prod_{k=1}^j \gamma_k}{1 + \sum_{j=1}^{N-1} \prod_{k=1}^j \gamma_k} \quad (9)$$


where:

$$\gamma_j = \frac{p_{j,j-1}}{p_{j,j+1}}$$


Using this comparisons of $x_1, x_{N/2}, x_{N-1}$ are shown in Figure 17. The points represent the simulated values and the line shows the theoretic value. Note that these are all deterministic strategies and show a perfect match up between the expected value of (9) and the actual Moran process for all strategies pairs.




(a) Alternator and Cooperator



(b) Alternator and Defector




(c) Alternator and Tit For Tat



(d) Cooperator and Tit For Tat




(e) Defector and Cooperator



(f) Defector and Tit For Tat



(g) Win Stay Lose Shift and Tit For Tat



(h) Alternator and Win Stay Lose Shift



(i) Defector and Win Stay Lose Shift

Figure 3: Comparison of theoretic and actual Moran Process fixation probabilities for **deterministic** strategies

Figure 18 shows the fixation probabilities for stochastic strategies. These are no longer a good match which highlights the weakness of the analytical formulae that relies on the average payoffs. A detailed analysis of the 164 strategies considered, using direct Moran processes will be shown in the next Section.


4 Empirical results

This section will outline the data analysis carried out:


- Section 4.1 will consider the specific case of $N = 2$.
- Section 4.2 will investigate the effect of population size on the ability of a strategy to invade another population. This will highlight how complex strategies with long memories outperform simpler strategies.
- Section 4.3 will similarly investigate the ability to defend against an invasion.
- Section 4.4 will investigate the relationship between performance for differing population sizes. This highlights the importance of considering population dynamics over large populations.
- Section 4.5 will calculate the relative fitness of all strategies.




(a) Random and Cooperator



(b) Random and Defector



(c) Random and Tit For Tat




(d) All C or all D and Cooperator




(e) All C or all D and Defector




(f) Calculator and Random



(g) Calculator and All C or all D



(h) Calculator and Arrogant Q learner



(i) All C or all D and Tit For Tat

Figure 4: Comparison of theoretic and actual Moran Process fixation probabilities for **stochastic** strategies

4.1 The special case of $N = 2$

The main fixation probabilities of interest are x_1 and x_{N-1} , these reflect a strategy's ability to invade or resist invasion. For $N = 2$ these two cases coincide. Figure 5 shows all pairwise fixation probabilities for strategies on the vertical column when being matched against probabilities on the horizontal column. This is summarised in Figure 6 and Table 3. It can be seen that, as described in [14], zero determinant strategies perform well. The strategy with infinite memory **Collective** is a strategy with a handshake which implies that it will perform well against itself. There is also one of the trained finite state machines in the top five. The remaining strategy "Feld" is the corresponding strategy submitted to the first tournament by Axelrod [3]. All these strategies are stochastic.

Player	Median p_1	Memory Depth	Stochastic
ZD-Extort-4: 0.23529411764705882, 0.25, 1	0.584	1	True
CollectiveStrategy	0.572	∞	False
FSM Player: [(0, 'C', 7, 'C'), (0, 'D', 1, 'C')...	0.570	1	False
Feld: 1.0, 0.5, 200	0.568	200	True
ZD-Extort-2: 0.1111111111111111, 0.5	0.568	1	True

Table 3: Summary of top five strategies for $N = 2$

As will be demonstrated in Section 4.4 $N = 2$ is a particular case. In the next sections we will pay close attention to strategies who are strong invaders/resistors and shown diagrammatically in Figure 7.

4.2 Strong invaders

In this section x_i will be investigated: the probability of 1 individual of a given type successfully becoming fixated in a population of $N - 1$ other individuals. Figure 8 shows these values for the players along the vertical axis when matched against the players on the horizontal axis. It can be seen that invasion is in general more challenging for $N = 7$ and




Figure 5: The pairwise fixation probabilities for $N = 2$




Figure 6: The median fixation probabilities for $N = 2$




Figure 7: A single individual will successfully invade the population with probability x_1 . The group of Individuals will successfully resist with probability x_{N-1}

$N = 11$ in comparison to $N = 3$. This information is summarised in Figure 9 showing the median fixation as well as the neutral fixation for each given scenario.




Figure 8: Pairwise fixation probability x_1 of all strategies

For $N \in \{3, 7, 11\}$ the top five strategies are given in Tables 5.

Player	Median p_1	Memory Depth	Stochastic
CollectiveStrategy	0.403	∞	False
Predator	0.396	9	False
Prober 4	0.368	∞	False
Remorseful Prober: 0.1	0.357	2	True
Worse and Worse 2	0.355	∞	True
(a) $N = 3$			
Player	Median p_1	Memory Depth	Stochastic
Prober 4	0.177	∞	False
CollectiveStrategy	0.170	∞	False
Worse and Worse 2	0.159	∞	True
Predator	0.158	9	False
Remorseful Prober: 0.1	0.146	2	True
(b) $N = 7$			
Player	Median p_1	Memory Depth	Stochastic
Worse and Worse 3	0.125	∞	True
ThueMorseInverse	0.122	∞	False
GrudgerAlternator	0.115	∞	False
Hard Tit For Tat	0.115	3	False
Inverse	0.115	∞	True
(c) $N = 11$			

Table 4: Properties of top five invaders




Figure 9: Median probabilities x_1 of all strategies as well as the neutral fixation probability

4.3 Strong resistors




Figure 10: Pairwise fixation probability x_{N-1} of all strategies

Player	Median p_{N-1}	Memory Depth	Stochastic
CollectiveStrategy	0.403	∞	False
Predator	0.396	9	False
Prober 4	0.368	∞	False
Handshake	0.346	∞	False
Winner21	0.341	2	False

(a) $N = 3$

Player	Median p_{N-1}	Memory Depth	Stochastic
Prober 4	0.177	∞	False
CollectiveStrategy	0.170	∞	False
Predator	0.158	9	False
Winner21	0.145	2	False
Handshake	0.133	∞	False

(b) $N = 7$

Player	Median p_{N-1}	Memory Depth	Stochastic
Adaptive	0.111	∞	False
Prober 4	0.108	∞	False
CollectiveStrategy	0.089	∞	False
Predator	0.084	9	False
Handshake	0.081	∞	False

(c) $N = 11$

Table 5: Properties of top five strategies resistors

4.4 The effect of population size

Figures 12, 13 and 14 show the median rank of each strategy against population size. Note that these ranks are not necessarily integers as group ties are given the average rank.

Tables 6a, 6b and 6c show the correlation coefficients of the ranks in of strategies in differing population size. This is shown graphically in Figure 15. It is immediate to note that how well a strategy performs in any Moran process for $N > 2$ has little to do with the performance for $N = 2$.




Figure 11: Median probabilities x_{N-1} of all strategies as well as the neutral fixation probability



Figure 12: invade





Figure 13: resist



N	2	3	4	5	6	7	8	9	10
2	1.00	0.44	0.26	0.17	0.15	0.12	0.08	0.08	0.08
3	0.44	1.00	0.92	0.87	0.87	0.86	0.83	0.83	0.84
4	0.26	0.92	1.00	0.97	0.96	0.97	0.95	0.95	0.95
5	0.17	0.87	0.97	1.00	0.98	0.99	0.97	0.98	0.98
6	0.15	0.87	0.96	0.98	1.00	0.99	0.97	0.97	0.98
7	0.12	0.86	0.97	0.99	0.99	1.00	0.98	0.98	0.99
8	0.08	0.83	0.95	0.97	0.97	0.98	1.00	0.97	0.98
9	0.08	0.83	0.95	0.98	0.97	0.98	0.97	1.00	0.99
10	0.08	0.84	0.95	0.98	0.98	0.99	0.98	0.99	1.00

(a) Correlation coefficients for ranks for invasion

N	2	3	4	5	6	7	8	9	10	12
2	1.00	0.61	0.42	0.29	0.35	0.34	0.34	0.21	0.30	0.27
3	0.61	1.00	0.91	0.81	0.87	0.87	0.87	0.76	0.85	0.83
4	0.42	0.91	1.00	0.93	0.98	0.97	0.97	0.89	0.96	0.95
5	0.29	0.81	0.93	1.00	0.93	0.94	0.94	0.96	0.93	0.91
6	0.35	0.87	0.98	0.93	1.00	0.98	0.98	0.92	0.99	0.98
7	0.34	0.87	0.97	0.94	0.98	1.00	1.00	0.92	0.99	0.98
8	0.34	0.87	0.97	0.94	0.98	1.00	1.00	0.91	0.98	0.98
9	0.21	0.76	0.89	0.96	0.92	0.92	0.91	1.00	0.93	0.93
10	0.30	0.85	0.96	0.93	0.99	0.99	0.98	0.93	1.00	0.99
12	0.27	0.83	0.95	0.91	0.98	0.98	0.98	0.93	0.99	1.00

(b) Correlation coefficients for ranks for resistance

N	2	4	6	8	10
2	1.00	0.25	0.19	0.12	0.13
4	0.25	1.00	0.99	0.97	0.98
6	0.19	0.99	1.00	0.98	1.00
8	0.12	0.97	0.98	1.00	0.99
10	0.13	0.98	1.00	0.99	1.00

(c) Correlation coefficients for ranks for coexistence

Table 6: Correlation coefficients




Figure 15: Correlation coefficients for ranks

4.5 Relative fitness

Under the assumption of a constant relative fitness r between two strategies [13] the formula for x_i (for given N, r is:

$$x_i = x_i(r) = \frac{1 - \frac{1}{r^i}}{1 - \frac{1}{r^N}} \quad (10)$$

Figure 16 shows this function for $N = 10$ and $i \in \{1, 5, 10\}$.




Figure 16: $x_i(r)$

The first and second derivative of (10) is given by equations (11) and (12).

$$\frac{dx_i}{dr} = \frac{r^{N-i-1}}{r^{2N} - 2r^N + 1} (-Nr^i + N + ir^N - i) \quad (11)$$

$$\frac{d^2x_i}{dr^2} = \frac{r^{N-i-2}}{(r^N - 1)^3} \left(2N^2 (r^i - 1) + N (r^N - 1) (N (r^i - 1) - 2i + r^i - 1) - i(i+1) (r^N - 1)^2 \right) \quad (12)$$

Using these, Halley's method [1] can be used to efficiently numerically invert $x_i(r)$ to obtain a theoretic relative fitness r that gives the calculated $x_i(r)$ between two strategies for a given N, i .

5 Conclusion

Further work:


- Spatial structure;
- More than two types in the population;
- Modified Moran processes (Fermi selection);
- Mutation;

Acknowledgements

This work was performed using the computational facilities of the Advanced Research Computing @ Cardiff (ARCCA) Division, Cardiff University.

A variety of software libraries have been used in this work:


- The Axelrod library (IPD strategies and Moran processes) [15].
- The matplotlib library (visualisation) [7].
- The pandas and numpy libraries (data manipulation) [10, 16].




(a) Alternator and Cooperator




(b) Alternator and Defector




(c) Alternator and Tit For Tat




(d) Cooperator and Tit For Tat




(e) Defector and Cooperator




(f) Defector and Tit For Tat



(g) Win Stay Lose Shift and Tit For Tat




(h) Alternator and Win Stay Lose Shift




(i) Defector and Win Stay Lose Shift

Figure 17: Estimated relative fitness for **deterministic** strategies




(a) Random and Cooperator




(b) Random and Defector




(c) Random and Tit For Tat




(d) All C or all D and Cooperator




(e) All C or all D and Defector




(f) Calculator and Random



(g) Calculator and All C or all D



(h) Calculator and Arrogant Q learner



(i) All C or all D and Tit For Tat

Figure 18: Estimated relative fitness for **stochastic** strategies

References

- [1] Author G Alefeld. “On the Convergence of Halley ’ s Method”. In: 88.7 (2012), pp. 530–536.
- [2] Wendy Ashlock and Daniel Ashlock. “Changes in Prisoner ’ s Dilemma Strategies Over Evolutionary Time With Different Population Sizes”. In: (2006), pp. 1001–1008.
- [3] R. Axelrod. “Effective Choice in the Prisoner’s Dilemma”. In: *Journal of Conflict Resolution* 24.1 (1980), pp. 3–25.
- [4] Seung Ki Baek et al. “Comparing reactive and memory- one strategies of direct reciprocity”. In: *Nature Publishing Group* (2016), pp. 1–13. DOI: 10.1038/srep25676. URL: <http://dx.doi.org/10.1038/srep25676>.
- [5] Jonathan Bendor. “Uncertainty and the Evolution of Cooperation”. In: *The Journal of Conflict Resolution* 37.4 (1993), pp. 709–734.
- [6] Christian Hilbe et al. “Memory- $\frac{1}{2}$ strategies of direct reciprocity”. In: *Proceedings of the National Academy of Sciences* (2017), p. 201621239. ISSN: 0027-8424. DOI: 10.1073/pnas.1621239114. URL: <http://www.pnas.org/lookup/doi/10.1073/pnas.1621239114>.
- [7] John D Hunter. “Matplotlib: A 2D graphics environment”. In: *Computing In Science & Engineering* 9.3 (2007), pp. 90–95.
- [8] Christopher Lee, Marc Harper, and Dashiell Fryer. “The Art of War: Beyond Memory-one Strategies in Population Games”. In: *Plos One* 10.3 (2015), e0120625. ISSN: 1932-6203. DOI: 10.1371/journal.pone.0120625. URL: <http://dx.plos.org/10.1371/journal.pone.0120625>.
- [9] Jiawei Li, Graham Kendall, and Senior Member. “The effect of memory size on the evolutionary stability of strategies in iterated prisoner ’ s dilemma”. In: X.X (2014), pp. 1–8.
- [10] Wes McKinney et al. “Data structures for statistical computing in python”. In: *Proceedings of the 9th Python in Science Conference*. Vol. 445. van der Voort S, Millman J. 2010, pp. 51–56.
- [11] P.A.P. Moran. “Random Processes in Genetics”. In: April (1957), pp. 60–71.
- [12] M Nowak and K Sigmund. “A strategy of win-stay, lose-shift that outperforms tit-for-tat in the Prisoner’s Dilemma game.” In: *Nature* 364.6432 (1993), pp. 56–58. ISSN: 0028-0836. DOI: 10.1038/364056a0.
- [13] Martin A Nowak. *Evolutionary Dynamics: Exploring the Equations of Life*. Cambridge: Harvard University Press. ISBN: 0674023382. DOI: 10.1086/523139.
- [14] William H Press and Freeman J Dyson. “Iterated Prisoner’s Dilemma contains strategies that dominate any evolutionary opponent.” In: *Proceedings of the National Academy of Sciences of the United States of America* 109.26 (2012), pp. 10409–13. ISSN: 1091-6490. DOI: 10.1073/pnas.1206569109. URL: <http://www.pnas.org/content/109/26/10409.abstract>.
- [15] The Axelrod project developers. *Axelrod: v2.9.0*. Apr. 2016. DOI: 499122. URL: <http://dx.doi.org/10.5281/zenodo.499122>.
- [16] Stfan van der Walt, S Chris Colbert, and Gael Varoquaux. “The NumPy array: a structure for efficient numerical computation”. In: *Computing in Science & Engineering* 13.2 (2011), pp. 22–30.
- [17] Jianzhong Wu and Robert Axelrod. “How to Cope with Noise in the Iterated Prisoner’s Dilemma”. In: *The Journal of Conflict Resolution* 39.1 (1995).

A List of players

- | | | |
|------------------------------|----------------|--------------------------------|
| 1. Retaliate 3: 0.05 | 7. Ripoff | 13. Risky QLearner |
| 2. Adaptive | 8. Aggravater | 14. Alternator |
| 3. PSO Gambler 2.2.2 | 9. Prober 3 | 15. Alternator Hunter |
| 4. Revised Downing: True | 10. SelfSteem | 16. PSO Gambler 2.2.2 Noise 05 |
| 5. Adaptive Tit For Tat: 0.5 | 11. ALLCorALLD | 17. ShortMem |
| 6. Negation | 12. Nydegger | 18. AntiCycler |

19. Shubik
20. Anti Tit For Tat
21. FSM Player: [(0, 'C', 0, 'C'), (0, 'D', 3, 'C'), (1, 'C', 5, 'D'), (1, 'D', 0, 'C'), (2, 'C', 3, 'C'), (2, 'D', 2, 'D'), (3, 'C', 4, 'D'), (3, 'D', 6, 'D'), (4, 'C', 3, 'C'), (4, 'D', 1, 'D'), (5, 'C', 6, 'C'), (5, 'D', 3, 'D'), (6, 'C', 6, 'D'), (6, 'D', 6, 'D'), (7, 'C', 7, 'D'), (7, 'D', 5, 'C')], 1, C
22. Once Bitten
23. Adaptive Pavlov 2006
24. Slow Tit For Two Tats
25. Adaptive Pavlov 2011
26. Slow Tit For Two Tats 2
27. Nice Average Copier
28. Appeaser
29. PSO Gambler Mem1
30. Punisher
31. Sneaky Tit For Tat
32. Raider
33. Arrogant QLearner
34. Soft Grudger
35. Average Copier
36. Omega TFT: 3, 8
37. Soft Joss: 0.9
38. Better and Better
39. π
40. Random Hunter
41. FSM Player: [(0, 'C', 13, 'D'), (0, 'D', 12, 'D'), (1, 'C', 3, 'D'), (1, 'D', 4, 'D'), (2, 'C', 14, 'D'), (2, 'D', 9, 'D'), (3, 'C', 0, 'C'), (3, 'D', 1, 'D'), (4, 'C', 1, 'D'), (4, 'D', 2, 'D'), (5, 'C', 12, 'C'), (5, 'D', 6, 'C'), (6, 'C', 1, 'C'), (6, 'D', 14, 'D'), (7, 'C', 12, 'D'), (7, 'D', 2, 'D'), (8, 'C', 7, 'D'), (8, 'D', 9, 'D'), (9, 'C', 8, 'D'), (9, 'D', 0, 'D'), (10, 'C', 2, 'C'), (10, 'D', 15, 'C'), (11, 'C', 7, 'D'), (11, 'D', 13, 'D'), (12, 'C', 3, 'C'), (12, 'D', 8, 'D'), (13, 'C', 7, 'C'), (13, 'D', 10, 'D'), (14, 'C', 10, 'D'), (14, 'D', 7, 'D'), (15, 'C', 15, 'C'), (15, 'D', 11, 'D')], 1, C
42. Opposite Grudger
43. Random: 0.5
44. SolutionB1
45. Pun1
46. Prober
47. Bully
48. Predator
49. Remorseful Prober: 0.1
50. SolutionB5
51. Resurrection
52. Calculator
53. Prober 2
54. Hard Tit For 2 Tats
55. Spiteful Tit For Tat
56. Prober 4
57. Retaliate: 0.1
58. Retaliate 2: 0.08
59. PSO Gambler 1_1_1
60. Grumpy: Nice, 10, -10
61. CollectiveStrategy
62. Stochastic Cooperator
63. Cautious QLearner
64. Cooperator
65. Fool Me Once
66. Hard Go By Majority: 10
67. Hard Go By Majority
68. Stochastic WSLs: 0.05
69. Worse and Worse 3
70. Hard Go By Majority: 40
71. Cooperator Hunter
72. Eventual Cycle Hunter
73. Firm But Fair
74. Contrite Tit For Tat
75. Forgetful Fool Me Once: 0.05
76. Math Constant Hunter
77. Cycle Hunter
78. Suspicious Tit For Tat
79. ZD-Extort-2: 0.1111111111111111, 0.5
80. Evolved ANN
81. Fool Me Forever
82. Hard Go By Majority: 5
83. MEM2
84. ZD-Extort-2 v2: 0.125, 0.5, 1
85. Forgetful Grudger
86. Cycler CCCCCD
87. Tester
88. Evolved ANN 5
89. Hard Tit For Tat
90. Forgiver
91. Fortress3
92. ThueMorse
93. Evolved ANN 5 Noise 05
94. Forgiving Tit For Tat
95. Cycler CCCD
96. ThueMorseInverse
97. Soft Go By Majority
98. ZD-Extort-4: 0.23529411764705882, 0.25, 1
99. Evolved FSM 4
100. Fortress4
101. ZD-GEN-2: 0.125, 0.5, 3
102. Thumper

103. FSM Player: [(0, 'C', 7, 'C'), (0, 'D', 1, 'C'), (1, 'C', 11, 'D'), (1, 'D', 11, 'D'), (2, 'C', 8, 'D'), (2, 'D', 8, 'C'), (3, 'C', 3, 'C'), (3, 'D', 12, 'D'), (4, 'C', 6, 'C'), (4, 'D', 3, 'C'), (5, 'C', 11, 'C'), (5, 'D', 8, 'D'), (6, 'C', 13, 'D'), (6, 'D', 14, 'C'), (7, 'C', 4, 'D'), (7, 'D', 2, 'D'), (8, 'C', 14, 'D'), (8, 'D', 8, 'D'), (9, 'C', 0, 'C'), (9, 'D', 10, 'D'), (10, 'C', 8, 'C'), (10, 'D', 15, 'C'), (11, 'C', 6, 'D'), (11, 'D', 5, 'D'), (12, 'C', 6, 'D'), (12, 'D', 9, 'D'), (13, 'C', 9, 'D'), (13, 'D', 8, 'D'), (14, 'C', 8, 'D'), (14, 'D', 13, 'D'), (15, 'C', 4, 'C'), (15, 'D', 5, 'C')], 1, C
104. ZD-GTFT-2: 0.25, 0.5
105. Cycler CCD
106. GTFT: 0.33
107. Tit For 2 Tats
108. Meta Hunter: 6 players
109. Hesitant QLearner
110. Evolved FSM 16
111. General Soft Grudger:
n=1,d=4,c=2
112. Joss: 0.9
113. Tullock: 11
114. Cycler DC
115. Soft Go By Majority: 10
116. Inverse
117. ZD-SET-2: 0.25, 0.0, 2
118. Limited Retaliate 2: 0.08, 15
119. Tricky Defector
120. Naive Prober: 0.1
121. Meta Hunter Aggressive: 7 players
122. Evolved FSM 16 Noise 05
123. Tricky Cooperator
124. e
125. Cycler DDC
126. Limited Retaliate 3: 0.05, 20
127. Hopeless
128. VeryBad
129. Soft Go By Majority: 20
130. EvolvedLookerUp2.2.2
131. Two Tits For Tat
132. Tit For Tat
133. Cycler CCCDCD
134. EvolvedLookerUp1.1.1
135. Soft Go By Majority: 40
136. Level Punisher
137. Hard Prober
138. Limited Retaliate: 0.1, 20
139. Winner21
140. Defector
141. Soft Go By Majority: 5
142. Davis: 10
143. Handshake
144. ϕ
145. Inverse Punisher
146. Winner12
147. Gradual
148. Defector Hunter
149. Willing
150. Desperate
151. Gradual Killer: ('D', 'D', 'D', 'D', 'D', 'C', 'C')
152. Hard Go By Majority: 20
153. Win-Shift Lose-Stay: D
154. Grofman
155. Win-Stay Lose-Shift: C
156. Doubler
157. Grudger
158. Evolved HMM 5
159. EasyGo
160. Worse and Worse
161. Feld: 1.0, 0.5, 200
162. GrudgerAlternator
163. Worse and Worse 2
164. Eatherley