

Introduction

Cluster analysis is a fundamental unsupervised learning tool used to group similar data points. Among clustering algorithms, **DBSCAN** stands out because it can find clusters of arbitrary shape and identify noise (outliers) without needing to pre-specify the number of clusters. In this paper, I will explain DBSCAN, how it works, real-world applications (especially in anomaly detection), discuss recent research trends, and reflect on its importance today.

Concept / Definition

DBSCAN (Density-Based Spatial Clustering of Applications with Noise) is a density-based clustering algorithm. At a high level:

- It groups together points that are “densely packed” (i.e., many neighbors within a given radius), and
- It considers points in low-density regions as **noise** (outliers).

Unlike K-means, you do **not** need to predefine the number of clusters. Instead, DBSCAN has two key parameters: ϵ (**eps**), the radius to search for neighbors, and **MinPts**, the minimum number of points required in the ϵ -neighborhood to form a “dense” region.

In DBSCAN terminology:

- A point is a **core point** if there are at least MinPts within its ϵ -neighborhood.
- A point is **directly density-reachable** from another if it is within ϵ of a core point.
- A point is **density-reachable** (via a chain of core points) from another.
- Points that are not reachable from any core point are labeled as **noise**.

Thus clusters are connected sets of density-reachable points.

How It Works

Here is a general algorithm flow:

1. **Initialize** all points as unvisited.
2. For each unvisited point p :
 1. Mark p as visited.
 2. Retrieve the ϵ -neighborhood of p (all points within distance $\leq \epsilon$).
 3. If the neighborhood has fewer than **MinPts**, mark p as **noise**.
 4. Otherwise, create a new cluster, add p and expand the cluster:
 - For each neighbor q in the neighborhood:
 - If q is not visited, mark visited and get its ϵ -neighborhood.

- If q 's neighborhood size $\geq \text{MinPts}$, include those neighbors recursively.
- If q is not yet assigned to any cluster, assign it to this cluster.

3. Continue until all points are visited.

Illustration (textual):

- Suppose you have points scattered on the plane.
- You pick a point p , check how many points lie within ϵ .
- If the count $\geq \text{MinPts}$, it's a core point.
- Expand outward: from neighbors that are also core, traverse further, aggregating reachable points.
- Border points (fewer neighbors than MinPts) can be included in clusters if reachable.
- Isolated points remain as noise.

Strengths & limitations:

Strengths	Limitation
Finds clusters of arbitrary shapes	Sensitive to parameter choices (ϵ , MinPts)
Detects outliers / noise naturally	Harder to scale to very high dimensions (distance becomes less meaningful)
No need to specify number of clusters	Does not work well when cluster densities vary widely

Examples / Real-world Applications

1. Anomaly detection / Fraud / Network intrusion

DBSCAN is often used in cybersecurity or financial systems to detect anomalous patterns. Because DBSCAN labels sparse regions as noise, those noise points may correspond to suspicious or rare events (e.g. fraudulent transactions). In cloud or network traffic monitoring, DBSCAN can cluster typical traffic patterns; anomalies are those that don't fit dense clusters. [ResearchGate+2MDPI+2](#)

2. Geospatial hotspot / crime clustering / earthquake epicenters

On a map, DBSCAN can cluster spatial events (like crime incidents, disease outbreaks, or geological data) into hotspots while discarding isolated points. For example, in seismology, clustered epicenters may indicate fault zones; isolated events may be background noise.

3. Underwater terrain / bathymetry anomaly detection

In terrain / topographic data, DBSCAN has been paired with other methods (e.g., IForest) to detect anomalous elevation readings or outliers in underwater measurement data. [MDPI](#)

4. **Flight anomaly detection**

DBSCAN has been applied to aviation data to detect flights whose behavior deviates from norms (e.g. unusual trajectories). arc.aiaa.org

Recent Trends / Research (2020–present)

- *“Anomaly Detection Based on GCNs and DBSCAN in a Graph Context”* (2024)
This work adapts DBSCAN for graph data by combining it with Graph Convolutional Networks (GCNs). The idea is to exploit structural density patterns in graphs: Dense regions in node embeddings are clusters; sparse regions may be anomalies. [MDPI](#)
- *“Research on a DBSCAN-IForest Optimisation-Based Anomaly Detection Algorithm for Underwater Terrain Data”* (2025)
This study proposes a hybrid approach: first use DBSCAN to do a coarse clustering, then apply an **Isolation Forest (IForest)** on subclusters to further detect anomalies. The combined method achieved a detection rate up to 93.75%. [MDPI](#)
- *“Hybrid iForest-DBSCAN for anomaly detection and wind forecasting”* (2025)
This work fuses Isolation Forest and DBSCAN to leverage the strengths of both: DBSCAN handles dense region discovery, IForest identifies outliers inside clusters. It showed improved performance in detecting anomalies in wind data. [ScienceDirect](#)
- *“Improved DBSCAN-based Data Anomaly Detection for Battery Energy Storage Systems”* (2022 / recent)
This paper applies DBSCAN with adaptive parameter selection (based on KNN, box plot methods) to detect anomalies in real-time power grid / battery storage system telemetry. [ResearchGate](#)

These trends show that DBSCAN is not just used as-is, but often **hybridized** or **extended** (with IForest, deep learning, graphs) to overcome limitations or tailor it to specific domains.

Reflection / Importance

Why is DBSCAN important today?

- **Noise / Outlier detection is crucial** in many domains (fraud detection, cybersecurity, sensor data monitoring). DBSCAN's built-in notion of noise gives it an advantage over many clustering methods.
- **Flexible cluster shapes** make it suited for real-world, messy data where clusters are not spherical or evenly distributed.
- **No need to predefine number of clusters** is a practical benefit, especially when the true number of groups is unknown.

- With the growth of **big data, streaming, graph data, and heterogeneous sensors**, robust clustering and anomaly detection remains a key task. DBSCAN and its variants provide building blocks for such systems (especially when combined with other techniques).
- In a world with increasing risks (cyberattacks, system failures, fraudulent behavior), methods that can detect anomalies efficiently and adaptively are very valuable.

References:

- Li, M., Su, M., Zhang, B., Yue, Y., Wang, J., & Deng, Y. (2025). Research on a DBSCAN-IForest Optimisation-Based Anomaly Detection Algorithm for Underwater Terrain Data. *Water*, 17(5), 626–626. <https://doi.org/10.3390/w17050626>
- Retiti, C., Song, S., Lee, H., Choi, D., Lim, J., Bok, K., & Yoo, J. (2024). Anomaly Detection Based on GCNs and DBSCAN in a Large-Scale Graph. *Electronics*, 13(13), 2625–2625. <https://doi.org/10.3390/electronics13132625>
- Dai, Y., Sun, S., & Che, L. (2022). Improved DBSCAN-based Data Anomaly Detection Approach for Battery Energy Storage Stations. *Journal of Physics: Conference Series*, 2351(1), 012025. <https://doi.org/10.1088/1742-6596/2351/1/012025>
- GeeksforGeeks. (2019, May 6). DBSCAN Clustering in ML Density based clustering. GeeksforGeeks. <https://www.geeksforgeeks.org/machine-learning/dbscan-clustering-in-ml-density-based-clustering/>