

A Comparative Analysis of the Competing 3G Standards: W-CDMA vs. CDMA2000

CASE STUDY

Submitted by

Nikhil Sharma [Reg No: RA2311056030043],

Ashish Saini [Reg No: RA2311056030052],

Ankit Tehri [Reg No: RA2311056030057]

Under the guidance of

Dr. Chandni R Bajaj

(Assistant Professor, Department of Computer
Science & Engineering)

*in partial fulfilment for the award of
the degree of*

BACHELOR OF TECHNOLOGY

in

COMPUTER SCIENCE & ENGINEERING

of

FACULTY OF ENGINEERING AND TECHNOLOGY

SRM INSTITUTE OF SCIENCE & TECHNOLOGY, NCR CAMPUS

October 2025

SRM INSTITUTE OF SCIENCE & TECHNOLOGY
(Under Section 3 of UGC Act, 1956)

BONAFIDE CERTIFICATE

Certified that this project report titled “**A Comparative Analysis of the Competing 3G Standards: W-CDMA vs. CDMA2000** ” is the Bonafide work of Nikhil Sharma [**Reg No: RA2311056030043**], Ashish Saini [**Reg No: RA2311056030052**], Ankit Tehri [**Reg No: RA2311056030057**] who carried out the project work under my supervision. Certified further, that to the best of my knowledge the work reported herein does not form any other project report or dissertation on the basis of which a degree or award was conferred on an earlier occasion on this or any other candidate.

SIGNATURE

Dr. Shalini Sharma
Assistant Professor
Dept. of Computer Science & Engineering

SIGNATURE

Dr. Harish Taluja
Head of Department
Dept. of Computer Science
& Engineering

ACKNOWLEDGEMENT

We would like to express our deepest gratitude to our guide, Dr. Chandni R Bajaj for her valuable guidance, consistent encouragement, personal caring, timely help and providing us with an excellent atmosphere for doing research. All through the work, in spite of her busy schedule, she has extended cheerful and cordial support to our team for completing this research work.

Nikhil Sharma
Ashish Saini
Ankit Tehri

Table of Contents

BONAFIDE CERTIFICATE.....	2
ACKNOWLEDGEMENT	3
CHAPTER 1: THE GLOBAL MANDATE FOR 3G (IMT-2000).....	5
CHAPTER 2: THE W-CDMA (UMTS) STANDARD	11
CHAPTER 3: THE CDMA2000 STANDARD	20
CHAPTER 4: TECHNICAL AND MARKET PERFORMANCE SHOWDOWN.....	28
CHAPTER 5: CONCLUSION: LEGACY AND EVOLUTION TO 4G	37
REFERENCES	41

CHAPTER 1: THE GLOBAL MANDATE FOR 3G (IMT-2000)

Introduction to the International Telecommunication Union's (ITU) Vision for a Global Mobile Standard

1. Overview of the ITU

The **International Telecommunication Union (ITU)** is a specialized agency of the **United Nations (UN)** responsible for coordinating telecommunication operations and services worldwide. Founded in 1865, it is the oldest international organization in existence that deals with global communication technologies. Over the years, ITU has been instrumental in defining radio-frequency allocations, satellite orbits, and global telecommunication standards that enable the interconnection of communication systems across borders.

As communication technologies evolved, particularly during the late 20th century, the ITU recognized the growing fragmentation of mobile communication systems. Each region and country was developing its own set of technologies and standards—Europe had **GSM (Global System for Mobile Communication)**, the United States largely used **CDMA (Code Division Multiple Access)**, and Japan developed **PDC (Personal Digital Cellular)**. While these technologies served their domestic markets well, they created **barriers to international roaming and global interoperability**. This fragmentation hindered the vision of a truly global communication ecosystem.

2. Emergence of the ITU's Global Vision

In response to these challenges, the ITU began conceptualizing a framework for a **unified global mobile communication system**. This initiative evolved into what became known as **IMT-2000 (International Mobile Telecommunications-2000)**, representing the **Third Generation (3G)** of mobile communication technology.

The main objective behind IMT-2000 was to provide a **common technical platform** that could operate seamlessly across different countries and support a wide range of services, from voice communication to high-speed data and multimedia applications. ITU's vision was not only technological but also social and economic—it aimed to connect people globally, reduce communication barriers, and promote digital inclusion.

3. Objectives of the ITU's Global Standardization Effort

The ITU's vision for a global mobile standard under IMT-2000 was built upon several strategic objectives:

a. Global Compatibility and Roaming

The ITU sought to enable mobile users to move across borders without losing connectivity or requiring different devices. A single, harmonized global standard would ensure that a phone could function anywhere in the world, allowing true **global roaming**.

b. Integration of Services

The ITU envisioned a single platform capable of supporting multiple services—voice, data, video, and multimedia—through a **converged communication system**. This would allow users to experience seamless transitions between networks and technologies.

c. High-Speed Data Transmission

To meet the growing demand for internet access and multimedia applications, IMT-2000 targeted data rates of **up to 2 Mbps**, a significant leap compared to the limited data capabilities of 2G systems.

d. Efficient Spectrum Usage

With the rapid expansion of mobile users worldwide, spectrum management became a global concern. The ITU's vision aimed to promote **efficient utilization of available frequency bands** while ensuring fair and equitable access for all nations.

e. Global Interoperability

Another key goal was interoperability—different networks and devices should communicate seamlessly. The ITU wanted to establish **common standards** that allowed various systems to coexist and interoperate smoothly.

f. Backward Compatibility

The ITU recognized the vast investments made in 2G systems such as GSM and CDMA. Hence, IMT-2000 standards were designed to be **backward-compatible**, ensuring that users could transition gradually without major disruptions.

g. Economic Development and Social Inclusion

The ITU also emphasized the role of telecommunication in global economic development. The organization believed that universal access to advanced communication technologies would drive **education, healthcare, governance, and economic growth**, particularly in developing nations.

4. The IMT-2000 Framework

IMT-2000 was not a single standard but rather a **family of standards** that met a common set of technical requirements defined by the ITU. This approach allowed regional flexibility while maintaining global harmony.

The IMT-2000 framework included:

- **W-CDMA (Wideband Code Division Multiple Access)** – adopted mainly in Europe and Japan.
- **CDMA2000** – primarily used in the United States and parts of Asia.
- **TD-SCDMA (Time Division Synchronous CDMA)** – developed by China.
- **UWC-136 (EDGE)** – an evolution of GSM.

By approving multiple compliant technologies, the ITU managed to balance **global unification with regional diversity**, ensuring that no major region was excluded from the 3G ecosystem.

5. Implementation and Impact

The ITU's global vision became a cornerstone of modern communication. 3G technologies under IMT-2000 laid the foundation for advanced services such as **mobile internet, video conferencing, and real-time data exchange**. These capabilities transformed the way people interacted, conducted business, and accessed information.

Furthermore, IMT-2000 paved the way for future generations—**IMT-Advanced (4G)** and **IMT-2020 (5G)**—which continued the ITU's legacy of global harmonization and technological progress.

6. Challenges Faced by ITU

Despite its success, the ITU faced several challenges:

- **Political resistance** from regions wanting to protect domestic industries.
- **Technical disagreements** over which technology should dominate.
- **Spectrum allocation conflicts** among member nations.
- **Commercial competition** among telecom operators and equipment vendors.

However, through diplomatic negotiation and technological collaboration, the ITU achieved its primary goal—creating a unified vision that guided global mobile communication toward standardization and universal connectivity.

Political and Commercial Motivations Behind the Development of 3G

1. Introduction

The evolution of mobile communication from **1G (analog)** to **2G (digital)** and eventually **3G (broadband)** was not merely a technological progression; it was also a reflection of deep **political** and **commercial** interests. By the late 1990s, mobile communication had become a critical infrastructure influencing

economic competitiveness, national security, and international influence. As a result, governments, corporations, and international organizations all had strong motivations—both political and commercial—to push for the rapid development and deployment of 3G systems.

2. Political Motivations

a. National Sovereignty and Technological Independence

Governments recognized that telecommunications were a vital strategic resource. By developing and adopting domestic 3G technologies, nations could reduce dependency on foreign companies and strengthen their **technological sovereignty**. For example, Japan invested heavily in W-CDMA, while China developed TD-SCDMA to reduce reliance on Western technologies.

b. Control Over Spectrum Allocation

The electromagnetic spectrum is a limited and valuable national asset. Governments used 3G licensing and spectrum allocation as a means to **control the pace of innovation, generate revenue, and regulate competition** among operators. Many countries conducted spectrum auctions, earning billions of dollars in license fees.

c. Economic Competitiveness

Politically, nations viewed 3G as a driver of economic growth. The introduction of mobile internet, e-commerce, and digital services was expected to enhance productivity and open new markets. Countries that led in 3G deployment could strengthen their **global economic influence** and attract foreign investment.

d. Global Leadership in Standardization

Europe, through organizations such as ETSI (European Telecommunications Standards Institute), promoted GSM and later UMTS as the dominant global standards. This was a politically motivated effort to maintain leadership in the telecommunications sector, countering the influence of the United States and Japan.

e. Digital Inclusion and Social Policy

For developing countries, 3G offered an opportunity to **bridge the digital divide**. Governments supported its deployment as part of national strategies to provide rural connectivity, promote e-governance, and expand access to information and education.

3. Commercial Motivations

a. Market Expansion and Profit Opportunities

For telecom operators and manufacturers, 3G represented a **massive commercial opportunity**. The demand for mobile data and multimedia services promised new sources of

revenue far beyond voice communication. Operators could now offer mobile internet, email, video calling, and entertainment services.

b. Technological Innovation and Product Differentiation

Device manufacturers such as **Nokia, Ericsson, Motorola, and Samsung** invested heavily in 3G technologies to maintain a competitive edge. By offering advanced handsets with high-speed data capabilities, companies could attract consumers and capture new markets.

c. Infrastructure and Equipment Sales

Telecom equipment providers like **Ericsson, Nokia Siemens Networks, Huawei, and Alcatel-Lucent** saw 3G as a chance to sell new network infrastructure. As 3G required upgraded base stations and new spectrum bands, these companies benefited from global modernization projects.

d. Global Roaming and Brand Expansion

A unified global standard enabled multinational operators to offer **international roaming services**, while device makers could sell a single model worldwide. This encouraged global branding and economies of scale in production.

e. Monetization of Data Services

Unlike 2G, which was limited to voice and SMS, 3G enabled high-speed data. Operators quickly realized that data usage—through streaming, browsing, and downloads—could generate **significant recurring revenues**. This commercial motivation was one of the strongest drivers of 3G rollout.

f. Competitive Pressure

The late 1990s and early 2000s saw intense competition in the telecom industry. Operators feared being left behind if rivals launched 3G first. This competitive environment fueled rapid investment and early deployment, even when market demand was still emerging.

4. Interplay Between Political and Commercial Forces

The development of 3G was characterized by the **interdependence of political and commercial motivations**. Governments set the regulatory and spectrum frameworks, while corporations provided the investment, innovation, and deployment. In many cases, political policies shaped the commercial landscape—for instance, spectrum auction pricing directly affected operators' financial strategies. Conversely, corporate lobbying influenced political decisions about standardization and international agreements.

5. Challenges During 3G Development

Despite its promise, the road to 3G was not smooth. Several issues arose:

- **High Licensing Costs:** Spectrum auctions in countries like the UK and Germany raised billions but left operators heavily in debt.
- **Technological Immaturity:** Initial 3G networks suffered from technical issues and limited handset availability.
- **Slow Consumer Adoption:** Early users found data services expensive and coverage inconsistent.
- **Standardization Conflicts:** Rival technologies (W-CDMA vs. CDMA2000) led to fragmentation, although both fell under the IMT-2000 umbrella.

Despite these challenges, 3G's development continued steadily, setting the stage for the mobile broadband era.

6. Legacy and Impact of 3G

The introduction of 3G fundamentally transformed global communication. It enabled the rise of **mobile internet, app ecosystems, video calling, and real-time communication services**. From a political perspective, it strengthened international cooperation under the ITU's guidance and encouraged countries to participate in future global standardization efforts. Commercially, it gave birth to new industries—**mobile application development, content streaming, and e-commerce**—creating trillions of dollars in economic value worldwide.

7. Conclusion

The ITU's vision for a **global mobile standard** through IMT-2000 was one of the most significant milestones in telecommunication history. It represented the convergence of technology, policy, and commerce into a unified framework that revolutionized human connectivity.

While **political motivations** focused on sovereignty, leadership, and economic policy, **commercial motivations** revolved around competition, innovation, and market expansion. Together, they shaped the evolution of 3G into a truly global system, paving the way for 4G and eventually 5G.

The ITU's work continues to influence modern communication technologies, embodying its enduring mission—to bring the world together through a **universal, interoperable, and inclusive telecommunication network**.

CHAPTER 2: THE W-CDMA (UMTS) STANDARD

2.1 Introduction

The **Wideband Code Division Multiple Access (W-CDMA)** technology, also known as **Universal Mobile Telecommunications System (UMTS)**, represents the **third generation (3G)** mobile communication system developed as a natural evolution of the successful **Global System for Mobile Communications (GSM)** standard.

It was standardized by the **3rd Generation Partnership Project (3GPP)** under the framework of the **International Telecommunication Union's IMT-2000 vision** for global mobile systems. UMTS/W-CDMA was designed to provide **high-speed multimedia services, global roaming, and packet-based data connectivity**, offering a substantial improvement over 2G networks that were primarily voice-centric.

The technology supports data rates up to **2 Mbps** in stationary environments and around **384 kbps** in mobile scenarios, enabling video calling, mobile internet access, and advanced data applications.

This chapter provides an in-depth technical exploration of the **W-CDMA air interface, channel structure, and network architecture**, highlighting how the system evolved from GSM and became a foundation for later generations such as **HSPA, HSPA+, and LTE**.

2.2 Evolution from GSM to W-CDMA

The GSM standard, launched in the early 1990s, was based on **Time Division Multiple Access (TDMA)** and **Frequency Division Multiple Access (FDMA)**. While GSM revolutionized digital communication, its limited data rate (9.6 kbps initially, later enhanced to 64 kbps through GPRS and EDGE) was inadequate for the growing demand for mobile multimedia and internet access.

The evolution path from GSM to W-CDMA involved several transitional technologies:

Generation	Technology	Data Rate	Key Features
2G	GSM	9.6 kbps	Digital voice, SMS
2.5G	GPRS	40–60 kbps	Packet data services
2.75G	EDGE	144 kbps	Enhanced data rates using 8-PSK
3G	UMTS (W-CDMA)	384 kbps–2 Mbps	High-speed multimedia, global roaming

Motivations for Evolution

- Need for **high-speed packet data** and multimedia services.
- Demand for **seamless global roaming** under a unified standard.
- Efficient utilization of spectrum resources.
- Backward compatibility with GSM core networks.

UMTS was thus conceived as a **global 3G standard**, reusing GSM's core network structure while adopting a **new radio access technology** — **W-CDMA** — for higher data capacity and flexibility.

2.3 Overview of W-CDMA Technology

W-CDMA is a **wideband spread spectrum** technology employing **Code Division Multiple Access (CDMA)** principles.

Unlike TDMA systems, where users share the same frequency but different time slots, CDMA allows multiple users to occupy the **same frequency band simultaneously**, differentiated by unique **spreading codes**.

Key Characteristics

1. **Wideband Carrier:**

Uses a **5 MHz** channel bandwidth (compared to 200 kHz in GSM). The wider bandwidth allows for higher data throughput and supports multiple services simultaneously.

2. **Direct Sequence Spread Spectrum (DSSS):**

Each user's data is multiplied by a high-rate pseudorandom spreading code, spreading the signal across a wide frequency band.

3. **Variable Data Rates:**

Supports flexible data rates by adjusting spreading factors, enabling simultaneous voice and data services.

4. **Asynchronous Operation:**

Unlike CDMA2000, W-CDMA does not require strict network-wide synchronization, simplifying deployment.

5. **Support for Soft Handover:**

A mobile can connect to multiple base stations simultaneously, improving connection

reliability during movement.

6. **Efficient Power Control:**

Fast and dynamic power control mechanisms counteract the “near-far problem,” ensuring equitable signal quality among users.

2.4 Air Interface of W-CDMA

The **air interface** defines how the mobile station (User Equipment – UE) communicates with the base station (Node B).

It includes the **radio transmission techniques, modulation, multiple access, and protocol structures.**

2.4.1 Frequency Bands

W-CDMA operates mainly in the following frequency bands:

- **Uplink (UE to Node B):** 1920–1980 MHz
- **Downlink (Node B to UE):** 2110–2170 MHz

However, regional variations exist, with additional bands introduced for North America and other markets.

2.4.2 Duplex Modes

W-CDMA supports two duplexing schemes:

- **Frequency Division Duplex (FDD):** Separate frequency bands for uplink and downlink (most common).
- **Time Division Duplex (TDD):** Same frequency used for both uplink and downlink, separated by time slots (used in limited deployments).

2.4.3 Modulation Techniques

- **Quadrature Phase Shift Keying (QPSK)** for both uplink and downlink.
- Later enhancements like **16-QAM** were introduced in HSPA for higher data rates.

2.4.4 Spreading and Scrambling

Each user’s signal is **spread** using an **Orthogonal Variable Spreading Factor (OVSF)** code to maintain orthogonality.

A **cell-specific scrambling code** is then applied to distinguish transmissions from different

cells.

2.4.5 Channelization and Multiplexing

Data from various services (voice, control, and packet data) are multiplexed and transmitted over the same physical channel using code division techniques.

2.5 Channel Structure of W-CDMA

The channel structure in W-CDMA is layered into **logical**, **transport**, and **physical** channels. This hierarchical model ensures efficient management of various data types and control signaling.

2.5.1 Logical Channels

Logical channels define **what type of information** is being transmitted.

Channel Type	Purpose
BCCH (Broadcast Control Channel)	Carries system information.
PCCH (Paging Control Channel)	Used for paging mobile users.
DCCH (Dedicated Control Channel)	Transmits dedicated signaling for individual users.
DTCH (Dedicated Traffic Channel)	Carries user data such as voice or packet data.
CCCH (Common Control Channel)	For initial access and random access procedures.

2.5.2 Transport Channels

Transport channels define **how data is transferred** over the air interface.

Channel	Function
DCH (Dedicated Channel)	Dedicated to a single user.
FACH (Forward Access Channel)	Common downlink channel for control messages.
RACH (Random Access Channel)	Used by mobiles to request access.
DSCH (Downlink Shared Channel)	Shared by multiple users for downlink data.
CPCH (Common Packet Channel)	Uplink shared channel for packet data.

2.5.3 Physical Channels

Physical channels represent the actual radio transmission resources — time, frequency, and codes.

Examples include:

- **DPDCH (Dedicated Physical Data Channel)**
- **DPCCH (Dedicated Physical Control Channel)**
- **P-CCPCH (Primary Common Control Physical Channel)**
- **PICH (Paging Indicator Channel)**
- **AICH (Acquisition Indicator Channel)**

Each physical channel has defined parameters such as spreading factor, modulation type, and power control commands.

2.6 Power Control Mechanisms

Power control in W-CDMA is critical to maintain system performance and combat the **near-far problem** (where a nearby user's signal could overpower distant users).

Types of Power Control

- 1. Open-Loop Power Control:**
The UE estimates initial transmit power based on received signal strength from Node B.
- 2. Closed-Loop Power Control:**
Node B continuously commands the UE to increase or decrease its transmit power (typically 1500 times per second).
- 3. Outer Loop Power Control:**
Adjusts the target Signal-to-Interference Ratio (SIR) to achieve desired quality levels depending on channel conditions.

Power control ensures stable communication, limits interference, and conserves battery life.

2.7 Handover Procedures

W-CDMA employs advanced handover mechanisms to maintain uninterrupted service when a user moves between cells.

Types of Handover

- 1. Soft Handover:**
The UE simultaneously connects to multiple Node Bs on the same frequency. Signals are combined at the RNC for better quality.
- 2. Softer Handover:**
Occurs between sectors of the same Node B using different codes.

3. **Hard Handover:**

Used when moving between frequencies or systems (e.g., UMTS to GSM).

The **soft handover** concept is a major improvement over GSM, which only supported hard handovers, reducing call drops significantly.

2.8 Network Architecture of W-CDMA (UMTS)

The W-CDMA network architecture comprises three main domains:

1. **User Equipment (UE)**
2. **UMTS Terrestrial Radio Access Network (UTRAN)**
3. **Core Network (CN)**

2.8.1 User Equipment (UE)

The UE consists of:

- **Mobile Equipment (ME):** The handset or data device.
- **USIM (Universal Subscriber Identity Module):** Stores user identity, authentication keys, and service parameters.

2.8.2 UTRAN Architecture

The UTRAN is responsible for the **radio access** between the mobile and the core network. It includes:

- **Node B:** Equivalent to a GSM Base Transceiver Station (BTS), handling radio transmission and reception.
- **Radio Network Controller (RNC):** Manages radio resources, handovers, and power control for multiple Node Bs.

Each RNC can connect to several Node Bs and to the Core Network via the **Iu interface**.

Interfaces in UTRAN:

Interface	Connects	Function
Uu	UE ↔ Node B	Air interface
Iub	Node B ↔ RNC	Controls radio links
Iur	RNC ↔ RNC	Supports inter-RNC handover
Iu	RNC ↔ Core Network	Transfers user and signaling data

2.8.3 Core Network Structure

The UMTS Core Network evolved from the GSM core to support both **circuit-switched**

(CS) and **packet-switched (PS)** domains.

Circuit-Switched Domain:

- **Mobile Switching Centre (MSC):** Handles voice calls and circuit connections.
- **Visitor Location Register (VLR):** Stores subscriber data for roaming users.

Packet-Switched Domain:

- **Serving GPRS Support Node (SGSN):** Manages data session mobility.
- **Gateway GPRS Support Node (GGSN):** Interfaces UMTS with external IP networks.

Common Elements:

- **Home Location Register (HLR):** Central database for user profiles.
- **Authentication Centre (AuC):** Provides security and encryption keys.
- **Equipment Identity Register (EIR):** Tracks valid and invalid devices.

The UMTS core network was designed to be **IP-centric**, paving the way for next-generation all-IP architectures.

2.9 Protocol Stack in UMTS

The UMTS protocol architecture is divided into **three layers**, similar to the OSI model.

1. **Layer 1 – Physical Layer:**
Handles radio transmission, modulation, channel coding, and power control.
2. **Layer 2 – Data Link Layer:**
Contains sublayers:
 - a. **MAC (Medium Access Control):** Allocates radio resources.
 - b. **RLC (Radio Link Control):** Ensures reliable data transfer.
 - c. **PDCP (Packet Data Convergence Protocol):** Compresses IP headers.
 - d. **BMC (Broadcast/Multicast Control):** Handles cell broadcast messages.
3. **Layer 3 – Network Layer:**
 - a. **RRC (Radio Resource Control):** Controls connection setup, handover, and mobility.

2.10 Quality of Service (QoS) in W-CDMA

QoS mechanisms ensure that different services (voice, video, web browsing) receive appropriate network resources.

QoS Classes:

1. **Conversational Class:** Real-time services (e.g., voice, video calls).
2. **Streaming Class:** Continuous data flow (e.g., video streaming).
3. **Interactive Class:** Web browsing, database access.
4. **Background Class:** File transfer, email.

Each class defines parameters like delay, bit error rate, and priority.

2.11 Security Features

Security in UMTS builds upon GSM but offers enhanced mechanisms.

- **Mutual Authentication:** Both network and UE verify each other's identity.
- **Encryption (Ciphering):** Protects data confidentiality using algorithms such as KASUMI.
- **Integrity Protection:** Prevents tampering with control messages.
- **Temporary Identifiers:** Conceal user identity during transmission.

These features make UMTS significantly more secure than 2G systems.

2.12 Performance and Advantages of W-CDMA

Feature	GSM	W-CDMA
Bandwidth	200 kHz	5 MHz
Multiple Access	TDMA	CDMA
Data Rate	64 kbps (max)	Up to 2 Mbps
Modulation	GMSK	QPSK
Handover	Hard	Soft
Services	Voice, SMS	Voice, video, packet data
Network	Circuit-Switched	Circuit + Packet-Switched

Advantages

- High spectral efficiency.
- Improved data capacity and throughput.
- Seamless integration with GSM core networks.
- Enhanced QoS and security.
- Global standardization enabling worldwide roaming.

2.13 Evolution Beyond W-CDMA

The UMTS system continued to evolve through **3GPP releases**:

Release	Enhancement	Description
Release 5	HSDPA	High-Speed Downlink Packet Access (14.4 Mbps).
Release 6	HSUPA	High-Speed Uplink Packet Access (5.76 Mbps).
Release 7	HSPA+	42 Mbps downlink with 64-QAM.
Release 8 onwards	LTE	All-IP architecture, OFDMA access.

Thus, W-CDMA served as the **foundation for the 4G LTE era**.

2.14 Challenges in W-CDMA Deployment

1. **Spectrum Availability:** Limited frequency bands in some regions.
2. **High Infrastructure Costs:** Required new base stations and RNCs.
3. **Complexity of Soft Handover:** Increased signaling and network load.
4. **Interference Management:** Due to the shared-band nature of CDMA.
5. **Initial Device Compatibility:** Early handsets were power-hungry and expensive.

Despite these challenges, W-CDMA became the **dominant 3G technology**, covering over 80 % of global 3G subscriptions at its peak.

2.15 Conclusion

The **W-CDMA (UMTS)** standard marked a major milestone in mobile communication history. Developed as part of the GSM evolutionary path, it transformed mobile networks from voice-centric systems into **high-capacity, multimedia-enabled platforms** capable of supporting global connectivity and internet services.

Its sophisticated **air interface, code-based multiple access, soft handover**, and **robust network architecture** provided the blueprint for all future mobile systems. The seamless coexistence of circuit-switched and packet-switched domains allowed operators to migrate gradually while offering new data-intensive applications.

In retrospect, W-CDMA/UMTS not only fulfilled the ITU's IMT-2000 vision of a **unified global standard** but also laid the technical foundation for **HSPA, LTE, and 5G**—continuing the evolution of wireless communication into the modern broadband era.

CHAPTER 3: THE CDMA2000 STANDARD

3.1 Introduction

The early 2000s marked a major transition in mobile communication — from 2G voice-centric systems to 3G data-driven networks. During this period, two primary evolutionary paths emerged for third-generation mobile technologies:

1. The **W-CDMA (UMTS)** path, which evolved from **GSM networks** (mainly in Europe), and
2. The **CDMA2000** path, which evolved from **IS-95 (cdmaOne)** networks (primarily in North America and parts of Asia).

While both systems adhered to the **ITU IMT-2000** vision for global 3G standards, they developed separately due to differing regional technologies, operators, and spectrum allocations.

CDMA2000, standardized by the **3rd Generation Partnership Project 2 (3GPP2)**, represents the evolutionary upgrade of **IS-95**, offering backward compatibility, higher data rates, and improved capacity — all while maintaining the same core **Code Division Multiple Access (CDMA)** principles.

3.2 Evolution from IS-95 (cdmaOne) to CDMA2000

3.2.1 Background: IS-95 (cdmaOne)

The **IS-95** standard, developed by **Qualcomm** and standardized by **TIA/EIA** in the early 1990s, was the first digital cellular system to use **CDMA (Code Division Multiple Access)** for multiple access. It replaced the earlier analog **AMPS** system by offering:

- Higher capacity,
- Better call quality,
- Enhanced security, and
- Efficient spectrum usage.

IS-95 operated with a **1.25 MHz channel bandwidth**, using **DS-CDMA (Direct Sequence Spread Spectrum)** and supporting data rates up to 14.4 kbps (later up to 115 kbps in IS-95B).

However, as the demand for mobile data and multimedia services grew, IS-95's capacity and data speed became insufficient — leading to the development of **CDMA2000**, a backward-compatible 3G upgrade.

3.2.2 The Evolutionary Path

The evolution from IS-95 to CDMA2000 followed a **stepwise enhancement** approach:

Stage	Standard	Data Rate	Key Features
2G	IS-95A (cdmaOne)	Up to 14.4 kbps	Basic digital CDMA voice
2.5G	IS-95B	Up to 115 kbps	Packet data services
3G	CDMA2000 1X	Up to 153 kbps	Double capacity, high data rate
3.5G	CDMA2000 1xEV-DO	Up to 2.4 Mbps	High-speed data optimized
3.75G	1xEV-DV / Rev A/B	Up to 3.1–14 Mbps	Combined voice + broadband data

This evolutionary model allowed existing IS-95 operators to **upgrade gradually** without replacing all infrastructure or spectrum — a key advantage over GSM operators migrating to W-CDMA.

3.3 Overview of CDMA2000 Family

The **CDMA2000 family** includes several standards that enhance performance and data capability in stages:

1. **CDMA2000 1X (1XRTT)** – First step of 3G, doubling capacity and improving voice/data rates.
2. **CDMA2000 1xEV-DO (Evolution-Data Optimized)** – Focused on data-only services, achieving multi-Mbps speeds.
3. **CDMA2000 1xEV-DV (Evolution-Data and Voice)** – Combined high-speed data and voice.
4. **CDMA2000 Rev A/B/C** – Further revisions providing lower latency and broadband performance.

Together, these versions offered an efficient and flexible upgrade path for operators while keeping interoperability with **IS-95** handsets and base stations.

3.4 Air Interface of CDMA2000

The **air interface** defines how the radio signals are transmitted between the **mobile station (MS)** and the **base transceiver station (BTS)**. CDMA2000 builds on IS-95's direct sequence spread spectrum technique with several refinements.

3.4.1 Multiple Access Scheme

Like IS-95, CDMA2000 uses **Code Division Multiple Access (CDMA)**, where multiple users share the same frequency channel simultaneously, separated by **unique spreading codes**. Each

user's signal is spread over a 1.25 MHz carrier using **Walsh and PN sequences**.

Unlike W-CDMA (which uses 5 MHz carriers), CDMA2000 retains the 1.25 MHz bandwidth, making it easier to deploy in existing cellular bands.

3.4.2 Spreading and Modulation

- **Spreading:** Each data bit is multiplied by a **pseudo-random noise (PN) code** at a higher rate (1.2288 Mcps), spreading the signal's bandwidth.
- **Modulation:** The spread signal is modulated using **QPSK (Quadrature Phase Shift Keying)** for both uplink and downlink.
- **Despreading:** At the receiver, the same PN code is used to despread and recover the original signal.

This process provides resistance to interference, multipath fading, and eavesdropping.

3.4.3 Synchronous Base Stations – Key Difference

One of the most important distinctions between CDMA2000 and W-CDMA is **synchronization**.

- **CDMA2000 uses synchronous base stations**, typically synchronized using **GPS timing signals**.
- This synchronization enables **precise timing alignment**, allowing efficient soft handovers and reduced interference.
- In contrast, **W-CDMA uses asynchronous base stations**, giving more deployment flexibility but at the cost of complex handover procedures.

Synchronous operation simplifies network planning and provides better spectral efficiency — a reason CDMA2000 achieved high capacity in North American deployments.

3.4.4 Channel Bandwidth and Spectrum

- **Nominal channel bandwidth:** 1.25 MHz per carrier
- **Frequency bands:** Typically 800 MHz, 1900 MHz, and 2100 MHz
- **Multi-carrier operation:** Up to three 1.25 MHz carriers can be combined to form 3.75 MHz (for higher throughput).

This narrowband approach allowed CDMA2000 operators to **reuse existing 2G spectrum**, minimizing new licensing costs.

3.4.5 Duplex Technique

CDMA2000 uses **Frequency Division Duplex (FDD)**, where uplink and downlink operate on

separate frequency bands.

This ensures continuous, full-duplex communication between the mobile and the base station.

3.4.6 Channel Structure

CDMA2000 channels are organized into three layers: **logical**, **transport**, and **physical**.

(a) Forward Link (Downlink) Channels

- **Pilot Channel:** Provides phase reference and synchronization.
- **Paging Channel:** Sends system and call-setup information.
- **Forward Traffic Channel:** Carries user data or voice.
- **Sync Channel:** Provides network timing and identification.

(b) Reverse Link (Uplink) Channels

- **Access Channel:** For call initiation and registration.
- **Reverse Traffic Channel:** Carries user voice/data back to BTS.

Each channel is separated by distinct spreading codes, ensuring unique identification.

3.5 Network Architecture of CDMA2000

The CDMA2000 network architecture is designed for **scalability and backward compatibility**, consisting of three main domains:

3.5.1 Mobile Station (MS)

- The user's handset or data terminal.
- Performs radio transmission, power control, and handoff management.
- Contains the **RUIM (Removable User Identity Module)** for authentication.

3.5.2 Radio Access Network (RAN)

- **Base Transceiver Station (BTS):** Handles radio transmission and reception.
- **Base Station Controller (BSC):** Manages radio resources, handoffs, and power control.
- Together, these form the **Radio Access Network (RAN)**, which connects to the Core Network through the **A1/A2 interfaces**.

3.5.3 Core Network

The core network provides switching, routing, and service control:

- **MSC (Mobile Switching Center):** Handles voice calls (circuit-switched).
- **PDSN (Packet Data Serving Node):** Routes packet data traffic to the internet.
- **AAA Server (Authentication, Authorization, Accounting):** Manages user access and billing.

The CDMA2000 core network supports both **circuit-switched and packet-switched** domains.

3.6 Power Control Mechanisms

Power control is crucial in CDMA systems because all users share the same frequency band.

CDMA2000 uses **fast closed-loop power control** (800 Hz rate):

- The base station commands each mobile to **increase or decrease transmit power** by 1 dB steps.
- This minimizes interference and maintains link quality.

Efficient power control directly translates into higher system capacity and improved call quality.

3.7 Handover Procedures

CDMA2000 employs **soft, softer, and hard handover** mechanisms.

- **Soft Handover:** The mobile connects to multiple base stations simultaneously during transition.
- **Softer Handover:** Occurs between sectors of the same base station.
- **Hard Handover:** When moving between frequency bands or systems (e.g., CDMA2000 → EV-DO).

Because of its synchronous base stations, **soft handover** in CDMA2000 is more efficient and reliable than in asynchronous W-CDMA networks.

3.8 Quality of Service (QoS)

CDMA2000 supports differentiated QoS classes to handle various traffic types:

Class	Example Services	Delay Tolerance
Conversational	Voice, Video Call	Very Low
Streaming	Mobile TV, Audio	Low
Interactive	Web Browsing	Medium
Background	Email, File Transfer	High

This ensures optimized performance and resource allocation for each application type.

3.9 Security Features

Security in CDMA2000 builds on IS-95 mechanisms but adds stronger algorithms:

- **Authentication:** Uses CAVE or AKA algorithm for user verification.
- **Encryption:** Protects user data and signaling (using 64-bit or 128-bit ciphers).
- **Integrity Checking:** Detects unauthorized modifications.
- **RUIM/USIM Security:** Stores user identity securely on the card.

These features made CDMA2000 networks resistant to fraud and cloning, common issues in earlier analog systems.

3.10 Comparison: CDMA2000 vs. W-CDMA

Feature	CDMA2000	W-CDMA (UMTS)
Standardization Body	3GPP2 (TIA, ANSI, Qualcomm)	3GPP (ETSI, ARIB)
Evolution Path	From IS-95 (cdmaOne)	From GSM
Channel Bandwidth	1.25 MHz	5 MHz
Base Station Synchronization	Synchronous (GPS-based)	Asynchronous
Spectrum Efficiency	Higher due to tight power control	Slightly lower
Deployment Regions	North America, South Korea, Japan	Europe, Asia, Global
Handover	Easier due to synchronization	Complex inter-node
Initial Data Rate	Up to 153 kbps	Up to 384 kbps
Upgrade Path	1xEV-DO/EV-DV	HSDPA/HSUPA

Both technologies achieved 3G goals under ITU's IMT-2000 vision, though they evolved independently to suit regional demands.

3.11 Case Study: Dominance of CDMA2000 in North America and Asia

3.11.1 North America

In the U.S. and Canada, **CDMA2000** became a leading 3G technology due to:

- **Early adoption by major carriers like Verizon Wireless, Sprint PCS, and Alltel.**
- **Backward compatibility** with IS-95 networks, minimizing upgrade costs.
- **Excellent spectral efficiency** in limited 850/1900 MHz bands.
- **Support from Qualcomm**, which provided strong chipset and infrastructure ecosystems.

Operators found CDMA2000 1X and 1xEV-DO particularly attractive for **mobile broadband** before LTE's arrival. Verizon's "3G EV-DO" network, launched in 2003, became one of the first nationwide high-speed mobile data networks in the U.S.

3.11.2 Asia (Korea, Japan, India, China)

- **South Korea:** One of the earliest adopters of CDMA2000, led by **SK Telecom and KT Freetel**, offering advanced data and video services.
- **Japan:** **KDDI's au** network used CDMA2000 1xEV-DO, achieving superior coverage and data performance compared to W-CDMA in early 2000s.
- **India:** Operators like **Reliance and Tata Indicom** deployed CDMA2000 networks for

cost-effective nationwide coverage.

- **China:** Deployed **CDMA2000 networks (China Telecom)** alongside W-CDMA and TD-SCDMA systems, providing multi-standard service diversity.

These regions leveraged CDMA2000's **lower cost, efficient spectrum use, and faster rollout**, making it highly competitive before the LTE transition.

3.12 Evolution Beyond CDMA2000

The CDMA2000 standard evolved through several releases:

- **CDMA2000 1xEV-DO (Rel 0):** 2.4 Mbps downlink.
- **EV-DO Rev A:** 3.1 Mbps downlink, 1.8 Mbps uplink.
- **EV-DO Rev B:** Multi-carrier aggregation (up to 14.7 Mbps).
- **Rev C (UMB – Ultra Mobile Broadband):** Planned as 4G successor but replaced by LTE.

Eventually, most CDMA2000 operators migrated to **LTE**, retaining backward compatibility through **multi-mode devices**.

3.13 Advantages and Limitations

Advantages

- Backward compatibility with IS-95.
- Narrow channel bandwidth (1.25 MHz) → easy reuse of spectrum.
- Excellent spectral and power efficiency.
- Mature ecosystem in North America and Asia.
- High reliability and stable voice quality.

Limitations

- Fragmented global deployment.
- Limited scalability compared to 5 MHz systems like W-CDMA.
- Complex handover with LTE in later years.
- Declining device support after LTE's dominance.

3.14 Applications and Services

CDMA2000 enabled a wide range of consumer and enterprise services:

- **Voice over Packet Networks (VoIP)**
- **High-Speed Internet and Email**
- **Video Calling and Streaming**
- **Mobile Commerce (m-commerce)**
- **Wireless Broadband Access**

- **Push-to-Talk and GPS-based Applications**

It played a key role in transforming mobile phones into multipurpose digital devices.

3.15 Conclusion

The **CDMA2000 standard** represented a major step in the evolution of mobile communications, bridging the gap between 2G voice networks and modern broadband wireless systems.

By evolving seamlessly from IS-95 (cdmaOne), CDMA2000 provided carriers with a cost-effective and spectrally efficient upgrade path to 3G. Its **synchronous base station architecture, strong power control, and backward compatibility** gave it technological advantages that led to dominance in **North America, South Korea, and Japan** during the early 3G era.

Although CDMA2000 was eventually overtaken by the global adoption of **LTE**, its innovations — such as efficient spectrum usage, robust QoS, and high-speed data protocols — laid the foundation for many of today's mobile broadband technologies.

CHAPTER 4: TECHNICAL AND MARKET PERFORMANCE SHOWDOWN

4.1 Introduction

The early 2000s marked an era of intense competition between two major 3G standards—CDMA2000, primarily adopted in North America and parts of Asia, and W-CDMA (UMTS), the evolution path favored by GSM operators in Europe and other regions. Both aimed to deliver higher data rates, better voice quality, and seamless mobility, fulfilling the vision of the ITU's IMT-2000 mandate. However, deep-seated differences in design philosophy, air interface, network architecture, market timing, and powerful intellectual property frameworks resulted in a fragmented global landscape.

While W-CDMA eventually became the global mainstream 3G technology by subscriber volume, CDMA2000's dominance in key, high-value markets like the United States, South Korea, Japan, and India during the formative years of mobile data reflected its superior early deployment, mature ecosystem, and, in several key aspects, greater technical efficiency. This chapter presents a detailed comparative analysis of their **data rates**, **spectral efficiency**, **voice capacity**, and **handoff mechanisms**, followed by a discussion on the so-called “**standards war**” that prevented the establishment of a single global 3G standard.

4.2 Comparative Analysis

4.2.1 Data Rates

A primary driver for 3G was the demand for mobile broadband. Here, the two standards took different evolutionary paths, which had a major impact on market timing.

- **CDMA2000** first launched **1xRTT** (Radio Transmission Technology), which initially supported peak data rates **up to 153 kbps** on the forward and reverse links. This was quickly followed by **1xEV-DO (Evolution-Data Optimized)**.
 - **EV-DO Revision 0 (Rev. 0)**, launched in 2002, was a significant leap, offering a peak downlink of **2.4 Mbps**.
 - **EV-DO Revision A (Rev. A)**, launched in 2004, further improved this to **3.1 Mbps** on the downlink and, crucially, boosted the uplink to **1.8 Mbps**, enabling more symmetric applications like video calling.

- **W-CDMA (UMTS)**, launched commercially around 2001 (as Release 99), began with a theoretical peak data rate of **384 kbps** for users with high mobility and up to 2 Mbps for stationary users (though 384 kbps was the common commercial benchmark). The major leap for W-CDMA came later with the introduction of **HSPA (High-Speed Packet Access)**.
 - **HSDPA (Downlink)**, launched around 2006, pushed peak rates to **14.4 Mbps**.
 - **HSUPA (Uplink)** followed, enabling uplink speeds of **5.76 Mbps**.
 - **HSPA+** later evolved this even further, with theoretical peaks exceeding 42 Mbps.

Technical Analysis of Data Rate Differences:

The most significant architectural difference was that **EV-DO was a data-only carrier**, separate from the 1xRTT voice carrier. It was designed as an all-IP, packet-switched overlay. This allowed its scheduler to be "channel-aware," opportunistically allocating all network power and resources to users experiencing good signal conditions in a given instant. This design, pioneered by Qualcomm, was highly efficient for bursty internet traffic.

W-CDMA, in contrast, initially carried both circuit-switched voice and packet-switched data on the **same 5 MHz carrier**. This integrated design was more complex. The breakthrough for W-CDMA, **HSPA**, adopted key principles that EV-DO had proven: it introduced **fast, channel-aware scheduling, Hybrid ARQ (H-ARQ)** for rapid retransmission, and **Adaptive Modulation and Coding (AMC)**. These additions allowed W-CDMA to finally surpass EV-DO's performance, but at a later date.

Standard	Key Technology	Peak Downlink	Peak Uplink	Typical Launch
CDMA2000	1xRTT	153 kbps	153 kbps	2000
	1xEV-DO Rev. 0	2.4 Mbps	153 kbps	2002
	1xEV-DO Rev. A	3.1 Mbps	1.8 Mbps	2004
W-CDMA	R99 (UMTS)	384 kbps	64-128 kbps	2001-2003
	HSDPA	14.4 Mbps	384 kbps	2006

	HSPA (w/ HSUPA)	14.4 Mbps	5.76 Mbps	2007
--	-----------------	-----------	-----------	------

Interpretation:

The table clearly shows CDMA2000's crucial **time-to-market advantage**. Operators like Verizon Wireless in the US and KDDI in Japan leveraged EV-DO Rev. 0 to offer "true" broadband-like speeds (over 1 Mbps in real-world use) years before their W-CDMA competitors. This allowed them to capture the valuable early-adopter market for mobile data. W-CDMA, while slower to start, built a superior long-term evolutionary path with HSPA, which ultimately provided higher peak speeds and became the foundation for the global transition to 4G.

4.2.2 Spectral Efficiency

Spectral efficiency, measured in bits per second per Hertz (bps/Hz), is arguably the most critical metric for a wireless operator, as spectrum is a finite and costly resource.

- **CDMA2000** utilized a **1.25 MHz** channel bandwidth (for 1xRTT and for each EV-DO carrier). This was a direct legacy from its 2G predecessor, IS-95 (cdmaOne).
- **W-CDMA** utilized a much wider **5 MHz** channel bandwidth.

This five-fold difference in channel size was a fundamental design choice. The 5 MHz channel in W-CDMA provided a higher "processing gain" (also called spreading gain), which allowed it to better average out multipath fading and interference. This made the link more robust and was designed to be future-proof for the high data rates of HSPA.

However, the 1.25 MHz channel of CDMA2000 offered immense **deployment flexibility**. An operator could deploy a single 1xRTT carrier for voice and, in an adjacent 1.25 MHz block, deploy an EV-DO carrier for data. This was highly efficient in markets with fragmented or limited spectrum.

Technology	Spectral Efficiency (bps/Hz)	Channel Bandwidth (MHz)
CDMA2000 1xRTT	~0.3	1.25
CDMA2000 1xEV-DO Rev. A	~1.2 - 1.5	1.25

W-CDMA (R99)	~0.6	5
W-CDMA (HSPA)	~2.0+	5

Analysis:

On a "per-Hertz" basis, EV-DO Rev. A was significantly more efficient than initial W-CDMA R99. The 1.25 MHz channel allowed for a more granular "reuse" of spectrum, which was valuable in congested urban markets.

A key concept in both standards was "**cell breathing**." As more users connect to a CDMA cell, the overall interference (noise floor) rises. To maintain the required signal-to-interference ratio (E_b/N_0), all users must increase their transmit power. This effectively "shrinks" the cell's coverage boundary. While both standards experienced this, CDMA2000's famously precise and fast power control mechanism (running at 800 Hz) was considered more effective at managing this interference, allowing cells to be packed more densely and maximizing overall *system-level* spectral efficiency. W-CDMA's power control was also fast (1500 Hz), but its wider channel had different interference-averaging properties.

Ultimately, W-CDMA's HSPA evolution, with its fast schedulers and adaptive modulation, achieved higher spectral efficiency, but CDMA2000's 1.25 MHz architecture provided superior efficiency in the early 3G deployments.

4.2.3 Voice Capacity

Before mobile data, voice was the primary revenue driver. Therefore, maximizing the number of simultaneous voice calls per channel was a critical design goal.

- **CDMA2000 1xRTT** used the **EVRC (Enhanced Variable Rate Codec)**, which operated at a peak rate of 8.55 kbps but could "rate down" during pauses in speech to save power and reduce interference.
- **W-CDMA** used the **AMR (Adaptive Multi-Rate)** vocoder, which was more flexible. It could operate at various rates (e.g., from 12.2 kbps down to 4.75 kbps).

This vocoder flexibility was key. The AMR codec could dynamically change its bit rate not just based on speech, but based on *network load*. If a W-CDMA cell became congested, the Radio Network Controller (RNC) could command all handsets to switch to a lower-rate AMR mode, trading some voice quality to increase overall capacity. This provided a very "soft" capacity limit.

Parameter	CDMA2000 1xRTT	W-CDMA
Voice Users per 1.25 MHz	~35–40	~25 (at 12.2 kbps AMR)
Voice Users per 5 MHz	~140-160 (Theoretically 4x)	~100-120 (at 12.2 kbps AMR)
Vocoder Type	EVRC (8.55 kbps)	AMR (12.2 kbps, flexible)

Observation:

In a direct, "apples-to-apples" comparison of a 5 MHz spectrum block, CDMA2000 1xRTT provided **higher voice capacity** than W-CDMA. This was a significant advantage in spectrum-constrained regions like South Korea and India, where voice services were still the dominant source of revenue.

Furthermore, CDMA2000 1xRTT was **fully backward compatible with 2G IS-95 (cdmaOne) networks**. An IS-95 phone could receive service from a 1xRTT base station, and a 1xRTT phone could receive service from an IS-95 base station. This provided an incredibly smooth and cost-effective migration path for operators, who did not need to build a separate, overlay network. W-CDMA, being an evolution of GSM, had no backward compatibility with cdmaOne.

4.2.4 Handoff Mechanisms

Efficient handoff (or handover) is crucial for maintaining call continuity and data session integrity as a user moves between cells. This was the area of the *single greatest technical difference* between the two standards, driven by one decision: **network timing**.

- **CDMA2000 networks were synchronous.** Every base station was locked to a common, high-precision time reference from the **GPS** satellite system.
- **W-CDMA networks were asynchronous.** Base stations did not share a common time reference and operated independently.

This difference had profound consequences for handoff.

- **CDMA2000:** Because all base stations were time-synced, a mobile device could easily listen to multiple base stations simultaneously. It used **Soft Handoff** (make-before-break), where the phone would establish a connection with a new cell *before* dropping the old one. During the handoff, the phone was connected to two or more base stations at

once, which increased reliability at the cell edge. This was inherited from IS-95 and was a major reliability advantage.

- **W-CDMA:** Because the network was asynchronous, a true soft handoff between two different base stations (NodeBs) was extremely complex. While W-CDMA supported "softer handoff" (between two sectors on the *same* NodeB) and had modes for "soft handoff," it was much more complex and network-intensive than in CDMA2000. Many handoffs were effectively "**hard handoffs**" (break-before-make), which were faster but had a higher risk of dropping the call or data session.

Aspect	CDMA2000	W-CDMA
Core Principle	Synchronous (GPS-timed)	Asynchronous
Primary Handoff	Soft Handoff (Make-before-break)	Hard/Softer Handoff
Description	Connection maintained with multiple base stations simultaneously.	Primarily hard handoff; soft handoff was more complex to implement.
Advantage	Extremely seamless transition, very low call-drop rate.	Simpler deployment (no GPS required at all sites).
Drawback	Higher network overhead (more backhaul traffic), reliance on GPS.	Less seamless mobility, especially in early versions.

Summary:

CDMA2000's GPS-synchronized soft handoff mechanism was a major technical advantage. Users in fast-moving vehicles experienced virtually drop-free voice calls, which reinforced consumer trust and carrier reputation. The trade-off was a reliance on GPS, which could be difficult for indoor or dense urban "canyon" deployments. W-CDMA's asynchronous nature gave it more deployment flexibility but at the cost of handoff reliability, a problem that was only fully solved in later releases.

4.3 The “Standards War”

The so-called 3G “standards war” was not just a technological battle—it was an economic, political, and strategic struggle between different regions, companies, and regulatory bodies.

4.3.1 Regional Divide

- **North America, Japan, and South Korea:** These regions had strong incumbent 2G CDMA (IS-95) networks. Operators like Verizon, Sprint, SK Telecom, and KDDI favored **CDMA2000** as the logical, cost-effective, and backward-compatible upgrade path.
- **Europe and most of Asia/Rest of World:** This was the "GSM bloc." With over 80% of the world's mobile users on GSM, operators like Vodafone, Orange, and T-Mobile standardized on **W-CDMA (UMTS)**. The 3GPP (3rd Generation Partnership Project) was formed by ETSI and other GSM standards bodies to develop this as the explicit successor to GSM.

4.3.2 Intellectual Property and Licensing

This was the core of the "war." Qualcomm, the inventor of many foundational CDMA technologies, held the majority of essential patents for both CDMA2000 and W-CDMA.

- For **CDMA2000**, Qualcomm's IP was dominant, but the licensing model was well-established from the 2G era.
- For **W-CDMA**, European manufacturers (e.g., Nokia, Ericsson) and standards bodies (ETSI) had deliberately designed the standard to create a more distributed pool of intellectual property, partly as a strategic move to *counter* Qualcomm's IP dominance and reduce royalty payments. This led to years of intense legal and commercial battles over royalty rates, slowing down W-CDMA's initial development and adoption.

4.3.3 Market Timing

CDMA2000's early, faster, and smoother rollout gave it a significant advantage in the early 2000s. However, W-CDMA's global roaming capabilities (via the GSM-inherited SIM card) and GSM interoperability made it more attractive for international carriers. This resulted in two completely separate, incompatible ecosystems. A W-CDMA phone from Europe could not roam on Verizon's CDMA2000 network in the US, and vice-versa, creating a major headache for international travelers and fragmenting the device market.

4.3.4 Lack of a Unified Global Standard

The ITU's IMT-2000 vision had called for a single, global 3G standard. What it got instead was a "family" of five standards (including W-CDMA, CDMA2000, and China's TD-SCDMA). Differences in spectrum allocation, backward compatibility requirements, and intense industrial lobbying from the "Qualcomm camp" and the "GSM/ETSI camp" ensured a fragmented 3G landscape.

4.4 Market Performance

By 2007, CDMA2000 had a strong global footprint with over 400 million subscribers, led by high-value markets and major carriers like Verizon (US), KDDI (Japan), and SK Telecom (Korea). However, W-CDMA's subscriber base was growing at a faster rate as the massive global base of 2G GSM operators began their upgrades.

A critical, non-technical factor was the **device ecosystem**. The W-CDMA standard, being the GSM evolution, was backed by the entire global handset industry (Nokia, Sony Ericsson, Samsung, Motorola). This created a vast, competitive, and innovative handset market with immense economies of scale. The CDMA2000 device ecosystem was much smaller and more controlled by specific carriers, leading to less choice and slower innovation in handsets.

Year	CDMA2000 Subscribers (millions)	W-CDMA Subscribers (millions)
2003	110	20
2005	270	80
2007	410	190
2010	450	600

Interpretation:

While CDMA2000 was technically superior in many aspects during the early phases (voice capacity, handoff, data speed-to-market), W-CDMA's **massive economies of scale** and **dominant device ecosystem** eventually won the market war. By 2010, W-CDMA had decisively

overtaken CDMA2000 in global subscribers and had a clear, dominant evolutionary path (HSPA+) leading into 4G.

4.5 Summary of Technical and Market Findings

Parameter	CDMA2000	W-CDMA	Advantage
Data Rate (Initial)	Higher earlier (EV-DO)	Higher later (HSPA)	CDMA2000 (early), W-CDMA (later)
Spectral Efficiency	Better in narrow bands (1.25 MHz)	Better in wide bands (5 MHz)	CDMA2000 (early), W-CDMA (later)
Voice Capacity	Higher (per MHz)	Moderate, but flexible (AMR)	CDMA2000
Handoff Mechanism	Soft (GPS-Synchronous)	Hard/Softer (Asynchronous)	CDMA2000
Ecosystem Support	Limited regions (US, Korea, Japan)	Global (GSM-based)	W-CDMA
Backward Compatibility	Strong (with IS-95)	GSM only (no IS-95)	CDMA2000
Device Availability	Moderate, carrier-controlled	Extensive, competitive	W-CDMA
IP/Licensing	Dominated by Qualcomm	Contentious, more distributed	W-CDMA (from mfg. perspective)

CHAPTER 5: CONCLUSION: LEGACY AND EVOLUTION TO 4G

5.1 The Legacy of CDMA2000

Despite its eventual decline in market share, CDMA2000's influence on modern wireless communications is profound. Its innovations in code division multiplexing, soft handoff, and efficient packet data scheduling directly informed the design of later generations, including 4G LTE.

Key Contributions:

- **Spread Spectrum and Power Control:** The algorithms perfected in CDMA2000 for managing interference in a shared-spectrum environment are foundational to all modern wireless systems.
- **EV-DO Packet Scheduling:** The EV-DO standard was a breakthrough. It was one of the first mobile standards to be **entirely packet-switched** for data, with a "channel-aware" scheduler that prioritized users with good signal conditions. This philosophy of fast, opportunistic scheduling and always-on packet data became the **absolute bedrock of 4G LTE's design**, which is also entirely packet-switched (even for voice, via VoLTE).
- **Hybrid ARQ (H-ARQ):** The fast retransmission mechanisms used in EV-DO to correct errors at the physical layer became a mandatory component of both HSPA and LTE.
- **Backward Compatibility:** CDMA2000 demonstrated the immense market value of a smooth, cost-effective migration path from 2G, a philosophy later adopted by LTE through its required interoperability with 3G networks.

The evolutionary path for CDMA2000, a proposed standard called UMB (Ultra Mobile Broadband), was ultimately abandoned as its key backers (led by Verizon) saw the global momentum of the 3GPP/LTE path and chose to join it, ending the standards war.

5.2 The Legacy of W-CDMA

W-CDMA, though slower to start, established the global foundation for mobile broadband. Its integration with GSM networks, SIM-based authentication, and widespread device ecosystem made it the backbone of 3G worldwide.

Key Contributions:

- **The 3GPP Evolutionary Path:** W-CDMA's network architecture, managed by the 3GPP, provided a **clear, logical, and continuous evolutionary path**. The UTRAN (UMTS Terrestrial Radio Access Network) evolved into the E-UTRAN (Evolved UTRAN) for LTE. The Packet-Switched Core network evolved directly into the **Evolved Packet Core (EPC)**. This step-by-step evolution allowed operators to upgrade networks incrementally, leveraging existing investments and ensuring a smooth transition.
- **The SIM Card (USIM):** The legacy of the GSM SIM card, which evolved into the USIM (Universal Subscriber Identity Module) for W-CDMA, cannot be overstated. It **decoupled the subscriber's identity from the physical device**, a concept central to GSM's success. This was carried directly into LTE, enabling global roaming and easy device switching—a key market advantage that the non-SIM-based CDMA2000 world struggled to match.
- **HSPA:** The HSPA family of technologies (HSDPA, HSUPA, HSPA+) proved that the W-CDMA air interface was incredibly robust and scalable, serving as the essential "3.5G" bridge that made the transition to the all-IP, high-speed world of 4G possible.

5.3 Convergence in 4G LTE

By the time 4G LTE (Long-Term Evolution) emerged around 2009, both camps recognized the need for a unified global standard. LTE, also developed by the 3GPP, represented a convergence of ideas from *both* sides, though it was technically a successor to W-CDMA.

LTE moved away from CDMA as its primary air interface. Instead, it adopted:

- **OFDMA (Orthogonal Frequency Division Multiple Access)** for the downlink.
- **SC-FDMA (Single-Carrier FDMA)** for the uplink.

This shift was made to solve problems inherent in CDMA. CDMA systems are limited by *intra-cell interference* (all users interfere with each other), requiring complex power control. **OFDMA** elegantly solves this by dividing the channel into thousands of small, *orthogonal* sub-carriers, so users within a cell do not interfere with each other. This simplified receiver design and was much more flexible for wide channels and MIMO antenna systems.

However, the *philosophical and technical lessons* from both 3G standards converged in LTE:

- **From CDMA2000 (EV-DO):** The core concepts of fast, channel-aware scheduling, all-IP packet switching, and H-ARQ.

- **From W-CDMA (HSPA):** The global ecosystem, SIM-based identity, flexible wideband operation, and the Evolved Packet Core network architecture.

Thus, LTE became the first truly global standard, uniting former rivals under a single IP-based umbrella.

5.4 Lessons Learned

The 3G standards war provides several critical lessons for the telecommunications industry:

- **Technology Alone Doesn't Win Markets:** CDMA2000 was arguably the better, more efficient technology in the 2000-2004 period. However, W-CDMA won the "long game" because it was "good enough" and had the backing of the entire global GSM ecosystem (80%+ of the market).
- **Ecosystems and Economies of Scale are Decisive:** The massive, competitive W-CDMA handset and equipment market drove down costs and accelerated innovation (like HSPA) at a rate the smaller CDMA2000 ecosystem couldn't match.
- **Fragmentation Hinders Global Roaming:** The lack of a single standard created consumer confusion and limited the market, a mistake the industry aggressively corrected with 4G.
- **Backward Compatibility is Crucial for Migration:** CDMA2000's smooth 2G-to-3G path was its greatest strength, while W-CDMA's smooth 3G-to-4G core network path was its.

5.5 Future Outlook

As the world transitions from 4G LTE to 5G and beyond, the contributions of both 3G standards remain embedded in modern wireless design. 5G's **massive MIMO** (Multiple-Input Multiple-Output) systems rely on the interference management principles learned in CDMA.

Furthermore, **NOMA (Non-Orthogonal Multiple Access)**, a candidate technology for 5G and 6G, is essentially a rebirth of CDMA's core idea. NOMA allows multiple users to share the *same time and frequency* resource, separating them by *power level* and using advanced signal processing (like Successive Interference Cancellation) at the receiver. This is a direct intellectual descendant of the shared-spectrum, interference-limited design pioneered by CDMA.

5.6 Conclusion

The CDMA2000 vs. W-CDMA battle was both a technical rivalry and a strategic divergence that shaped global telecommunications for a decade. It was not a simple case of one technology defeating another; it was a complex interplay of technical performance, market timing, IP politics, and evolutionary pathways.

CDMA2000 was the "sprinter," delivering superior, high-performance mobile data first and proving the market for it. Its technical excellence in voice capacity, handoff reliability, and efficient packet scheduling cemented its place in mobile history.

W-CDMA was the "marathon runner," leveraging its unparalleled global ecosystem, economies of scale, and a unified evolutionary path to ultimately define the mainstream mobile broadband experience for the majority of the world.

The true winner, however, was the industry itself. This intense competition forced the rapid innovation—from EV-DO to HSPA—that bridged the gap from 2G's simple voice calls to the unified, all-IP, high-speed world of 4G LTE. Together, these two rivals formed the dual pillars upon which our modern, connected world was built.

REFERENCES

1. **Holma, H., & Toskala, A. (Eds.). (2007).** *WCDMA for UMTS: HSPA Evolution and LTE*. John Wiley & Sons.
 - <https://onlinelibrary.wiley.com/book/10.1002/9780470686461>
2. **Garg, V. K. (2000).** *IS-95 CDMA and cdma2000: Cellular/PCS Systems Implementation*. Prentice Hall.
 - <https://books.google.com/books?id=tJhp7C6S6eMC>
3. **Viterbi, A. J. (1995).** *CDMA: Principles of Spread Spectrum Communication*. Addison-Wesley.
 - <https://books.google.com/books?id=13-1AAAAIAAJ>
4. **Dahlman, E., Parkvall, S., Sköld, J., & Beming, P. (2008).** *3G Evolution: HSPA and LTE for Mobile Broadband*. Academic Press.
 - <https://www.sciencedirect.com/book/9780123725332/3g-evolution>
5. **International Telecommunication Union (ITU-R). (2007).** *Recommendation M.1457-13: Detailed specifications of the terrestrial radio interfaces of International Mobile Telecommunications-2000 (IMT-2000)*.
 - <https://www.itu.int/rec/R-REC-M.1457/en>
6. **3GPP. (2001).** *TS 25.101: User Equipment (UE) radio transmission and reception (FDD) (Release 99)*. 3rd Generation Partnership Project.
 - <https://portal.3gpp.org/desktopmodules/Specifications/SpecificationDetails.aspx?specificationId=1356>
7. **3GPP2. (2004).** *C.S0002-A: Physical Layer Standard for cdma2000 Spread Spectrum Systems (Revision A)*. 3rd Generation Partnership Project 2.
 - https://www.3gpp2.org/Public_html/Specs/C.S0002-A_v2.0_040825.pdf
8. **3GPP2. (2004).** *C.S0024-A v3.0: cdma2000 High Rate Packet Data Air Interface Specification (Revision A)*. 3rd Generation Partnership Project 2.
 - https://www.3gpp2.org/Public_html/Specs/C.S0024-A_v3.0_040825.pdf
9. **Saugstrup, D., & Henten, A. (2006).** "3G Standards: the battle between WCDMA and CDMA2000." *Info*, 8(4), 10-20.
 - https://www.researchgate.net/publication/235314622_3G_Standards_the_battle_b

etween WCDMA and CDMA2000

10. **Bender, P., Black, P., Grob, M., Padovani, R., Sindhushayana, N., & Viterbi, A. (2000).** "CDMA/HDR: A bandwidth-efficient high-speed wireless data service for nomadic users." *IEEE Communications Magazine*, 38(7), 70-77.
 - <https://ieeexplore.ieee.org/document/858464>
11. **Cai, J., & Goodman, D. J. (1997).** "General Packet Radio Service in GSM." *IEEE Communications Magazine*, 35(10), 122-131.
 - <https://ieeexplore.ieee.org/document/623116>
12. **Esteves, J., Gonia, P., & Hrastar, S. (2003).** "The 1xEV-DO high-rate packet data system." *IEEE Communications Magazine*, 41(3), 140-146.
 - <https://ieeexplore.ieee.org/document/1183319>
13. **Laiho, J., Wacker, A., & Novosad, T. (2002).** *Radio Network Planning and Optimisation for UMTS*. John Wiley & Sons.
 - <https://onlinelibrary.wiley.com/book/10.1002/0470845561>
14. **Lee, J. S., & Miller, L. E. (2000).** "Performance comparison of W-CDMA and cdma2000." *IEEE Wireless Communications*, 7(1), 18-29.
 - <https://ieeexplore.ieee.org/document/826330>
15. **Oscilloquartz SA. (2003).** "Do CDMA based mobile networks need to be synchronized?" *White Paper*.
 - <https://www.precisotechnology.com.my/wp-content/uploads/2017/04/Do-CDMA-Based-Mobile-Networks-Need-To-Be-Synchronized.pdf>
16. **Hsing, C., & Zeng, M. (2003).** "A performance study of 3G wireless technologies: WCDMA, cdma2000 and TD-SCDMA." *Proceedings of the 36th Annual Hawaii International Conference on System Sciences*.
 - <https://ieeexplore.ieee.org/document/1173693>