

STATION# 1: EMPTY

TONNAGE: 850 T

LEAVE TONGS IN YES

STATION# 2: PREFORM

TONNAGE: 1400 T

STATION# 3: FINISH

TONNAGE: 1180 T

SPECIAL FORGE INSTRUCTION
RUN HOT, WATCH FLASH

SPECIAL TRIM INSTRUCTION
TRIM FROM TOP

BILLET HEATING REQUIREMENTS

NUMBER OF COILS	3	
BILLET TEMPERATURE	2275	°F
LOW REJECT TEMPERATURE	2200	°F
HI REJECT TEMPERATURE	2400	°F
SCRAP TEMPERATURE	2425	°F
BILLET DIAMETER	2.375	"
BILLET LENGTH	3.944	"
BILLET WEIGHT	4.95	LB
BILLET GRADE MAT'L	1045 STEEL	
COIL NUMBER	25Z3	
% OF COIL AMPS		
COIL# 1:	46.5	
COIL# 2:	54.5	
COIL# 3:	61.0	
CYCLE TIME	12	secs

FORGE PRESS REQUIREMENTS

WEDGE	0.125
DIE STATIONS	3
KICK SETUP	DIE POSITION KO# DWELL
HIT# 1	1 1 0.50
HIT# 2	2 2 0.75
HIT# 3	3 3 1.00

DIE LUBE REQUIREMENTS

LUBE TYPE	CONDAT ORAFOR 630
LUBE CONCENTRATION	2100
LUBE PROGRAM	14
LUBE HEAD NUMBER	LARGE CONE

BILLET SPACERS REQUIREMENTS

SPACER DIAMETER	2.500	"
NUMBER OF SPACERS	5	

PICK AND PLACE ROBOT SETTINGS

ROBOT HEAD NUMBER	2	
COOL DOWN	8	secs
DROP POSITION	3	
Z OFFSET	0.040	

TRIM PRESS REQUIREMENTS

SHUT HEIGHT	16.250	"
NITROGEN	500	PSI
PART COOLING REQUIREMENT	FANS ON	
	1 SLOW CONVEYOR	
	HOT BOX	
SCRAP DISPOSAL	CARBON	