

STATION# 1: EMPTY TONNAGE: 850 T LEAVE TONGS IN YES STATION# 2: PREFORM TONNAGE: 1400 T STATION# 3: FINISH TONNAGE: 1180 T SPECIAL FORGE INSTRUCTION RUN HOT, WATCH FLASH SPECIAL TRIM INSTRUCTION TRIM FROM TOP	BILLET HEATING REQUIREMENTS NUMBER OF COILS3 BILLET TEMPERATURE2275°F LOW REJECT TEMPERATURE2200°F HI REJECT TEMPERATURE2400°F SCRAP TEMPERATURE2425°F BILLET DIAMETER2.375" BILLET LENGTH3.944" BILLET WEIGHT4.95LB BILLET GRADE MAT'L1045 STEEL COIL NUMBER25Z3 % OF COIL AMPS COIL# 1: 46.5 COIL# 2: 54.5 COIL# 3: 61.0 CYCLE TIME12secs FORGE PRESS REQUIREMENTS WEDGE0.125 DIE STATIONS3 KICK SETUPDIE POSITION KO# DWELL HIT# 1110.50 HIT# 2220.75 HIT# 3331.00 DIE LUBE REQUIREMENTS LUBE TYPECONDAT ORAFOR 630 LUBE CONCENTRATION2100 LUBE PROGRAM14 LUBE HEAD NUMBERLARGE CONE BILLET SPACERS REQUIREMENTS SPACER DIAMETER2.500" NUMBER OF SPACERS5 PICK AND PLACE ROBOT SETTINGS ROBOT HEAD NUMBER2 COOL DOWN8secs DROP POSITION3 Z OFFSET0.040 TRIM PRESS REQUIREMENTS SHUT HEIGHT16.250" NITROGEN500PSI PART COOLING REQUIREMENTFANS ON 1 SLOW CONVEYOR HOT BOX SCRAP DISPOSALCARBON		
FORM#: 10899	REVISION: A	ECN: 11583	DATE: 04/25/2023