RTL8211D-VB/8211E-VB/8211E-VL Schematic

REV.1.7

Page Index

1. Title Page
2. PHY
3. MDI
4. CMC
5. Power
6. History

Title	RTL8211D/8211E	REALTEK
Size A3	Document Number TITLE PAGE	Rev
Date:	Sheet 1 of 6	

External clock and Crystal

External clock source from OSC or Chipset.



If use external clock then the XTAL2 need connect to GND for RTL8211E.
R28 NC for RTL8211D

Enable/Disable SWREG

AVDD33



Connect ENSWREG to AVDD33 to enable Switching regulator or connect ENSWREG to GND to disable Switching regulator.

Enable SWREG: R75
Disable SWREG: R77

PHY Reset

DVDD33

For wake on LAN function, please keep PHYRSTB pin to high.

WOL & Interrupt



RTL8211D/8211E



RGMII Interface

Place filter network close to RX_CLK.
Reserved for EMI



Power



RSET



Configuration Setting



Output Clock

Place filter network close to CLK125.
Reserved for EMI



MDC/MDIO



R36 for RTL8211D
R147 for RTL8211E

Title	RTL8211D/8211E	REALTEK
Size A3	Document Number PHY	Rev
Date:	Sheet 2 of 6	

RJ45 & Transformer



The transformer center tap must be short together

LED



TVS



U4,U5 Reserve for cable discharge.

Title	RTL8211D/8211E	REALTEK
Size A3	Document Number MDI	Rev
Date:	Sheet 3 of 6	

Common mode choke (Option)



L2,L3,L4,L5 Reserve for EMI, close to transformer.

Title	RTL8211D/8211E	REALTEK
Size A3	Document Number CMC	Rev
Date:	Sheet 4 of 6	

3.3V Power



3.3/2.5V/1.8/1.5V RGMII Power



1.05V Power



External Power Source (1.05V)



VDDREG



Title	RTL8211D/8211E	REALTEK
Size A3	Document Number POWER	Rev
Date:	Sheet 5 of 6	

History

Version	Date	
V1.0	2010.8.10	First release
V1.1	2010.12.3	Modify LED2 and MDIO pull up circuit
V1.2	2011.1.30	Remove ACR page
V1.3	2011.3.22	Add common mode choke for EMI Modify XTAL2 for RTL8211D
V1.4	2011.4.22	Modify transformer pin name
V1.5	2011.5.2	Add RTL8211E-VL 1.5V RGMII application
V1.6	2011.6.27	Add RTL8211E-VL 1.8V RGMII application
V1.7	2012.10.23	Modify Note 1 for P5_Power