Learn RISC-V CPU Implementation and BSV
### (BSV: a High-Level Hardware Design Language)

Rishiyur S. Nikhil

L2: Overview of the RISC-V ISA

bluespec ⬡

What is an ISA?

Architectural State

The "architectural state" is the state that is visible to instructions. For RV32I, these are:

- The PC (program counter)
- 32 General-Purpose Registers (GPRs, the "register file")
- Memory (byte-addressed)

(More architectural state is defined for RV64I, and for most extensions A, F, D, Vector, ...)

The architectural state *does not include* other registers, buffers, FIFOs, memories that may be present in an implementation (they are not visible to instructions).
As such, the architectural state is present in every RISC-V implementation, from tiny CPUs for IoT devices to massive warehouse-scale servers.
Compilers only care about/know about architectural state.

Modularity of the RISC-V ISA

RISC-V Instruction Encodings

From the RISC-V specification documents:

130							*Volume I: RISC-V Unprivileged ISA V20191213*

| 31	27	26	25	24		20	19	15	14	12	11	7	6	0	
funct7				rs2			rs1		funct3		rd		opcode		R-type
imm[11:0]							rs1		funct3		rd		opcode		I-type
imm[11:5]				rs2			rs1		funct3		imm[4:0]		opcode		S-type
imm[12|10:5]				rs2			rs1		funct3		imm[4:1|11]		opcode		B-type
imm[31:12]											rd		opcode		U-type
imm[20|10:1|11|19:12]											rd		opcode		J-type

RISC-V Instruction Encodings; J-type immediates

For JAL instruction

RISC-V Instruction Encodings; B-type immediates

For BRANCH set of instructions (BEQ, BNE, BLT, BGE, BLTU, BGEU)

RV32I Base Instruction Set

imm[31:12]				rd	0110111	LUI	"load immediate"-kind: to load constant values into a register
imm[31:12]				rd	0010111	AUIPC	
imm[20|10:1|11|19:12]				rd	1101111	JAL	"jump-and-link"-kind: subroutine calls and returns; distant jumps
imm[11:0]		rs1	000	rd	1100111	JALR	
imm[12|10:5]	rs2	rs1	000	imm[4:1|11]	1100011	BEQ	
imm[12|10:5]	rs2	rs1	001	imm[4:1|11]	1100011	BNE	
imm[12|10:5]	rs2	rs1	100	imm[4:1|11]	1100011	BLT	"conditional branch"-kind: test and possibly jump up to ~0x1000 distance
imm[12|10:5]	rs2	rs1	101	imm[4:1|11]	1100011	BGE	
imm[12|10:5]	rs2	rs1	110	imm[4:1|11]	1100011	BLTU	
imm[12|10:5]	rs2	rs1	111	imm[4:1|11]	1100011	BGEU	
imm[11:0]		rs1	000	rd	0000011	LB	
imm[11:0]		rs1	001	rd	0000011	LH	
imm[11:0]		rs1	010	rd	0000011	LW	"load data from memory into register" (rs1 and imm specify address)
imm[11:0]		rs1	100	rd	0000011	LBU	
imm[11:0]		rs1	101	rd	0000011	LHU	
imm[11:5]	rs2	rs1	000	imm[4:0]	0100011	SB	
imm[11:5]	rs2	rs1	001	imm[4:0]	0100011	SH	"store data from register rs2 to memory" (rs1 and imm specify address)
imm[11:5]	rs2	rs1	010	imm[4:0]	0100011	SW	
imm[11:0]		rs1	000	rd	0010011	ADDI	
imm[11:0]		rs1	010	rd	0010011	SLTI	
imm[11:0]		rs1	011	rd	0010011	SLTIU	
imm[11:0]		rs1	100	rd	0010011	XORI	
imm[11:0]		rs1	110	rd	0010011	ORI	"integer arithmetic operations (register-immediate)"
imm[11:0]		rs1	111	rd	0010011	ANDI	
0000000	shamt	rs1	001	rd	0010011	SLLI	
0000000	shamt	rs1	101	rd	0010011	SRLI	
0100000	shamt	rs1	101	rd	0010011	SRAI	
0000000	rs2	rs1	000	rd	0110011	ADD	
0100000	rs2	rs1	000	rd	0110011	SUB	
0000000	rs2	rs1	001	rd	0110011	SLL	
0000000	rs2	rs1	010	rd	0110011	SLT	
0000000	rs2	rs1	011	rd	0110011	SLTU	
0000000	rs2	rs1	100	rd	0110011	XOR	"integer arithmetic operations (register-register)"
0000000	rs2	rs1	101	rd	0110011	SRL	
0100000	rs2	rs1	101	rd	0110011	SRA	
0000000	rs2	rs1	110	rd	0110011	OR	
0000000	rs2	rs1	111	rd	0110011	AND	
fm	pred	succ	rs1	000	rd	0001111	FENCE	"system" operations (ignore FENCE for now)
000000000000		00000	000	00000	1110011	ECALL	
000000000001		00000	000	00000	1110011	EBREAK	

Example specifications

Excerpt from text of ISA specification document for LUI and AUIPC instructions

SRLI is a logical right shift (zeros are shifted into the upper bits); and SRAI is an arithmetic right shift (the original sign bit is copied into the vacated upper bits).

31		12	11	7	6	0
	imm[31:12]			rd		opcode
	20			5		7
	U-immediate[31:12]			dest		LUI
	U-immediate[31:12]			dest		AUIPC

LUI (load upper immediate) is used to build 32-bit constants and uses the U-type format. LUI places the U-immediate value in the top 20 bits of the destination register rd, filling in the lowest 12 bits with zeros.

AUIPC (add upper immediate to pc) is used to build pc-relative addresses and uses the U-type format. AUIPC forms a 32-bit offset from the 20-bit U-immediate, filling in the lowest 12 bits with zeros, adds this offset to the address of the AUIPC instruction, then places the result in register rd.

Execution semantics: example

Execution semantics of LUI instruction

Execution semantics: example

Execution semantics of AUIPC instruction

Execution semantics: example

Execution semantics of JAL and JALR instructions (unconditional jumps)

Control and Status Registers (CSRs) for Trap-Handling

These CSRs are implicitly read and written when taking and returning from a trap.
These CSRs can be explicitly read and written by CSRRxx instructions.

Trap and Trap-return flow

There are many possible causes for exceptions and traps;
the illustration is for an illegal instruction.

Exception causes

On a trap, a cause-code is written into the `mcause` CSR:

| Exception-Cause code	Description
0	Instruction address misaligned
1	Instruction access fault
2	Illegal instruction
3	Breakpoint
4	Load address misaligned
5	Load access fault
6	Store/AMO address misaligned
7	Store/AMO access fault
...	...
11	Environment call M-mode
...	...

CSRRxx Instructions

For reading and writing CSRs from RISC-V code
(from the RISC-V ISA specifications document)

9.1 CSR Instructions

All CSR instructions atomically read-modify-write a single CSR, whose CSR specifier is encoded in the 12-bit *csr* field of the instruction held in bits 31–20. The immediate forms use a 5-bit zero-extended immediate encoded in the *rs1* field.

31		20 19	15 14	12 11	7 6	0
csr		rs1	funct3	rd	opcode	
12		5	3	5	7	
source/dest		source	CSRRW	dest	SYSTEM	
source/dest		source	CSRRS	dest	SYSTEM	
source/dest		source	CSRRC	dest	SYSTEM	
source/dest		uimm[4:0]	CSRRWI	dest	SYSTEM	
source/dest		uimm[4:0]	CSRRSI	dest	SYSTEM	
source/dest		uimm[4:0]	CSRRCI	dest	SYSTEM	

CSRRxx Instruction Semantics

- They all move potentially data into a CSR, and from a CSR to a GPR
- The non "I" variants take input from GPR[rs1] (unless rs1 is zero)
- The "I" variants use rs1 itself as input (unless rs1 is zero)

RV64I instructions

From the RISC-V ISA specifications document

31 27	26 25	24 20	19 15	14 12	11 7	6 0	
funct7		rs2	rs1	funct3	rd	opcode	R-type
imm[11:0]			rs1	funct3	rd	opcode	I-type
imm[11:5]		rs2	rs1	funct3	imm[4:0]	opcode	S-type

RV64I Base Instruction Set (in addition to RV32I)

imm[11:0]			rs1	110	rd	0000011	LWU
imm[11:0]			rs1	011	rd	0000011	LD
imm[11:5]		rs2	rs1	011	imm[4:0]	0100011	SD
000000		shamt	rs1	001	rd	0010011	SLLI
000000		shamt	rs1	101	rd	0010011	SRLI
010000		shamt	rs1	101	rd	0010011	SRAI
imm[11:0]			rs1	000	rd	0011011	ADDIW
0000000		shamt	rs1	001	rd	0011011	SLLIW
0000000		shamt	rs1	101	rd	0011011	SRLIW
0100000		shamt	rs1	101	rd	0011011	SRAIW
0000000		rs2	rs1	000	rd	0111011	ADDW
0100000		rs2	rs1	000	rd	0111011	SUBW
0000000		rs2	rs1	001	rd	0111011	SLLW
0000000		rs2	rs1	101	rd	0111011	SRLW
0100000		rs2	rs1	101	rd	0111011	SRAW

RV64I instructions

In RV64, the 32 GPRs (General Purpose Registers) are each 64-bits wide.

- Most of the RV32I instruction have identical RV64I counterparts
  (here they operate on 64-bit values).
- A few instructions (SLLI, SRLI, SRAI) are slightly different
  (allowing 6 bits instead of 5 for the shift amount).
- A few instructions are new, to opoerate on 32-bit values in the 64-bit registers.
  - LWU to move a 32-bit value from memory into a 64-bit register
  - LD to load a 64-bit value from memory to a 64-bit register
  - SD to store a 64-bit value to memory from 64-bit register
  - ADDIW, SLLIW, ... SRAW to operate on 32-bits of 64-bit registers

End