


# Linear Regression



## Overview

- **Linear Regression** is a powerful and widely used technique in machine learning, serving as the **foundation** for many predictive modeling tasks.
- Used to predict **continuous** values.
- It is one of the most important and **mostly used** supervised learning algorithms.
- At its core, Linear Regression aims to establish a **relationship** between a **dependent variable/target** and one or more **independent variables/feature**.

## Types of Linear Regression


### 1. Simple Linear Regression:

- If a **single** independent variable is used to predict the value of a numerical dependent variable.


### 2. Multiple Linear regression:

- If **more than one** independent variable is used to predict the value of a numerical dependent variable.


## Linear regression algorithm




1. We collected some data



2. We should fit the line to the data. But which line is better?



3. Start with the line across the mean value!





4. Find the distances of all data points from that line

## Learn by example

In [164...

```
import pandas as pd
df = pd.read_csv("ames-housing.csv")
df.plot.scatter(x='Living Area Sqft', y='SalePrice');
```





## Linear equation general form:

$\hat{y}$ : predicted  $y$

$x_1, x_2, x_3 \dots$  etc: input features

$\beta_1, \beta_2, \beta_3 \dots$  etc: coefficients for the corresponding  $x$ s.

$\beta_0$  : intercept

$$\hat{y} = \beta_0 + \beta_1 * x_1 + \beta_2 * x_2 + \beta_3 * x_3 + \dots + \beta_n * x_n$$

## How to find the *optimal* line ?

- **Optimizer:** Its primary role is to find the best values for model parameters that minimize the model's error or loss function.
- Model parameters = weights = coefficients
- Examples of ML Optimizers:
  - **GD:** (Gradient Descent)
  - **SGD:** Stochastic Gradient Descent)
  - **Adagrad** (Adaptive Gradient Algorithm)
  - **Adam** (Adaptive Moment Estimation)

## Training a linear regression model

### Execute preprocessing steps

In [165...

```
import pandas as pd
from sklearn.model_selection import train_test_split
from sklearn.impute import SimpleImputer
```

```

from sklearn.pipeline import make_pipeline
from sklearn.compose import ColumnTransformer
from sklearn.preprocessing import StandardScaler

from sklearn.preprocessing import OneHotEncoder
from sklearn.preprocessing import OrdinalEncoder
from sklearn import set_config
set_config(transform_output='pandas')

df = pd.read_csv("galton_handson.csv")
df.head()

```

Out[165...

	family	father	mother	midparentHeight	children	childNum	gender	childHeight	fan
0	1	78.5	67.0	75.43	4	1.0	male	73.2	
1	1	78.5	67.0	75.43	4	2.0	female	69.2	
2	1	78.5	67.0	75.43	4	3.0	female	69.0	
3	1	78.5	67.0	75.43	4	4.0	female	69.0	
4	2	75.5	66.5	73.66	4	1.0	male	73.5	

## Building a machine learning model that predicts a child's height based on historical data.

### First step : prepare and clean dataset

In [166...

```

#Drop non relevant columns
df = df.drop(columns='family')

#Fix inconsistency
df['midparentHeight'] = df['midparentHeight'].str.replace(",", '.')
df['midparentHeight'] = df['midparentHeight'].astype(float)

df = df.drop_duplicates()

# The target we are trying to predict
y = df['childHeight']
# The features we will use to make the prediction
X = df.drop(columns = 'childHeight')
X.head(5)

```

Out[166...

	<b>father</b>	<b>mother</b>	<b>midparentHeight</b>	<b>children</b>	<b>childNum</b>	<b>gender</b>	<b>familySize</b>
<b>0</b>	78.5	67.0	75.43	4	1.0	male	Mid
<b>1</b>	78.5	67.0	75.43	4	2.0	female	Mid
<b>2</b>	78.5	67.0	75.43	4	3.0	female	Mid
<b>3</b>	78.5	67.0	75.43	4	4.0	female	Mid
<b>4</b>	75.5	66.5	73.66	4	1.0	male	Mid

In [167...

```
# Train test split
X_train, X_test, y_train, y_test = train_test_split(X, y, random_state=1)

## Three types of data
num_cols = X_train.select_dtypes("number").columns
ordinal_cols = ['familySize']
ohe_cols = X_train.select_dtypes("object").drop(columns=ordinal_cols).columns

##### Numrical pipeline
# instantiate preprocessors
# Fills missing values with the median
impute_median = SimpleImputer(strategy='median')
#cales features to have mean = 0, std = 1
scaler = StandardScaler()

# Make a numeric preprocessing pipeline
num_pipe = make_pipeline(impute_median, scaler)

##### Ordinal pipeline
'''Fills missing with 'NA'
Encodes ordered categories (Small, Mid, Large)
Scales them numerically'''
impute_na_ord = SimpleImputer(strategy='constant', fill_value='NA')

# Specifying the order of categories in quality/condition columns
fam_size_order = ["Small", "Mid", "Large"]
# Making the list of order lists for OrdinalEncoder
ordinal_category_orders = [fam_size_order]
# Instantiate the encoder and include the list of ordered values as an argument
ord_encoder = OrdinalEncoder(categories=ordinal_category_orders)

# Making a final scaler to scale category #'s
scaler_ord = StandardScaler()

ord_pipe = make_pipeline(impute_na_ord, ord_encoder, scaler_ord)

##### Nominal pipeline
impute_na = SimpleImputer(strategy='constant', fill_value = "male")

# Instantiate one hot encoder
'''handle_unknown='ignore' : Ignores unseen (unknown) categories during transform
Fills the one-hot vector with all zeros for that value to prevents the code from cr
ohe_encoder = OneHotEncoder(sparse_output=False, handle_unknown='ignore')
```

```

# Make pipeline with imputer and encoder
ohe_pipe = make_pipeline(impute_na, ohe_encoder)

##### Build pipelines tuples
num_tuple = ('numeric', num_pipe, num_cols)
ord_tuple = ('ordinal', ord_pipe, ordinal_cols)
ohe_tuple = ('categorical', ohe_pipe, ohe_cols)

##### Create ColumnTransformer
# Instantiate with verbose_feature_names_out=False
# remainder: Keep unlisted columns unchanged
'''False => Keeps clean column names (e.g., 'gender_female'),
True => Adds transformer name as prefix (e.g., 'categorical__gender_female)'''
col_transformer = ColumnTransformer([num_tuple, ord_tuple, ohe_tuple],
                                   remainder='passthrough',
                                   verbose_feature_names_out=False)

# Fit on training data
col_transformer.fit(X_train)
# Transform the training data
X_train_tf = col_transformer.transform(X_train)
# Transform the testing data
X_test_tf = col_transformer.transform(X_test)
# View the processed training data
X_train_tf

```

Out[167...

	<b>father</b>	<b>mother</b>	<b>midparentHeight</b>	<b>children</b>	<b>childNum</b>	<b>familySize</b>	<b>gender_fema</b>
<b>385</b>	0.519228	-0.922169	-0.260641	0.676793	1.898582	0.813335	1
<b>453</b>	0.096910	1.030101	0.834581	-0.784453	-0.262833	-0.698689	1
<b>347</b>	0.308069	-0.054494	0.210361	1.042104	1.898582	0.813335	1
<b>602</b>	-0.325409	0.379344	0.091192	0.676793	-0.695116	0.813335	0
<b>622</b>	-0.536568	-0.054494	-0.357112	1.407416	1.034016	0.813335	1
...	...	...	...	...	...	...	...
<b>767</b>	-0.958887	-0.271412	-0.794066	0.676793	0.169450	0.813335	0
<b>72</b>	1.448329	2.114696	2.508626	0.676793	0.601733	0.813335	1
<b>908</b>	-1.592365	-1.789845	-2.292194	-0.419141	0.169450	-0.698689	0
<b>235</b>	0.730388	-2.657521	-1.344514	-1.515075	-0.695116	-2.210713	0
<b>37</b>	1.997344	-0.922169	0.732436	0.676793	0.601733	0.813335	1

699 rows × 8 columns



## Fit a Linear regression model

```
In [168... from sklearn.linear_model import LinearRegression
# from sklearn.linear_model SGDRegressor
model = LinearRegression()

# Fit the model on the training data
model.fit(X_train_tf, y_train)
model
```

```
Out[168... LinearRegression
LinearRegression()
```

By calling the *fit* function, the model studied the patterns between the features and the target, and found the optimal weights which minimize the loss

## Look to the model parameters/weights:

```
In [169... print(X_train.describe())
```

	father	mother	midparentHeight	children	childNum
count	683.000000	675.000000	693.000000	699.000000	695.000000
mean	69.265154	64.130074	69.188603	6.147353	3.611511
std	2.396947	2.347244	1.771073	2.739351	2.321156
min	62.000000	58.000000	64.400000	1.000000	1.000000
25%	68.000000	63.000000	68.230000	4.000000	2.000000
50%	69.500000	64.000000	69.270000	6.000000	3.000000
75%	71.000000	66.000000	70.140000	8.000000	5.000000
max	78.500000	70.500000	75.430000	15.000000	11.000000

```
In [170... b_0 = model.intercept_.round(2)
b_i = model.coef_.round(2)
feature_names = col_transformer.get_feature_names_out()
print(f"features: {feature_names}")
print(f"coefficients (weights): {b_i}")
print(f"intercept (bias): {b_0}")
```

```
features: ['father' 'mother' 'midparentHeight' 'children' 'childNum' 'familySize'
'gender_female' 'gender_male']
coefficients (weights): [ 0.63  0.33  0.45  0.58 -1.55  0.19 -1.73  1.73]
intercept (bias): 66.62
```

```
In [171... eq = " +\n".join([ f"{' ' if i == 0 else ' '*24}{b_i[i]} * {feature_names[i]}" for
print(f"Model equation: y_hat = {eq}")
```

```
Model equation: y_hat = 0.63 * father +
0.33 * mother +
0.45 * midparentHeight +
0.58 * children +
-1.55 * childNum +
0.19 * familySize +
-1.73 * gender_female +
1.73 * gender_male
```

### Interpret 0.63 (father 'weight'):

- When the father height increase by one centemeter, the child hight expected to increase by 0.63, holding other features constant.

Is the above sentence correct after scaling ?

or :

When the father height increase by one **STD**, the child hight expected to increase by 0.63, holding other features constant.

**A 1 cm increase in father's height leads to a 0.263 cm increase in child height, holding all other features constant**

$$1 \text{ cm} = 0.63 \text{ (Coef)} / 2.396947 \text{ (std)}$$

### Interpret 0.33 (mother weight):

### Interpret -1.55 (childNum weight):

### Interpret -1.73 (gender\_F weight):


## Predict new childs

```
In [175... # import numpy as np
#['father' 'mother' 'midparentHeight' 'children' 'childNum' 'familySize' 'gender_fe
new_child = [72, 64, 69.6, 3, 3, 'male', 'Small']
X = pd.DataFrame(columns=X_train.columns)
X.loc[0] = new_child
X = col_transformer.transform(X)
#print(X)
model.predict(X)
```

```
Out[175... array([68.48076626])
```

## Model evaluation





$$\text{Error/Residual} = y - \hat{y}$$

where:

- $y$  is the true values for the target.
- $\hat{y}$ : (y-hat) is the predicted values

## Mean Absolute Error (MAE)

$$MAE = \frac{\sum_{i=1}^n |y_i - \hat{y}_i|}{n}$$

where:

- $|y_i - \hat{y}_i|$  represents taking the absolute value of the error.
- $\sum_{i=1}^n$ : represents summing the values for every row/prediction.
- $n$  represents the total number of rows/predictions.

## Mean Squared Error (MSE)

$$MSE = \frac{\sum_{i=1}^n (y_i - \hat{y}_i)^2}{n}$$

where:

- $(y_i - \hat{y}_i)^2$  represents squaring the error.
- $\sum_{i=1}^n$ : represents summing the values for every row/prediction.
- $n$  represents the total number of rows/predictions.

**Which is better, MSE or MAE ?**

- Mean squared error penalizes large errors more because the errors are being squared.
- Interpretation is hard

**Root Mean Squared Error (RMSE)**

$$RMSE = \sqrt{\frac{\sum_{i=1}^n (y_i - \hat{y}_i)^2}{n}}$$

where:

- $\sqrt{\dots}$  represents taking the square root
- $(y_i - \hat{y}_i)^2$  represents squaring the error.
- $\sum_{i=1}^n$ : represents summing the values for every row/prediction.
- $n$  represents the total number of rows/predictions.

**How to decide if the error metrics have acceptable/good values ?**

MSE and RMSE scores are all dependent on the scale and units of the target. 5,000 USD on the sale of a house isn't too bad, but being off by 5,000 USD on the sale of a car would be horrible!

MAE, MSE, and RMSE scores are all dependent on the scale and units of the target. 5,000 USD on the sale of a house isn't too bad, but being off by 5,000 USD on the sale of a car would be horrible!

## Let's evaluate our model

In [140...

```
# Calculating RMSE with sklearn
from sklearn.metrics import root_mean_squared_error

#Get predictions for test data
y_pred_test = model.predict(X_test_tf)

test_RMSE = root_mean_squared_error(y_test, y_pred_test)
print(f'Model Testing RMSE: {test_RMSE:,.2f}')
```

Model Testing RMSE: 1.86

**What this result means : On average, our model's predictions are off by ~1.86 inch from the actual child height**

### R-Squared

- Coefficient of determination
- Describes the percentage of the variation in the target variable that a model can explain by using all the features together

### Pros

- Consistent scale

### Cons

- Difficult to interpret
- A high R2 doesn't always mean a good model and a low one doesn't always mean a bad one.

## R<sup>2</sup> (Coefficient of Determination)

The R<sup>2</sup> score measures how well the regression model explains the variability in the target variable.

$$R^2 = 1 - \frac{SSE}{SST}$$

## Interpretation:

- **SSE** (Sum of Squared Errors) measures how far predictions are from actual values.
- **SST** (Total Sum of Squares) measures how far actual values are from their mean.
- The closer  $R^2$  is to **1**, the better the model explains the data.

$$R^2 = 1 - \frac{\sum (y_{\text{true}} - y_{\text{pred}})^2}{\sum (y_{\text{true}} - \bar{y})^2}$$

In [141... `from sklearn.metrics import r2_score`


```
y_pred = model.predict(X_test_tf)
r2 = r2_score(y_test, y_pred)
print("R2 score:", r2)
```

R<sup>2</sup> score: 0.7112764091636733


## R<sup>2</sup> Score Interpretation

- 0.9 – 1.0 Excellent fit
- 0.7 – 0.9 Good fit
- 0.5 – 0.7 Moderate — model explains some, but not all
- < 0.5 Weak — model is underperforming

## Bias vs. Variance



## Bias and Variance on LR



## How to detect underfit ?

The model shows bad quality in both train and test data

## How to detect overfit ?

1. Evaluate the model on both the training and testing data, then
2. If there is a significant gap between both quality => Overfit

### Example 1 : How you interpret the quality of a model predicting house prices ?

Regression Metrics: Train Data

- MSE = 15,876.00
- RMSE = 126.00

Regression Metrics: Test Data

- MSE = 302,500.00
- RMSE = 550.00

**Overfit/High varianc** since there is a significant gap in RMSE/MSE between train and test data

### Example 2 : How you interpret the quality of a model predicting child height ?

Regression Metrics: Train Data

- MSE = 36.00
- RMSE = 6.00

Regression Metrics: Test Data

- $MSE = 37.00$
- $RMSE = 6.08$

**Underfit/High bias** since MSE/RMSE is high on both train and test data

**Example 3 : How you interpret the quality of a model predicting number of students will enroll in BZU next semester?**

Regression Metrics: Train Data

- $MSE = 90,000.00$
- $RMSE = 300.00$

Regression Metrics: Test Data

- $MSE = 100,200.00$
- $RMSE = 316.54$
- **No overfit:** since the error on both train and test is close
- **No underfit:** since the error amount of ~300 student is acceptable comparing to the total number of students usually enroll (~5,000?)

=> Acceptable model

## High bias (underfitting):

### Reasons:

- A model that is too simple
- Not enough data.
- Features that do not correlate well with the target.

### How to fix:

- Increasing the complexity of your model. (Add more features)
- Adding more data.
- Adding features with higher correlation to the target.

## High Variance (Overfitting)

### Reasons:

- Too complex of a model
- Not enough data.

- Training data that is not a representative sample of the population, all new data the model might encounter.

## How to fix:

- Decrease the complexity of the model. (feature selection)
- Add regularization.
- Add more data to the training set.
- Ensure that the training set is a representative subset of all data the model will encounter.

## End-to-End example

```
In [1]: import pandas as pd
from sklearn.compose import ColumnTransformer, make_column_selector
from sklearn.pipeline import make_pipeline
from sklearn.preprocessing import StandardScaler, OneHotEncoder
from sklearn.impute import SimpleImputer
from sklearn.model_selection import train_test_split
from sklearn import set_config
set_config(transform_output='pandas')
```

```
In [2]: df = pd.read_csv('medical_data.csv')
df.head()
```

```
Out[2]:
```

	State	Lat	Lng	Area	Children	Age	Income	Marital	Gender	ReAd
0	AL	34.34960	-86.72508	Suburban	1.0	53	86575.93	Divorced	Male	
1	FL	30.84513	-85.22907	Urban	3.0	51	46805.99	Married	Female	
2	SD	43.54321	-96.63772	Suburban	3.0	53	14370.14	Widowed	Female	
3	MN	43.89744	-93.51479	Suburban	0.0	78	39741.49	Married	Male	
4	VA	37.59894	-76.88958	Rural	1.0	22	1209.56	Widowed	Female	

5 rows × 32 columns



```
In [8]: df.info()
```

```

<class 'pandas.core.frame.DataFrame'>
RangeIndex: 1000 entries, 0 to 999
Data columns (total 32 columns):
#   Column                Non-Null Count  Dtype
---  -
0   State                  995 non-null    object
1   Lat                    1000 non-null   float64
2   Lng                    1000 non-null   float64
3   Area                   995 non-null    object
4   Children               993 non-null    float64
5   Age                    1000 non-null   int64
6   Income                 1000 non-null   float64
7   Marital                995 non-null    object
8   Gender                 995 non-null    object
9   ReAdmis                1000 non-null   int64
10  VitD_levels            1000 non-null   float64
11  Doc_visits             1000 non-null   int64
12  Full_meals_eaten       1000 non-null   int64
13  vitD_supp              1000 non-null   int64
14  Soft_drink             1000 non-null   int64
15  Initial_admin          995 non-null    object
16  HighBlood              1000 non-null   int64
17  Stroke                 1000 non-null   int64
18  Complication_risk      995 non-null    object
19  Overweight             1000 non-null   int64
20  Arthritis              994 non-null    float64
21  Diabetes                994 non-null    float64
22  Hyperlipidemia         998 non-null    float64
23  BackPain               992 non-null    float64
24  Anxiety                998 non-null    float64
25  Allergic_rhinitis      994 non-null    float64
26  Reflux_esophagitis     1000 non-null   int64
27  Asthma                 1000 non-null   int64
28  Services               995 non-null    object
29  Initial_days           1000 non-null   float64
30  TotalCharge            1000 non-null   float64
31  Additional_charges     1000 non-null   float64
dtypes: float64(14), int64(11), object(7)
memory usage: 250.1+ KB

```

In [144...

```

# Drop State
droplist = ['State']
df = df.drop(droplist, axis=1)

# Correct inconsistencies in values in Gender column
df['Gender'] = df['Gender'].replace(['male', 'm', 'M'], 'Male')
df['Gender'] = df['Gender'].replace(['F', 'f'], 'Female')

# Define X and y
X = df.drop(columns='Additional_charges')
y = df['Additional_charges']
# Split the data into train and test sets
X_train, X_test, y_train, y_test = train_test_split(X, y, random_state=42)

# Create the preprocessing pipeline for categorical data
# (New) Select columns with make_column_selector

```



```

cat_selector = make_column_selector(dtype_include='object')
# Instantiate transformers
freq_imputer = SimpleImputer(strategy='most_frequent')
ohe = OneHotEncoder(sparse_output=False, handle_unknown='ignore')
# Instantiate the pipeline
cat_pipe = make_pipeline(freq_imputer, ohe)
# Make a tuple for column transformer
cat_tuple = ('categorical', cat_pipe, cat_selector)

# Create the preprocessing pipeline for numeric data
# (New) Select columns with make_column_selector
num_selector = make_column_selector(dtype_include='number')
# Instantiate the transformers
scaler = StandardScaler()
mean_imputer = SimpleImputer(strategy='mean')
# Instantiate the pipeline
num_pipe = make_pipeline(mean_imputer, scaler)
# Make the tuple for ColumnTransformer
num_tuple = ('numeric', num_pipe, num_selector)

# Create the preprocessing ColumnTransformer
preprocessor = ColumnTransformer([cat_tuple, num_tuple],
                                verbose_feature_names_out=False)

```

## Create model pipeline

In [145...


```

from sklearn.linear_model import LinearRegression

# Instantiate a linear regression model
model = LinearRegression()
# Combine the preprocessing ColumnTransformer and the linear regression model in a
model_pipe = make_pipeline(preprocessor, model)
model_pipe

```

Out[145...



## Fit the model pipeline on the training data


In [146...

```

model_pipe.fit(X_train, y_train)

```

Out[146...



## Model evaluation

### Steps:

#### 1. Evaluate the model on the train data

- Use the model to predict the train data ( `X_train` ) => `y_train_pred`
- Compare between predicted values( `y_train_pred` ) and the actual values ( `y_train` )
- Calculate the quality metrics (MSE/RMSE) using `mean_squared_error` and `root_mean_squared_error` from `sklearn` module

#### 2. Evaluate the model on the test data

- Use the model to predict the train data ( `X_test` ) => `y_test_pred`
- Compare between predicted values( `y_test_pred` ) and the actual values ( `y_test` )
- Calculate the quality metrics (MSE/RMSE) using `mean_squared_error` and `root_mean_squared_error` from `sklearn` module

#### 3. Identify underfit and overfit (if any)

In [147...

```
from sklearn.metrics import mean_squared_error, root_mean_squared_error, mean_absol

def regression_metrics(y_true, y_pred, label='', verbose = True, output_dict=False)
    # Get metrics
    rmse = root_mean_squared_error(y_true, y_pred)
    mse = mean_squared_error(y_true, y_pred)
    if verbose == True:
        # Print Result with Label and Header
        header = "-"*60
        print(header, f"Regression Metrics: {label}", header, sep='\n')
        print(f"- MSE = {mse:,.3f}")
        print(f"- RMSE = {rmse:,.3f}")
    if output_dict == True:
        metrics = {'Label':label, 'MSE':mse, 'RMSE':rmse}
```

```

# Get predictions for training data
y_train_pred = model_pipe.predict(X_train)

# Call the helper function to obtain regression metrics for training data
results_train = regression_metrics(y_train, y_train_pred, label='Training Data')
print()
# Get predictions for test data
y_test_pred = model_pipe.predict(X_test)
# Call the helper function to obtain regression metrics for test data
results_test = regression_metrics(y_test, y_test_pred, label='Test Data' )

df['Additional_charges'].hist()

```


-----  
Regression Metrics: Training Data  
-----

- MSE = 2,614,407.658  
- RMSE = 1,616.913

-----  
Regression Metrics: Test Data  
-----

- MSE = 2,866,953.025  
- RMSE = 1,693.208

Out[147... <Axes: >



## Summary of training a model

- Clean and explore the data using EDA

- Preprocess the data
- Fit a machine learning algorithm (Linear Regression)
- Evaluate the quality of the model
- Improve model quality with proper techniques in respect to underfit and overfit problems

In [148...

```
def regression_metrics(y_true, y_pred, label='', verbose = True, output_dict=False)
    # Get metrics
    mae = mean_absolute_error(y_true, y_pred)
    mse = mean_squared_error(y_true, y_pred)
    rmse = mean_squared_error(y_true, y_pred, squared=False)
    r_squared = r2_score(y_true, y_pred)
    if verbose == True:
        # Print Result with Label and Header
        header = "-"*60
        print(header, f"Regression Metrics: {label}", header, sep='\n')
        print(f"- MAE = {mae:,.3f}")
        print(f"- MSE = {mse:,.3f}")
        print(f"- RMSE = {rmse:,.3f}")
        print(f"- R^2 = {r_squared:,.3f}")
    if output_dict == True:
        metrics = {'Label':label, 'MAE':mae,
                  'MSE':mse, 'RMSE':rmse, 'R^2':r_squared}

    # Get predictions for training data
    y_train_pred = model_pipe.predict(X_train)

    # Call the helper function to obtain regression metrics for training data
    results_train = regression_metrics(y_train, y_train_pred, label='Training Data')
    print()

    # Get predictions for test data
    y_test_pred = model_pipe.predict(X_test)
    # Call the helper function to obtain regression metrics for test data
    results_test = regression_metrics(y_test, y_test_pred, label='Test Data' )
```

```
-----
Regression Metrics: Training Data
-----
```

```
- MAE = 1,370.542
- MSE = 2,614,407.658
- RMSE = 1,616.913
- R^2 = 0.943
```

```
-----
Regression Metrics: Test Data
-----
```

```
- MAE = 1,389.304
- MSE = 2,866,953.025
- RMSE = 1,693.208
- R^2 = 0.930
```

```
C:\Users\asabb\anaconda3\envs\EnvML\Lib\site-packages\sklearn\metrics\_regression.p
y:492: FutureWarning: 'squared' is deprecated in version 1.4 and will be removed in
1.6. To calculate the root mean squared error, use the function'root_mean_squared_er
ror'.
  warnings.warn(
C:\Users\asabb\anaconda3\envs\EnvML\Lib\site-packages\sklearn\metrics\_regression.p
y:492: FutureWarning: 'squared' is deprecated in version 1.4 and will be removed in
1.6. To calculate the root mean squared error, use the function'root_mean_squared_er
ror'.
  warnings.warn(
```

## Assignment 7

- Explore Kaggle and select a dataset for regression modeling. Ensure the dataset adheres to the following criteria:
  - Must include at least 5 features (excluding the target), with a mix of ordinal and nominal features.
  - The target feature must be numeric.
- Perform necessary data cleaning and preprocessing, The splitting of the data should use 80% train and 20% test ratio. **Use your student ID as the random\_state when splitting.**
- Fit a linear regression model on the transformed data.
- Print the model parameters and provide an interpretation for each.
- Evaluate the model's quality using appropriate metrics.
- Determine if the model exhibits overfitting or underfitting and explain your reasoning.
- Provide link to your selected data set in Kaggle.

**Any attempt of using generative AI will be considered as cheating !**

In [149...

```
print(f"Regression Metrics: Train Data", sep='\n')
print(f"- MAE = {88:,.2f}")
print(f"- MSE = {15876:,.2f}")
print(f"- RMSE = {126:,.2f}")
print(f"- R^2 = {0.87:,.2f}")
print()
print(f"Regression Metrics: Test Data", sep='\n')
print(f"- MAE = {484:,.2f}")
print(f"- MSE = {302500:,.2f}")
print(f"- RMSE = {550:,.2f}")
print(f"- R^2 = {0.61:,.2f}")
```

Regression Metrics: Train Data

- MAE = 88.00
- MSE = 15,876.00
- RMSE = 126.00
- $R^2$  = 0.87

Regression Metrics: Test Data

- MAE = 484.00
- MSE = 302,500.00
- RMSE = 550.00
- $R^2$  = 0.61

In [150...

```
import math
print(f"Regression Metrics: Train Data", sep='\n')
print(f"- MSE = {90000:,.2f}")
print(f"- RMSE = {math.sqrt(90000):,.2f}")
print()
print(f"Regression Metrics: Test Data", sep='\n')
print(f"- MSE = {100200:,.2f}")
print(f"- RMSE = {math.sqrt(100200):,.2f}")
```

Regression Metrics: Train Data

- MSE = 90,000.00
- RMSE = 300.00

Regression Metrics: Test Data

- MSE = 100,200.00
- RMSE = 316.54