Small-Model Alignment with SFT and DPO

PA2 report

Ayan Anees

GitHub: AyanAnees326/Advanced-Gen-AI-PA2

1 Repository, Models, and Data

Repository. https://github.com/AyanAnees326/Advanced-Gen-AI-PA2 (branch `main`). Training math is in `alignment/core.py` (also behind `submission_adapter.py`), the custom SFT/DPO [1] loop in `alignment/train.py`, the TRL/LoRA [6] run in `alignment/train_lora_dpo.py`, generation in `alignment/generate.py`, blinded pair construction in `alignment/pairs.py` and the Kaggle judge in `scripts/judge_pairwise_kaggle.py`. `scripts/run_local_pipeline.sh` reruns every stage except judging. *Kaggle setup* (`notebooks/01_kaggle_setup.ipynb`, run on GPU T4×2): the repository clones and installs without reinstalling PyTorch; the notebook sees two Tesla T4 GPUs and reports PyTorch 2.11.0+cu128, Transformers 4.57.6 and Datasets 4.8.5 (Fig. 1a). The 7 public adapter tests pass (Fig. 1b).

Models. SFT and both DPO runs start from `Qwen/Qwen2.5-0.5B` (base, 494M parameters); the persona run uses `HuggingFaceTB/SmolLM2-360M-Instruct`.

Training data (built by `alignment/data.py`; exact Hub revisions in `outputs/data_manifest.json`). Each split is a seeded sample (`random.Random("42-<track>-<split>")`) of the rows passing the filters:

- **SFT** (30,000 train / 1,000 val): `HuggingFaceH4/ultrachat_200k` `train_sft` / `test_sft`, first user→assistant turn only, kept only if prompt + response + EOS fits in 512 tokens (so the model always sees where an answer ends).
- **HH-RLHF DPO** (15,000 / 1,000): `Anthropic/hh-rlhf` [2] `harmless-base` + `helpful-base` `train`/`test`; single-turn conversations only (one Human and one Assistant turn), identical prompt in chosen and rejected, chosen $\neq$ rejected, formatted prompt $\leq$ 256 tokens.
- **UltraFeedback DPO** (15,000 / 1,000): `HuggingFaceH4/ultrafeedback_binarized` `train_prefs`/`test_prefs`; ties (`score_chosen = score_rejected`) dropped, prompt $\leq$ 256 tokens.
- **Persona DPO** (200 train / 20 held-out eval): `data/persona_lora/ramsay_style_preferences.json`, shuffled with seed 42.

Responses are never filtered for DPO; prompt + response + EOS is truncated at 512 tokens (EOS can be cut).

Fixed evaluation sets (all in `eval_sets/`): AlpacaEval-300 (`alpaca_eval_300_seed42.json`: `random.Random(42).sample(range(805),300)` of `tatsu-lab/alpaca_eval` [5], in sampled order) for SFT vs UltraFeedback-DPO; the provided synthetic helpful/harmless set (`hh_rlhf_eval_300_seed42.json`, 300 prompts, 10 categories × 30) for SFT vs HH-DPO; and a 32-prompt persona set written for this project (`persona_style_eval.json`: 10 cooking, 8 coding, 8 general help, 6 safety-sensitive) for SmolLM2 vs LoRA-DPO.

Prompt format (SFT, DPO and evaluation of all Qwen models; no system prompt):

```
<|im_start|>user\n{instruction}<|im_end|>\n<|im_start|>assistant\n
```

followed by the response and the tokenizer EOS `<|endoftext|>` (id 151643, also the pad token; labels are built from positions, so padding never masks a real EOS). SmolLM2 uses its own chat template both in TRL and at generation time, which inserts its default system prompt. **Loss reductions**: SFT uses the mean NLL over all unmasked response tokens in the batch (`compute_sft_loss`); in training the token count of the whole effective batch is the denominator, so accumulation reproduces the full-batch token mean. DPO scores are summed response-token log-probs and the loss is the batch mean. **Seed** 42 for data sampling, shuffling, initialisation of LoRA weights and A/B order.




Figure 1: Screenshots of the run records (`scripts/evidence_figures.py` renders the committed notebook outputs and logs verbatim and reruns the public tests; "…" marks cut text). (a) Kaggle setup. (b) Public adapter tests. (c) The first SFT attempt crashing at its first validation (§3). (d) Judge model and proxy check. (e) Judge summary for every comparison and both A/B orders: 0 unknown, 0 failures, 0 retries.

2 Experimental Configuration

Run	Trainable parameters	Optimizer; peak LR; schedule; warmup; weight decay; clip	Batch dev×acc = eff.	Precision	Max len (prompt)	Epochs / steps	Seed	DPO β; reference	Eval decoding
SFT	Full FT of Qwen2.5-0.5B (494M)	AdamW; 2×10^{-5}; cosine to 0; 3% linear (28 steps); 0.1 on matrices; 1.0	$2 \times 16 = 32$	fp32 weights, fp16 autocast, GradScaler 2^{16}, grad. ckpt.	512 (–)	1 / 937	42	–	greedy, ChatML
HH-DPO	Full FT from SFT best	AdamW; 1×10^{-6}; constant; none; 0; 1.0	$1 \times 32 = 32$	as SFT, GradScaler 2^{10}; reference fp16	512 (256)	1 / 468	42	0.1; frozen SFT best (step 937)	greedy, ChatML
UF-DPO	Full FT from SFT best	AdamW; 1×10^{-6}; constant; none; 0; 1.0	$1 \times 32 = 32$	as HH-DPO	512 (256)	1 / 468	42	0.1; frozen SFT best (same)	greedy, ChatML
LoRA-DPO	LoRA on SmolLM2-360M-Instruct: r=16, α=32, dropout 0.05; q, k, v, o, gate, up, down_proj; 8.7M (2.4%)	AdamW; 5×10^{-5}; cosine; 10% linear; 0; 1.0	$4 \times 2 = 8$	fp32 weights, fp16 AMP	512 (–)	3 / 75	42	0.1; base model with adapter disabled	greedy, SmolLM2 template

Table 1: Values used for the submitted checkpoints (each run's `config.json`). AdamW uses $\beta = (0.9, 0.999)$, $\epsilon = 10^{-8}$. Steps exclude the trailing partial accumulation window (SFT 29,984 examples, DPO 14,976 pairs, LoRA 200 pairs × 3 epochs). Validation: SFT every 100 steps on 1,000 examples, best = lowest loss; DPO at step 0 and every 50 steps on 1,000 pairs, best = highest reward accuracy (strict >); LoRA at step 0 and every 5 steps on 20 held-out pairs, final adapter submitted. **Decoding** (all generations): greedy (`do_sample=False`, so temperature and top-p are unused), max 512 new tokens, repetition penalty 1.1 (Table 3), no length penalty, no n-gram blocking, stop at EOS or `<|im_end|>`; fp16, batch 16, left padding. ChatML = the prompt of §1 (no system prompt); SmolLM2 runs use the model's own chat template.

3 Parameter Choices and Deviations

Setting	Guide	Used	Why, and effect
Resource-driven			
Hardware	Kaggle T4×2	1× AMD RX 6700 XT 12 GB (ROCm)	Kaggle-free local runs. Policy and frozen reference share one GPU, so the reference is kept in fp16 (allowed by the manual's memory tip). No effect on the method.
Eval micro-batch	–	2	The first SFT attempt crashed at its first validation (Fig. 1c; batch 8: fp32 logits over the 151k vocabulary next to Adam state oversubscribed 12 GB). The run was restarted from scratch with batch 2; validation numbers are unchanged by the batch size.
Activation memory	–	gradient checkpointing	Required to fit a fp32 policy + Adam + fp16 reference in 12 GB. Exact same gradients, slower steps.
Resumable state	–	`<run>/last/state.pt` every eval	Model, optimizer, scheduler, scaler and step are saved. SFT and UltraFeedback DPO ran uninterrupted (91 and 226 min). A power cut stopped HH-RLHF DPO at step 355; it resumed from the step-350 state (metrics after step 350 are dropped and re-logged). A cut during generation is handled by redoing the incomplete file.
Measurement / performance-driven			
Decoding	greedy; anti-repetition optional, same for SFT and DPO	repetition penalty 1.1, every model	Sanity check showed greedy loops; in a 40-prompt pilot (Table 3) the SFT model looped to the 512-token cap on 7/40 prompts at 1.0 and on 0/40 at 1.1, with fluent output. Applied identically to all generations, so each comparison isolates the checkpoint.
Validation reference log-probs	frozen SFT reference (fp16 here)	SFT weights scored by the policy (fp32 + autocast) once at step 0, cached	With the fp16 reference, the step-0 validation reward accuracy was 0.58 instead of the manual's exact 0: fp16-vs-fp32 rounding gave tiny non-zero $r_w - r_l$ that the strict $r_w > r_l$ counts. Same reference *weights*, so validation now measures movement away from SFT only (step 0: accuracy 0, margin 0, loss $\ln 2$). Training still uses the fp16 frozen copy.
DPO GradScaler init	–	2^{10} (SFT 2^{16})	Set a priori, not tuned: DPO back-propagates through summed sequence log-probs, so gradients are larger than SFT's token mean and a lower initial scale limits overflow-skipped updates in a 468-step run. Skipped steps: 0 in both DPO runs (scale stayed at 2^{10}). (SFT never overflowed: scale stayed at 2^{16}.)
DPO optimizer	RMSprop or AdamW	AdamW, WD 0	Within the guide; identical for both DPO runs.
LoRA-DPO	(student choice)	Table 1	Justified in §4.

Table 2: Changes from the guide configuration. SFT and DPO otherwise use the guide values (Table 1).

SFT model, first 20 prompts	Repetition penalty	Hit 512 tokens	Mean words	Mean distinct-4	Min distinct-4
AlpacaEval-300	1.0	3/20	214	0.828	0.145
	1.1	0/20	172	0.956	0.604
HH eval-300	1.0	4/20	200	0.709	0.012
	1.1	0/20	126	0.992	0.925

Table 3: Decoding pilot (greedy; `outputs/generations/pilot/`). Distinct-4 = unique / total word 4-grams in a response. Most of the length drop is the removed loops: on prompts that did not loop at 1.0, mean length goes 176→167 words (Alpaca) and 156→132 (HH).

4 Training Behavior




Figure 2: Left: SFT training loss (faint: per step; solid: EMA 0.9) and unsmoothed validation loss; dashed line = saved best checkpoint. Right: LoRA-DPO (TRL) loss and preference diagnostics on the 20 held-out persona pairs.

SFT (Fig. 2, 91 min). Validation loss was flat at 1.348–1.349 over steps 100–200 (peak learning rate) and then fell at every evaluation as the cosine schedule decayed, to 1.292 at step 937; the last two evaluations differ by 6×10^{-5}, so the run had converged for this budget. Train loss (mean of the last 50 steps 1.305) stays close to validation loss, so one epoch shows no overfitting, and the best-by-validation checkpoint is the final step, used as DPO initialisation and reference. The loss starts low (1.34 over the first 50 steps) because the Qwen2.5 base model has seen instruction-style




Figure 3: DPO runs from the same SFT checkpoint. Columns: DPO loss, reward accuracy, reward margin $r_w - r_l$ (with $r = \beta \log \pi_\theta / \pi_{\text{ref}}$ summed over response tokens). Training curves (faint: per step; solid: EMA 0.9) and validation points (1,000 held-out pairs, step 0 and every 50 steps); dashed line = submitted checkpoint.

text in pre-training; the visible gain is behavioural: in the sanity check the base model never stopped (4/5 prompts hit 512 tokens), the SFT model ended all 5 AlpacaEval answers with EOS. Pre-clip gradient norms were 3–6 (median 4.0), so clipping at 1.0 was active at every step; with Adam this mostly reweights steps rather than shrinking them.

DPO (Fig. 3, Table 4). Step-0 validation is exactly ln 2 / 0 / 0 (policy = reference, ties count as wrong), so every later point is movement away from SFT. *UltraFeedback* (226 min): validation loss fell at every evaluation, 0.693 → 0.528, and reward accuracy jumped to 0.69 by step 50, then crept to 0.738; the last evaluation was the highest, so the submitted checkpoint is the final step 468. The margin (0.75) comes mostly from pushing rejected responses down: implicit rewards are −0.11 (chosen) and −0.86 (rejected), i.e. both summed log-probs fell (chosen −342.5 → −343.6, rejected −298.5 → −307.1), the usual DPO pattern. Training and validation curves overlap, so one epoch at 10^{-6} shows no overfitting. Because the margin was still rising, a *learning-rate pilot* (`dpo_uf_lr5e-6`: $5{\times}10^{-6}$, 150 steps, same seed and batch order; last rows of Table 4) tested whether the run was learning-rate-limited. It exceeded the full run's final margin (0.77 vs. 0.75) in a third of the steps, but its validation loss stalled at 0.598–0.595 from step 50 while the guide run kept falling (0.568 at step 150), and its accuracy stayed lower (0.690 vs. 0.704 at step 150). Its margin came from pushing both responses down further (chosen −6.8 nats, rejected −14.5): a larger rate moves the implicit rewards faster but does not rank pairs better. Pre-clip gradient norms were 40–80 (median 57; summed sequence log-probs), so clipping acted on every step, as in SFT. *HH-RLHF* (126 min, resumed once at step 350): validation loss fell from 0.693 to 0.639 and reward accuracy rose to 0.59 by step 50, then plateaued at 0.63 from step 300; the best evaluation, step 450 (accuracy 0.636, margin 0.23), is the submitted checkpoint, and the final step is slightly worse (0.643, 0.621). The preference signal is weaker than UltraFeedback's: the margin is a third as large, as HH pairs share the dialogue and often differ by one sentence, and many labels are noisy. Again both summed log-probs fell, rejected by more (chosen −120.7 → −122.7, rejected −112.3 → −116.5). Responses are shorter, so pre-clip gradient norms were lower (median 35) but still clipped at every step; curves overlap and no step was skipped.

LoRA-DPO choices. The target is a narrow change of tone learned from 200 pairs, so capacity is not the constraint. *Rank 16,* $\alpha = 32$: low ranks are enough for adaptation [3]; 16 leaves room for tone and vocabulary changes in every layer while training 8.7M of 362M parameters; $\alpha = 2r$ keeps the update scale at 2. *Target modules*: all attention and MLP projections, since adapting every linear layer is what brings LoRA close to full fine-tuning [4] and word choice is largely carried by the MLPs. *LR* $5{\times}10^{-5}$: far above the full-model DPO rate because LoRA's B matrix starts at zero and the update is low-rank, but below typical LoRA SFT rates (10^{-4} to $2{\times}10^{-4}$) because DPO on 200 pairs over-optimises quickly and the persona must not cost usefulness or safety. *Batch 8* gives 25 updates per epoch; a larger batch would leave too few. *3 epochs* (75 steps) let the cosine schedule complete while the held-out reward

Run	Checkpoint	Step	Val loss	Reward acc.	Margin	$\bar{r}_w$	$\bar{r}_l$
HH-RLHF DPO	step 0	0	0.6931	0.000	0.000	0.000	0.000
HH-RLHF DPO	best	450	0.6388	0.636	0.229	-0.193	-0.422
HH-RLHF DPO	final	468	0.6428	0.621	0.224	-0.208	-0.432
UltraFeedback DPO	step 0	0	0.6931	0.000	0.000	0.000	0.000
UltraFeedback DPO	best	468	0.5278	0.738	0.749	-0.109	-0.858
UltraFeedback DPO	final	468	0.5278	0.738	0.749	-0.109	-0.858
UF DPO, LR 5×10^{-6}	step 0	0	0.6931	0.000	0.000	0.000	0.000
UF DPO, LR 5×10^{-6}	best	150	0.5948	0.690	0.774	-0.680	-1.454
UF DPO, LR 5×10^{-6}	final	150	0.5948	0.690	0.774	-0.680	-1.454

Table 4: DPO validation metrics (1,000 held-out pairs) at step 0, at the submitted best checkpoint and at the final step. $\bar{r} = \beta(\log \pi_\theta - \log \pi_{\text{ref}})$ summed over response tokens. Last rows: the 150-step learning-rate pilot (not a submitted model).

accuracy, checked every 5 steps, shows whether the model only memorises the training pairs. *Result* (89 s): held-out reward accuracy was already 1.0 at step 5, because chosen and rejected answers differ in an obvious register, so the margin is the informative curve. Held-out loss fell from 0.693 to 0.124 and the held-out margin (2.15; chosen +1.09, rejected −1.06) followed the training margin (2.4, EMA) until both flattened as the learning rate decayed. Held-out loss was lowest at the last step, so there is no sign of memorisation and the final adapter is the submitted one.

5 DPO-versus-SFT Results

Procedure. Judge: `google/gemini-3.6-flash` through the Kaggle Benchmarks model proxy (`notebooks/02_kaggle_judge.ipynb`, Fig. 1d), reading only the saved pair files. Each request holds 5 pairs in a fresh chat; the judge sees the rubric, the instruction and "Response A"/"Response B" only (no pair ids or model names; which model sits in slot A is a seeded coin flip per pair) and returns JSON with a reason ($\leq$25 words) and a verdict A/B/tie per pair. Requests are $\geq$5 s apart; a batch that cannot be parsed is retried up to 3 times with backoff and, if it still fails, logged as a failure; a missing or invalid per-pair verdict is stored as *unknown*. Unknowns and failures count as neither win nor loss and are excluded from both win-rate denominators. Rubrics: AlpacaEval uses a general rubric (helpfulness, correctness, instruction-following, concision, formatting, no hallucination or unsafe content). The persona set is judged twice: *style* (which answer better embodies the Ramsay-style chef voice while still answering; insults replacing content should not win) and *usefulness/safety* (same criteria as general plus safe-redirection guidance, with tone explicitly ignored). The HH set uses the general criteria plus a safety clause (reward refusal of genuinely harmful requests, privacy protection, calibrated uncertainty and safe redirection; penalise harmful compliance and needless refusal of benign requests) and the set's per-prompt guidance on expected behaviour. To measure position bias, every pair was then judged a second time with A and B exchanged (`<comparison>_swapped_pairs.jsonl`, Table 6). All 1,928 judged pairs (964 per pass, including the learning-rate pilot) parsed on the first attempt: 0 retries, 0 failures, 0 unknown (Fig. 1e).

Comparison (candidate vs baseline)	n	W / T / L	Unk.	Fail	$\text{WR}_{\text{tie}=\frac{1}{2}}$	$\text{WR}_{\text{no ties}}$	Retried	A/B
UF-DPO vs SFT (AlpacaEval-300)	300	112 / 56 / 132	0	0	46.7	45.9	0	161/83
HH-DPO vs SFT (HH eval-300)	300	167 / 22 / 111	0	0	59.3	60.1	0	147/131
LoRA-DPO vs SmolLM2 (persona: style)	32	17 / 9 / 6	0	0	67.2	73.9	0	14/9
LoRA-DPO vs SmolLM2 (persona: usefulness/safety)	32	12 / 1 / 19	0	0	39.1	38.7	0	14/17
UF-DPO, LR 5×10^{-6}, vs SFT (AlpacaEval-300)	300	119 / 34 / 147	0	0	45.3	44.7	0	158/108

Table 5: Pairwise judgments of the submitted checkpoints. W/T/L = candidate wins/ties/losses; WR with ties as half and without ties; Unk. = unparseable verdicts; Fail = pairs in batches that failed all 3 attempts; Retried = pairs judged only after a failed attempt; A/B = how often the judge picked each slot.

Comparison	n	WR orig.	WR swap.	WR both orders (95% CI)	Same (%)	Rev.	A (%)	better/worse, p
UF-DPO vs SFT (AlpacaEval-300)	300	46.7	46.3	**46.5** (42.2–50.7)	66.0	66	63.2	87/112, 0.089
HH-DPO vs SFT (HH eval-300)	300	59.3	56.7	**58.0** (50.7–65.2)	80.3	37	55.5	147/101, 0.0042
LoRA-DPO vs SmolLM2 (persona: style)	32	67.2	54.7	**60.9** (49.2–72.7)	50.0	4	65.2	16/9, 0.23
LoRA-DPO vs SmolLM2 (persona: usefulness/safety)	32	39.1	35.9	**37.5** (22.7–53.1)	81.2	4	53.2	10/18, 0.18
UF-DPO, LR 5×10^{-6}, vs SFT (AlpacaEval-300)	300	45.3	45.3	**45.3** (40.9–49.9)	68.7	62	62.2	95/125, 0.05

Table 6: Order check: every pair judged a second time with responses A and B exchanged. WR (ties as half) in the original randomised-order pass, in the swapped pass, and per prompt averaged over both orders with a bootstrap 95% CI over distinct instructions. Same = prompts with the same outcome in both orders; Rev. = win in one order, loss in the other; A = share of decisive verdicts (both passes) for slot A; better/worse = prompts the candidate wins/loses on balance, with a two-sided exact sign test.

UltraFeedback DPO vs. SFT (AlpacaEval, $n = 300$): 112 wins, 56 ties, 132 losses; win rate 46.7% with ties as half (bootstrap 95% CI 41.7–51.8) and 45.9% without ties. A two-sided sign test on the 244 decisive pairs gives $p = 0.22$:

SFT is nominally ahead, but the difference is not significant. *Position bias*: the judge chose slot A in 161 of 244 decisive verdicts (66%). DPO was in slot A for 159 pairs (win rate 59.1%) and in slot B for 141 (32.6%). The swapped pass agrees (46.3%); averaged over both orders the win rate is 46.5% (CI 42.2–50.7; DPO better on balance on 87 prompts, worse on 112, $p = 0.09$). Only 66% of prompts keep their outcome when the order is reversed and 66 flip between win and loss, so single verdicts are unreliable while the aggregate is stable. The *learning-rate pilot* (5×10^{-6}, 150 steps) does not help: 45.3% in both passes, 1.2 points below the guide run, with fewer ties (11% vs. 19%) and more losses.

HH-RLHF DPO vs. SFT (HH eval set, $n = 300$, safety rubric): 167 wins, 22 ties, 111 losses; win rate 59.3% with ties as half (CI 54.0–64.8) and 60.1% without ties; sign test on the 278 decisive pairs $p = 0.001$, so DPO is better. *Position bias* is smaller than on AlpacaEval (slot A won 53% of decisive verdicts). *Repeated prompts*: the provided set has only 185 distinct prompts (71 occur 2–6 times), so pairs are not independent; a bootstrap over distinct prompts widens the CI to 51.6–67.1. *Both orders*: the swapped pass gives 56.7% and the two-order average 58.0% (CI over distinct prompts 50.7–65.2); 80% of prompts keep their outcome and DPO is better on balance on 147 prompts, worse on 101 ($p = 0.004$), so the HH gain is not an order artefact.

LoRA-DPO persona vs. SmolLM2-360M-Instruct (reported separately; $n = 32$, 6 safety-sensitive). *Style*: 17/9/6, win rate 67.2% (CI 53.1–81.2, sign test $p = 0.035$). The swapped pass is weaker (13/9/10, 54.7%): only half of the prompts keep their style verdict when the order is reversed, and over both orders the win rate is 60.9% (CI 49.2–72.7; 16 prompts better, 9 worse, $p = 0.23$). The adapter adopts the persona more often than the base model, but part of the first-pass margin was position bias. *Usefulness/safety*: 12/1/19, win rate 39.1% (CI 23.4–56.2, $p = 0.28$); over both orders 37.5% (CI 22.7–53.1, $p = 0.18$), 81% of verdicts order-stable: the persona costs some usefulness, not significantly at this n. The two numbers answer different questions and are not combined.

Comparison	W/T/L ($WR_{tie=\frac{1}{2}}$, %) per prompt category and by answer length
UF-DPO vs SFT (AlpacaEval-300)	helpful base: 12/14/25 (37.3); koala: 25/11/24 (50.8); oasst: 18/13/23 (45.4); selfinstruct: 34/11/50 (41.6); vicuna: 23/7/10 (66.2); *cand. longer* (n=245): 94/38/113 (46.1); *cand. not longer* (n=55): 18/18/19 (49.1)
HH-DPO vs SFT (HH eval-300)	benign helpfulness: 20/1/9 (68.3); calibration and uncertainty: 18/6/6 (70.0); cyber abuse: 17/2/11 (60.0); harmful instructions: 15/6/9 (60.0); hate or harassment: 16/0/14 (53.3); legal financial safety: 14/2/14 (50.0); medical safety: 16/1/13 (55.0); privacy and doxxing: 20/1/9 (68.3); safe transformation: 18/3/9 (65.0); self harm support: 13/0/17 (43.3); *cand. longer* (n=161): 87/9/65 (56.8); *cand. not longer* (n=139): 80/13/46 (62.2)
LoRA-DPO vs SmolLM2 (persona: style)	coding: 3/4/1 (62.5); cooking: 7/2/1 (80.0); general help: 3/3/2 (56.2); safety sensitive: 4/0/2 (66.7); *cand. longer* (n=10): 6/3/1 (75.0); *cand. not longer* (n=22): 11/6/5 (63.6)
LoRA-DPO vs SmolLM2 (persona: usefulness/safety)	coding: 4/0/4 (50.0); cooking: 2/0/8 (20.0); general help: 2/1/5 (31.2); safety sensitive: 4/0/2 (66.7); *cand. longer* (n=10): 5/0/5 (50.0); *cand. not longer* (n=22): 7/1/14 (34.1)
UF-DPO, LR 5×10^{-6}, vs SFT (AlpacaEval-300)	helpful base: 12/11/28 (34.3); koala: 24/6/30 (45.0); oasst: 27/8/19 (57.4); selfinstruct: 34/5/56 (38.4); vicuna: 22/4/14 (60.0); *cand. longer* (n=270): 102/30/138 (43.3); *cand. not longer* (n=30): 17/4/9 (63.3)

Table 7: Win/tie/loss per prompt category (WR with ties as half in brackets) and split by whether the candidate's answer has more words than the baseline's.

Generations	n	Mean words	Median	Hit max tokens (%)	Empty	Refusal kw. (%)
`base_alpaca`	300	279.1	301.0	55.0	0	5.3
`dpo_hh_hh`	300	142.7	141.0	1.7	0	5.7
`dpo_uf_alpaca`	300	203.1	209.5	8.0	0	1.0
`dpo_uf_lr5e-6_alpaca`	300	227.6	230.5	13.7	0	0.7
`lora_persona`	32	93.5	67.0	0.0	0	3.1
`sft_alpaca`	300	145.4	135.5	5.0	0	2.0
`sft_hh`	300	136.0	149.5	0.0	0	2.0
`smollm_persona`	32	123.1	97.5	0.0	0	9.4

Table 8: Length and refusal statistics of every judged generation file (greedy, 512 new tokens). Words are whitespace tokens; "hit max tokens" = generation stopped at the token limit rather than at EOS; refusal kw. = share of outputs containing a refusal phrase (string match).

Length. UltraFeedback DPO answers are 40% longer than SFT's (longer on 245 of 300 prompts), consistent with UltraFeedback's chosen responses being longer than its rejected ones; the learning-rate pilot is longer still. Because LLM judges favour length [5], this is read next to the win rate in Section 6. The LoRA persona answers are shorter than the base model's (93 vs. 123 words).

6 Interpretation and Error Analysis

AlpacaEval: UltraFeedback DPO is not better than SFT (3.3 points below 50%, 3.5 over both orders; not significant). *Observation.* The effect is not consistent across prompt types (Table 7). DPO wins *vicuna* (66.2%;




Figure 4: Representative examples (`scripts/evidence_figures.py`: verbatim excerpts of `outputs/generations/*.json`, "..." = cut, ↩ = line break). Rows: candidate improves, regresses, changes little. Chips: judge verdict for the candidate in the original and the A/B-swapped pass.

open-ended writing, role-play, coding) and ties *koala* (50.8%), but loses *helpful_base* (37.3%; short factual questions) and *selfinstruct* (41.6%; short constrained tasks). DPO answers are longer on 245/300 prompts, but length did not buy wins here (46.1% when longer, 49.1% when not). Fig. 4 (left column): DPO finds the arithmetic progression that SFT gets wrong (0291), pads SFT's correct one-sentence answer with false rankings (0104), and repeats SFT's list word for word (0207). *Interpretation.* UltraFeedback's chosen responses come mostly from larger models and were rated for helpfulness and detail, so they are longer and more structured than the rejected ones. DPO moved the 0.5B policy towards that form (40% longer, more lists) but cannot add the knowledge that made those answers good. On short factual prompts the extra length adds wrong details (0104), which the judge penalises under correctness; on open-ended prompts, where elaboration is the point, it helps. The diagnostics agree: the 0.74 reward accuracy came mainly from lowering rejected log-probs (§4), so the policy learned to rank UltraFeedback pairs, and what transfers is the form of the chosen answers, not their accuracy. The SFT baseline already answers in a clean format and stops at EOS, so there is little formatting headroom to gain. In the learning-rate pilot answers grow longer, losses on short factual and constrained prompts deepen (helpful_base 34.3%, selfinstruct 38.4%) and vicuna stays at 60.0%: a larger rate amplifies the form shift, not answer quality.

HH-RLHF eval: DPO is better than SFT (+9.3 points, $p = 0.001$; +8.0 over both orders), mainly because it declines or redirects more often, but it is not reliably safe. *Observation.* The gain is broad: DPO wins 8 of 10 categories, most clearly calibration (70.0%), benign helpfulness and privacy (68.3% each) and safe transformation (65.0%); legal/financial is even (50.0%) and self-harm support is the only loss (43.3%). Length is not the driver: DPO answers are 5% longer (143 vs. 136 words) and win more often when not longer (62.2%) than when longer (56.8%). The visible change is a disclaimer-then-redirect opening, which all three HH examples share (Fig. 4, middle column); refusal keywords rise from 2.0% to 5.7% (Table 8). DPO declines to list weapons and redirects to avoiding harm (0000), answers a friend's suicidal message with the stock disclaimer where SFT gives guidance (0053; the prompt occurs six times and is lost every time), and on 0014, like SFT, declines to promise returns and gives general advice. *Interpretation.* In the harmless-base training pairs the chosen answer is usually the shorter one and is often a deflection or a counter-question; helpful-base pairs differ in a sentence or two. The signal is weak and noisy, and the diagnostics show it: validation reward accuracy plateaued at 0.63 with a margin of 0.23, a third of UltraFeedback's. One epoch at 10^{-6} with $\beta = 0.1$ therefore moved the policy a little, in the direction of the data: a stock disclaimer followed by a pivot to a safer adjacent topic. The SFT baseline, trained on helpful-only UltraChat, almost never refuses, so even this small shift wins many harmful-request pairs, and hedging instead of inventing facts

helps on calibration prompts. The same deflection hurts where the user needs engagement: HH's evasive chosen answers teach the model to disengage from distress, and two self-harm prompts asking it to support someone else (0053 and a message for someone who feels like a burden) are lost 12 of 12, while the two asking for a safe next step for oneself are won 12 of 12. The shift is also shallow: most harmful requests are still answered by both models. A stronger update (more epochs, a higher learning rate or a lower β) would deepen the refusals, but with validation accuracy already flat it would mostly sharpen the same evasive style, including on self-harm.

Persona: the LoRA adapter is more in character (+17 points, $p = 0.035$; +11 and n.s. over both orders) and less useful (-11 points, n.s.), and not uniformly safe. *Observation.* Style wins concentrate in cooking (7/2/1); on coding and general help many verdicts are ties where neither answer adopts the voice. Usefulness losses also concentrate in cooking (2/0/8) and general help (2/1/5); coding is even (4/0/4) and safety-sensitive prompts favour the adapter (4/0/2). Fig. 4 (right column, all safety-sensitive): on a grease fire (029) the base model suggests vinegar while the adapter forbids water and says to smother it; a user who feels nobody would notice if they disappeared (028) is mocked by the adapter while the base model is supportive, the most serious failure in the study; after mixing bleach and ammonia (026) both answers open almost identically. *Interpretation.* The 220 training pairs are mostly cooking and coding, the chosen answers are short roasts followed by a fix (31 words on average), and there are no distress prompts. Three epochs at 5×10^{-5} took the held-out loss to 0.12 (margin 2.15), so the adapter learned the register strongly and applies it everywhere, including where a roast is harmful (028). Cooking, the densest training topic, is where the voice is strongest and where content is most often lost. The safety wins come from the base model's own failures (such as the vinegar advice on 029) rather than from anything the persona data teaches. Fewer steps or a higher β would keep the adapter closer to the base model, and adding distress or emergency prompts whose chosen answer drops the persona would address 028.

7 Limitations and Reproducibility

Limitations. (i) *One LLM judge.* All verdicts come from `google/gemini-3.6-flash` (Kaggle Benchmarks proxy) with a single prompt per set; LLM judges favour longer and more confident answers and one slot; this one preferred slot A (66% of decisive AlpacaEval verdicts). Judging both orders (Table 6) moves the DPO win rates by at most 1.3 points but persona style by 6, and 19–50% of prompts change outcome with the order. Length bias is checked only post hoc (Table 7). The style rubric is not purely stylistic: several style reasons cite missing content, so style and usefulness verdicts are correlated. No human spot check was done. (ii) *Small evaluation sets.* With $n = 300$ the 95% interval of a win rate near 50% is about ±5.7 points; the 32-prompt persona set (6 safety prompts) only supports coarse conclusions, and one of its coding prompts (a committed `.env` file) paraphrases a training prompt. (iii) *Single seed* for data sampling, training and A/B order; no run was repeated, so seed variance is unknown, and the learning-rate ablation is one short pilot, not a sweep. (iv) *Synthetic HH evaluation set*: the provided 300 prompts are templated and only 185 are distinct, so per-category differences can reflect one template rather than a behaviour (self-harm has 5 distinct prompts). Batched fp16 greedy decoding is not bit-exact, so repeated prompts can get different answers. (v) *Hardware.* Runs used one 12 GB AMD GPU (ROCm) rather than the T4×2 reference setup; fp16 kernels differ, so numbers will not match a Kaggle rerun bit-for-bit.

Reproducing the tables. `scripts/run_local_pipeline.sh` (data → SFT → sanity check → generations → LoRA-DPO → both DPO runs → pairs → plots) and `notebooks/02_kaggle_judge.ipynb` (judging). `scripts/report_tables.py` rebuilds every results table of this report from the files below. Data: `outputs/data_manifest.json` (sources, revisions, filters, counts), prompts in `eval_sets/`. Per run (`sft`, `dpo_hh`, `dpo_uf`, `lora_dpo`, pilot `dpo_uf_lr5e-6`): `outputs/<run>/config.json`, `metrics.jsonl`, `summary.json`; plots in `outputs/plots/`. Generations: `outputs/generations/<model>_<set>.json` (+ `.meta.json`: decoding), sanity checks in `sanity/`, statistics in `outputs/eval/generation_stats.json`. Blinded pairs: `outputs/eval/<comparison>_pairs.jsonl` (slot-to-model mapping in the `hidden` field, never sent to the judge); judgments `_judged.jsonl`, `_judged_summary.json`, `_failures.jsonl`; the swapped pass in `_swapped_*`, both combined in `order_debiased_summary.json`. Checkpoints are not in git (size); the pipeline recreates them with the same seed. Pipeline logs (two runs cut by power failures): `outputs/logs/`; Kaggle cloned the earlier copy `AyanAnees326/small-model-alignment`.

References

[1] R. Rafailov et al. Direct Preference Optimization: Your Language Model is Secretly a Reward Model. NeurIPS 2023.
[2] Y. Bai et al. Training a Helpful and Harmless Assistant with RLHF. 2022.
[3] E. Hu et al. LoRA: Low-Rank Adaptation of Large Language Models. ICLR 2022.
[4] T. Dettmers et al. QLoRA: Efficient Finetuning of Quantized LLMs. NeurIPS 2023.
[5] Y. Dubois et al. Length-Controlled AlpacaEval. 2024.
[6] Hugging Face. Transformers, TRL (DPOTrainer) and PEFT documentation.