IET, C-DAC

500 MCQ PRACTICE QUESTION BANK

C++ Programming

Moderate to Difficult | Conceptual | Code Output | Error Analysis | Tricky Applications

Purpose

A subject-wise practice resource for engineering graduates preparing for C-DAC course examinations. Questions are freshly authored for practice and are not represented as actual or leaked C-DAC examination questions.

Coverage

C++ fundamentals; expressions and control flow; pointers and references; classes and object lifetime; constructors/destructors; inheritance and polymorphism; operator overloading; templates; STL; exceptions; file handling; dynamic memory and modern C++ ownership.

Instructions

Each question has four options and one best answer. Attempt the questions before consulting the consolidated answer key at the end. For code questions, assume standard language behavior and the stated code fragment is complete for the operation being tested.

Question count: 500 **Options:** A–D **Answer key:** Included

IET, C-DAC

QUESTION PAPER

C++ Programming — 500 Questions

Q1.

Find the output.
int x=5+8; int s=0; for(int i=0;i<6;++i) s+=x-i; cout<<s;

A. 63
B. 62
C. 60
D. 64

Q2.

Evaluate the expression using integer arithmetic.
int x=6, y=6; cout << x%y + (x/y)*2;

A. 3
B. 2
C. -1
D. 1

Q3.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=2;++i) s += 16*i-6; cout<<s;

A. 37
B. 35
C. 36
D. 33

Q4.

What is printed?
int x=4; int i=3; while(i--) x/=2; cout<<x;

A. 0
B. -3
C. 1
D. -1

Q5.

Choose the output of this loop.
int s=0; for(int i=1;i<=4;i++) s += (i%2==0 ? 14 : 9); cout<<s;

A. 43
B. 46
C. 47
D. 45

Q6.

What is printed?
int x=14; int i=7; while(i--) x/=2; cout<<x;

A. -3
B. 0
C. -1
D. 1

IET, C-DAC

Q7.

Determine the output.
int x=5; for(int i=0;i<3;++i) x=(x*11+i)%97; cout<<x;

A. 73
B. 71
C. 69
D. 72

Q8.

What is printed?
int x=14; int i=3; while(i--) x/=2; cout<<x;

A. 0
B. -2
C. 1
D. 2

Q9.

What is the final value of s?
int s=0; for(int i=1;i<=2;++i) s+=i*i; cout<<s;

A. 2
B. 4
C. 5
D. 6

Q10.

What is the value printed?
int x=(5 << 2) ^ (2+3); cout<<x;

A. 14
B. 18
C. 17
D. 16

Q11.

Choose the output of this loop.
int s=0; for(int i=1;i<=2;i++) s += (i%2==0 ? 13 : 8); cout<<s;

A. 20
B. 21
C. 18
D. 22

Q12.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=2;++i) s += 5*i-11; cout<<s;

A. -8
B. -7
C. -10
D. -6

Q13.

What is the final value of s?
int s=0; for(int i=1;i<=7;++i) s+=i*i; cout<<s;

A. 137
B. 140
C. 141
D. 139

IET, C-DAC

Q14.

Evaluate the expression using integer arithmetic.
int x=12, y=2; cout << x%y + (x/y)*2;

A. 13
B. 12
C. 9
D. 11

Q15.

What is printed?
int x=15; int i=4; while(i--) x/=2; cout<<x;

A. 0
B. -3
C. -1
D. 1

Q16.

Choose the output of this loop.
int s=0; for(int i=1;i<=6;i++) s += (i%2==0 ? 9 : 13); cout<<s;

A. 65
B. 63
C. 67
D. 66

Q17.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=4;++i) s += 2*i-6; cout<<s;

A. -5
B. -7
C. -3
D. -4

Q18.

Determine the output.
int x=5; for(int i=0;i<3;++i) x=(x*11+i)%97; cout<<x;

A. 69
B. 71
C. 73
D. 72

Q19.

Which header provides std::sort?

A. <vector>
B. <iostream>
C. <algorithm>
D. <memory>

Q20.

Which operator cannot be overloaded as a user-defined operator in C++?

A. ()
B. ::
C. []
D. +

IET, C-DAC

Q21.

Find the output.
int x=13+5; int s=0; for(int i=0;i<6;++i) s+=x-i; cout<<s;

A. 90
B. 93
C. 94
D. 92

Q22.

What is the final value of s?
int s=0; for(int i=1;i<=7;++i) s+=i*i; cout<<s;

A. 139
B. 141
C. 137
D. 140

Q23.

What is the final value of s?
int s=0; for(int i=1;i<=3;++i) s+=i*i; cout<<s;

A. 11
B. 15
C. 13
D. 14

Q24.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=4;++i) s += 18*i-7; cout<<s;

A. 151
B. 149
C. 153
D. 152

Q25.

What is printed?
int x=2; int i=8; while(i--) x/=2; cout<<x;

A. 1
B. -1
C. -3
D. 0

Q26.

Determine the output.
int x=16; for(int i=0;i<7;++i) x=(x*3+i)%97; cout<<x;

A. 33
B. 32
C. 30
D. 34

Q27.

What is the value printed?
int x=(15 << 2) ^ (2+3); cout<<x;

A. 58
B. 56
C. 57
D. 54

IET, C-DAC

Q28.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=7;++i) s += 15*i-7; cout<<s;

A. 370
B. 371
C. 372
D. 368

Q29.

Evaluate the expression using integer arithmetic.
int x=14, y=11; cout << x%y + (x/y)*2;

A. 4
B. 6
C. 5
D. 2

Q30.

Find the output.
int x=16+3; int s=0; for(int i=0;i<2;++i) s+=x-i; cout<<s;

A. 37
B. 36
C. 34
D. 38

Q31.

What happens when a non-const lvalue reference parameter is bound to a temporary value?

A. The reference becomes null
B. The temporary is copied into the reference
C. The program always throws bad_alloc
D. The binding is ill-formed

Q32.

What is printed?
int x=3; int i=6; while(i--) x/=2; cout<<x;

A. -3
B. 0
C. 1
D. -1

Q33.

Find the output.
int x=18+6; int s=0; for(int i=0;i<4;++i) s+=x-i; cout<<s;

A. 87
B. 89
C. 90
D. 91

Q34.

What is the final value of s?
int s=0; for(int i=1;i<=4;++i) s+=i*i; cout<<s;

A. 30
B. 29
C. 27
D. 31

IET, C-DAC

Q35.

Determine the output.
int x=8; for(int i=0;i<7;++i) x=(x*9+i)%97; cout<<x;

A. 12
B. 8
C. 11
D. 10

Q36.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=2;++i) s += 12*i-13; cout<<s;

A. 10
B. 7
C. 11
D. 9

Q37.

What is the final value of s?
int s=0; for(int i=1;i<=4;++i) s+=i*i; cout<<s;

A. 31
B. 30
C. 29
D. 27

Q38.

Choose the output of this loop.
int s=0; for(int i=1;i<=2;i++) s += (i%2==0 ? 7 : 10); cout<<s;

A. 17
B. 18
C. 14
D. 16

Q39.

Find the output.
int x=6+7; int s=0; for(int i=0;i<2;++i) s+=x-i; cout<<s;

A. 24
B. 22
C. 26
D. 25

Q40.

What is the value printed?
int x=(10 << 2) ^ (6+3); cout<<x;

A. 33
B. 34
C. 30
D. 32

Q41.

What is the value printed?
int x=(6 << 2) ^ (11+3); cout<<x;

A. 21
B. 19
C. 23
D. 22

IET, C-DAC

Q42.

What is printed?
int x=9; int i=5; while(i--) x/=2; cout<<x;

A. 0
B. 1
C. -3
D. -1

Q43.

Determine the output.
int x=8; for(int i=0;i<6;++i) x=(x*8+i)%97; cout<<x;

A. 27
B. 23
C. 25
D. 26

Q44.

Evaluate the expression using integer arithmetic.
int x=8, y=7; cout << x%y + (x/y)*2;

A. 3
B. 4
C. 2
D. 0

Q45.

Determine the output.
int x=12; for(int i=0;i<6;++i) x=(x*4+i)%97; cout<<x;

A. 35
B. 37
C. 38
D. 39

Q46.

Which statement about a pure virtual function is correct?

A. It makes the class abstract unless implemented as permitted by the language rules
B. It must be private
C. It is called only by constructors
D. It cannot have a definition

Q47.

What is the value printed?
int x=(16 << 2) ^ (13+3); cout<<x;

A. 79
B. 80
C. 77
D. 81

Q48.

Which is the correct purpose of a copy constructor?

A. Convert every pointer to a reference
B. Initialize a new object from an existing object of the same class
C. Assign to an already initialized object
D. Destroy an object

IET, C-DAC

Q49.

Evaluate the expression using integer arithmetic.
int x=2, y=8; cout << x%y + (x/y)*2;

A. 3
B. 1
C. 2
D. -1

Q50.

What is printed?
int x=4; int i=2; while(i--) x/=2; cout<<x;

A. -2
B. 1
C. 0
D. 2

Q51.

Evaluate the expression using integer arithmetic.
int x=9, y=8; cout << x%y + (x/y)*2;

A. 2
B. 4
C. 0
D. 3

Q52.

Determine the output.
int x=11; for(int i=0;i<7;++i) x=(x*4+i)%97; cout<<x;

A. 67
B. 71
C. 70
D. 69

Q53.

Determine the output.
int x=8; for(int i=0;i<2;++i) x=(x*9+i)%97; cout<<x;

A. 68
B. 66
C. 64
D. 67

Q54.

Find the output.
int x=18+5; int s=0; for(int i=0;i<3;++i) s+=x-i; cout<<s;

A. 67
B. 66
C. 65
D. 63

Q55.

What is the value printed?
int x=(2 << 2) ^ (11+3); cout<<x;

A. 6
B. 5
C. 7
D. 3

IET, C-DAC

Q56.

What is the final value of s?
int s=0; for(int i=1;i<=7;++i) s+=i*i; cout<<s;

A. 140
B. 139
C. 137
D. 141

Q57.

Determine the output.
int x=18; for(int i=0;i<5;++i) x=(x*8+i)%97; cout<<x;

A. 54
B. 52
C. 50
D. 53

Q58.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=7;++i) s += 18*i-12; cout<<s;

A. 421
B. 420
C. 419
D. 417

Q59.

Determine the output.
int x=12; for(int i=0;i<5;++i) x=(x*3+i)%97; cout<<x;

A. 63
B. 61
C. 64
D. 65

Q60.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=2;++i) s += 17*i-3; cout<<s;

A. 45
B. 46
C. 42
D. 44

Q61.

Find the output.
int x=11+3; int s=0; for(int i=0;i<4;++i) s+=x-i; cout<<s;

A. 51
B. 50
C. 47
D. 49

Q62.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=4;++i) s += 17*i-3; cout<<s;

A. 158
B. 157
C. 155
D. 159

IET, C-DAC

Q63.

What is the value printed?
int x=(3 << 2) ^ (11+3); cout<<x;

A. 1
B. 2
C. 3
D. -1

Q64.

Determine the output.
int x=16; for(int i=0;i<5;++i) x=(x*11+i)%97; cout<<x;

A. 66
B. 68
C. 69
D. 70

Q65.

Which STL container provides constant-time random access by index?

A. std::vector
B. std::list
C. std::forward_list
D. std::map

Q66.

What is the final value of s?
int s=0; for(int i=1;i<=3;++i) s+=i*i; cout<<s;

A. 15
B. 13
C. 14
D. 11

Q67.

Choose the output of this loop.
int s=0; for(int i=1;i<=5;i++) s += (i%2==0 ? 16 : 13); cout<<s;

A. 70
B. 68
C. 71
D. 72

Q68.

Find the output.
int x=10+13; int s=0; for(int i=0;i<3;++i) s+=x-i; cout<<s;

A. 65
B. 63
C. 66
D. 67

Q69.

Evaluate the expression using integer arithmetic.
int x=8, y=6; cout << x%y + (x/y)*2;

A. 1
B. 3
C. 5
D. 4

IET, C-DAC

Q70.

Evaluate the expression using integer arithmetic.
int x=4, y=7; cout << x%y + (x/y)*2;

A. 4
B. 3
C. 1
D. 5

Q71.

Find the output.
int x=3+4; int s=0; for(int i=0;i<6;++i) s+=x-i; cout<<s;

A. 26
B. 27
C. 24
D. 28

Q72.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=8;++i) s += 4*i-10; cout<<s;

A. 65
B. 63
C. 64
D. 61

Q73.

Determine the output.
int x=5; for(int i=0;i<2;++i) x=(x*6+i)%97; cout<<x;

A. 84
B. 81
C. 85
D. 83

Q74.

Determine the output.
int x=15; for(int i=0;i<3;++i) x=(x*6+i)%97; cout<<x;

A. 44
B. 47
C. 46
D. 48

Q75.

What is printed?
int x=6; int i=4; while(i--) x/=2; cout<<x;

A. 0
B. 1
C. -3
D. -1

Q76.

Determine the output.
int x=18; for(int i=0;i<3;++i) x=(x*3+i)%97; cout<<x;

A. 6
B. 7
C. 3
D. 5

IET, C-DAC

Q77.

Choose the output of this loop.
int s=0; for(int i=1;i<=3;i++) s += (i%2==0 ? 2 : 3); cout<<s;

A. 9
B. 5
C. 7
D. 8

Q78.

Choose the output of this loop.
int s=0; for(int i=1;i<=8;i++) s += (i%2==0 ? 9 : 6); cout<<s;

A. 59
B. 57
C. 60
D. 61

Q79.

Determine the output.
int x=3; for(int i=0;i<8;++i) x=(x*13+i)%97; cout<<x;

A. 14
B. 15
C. 11
D. 13

Q80.

What is the final value of s?
int s=0; for(int i=1;i<=6;++i) s+=i*i; cout<<s;

A. 90
B. 88
C. 92
D. 91

Q81.

Determine the output.
int x=16; for(int i=0;i<5;++i) x=(x*6+i)%97; cout<<x;

A. 82
B. 80
C. 78
D. 81

Q82.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=5;++i) s += 3*i-6; cout<<s;

A. 14
B. 16
C. 15
D. 12

Q83.

What is the final value of s?
int s=0; for(int i=1;i<=8;++i) s+=i*i; cout<<s;

A. 201
B. 204
C. 203
D. 205

IET, C-DAC

Q84.

Determine the output.
int x=2; for(int i=0;i<5;++i) x=(x*7+i)%97; cout<<x;

A. 32
B. 34
C. 30
D. 33

Q85.

What is the final value of s?
int s=0; for(int i=1;i<=7;++i) s+=i*i; cout<<s;

A. 141
B. 140
C. 137
D. 139

Q86.

Evaluate the expression using integer arithmetic.
int x=2, y=6; cout << x%y + (x/y)*2;

A. 3
B. 1
C. 2
D. -1

Q87.

Determine the output.
int x=10; for(int i=0;i<5;++i) x=(x*7+i)%97; cout<<x;

A. 48
B. 46
C. 47
D. 44

Q88.

What is the value printed?
int x=(7 << 2) ^ (6+3); cout<<x;

A. 22
B. 21
C. 20
D. 18

Q89.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=5;++i) s += 14*i-11; cout<<s;

A. 156
B. 154
C. 155
D. 152

Q90.

What is the final value of s?
int s=0; for(int i=1;i<=8;++i) s+=i*i; cout<<s;

A. 201
B. 204
C. 205
D. 203

IET, C-DAC

Q91.

What is the value printed?
int x=(18 << 2) ^ (8+3); cout<<x;

A. 67
B. 68
C. 64
D. 66

Q92.

Which statement about a reference in C++ is correct?

A. It must be initialized when declared
B. It is always nullable
C. It owns dynamically allocated memory
D. It can be reseated to refer to another object

Q93.

Find the output.
int x=17+12; int s=0; for(int i=0;i<3;++i) s+=x-i; cout<<s;

A. 85
B. 81
C. 84
D. 83

Q94.

Choose the output of this loop.
int s=0; for(int i=1;i<=5;i++) s += (i%2==0 ? 7 : 11); cout<<s;

A. 47
B. 46
C. 44
D. 48

Q95.

Find the output.
int x=14+2; int s=0; for(int i=0;i<2;++i) s+=x-i; cout<<s;

A. 31
B. 28
C. 30
D. 32

Q96.

Evaluate the expression using integer arithmetic.
int x=14, y=10; cout << x%y + (x/y)*2;

A. 5
B. 3
C. 6
D. 7

Q97.

Evaluate the expression using integer arithmetic.
int x=5, y=9; cout << x%y + (x/y)*2;

A. 2
B. 6
C. 4
D. 5

IET, C-DAC

Q98.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=7;++i) s += 2*i-9; cout<<s;

A. -7
B. -8
C. -6
D. -10

Q99.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=4;++i) s += 9*i-5; cout<<s;

A. 71
B. 70
C. 67
D. 69

Q100.

Which statement about static data members is correct?

A. They can only be accessed in constructors
B. They are shared by all objects of the class
C. They are always constant
D. Each object gets a separate copy

Q101.

What is printed?
int x=10; int i=5; while(i--) x/=2; cout<<x;

A. -3
B. 0
C. -1
D. 1

Q102.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=4;++i) s += 18*i-3; cout<<s;

A. 169
B. 165
C. 167
D. 168

Q103.

What is printed?
int x=17; int i=2; while(i--) x/=2; cout<<x;

A. 3
B. 1
C. 5
D. 4

Q104.

Find the output.
int x=11+2; int s=0; for(int i=0;i<4;++i) s+=x-i; cout<<s;

A. 46
B. 43
C. 45
D. 47

IET, C-DAC

Q105.

What is printed?
int x=11; int i=4; while(i--) x/=2; cout<<x;

A. -1
B. 1
C. 0
D. -3

Q106.

Determine the output.
int x=18; for(int i=0;i<2;++i) x=(x*6+i)%97; cout<<x;

A. 68
B. 67
C. 66
D. 64

Q107.

Choose the output of this loop.
int s=0; for(int i=1;i<=8;i++) s += (i%2==0 ? 16 : 11); cout<<s;

A. 108
B. 109
C. 105
D. 107

Q108.

Evaluate the expression using integer arithmetic.
int x=7, y=7; cout << x%y + (x/y)*2;

A. -1
B. 3
C. 1
D. 2

Q109.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=6;++i) s += 12*i-8; cout<<s;

A. 203
B. 205
C. 204
D. 201

Q110.

Evaluate the expression using integer arithmetic.
int x=7, y=12; cout << x%y + (x/y)*2;

A. 6
B. 8
C. 7
D. 4

Q111.

Evaluate the expression using integer arithmetic.
int x=7, y=5; cout << x%y + (x/y)*2;

A. 3
B. 1
C. 4
D. 5

IET, C-DAC

Q112.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=2;++i) s += 16*i-3; cout<<s;

A. 41
B. 43
C. 42
D. 39

Q113.

Choose the output of this loop.
int s=0; for(int i=1;i<=8;i++) s += (i%2==0 ? 9 : 2); cout<<s;

A. 41
B. 45
C. 43
D. 44

Q114.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=6;++i) s += 2*i-3; cout<<s;

A. 21
B. 24
C. 23
D. 25

Q115.

What is printed?
int x=4; int i=8; while(i--) x/=2; cout<<x;

A. 0
B. -3
C. -1
D. 1

Q116.

Which smart pointer supports shared ownership?

A. std::shared_ptr
B. std::unique_ptr
C. std::span
D. std::weak_ptr

Q117.

What is printed?
int x=14; int i=4; while(i--) x/=2; cout<<x;

A. 0
B. -1
C. 1
D. -3

Q118.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=5;++i) s += 19*i-12; cout<<s;

A. 226
B. 222
C. 224
D. 225

IET, C-DAC

Q119.

What is printed?
int x=4; int i=3; while(i--) x/=2; cout<<x;

A. 1
B. -1
C. 0
D. -3

Q120.

Determine the output.
int x=8; for(int i=0;i<7;++i) x=(x*5+i)%97; cout<<x;

A. 60
B. 57
C. 61
D. 59

Q121.

Determine the output.
int x=15; for(int i=0;i<7;++i) x=(x*9+i)%97; cout<<x;

A. 80
B. 81
C. 77
D. 79

Q122.

Evaluate the expression using integer arithmetic.
int x=3, y=6; cout << x%y + (x/y)*2;

A. 2
B. 4
C. 3
D. 0

Q123.

What is the final value of s?
int s=0; for(int i=1;i<=3;++i) s+=i*i; cout<<s;

A. 15
B. 13
C. 14
D. 11

Q124.

Find the output.
int x=9+5; int s=0; for(int i=0;i<4;++i) s+=x-i; cout<<s;

A. 47
B. 50
C. 51
D. 49

Q125.

Evaluate the expression using integer arithmetic.
int x=11, y=6; cout << x%y + (x/y)*2;

A. 8
B. 6
C. 7
D. 4

IET, C-DAC

Q126.

Evaluate the expression using integer arithmetic.
int x=5, y=8; cout << x%y + (x/y)*2;

A. 4
B. 6
C. 5
D. 2

Q127.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=3;++i) s += 8*i-8; cout<<s;

A. 24
B. 23
C. 21
D. 25

Q128.

What is the value printed?
int x=(4 << 2) ^ (9+3); cout<<x;

A. 27
B. 28
C. 25
D. 29

Q129.

Determine the output.
int x=6; for(int i=0;i<6;++i) x=(x*10+i)%97; cout<<x;

A. 88
B. 90
C. 91
D. 92

Q130.

Determine the output.
int x=14; for(int i=0;i<3;++i) x=(x*11+i)%97; cout<<x;

A. 22
B. 24
C. 23
D. 20

Q131.

Choose the output of this loop.
int s=0; for(int i=1;i<=8;i++) s += (i%2==0 ? 13 : 11); cout<<s;

A. 96
B. 93
C. 97
D. 95

Q132.

What is printed?
int x=9; int i=8; while(i--) x/=2; cout<<x;

A. -3
B. -1
C. 0
D. 1

IET, C-DAC

Q133.

Evaluate the expression using integer arithmetic.
int x=7, y=10; cout << x%y + (x/y)*2;

A. 7
B. 8
C. 6
D. 4

Q134.

What is the final value of s?
int s=0; for(int i=1;i<=5;++i) s+=i*i; cout<<s;

A. 54
B. 52
C. 56
D. 55

Q135.

Determine the output.
int x=10; for(int i=0;i<4;++i) x=(x*13+i)%97; cout<<x;

A. 47
B. 46
C. 43
D. 45

Q136.

What is the final value of s?
int s=0; for(int i=1;i<=8;++i) s+=i*i; cout<<s;

A. 204
B. 201
C. 203
D. 205

Q137.

What is the final value of s?
int s=0; for(int i=1;i<=6;++i) s+=i*i; cout<<s;

A. 90
B. 88
C. 92
D. 91

Q138.

What is the value printed?
int x=(2 << 2) ^ (8+3); cout<<x;

A. 0
B. 3
C. 4
D. 2

Q139.

Find the output.
int x=9+13; int s=0; for(int i=0;i<2;++i) s+=x-i; cout<<s;

A. 42
B. 40
C. 44
D. 43

IET, C-DAC

Q140.

When should delete[] be used?

A. When releasing a single object allocated with new
B. When releasing memory allocated with new[]
C. When releasing a reference
D. When releasing an automatic local variable

Q141.

What is printed?
int x=11; int i=4; while(i--) x/=2; cout<<x;

A. 1
B. -3
C. 0
D. -1

Q142.

Determine the output.
int x=15; for(int i=0;i<4;++i) x=(x*6+i)%97; cout<<x;

A. 91
B. 92
C. 88
D. 90

Q143.

Choose the output of this loop.
int s=0; for(int i=1;i<=5;i++) s += (i%2==0 ? 10 : 12); cout<<s;

A. 53
B. 57
C. 55
D. 56

Q144.

Which operation on std::map is logarithmic on average/guaranteed by its ordered-tree implementation?

A. push_back(value)
B. Appending to a vector with spare capacity
C. Accessing the first character of a string
D. find(key)

Q145.

What is the value printed?
int x=(8 << 2) ^ (6+3); cout<<x;

A. 41
B. 40
C. 42
D. 38

Q146.

Find the output.
int x=6+10; int s=0; for(int i=0;i<7;++i) s+=x-i; cout<<s;

A. 91
B. 88
C. 90
D. 92

IET, C-DAC

Q147.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=3;++i) s += 4*i-4; cout<<s;

A. 12
B. 11
C. 9
D. 13

Q148.

Determine the output.
int x=3; for(int i=0;i<8;++i) x=(x*4+i)%97; cout<<x;

A. 89
B. 91
C. 87
D. 90

Q149.

Choose the output of this loop.
int s=0; for(int i=1;i<=6;i++) s += (i%2==0 ? 16 : 4); cout<<s;

A. 60
B. 61
C. 59
D. 57

Q150.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=3;++i) s += 3*i-6; cout<<s;

A. -1
B. 1
C. -3
D. 0

Q151.

Which C++ mechanism resolves a virtual call through a base reference?

A. Template argument deduction
B. Preprocessor substitution
C. Dynamic dispatch using the object's dynamic type
D. Static binding using only the declared reference type

Q152.

What is the final value of s?
int s=0; for(int i=1;i<=5;++i) s+=i*i; cout<<s;

A. 54
B. 56
C. 55
D. 52

Q153.

What is the final value of s?
int s=0; for(int i=1;i<=3;++i) s+=i*i; cout<<s;

A. 15
B. 14
C. 11
D. 13

IET, C-DAC

Q154.

Find the output.
int x=3+7; int s=0; for(int i=0;i<8;++i) s+=x-i; cout<<s;

A. 53
B. 51
C. 52
D. 49

Q155.

What is the value printed?
int x=(10 << 2) ^ (9+3); cout<<x;

A. 33
B. 36
C. 37
D. 35

Q156.

What is the value printed?
int x=(5 << 2) ^ (11+3); cout<<x;

A. 26
B. 23
C. 25
D. 27

Q157.

Determine the output.
int x=14; for(int i=0;i<5;++i) x=(x*13+i)%97; cout<<x;

A. 24
B. 22
C. 25
D. 26

Q158.

What is the final value of s?
int s=0; for(int i=1;i<=5;++i) s+=i*i; cout<<s;

A. 52
B. 55
C. 54
D. 56

Q159.

What is printed?
int x=16; int i=4; while(i--) x/=2; cout<<x;

A. 0
B. -2
C. 2
D. 1

Q160.

Which member is not inherited as an accessible member in the ordinary sense?

A. A base class's private member
B. A public virtual function
C. A protected base member
D. A public base member

IET, C-DAC

Q161.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=2;++i) s += 8*i-5; cout<<s;

A. 11
B. 14
C. 15
D. 13

Q162.

Determine the output.
int x=17; for(int i=0;i<3;++i) x=(x*13+i)%97; cout<<x;

A. 19
B. 20
C. 16
D. 18

Q163.

Determine the output.
int x=10; for(int i=0;i<6;++i) x=(x*9+i)%97; cout<<x;

A. 29
B. 32
C. 33
D. 31

Q164.

Find the output.
int x=6+10; int s=0; for(int i=0;i<4;++i) s+=x-i; cout<<s;

A. 59
B. 58
C. 57
D. 55

Q165.

Determine the output.
int x=11; for(int i=0;i<7;++i) x=(x*8+i)%97; cout<<x;

A. 57
B. 53
C. 56
D. 55

Q166.

What is the value printed?
int x=(16 << 2) ^ (2+3); cout<<x;

A. 66
B. 68
C. 70
D. 69

Q167.

Choose the output of this loop.
int s=0; for(int i=1;i<=3;i++) s += (i%2==0 ? 8 : 11); cout<<s;

A. 27
B. 31
C. 29
D. 30

IET, C-DAC

Q168.

Choose the output of this loop.
int s=0; for(int i=1;i<=7;i++) s += (i%2==0 ? 13 : 11); cout<<s;

A. 83
B. 80
C. 82
D. 84

Q169.

What does the explicit keyword on a single-argument constructor commonly prevent?

A. Destruction
B. Direct construction
C. Implicit conversion through that constructor
D. Inheritance

Q170.

What is the final value of s?
int s=0; for(int i=1;i<=8;++i) s+=i*i; cout<<s;

A. 205
B. 203
C. 204
D. 201

Q171.

Choose the output of this loop.
int s=0; for(int i=1;i<=6;i++) s += (i%2==0 ? 4 : 11); cout<<s;

A. 46
B. 44
C. 45
D. 42

Q172.

What is the value printed?
int x=(5 << 2) ^ (8+3); cout<<x;

A. 28
B. 31
C. 30
D. 32

Q173.

What is the value printed?
int x=(6 << 2) ^ (13+3); cout<<x;

A. 8
B. 9
C. 5
D. 7

Q174.

What is the value printed?
int x=(7 << 2) ^ (12+3); cout<<x;

A. 16
B. 20
C. 18
D. 19

IET, C-DAC

Q175.

Evaluate the expression using integer arithmetic.
int x=5, y=6; cout << x%y + (x/y)*2;

A. 6
B. 2
C. 4
D. 5

Q176.

Choose the output of this loop.
int s=0; for(int i=1;i<=4;i++) s += (i%2==0 ? 19 : 5); cout<<s;

A. 48
B. 47
C. 45
D. 49

Q177.

What is the value printed?
int x=(7 << 2) ^ (5+3); cout<<x;

A. 20
B. 17
C. 19
D. 21

Q178.

Evaluate the expression using integer arithmetic.
int x=12, y=12; cout << x%y + (x/y)*2;

A. 2
B. -1
C. 1
D. 3

Q179.

Evaluate the expression using integer arithmetic.
int x=12, y=7; cout << x%y + (x/y)*2;

A. 4
B. 8
C. 6
D. 7

Q180.

What is the usual complexity of insertion at the beginning of std::list when an iterator is already available?

A. O(log n)
B. O(n log n)
C. O(1)
D. O(n)

Q181.

Choose the output of this loop.
int s=0; for(int i=1;i<=4;i++) s += (i%2==0 ? 9 : 8); cout<<s;

A. 33
B. 34
C. 31
D. 35

IET, C-DAC

Q182.

Find the output.
int x=9+9; int s=0; for(int i=0;i<8;++i) s+=x-i; cout<<s;

A. 116
B. 117
C. 115
D. 113

Q183.

Choose the output of this loop.
int s=0; for(int i=1;i<=2;i++) s += (i%2==0 ? 17 : 10); cout<<s;

A. 28
B. 24
C. 26
D. 27

Q184.

What is the value printed?
int x=(19 << 2) ^ (13+3); cout<<x;

A. 92
B. 93
C. 91
D. 89

Q185.

What is the value printed?
int x=(18 << 2) ^ (5+3); cout<<x;

A. 61
B. 65
C. 63
D. 64

Q186.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=8;++i) s += 8*i-7; cout<<s;

A. 229
B. 232
C. 233
D. 231

Q187.

What is the final value of s?
int s=0; for(int i=1;i<=8;++i) s+=i*i; cout<<s;

A. 204
B. 203
C. 201
D. 205

Q188.

Choose the output of this loop.
int s=0; for(int i=1;i<=2;i++) s += (i%2==0 ? 19 : 8); cout<<s;

A. 27
B. 28
C. 26
D. 24

IET, C-DAC

Q189.

What is printed?
int x=17; int i=8; while(i--) x/=2; cout<<x;

A. 0
B. 1
C. -1
D. -3

Q190.

What is the purpose of std::weak_ptr?

A. Observe a shared object without increasing its reference count
B. Disable reference counting
C. Own an object exclusively
D. Allocate an array on the stack

Q191.

What is the value printed?
int x=(19 << 2) ^ (5+3); cout<<x;

A. 67
B. 69
C. 65
D. 68

Q192.

Evaluate the expression using integer arithmetic.
int x=6, y=5; cout << x%y + (x/y)*2;

A. 4
B. 3
C. 2
D. 0

Q193.

What is printed?
int x=11; int i=8; while(i--) x/=2; cout<<x;

A. 1
B. -3
C. -1
D. 0

Q194.

What is the result of deleting a derived object through a base pointer when the base destructor is non-virtual?

A. Only the derived destructor runs
B. Undefined behavior
C. Compile-time conversion to delete[]
D. Guaranteed call to both destructors

Q195.

What is the final value of s?
int s=0; for(int i=1;i<=4;++i) s+=i*i; cout<<s;

A. 31
B. 30
C. 29
D. 27

IET, C-DAC

Q196.

What is the final value of s?
int s=0; for(int i=1;i<=4;++i) s+=i*i; cout<<s;

A. 31
B. 30
C. 29
D. 27

Q197.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=3;++i) s += 17*i-4; cout<<s;

A. 90
B. 89
C. 87
D. 91

Q198.

Choose the output of this loop.
int s=0; for(int i=1;i<=5;i++) s += (i%2==0 ? 8 : 8); cout<<s;

A. 39
B. 40
C. 37
D. 41

Q199.

Find the output.
int x=10+12; int s=0; for(int i=0;i<5;++i) s+=x-i; cout<<s;

A. 97
B. 99
C. 100
D. 101

Q200.

What is printed?
int x=3; int i=6; while(i--) x/=2; cout<<x;

A. -3
B. 0
C. 1
D. -1

Q201.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=5;++i) s += 4*i-11; cout<<s;

A. 6
B. 5
C. 4
D. 2

Q202.

What is the value printed?
int x=(5 << 2) ^ (9+3); cout<<x;

A. 25
B. 23
C. 21
D. 24

IET, C-DAC

Q203.

What is printed?
int x=16; int i=7; while(i--) x/=2; cout<<x;

A. 0
B. 1
C. -3
D. -1

Q204.

What is the value printed?
int x=(13 << 2) ^ (9+3); cout<<x;

A. 56
B. 53
C. 55
D. 57

Q205.

Choose the output of this loop.
int s=0; for(int i=1;i<=4;i++) s += (i%2==0 ? 4 : 12); cout<<s;

A. 29
B. 32
C. 33
D. 31

Q206.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=7;++i) s += 8*i-8; cout<<s;

A. 168
B. 169
C. 165
D. 167

Q207.

Which expression is valid for accessing a member through a pointer p?

A. p->member
B. p::member
C. p.member
D. p=>member

Q208.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=2;++i) s += 15*i-8; cout<<s;

A. 28
B. 26
C. 29
D. 30

Q209.

What does noexcept communicate about a function?

A. The function cannot call other functions
B. The function returns void
C. The function is always optimized away
D. The function is specified not to propagate exceptions

IET, C-DAC

Q210.

What is the final value of s?
int s=0; for(int i=1;i<=6;++i) s+=i*i; cout<<s;

A. 91
B. 90
C. 92
D. 88

Q211.

Evaluate the expression using integer arithmetic.
int x=15, y=8; cout << x%y + (x/y)*2;

A. 10
B. 6
C. 8
D. 9

Q212.

Choose the output of this loop.
int s=0; for(int i=1;i<=8;i++) s += (i%2==0 ? 12 : 5); cout<<s;

A. 69
B. 65
C. 68
D. 67

Q213.

Which cast is intended primarily for safe runtime-checked downcasting in a polymorphic hierarchy?

A. static_cast
B. reinterpret_cast
C. const_cast
D. dynamic_cast

Q214.

What is the final value of s?
int s=0; for(int i=1;i<=3;++i) s+=i*i; cout<<s;

A. 11
B. 13
C. 15
D. 14

Q215.

What is printed?
int x=6; int i=3; while(i--) x/=2; cout<<x;

A. 0
B. -3
C. -1
D. 1

Q216.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=7;++i) s += 6*i-3; cout<<s;

A. 147
B. 146
C. 148
D. 144

IET, C-DAC

Q217.

What is the final value of s?
int s=0; for(int i=1;i<=2;++i) s+=i*i; cout<<s;

A. 6
B. 5
C. 2
D. 4

Q218.

What is the value printed?
int x=(7 << 2) ^ (2+3); cout<<x;

A. 25
B. 22
C. 26
D. 24

Q219.

Find the output.
int x=12+11; int s=0; for(int i=0;i<7;++i) s+=x-i; cout<<s;

A. 139
B. 137
C. 140
D. 141

Q220.

What is printed?
int x=11; int i=8; while(i--) x/=2; cout<<x;

A. -1
B. 1
C. 0
D. -3

Q221.

Evaluate the expression using integer arithmetic.
int x=19, y=12; cout << x%y + (x/y)*2;

A. 10
B. 8
C. 9
D. 6

Q222.

Evaluate the expression using integer arithmetic.
int x=16, y=3; cout << x%y + (x/y)*2;

A. 10
B. 11
C. 8
D. 12

Q223.

Which feature allows a derived class to provide a specialized implementation of a base-class virtual function?

A. Name mangling
B. Default argument promotion
C. Function overloading
D. Function overriding

IET, C-DAC

Q224.

What is printed?
int x=18; int i=4; while(i--) x/=2; cout<<x;

A. 0
B. 2
C. -2
D. 1

Q225.

What is printed?
int x=14; int i=7; while(i--) x/=2; cout<<x;

A. -1
B. 1
C. -3
D. 0

Q226.

What is the value printed?
int x=(11 << 2) ^ (7+3); cout<<x;

A. 37
B. 38
C. 35
D. 39

Q227.

What is the value printed?
int x=(11 << 2) ^ (11+3); cout<<x;

A. 33
B. 31
C. 34
D. 35

Q228.

What is printed?
int x=7; int i=8; while(i--) x/=2; cout<<x;

A. -1
B. 1
C. -3
D. 0

Q229.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=7;++i) s += 16*i-4; cout<<s;

A. 419
B. 421
C. 420
D. 417

Q230.

What is the value printed?
int x=(8 << 2) ^ (2+3); cout<<x;

A. 36
B. 37
C. 38
D. 34

IET, C-DAC

Q231.

What is printed?
int x=4; int i=4; while(i--) x/=2; cout<<x;

A. 1
B. -3
C. 0
D. -1

Q232.

Choose the output of this loop.
int s=0; for(int i=1;i<=4;i++) s += (i%2==0 ? 15 : 11); cout<<s;

A. 49
B. 53
C. 52
D. 51

Q233.

What is the final value of s?
int s=0; for(int i=1;i<=7;++i) s+=i*i; cout<<s;

A. 140
B. 137
C. 141
D. 139

Q234.

What is printed?
int x=7; int i=4; while(i--) x/=2; cout<<x;

A. 0
B. 1
C. -3
D. -1

Q235.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=8;++i) s += 5*i-2; cout<<s;

A. 163
B. 161
C. 165
D. 164

Q236.

What is the final value of s?
int s=0; for(int i=1;i<=4;++i) s+=i*i; cout<<s;

A. 31
B. 29
C. 27
D. 30

Q237.

What is the final value of s?
int s=0; for(int i=1;i<=4;++i) s+=i*i; cout<<s;

A. 31
B. 29
C. 30
D. 27

IET, C-DAC

Q238.

Determine the output.
int x=19; for(int i=0;i<6;++i) x=(x*2+i)%97; cout<<x;

A. 9
B. 11
C. 12
D. 13

Q239.

Determine the output.
int x=12; for(int i=0;i<5;++i) x=(x*7+i)%97; cout<<x;

A. 1
B. 2
C. -1
D. 3

Q240.

What is printed?
int x=3; int i=4; while(i--) x/=2; cout<<x;

A. -1
B. 0
C. 1
D. -3

Q241.

Evaluate the expression using integer arithmetic.
int x=15, y=13; cout << x%y + (x/y)*2;

A. 1
B. 3
C. 5
D. 4

Q242.

Find the output.
int x=2+8; int s=0; for(int i=0;i<7;++i) s+=x-i; cout<<s;

A. 49
B. 50
C. 46
D. 48

Q243.

Determine the output.
int x=3; for(int i=0;i<3;++i) x=(x*10+i)%97; cout<<x;

A. 6
B. 5
C. 2
D. 4

Q244.

What is the value printed?
int x=(18 << 2) ^ (7+3); cout<<x;

A. 65
B. 66
C. 67
D. 63

IET, C-DAC

Q245.

What is the value printed?
int x=(6 << 2) ^ (5+3); cout<<x;

A. 17
B. 16
C. 13
D. 15

Q246.

Find the output.
int x=14+5; int s=0; for(int i=0;i<4;++i) s+=x-i; cout<<s;

A. 70
B. 67
C. 69
D. 71

Q247.

What is the usual effect of declaring a member function as virtual?

A. Calls through a base pointer/reference can dispatch according to dynamic type
B. The function is executed at compile time only
C. The function becomes inline
D. The function cannot be overridden

Q248.

Which declaration makes a class non-copyable by default in modern C++?

A. Delete its copy constructor and copy assignment operator
B. Declare its destructor public
C. Use the mutable keyword
D. Declare every member static

Q249.

What is the value printed?
int x=(14 << 2) ^ (10+3); cout<<x;

A. 50
B. 53
C. 52
D. 54

Q250.

Choose the output of this loop.
int s=0; for(int i=1;i<=6;i++) s += (i%2==0 ? 17 : 6); cout<<s;

A. 70
B. 66
C. 68
D. 69

Q251.

Find the output.
int x=14+7; int s=0; for(int i=0;i<4;++i) s+=x-i; cout<<s;

A. 75
B. 79
C. 77
D. 78

IET, C-DAC

Q252.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=2;++i) s += 16*i-12; cout<<s;

A. 23
B. 24
C. 25
D. 21

Q253.

Determine the output.
int x=16; for(int i=0;i<3;++i) x=(x*6+i)%97; cout<<x;

A. 70
B. 68
C. 69
D. 66

Q254.

What is the value printed?
int x=(13 << 2) ^ (6+3); cout<<x;

A. 60
B. 61
C. 62
D. 58

Q255.

Evaluate the expression using integer arithmetic.
int x=7, y=4; cout << x%y + (x/y)*2;

A. 6
B. 2
C. 5
D. 4

Q256.

Choose the output of this loop.
int s=0; for(int i=1;i<=4;i++) s += (i%2==0 ? 7 : 12); cout<<s;

A. 37
B. 39
C. 38
D. 35

Q257.

What is the final value of s?
int s=0; for(int i=1;i<=7;++i) s+=i*i; cout<<s;

A. 141
B. 139
C. 140
D. 137

Q258.

Choose the output of this loop.
int s=0; for(int i=1;i<=7;i++) s += (i%2==0 ? 18 : 12); cout<<s;

A. 103
B. 101
C. 102
D. 99

IET, C-DAC

Q259.

Evaluate the expression using integer arithmetic.
int x=14, y=3; cout << x%y + (x/y)*2;

A. 7
B. 10
C. 9
D. 11

Q260.

What is the final value of s?
int s=0; for(int i=1;i<=4;++i) s+=i*i; cout<<s;

A. 27
B. 30
C. 29
D. 31

Q261.

Find the output.
int x=9+13; int s=0; for(int i=0;i<8;++i) s+=x-i; cout<<s;

A. 148
B. 147
C. 149
D. 145

Q262.

Choose the output of this loop.
int s=0; for(int i=1;i<=2;i++) s += (i%2==0 ? 12 : 13); cout<<s;

A. 24
B. 26
C. 25
D. 22

Q263.

Find the output.
int x=7+12; int s=0; for(int i=0;i<4;++i) s+=x-i; cout<<s;

A. 71
B. 69
C. 70
D. 67

Q264.

Which statement about function templates is correct?

A. A template must be compiled only once for all types
B. The compiler can instantiate a specialization for a deduced type
C. Templates cannot accept class types
D. Templates cannot be overloaded

Q265.

Find the output.
int x=2+10; int s=0; for(int i=0;i<7;++i) s+=x-i; cout<<s;

A. 62
B. 64
C. 63
D. 60

IET, C-DAC

Q266.

What is printed?
int x=14; int i=7; while(i--) x/=2; cout<<x;

A. 1
B. 0
C. -3
D. -1

Q267.

What is the final value of s?
int s=0; for(int i=1;i<=6;++i) s+=i*i; cout<<s;

A. 88
B. 92
C. 91
D. 90

Q268.

Determine the output.
int x=12; for(int i=0;i<4;++i) x=(x*11+i)%97; cout<<x;

A. 74
B. 71
C. 73
D. 75

Q269.

Find the output.
int x=2+2; int s=0; for(int i=0;i<5;++i) s+=x-i; cout<<s;

A. 10
B. 11
C. 9
D. 7

Q270.

What is the value printed?
int x=(14 << 2) ^ (2+3); cout<<x;

A. 60
B. 58
C. 62
D. 61

Q271.

Evaluate the expression using integer arithmetic.
int x=15, y=11; cout << x%y + (x/y)*2;

A. 3
B. 7
C. 5
D. 6

Q272.

Evaluate the expression using integer arithmetic.
int x=18, y=12; cout << x%y + (x/y)*2;

A. 7
B. 5
C. 8
D. 9

IET, C-DAC

Q273.

Evaluate the expression using integer arithmetic.
int x=12, y=6; cout << x%y + (x/y)*2;

A. 5
B. 4
C. 3
D. 1

Q274.

What is printed?
int x=12; int i=8; while(i--) x/=2; cout<<x;

A. 0
B. -3
C. -1
D. 1

Q275.

Evaluate the expression using integer arithmetic.
int x=10, y=5; cout << x%y + (x/y)*2;

A. 3
B. 4
C. 1
D. 5

Q276.

What does std::unique_ptr primarily represent?

A. Exclusive ownership of a dynamically managed object
B. Shared ownership with reference counting
C. A fixed-size array on the stack
D. A non-owning observer pointer

Q277.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=2;++i) s += 10*i-8; cout<<s;

A. 11
B. 15
C. 13
D. 14

Q278.

What is object slicing?

A. Moving an object into a vector
B. Copying a derived object into a base object by value, losing derived parts
C. Deleting an object twice
D. Converting a pointer to void*

Q279.

Choose the output of this loop.
int s=0; for(int i=1;i<=3;i++) s += (i%2==0 ? 7 : 8); cout<<s;

A. 20
B. 22
C. 23
D. 24

IET, C-DAC

Q280.

Choose the output of this loop.
int s=0; for(int i=1;i<=8;i++) s += (i%2==0 ? 3 : 7); cout<<s;

A. 41
B. 37
C. 40
D. 39

Q281.

What is the value printed?
int x=(9 << 2) ^ (5+3); cout<<x;

A. 44
B. 41
C. 45
D. 43

Q282.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=3;++i) s += 18*i-2; cout<<s;

A. 101
B. 103
C. 102
D. 99

Q283.

Evaluate the expression using integer arithmetic.
int x=3, y=6; cout << x%y + (x/y)*2;

A. 0
B. 3
C. 4
D. 2

Q284.

Evaluate the expression using integer arithmetic.
int x=17, y=11; cout << x%y + (x/y)*2;

A. 8
B. 9
C. 5
D. 7

Q285.

Find the output.
int x=16+2; int s=0; for(int i=0;i<2;++i) s+=x-i; cout<<s;

A. 36
B. 32
C. 34
D. 35

Q286.

What is the value printed?
int x=(7 << 2) ^ (3+3); cout<<x;

A. 25
B. 27
C. 26
D. 23

IET, C-DAC

Q287.

What is the final value of s?
int s=0; for(int i=1;i<=3;++i) s+=i*i; cout<<s;

A. 13
B. 11
C. 15
D. 14

Q288.

Which exception-safety guarantee means an operation either succeeds or has no observable effect?

A. Basic guarantee
B. Strong guarantee
C. No-throw guarantee
D. Unchecked guarantee

Q289.

Find the output.
int x=3+3; int s=0; for(int i=0;i<3;++i) s+=x-i; cout<<s;

A. 12
B. 15
C. 14
D. 16

Q290.

What is the final value of s?
int s=0; for(int i=1;i<=8;++i) s+=i*i; cout<<s;

A. 203
B. 205
C. 201
D. 204

Q291.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=2;++i) s += 8*i-10; cout<<s;

A. 5
B. 3
C. 4
D. 1

Q292.

Find the output.
int x=8+12; int s=0; for(int i=0;i<5;++i) s+=x-i; cout<<s;

A. 89
B. 90
C. 87
D. 91

Q293.

What is printed?
int x=8; int i=2; while(i--) x/=2; cout<<x;

A. 3
B. 1
C. 2
D. -1

IET, C-DAC

Q294.

What is the value printed?
int x=(12 << 2) ^ (8+3); cout<<x;

A. 56
B. 59
C. 58
D. 60

Q295.

Evaluate the expression using integer arithmetic.
int x=12, y=13; cout << x%y + (x/y)*2;

A. 12
B. 11
C. 9
D. 13

Q296.

Choose the output of this loop.
int s=0; for(int i=1;i<=7;i++) s += (i%2==0 ? 3 : 7); cout<<s;

A. 36
B. 34
C. 37
D. 38

Q297.

Evaluate the expression using integer arithmetic.
int x=14, y=10; cout << x%y + (x/y)*2;

A. 7
B. 6
C. 3
D. 5

Q298.

What is printed?
int x=10; int i=6; while(i--) x/=2; cout<<x;

A. 1
B. -3
C. 0
D. -1

Q299.

Evaluate the expression using integer arithmetic.
int x=6, y=5; cout << x%y + (x/y)*2;

A. 0
B. 4
C. 3
D. 2

Q300.

Find the output.
int x=12+6; int s=0; for(int i=0;i<7;++i) s+=x-i; cout<<s;

A. 104
B. 106
C. 102
D. 105

IET, C-DAC

Q301.

Determine the output.
int x=9; for(int i=0;i<5;++i) x=(x*12+i)%97; cout<<x;

A. 65
B. 69
C. 68
D. 67

Q302.

Find the output.
int x=8+12; int s=0; for(int i=0;i<3;++i) s+=x-i; cout<<s;

A. 56
B. 54
C. 57
D. 58

Q303.

Determine the output.
int x=8; for(int i=0;i<6;++i) x=(x*11+i)%97; cout<<x;

A. 73
B. 70
C. 72
D. 74

Q304.

Determine the output.
int x=5; for(int i=0;i<7;++i) x=(x*3+i)%97; cout<<x;

A. 32
B. 33
C. 29
D. 31

Q305.

What is the final value of s?
int s=0; for(int i=1;i<=5;++i) s+=i*i; cout<<s;

A. 55
B. 54
C. 56
D. 52

Q306.

What is the final value of s?
int s=0; for(int i=1;i<=8;++i) s+=i*i; cout<<s;

A. 204
B. 205
C. 203
D. 201

Q307.

Determine the output.
int x=2; for(int i=0;i<6;++i) x=(x*4+i)%97; cout<<x;

A. 13
B. 12
C. 9
D. 11

IET, C-DAC

Q308.

What is printed?
int x=11; int i=2; while(i--) x/=2; cout<<x;

A. 2
B. -1
C. 3
D. 1

Q309.

Determine the output.
int x=11; for(int i=0;i<6;++i) x=(x*8+i)%97; cout<<x;

A. 78
B. 79
C. 80
D. 76

Q310.

What is the final value of s?
int s=0; for(int i=1;i<=5;++i) s+=i*i; cout<<s;

A. 55
B. 54
C. 52
D. 56

Q311.

What is printed?
int x=7; int i=7; while(i--) x/=2; cout<<x;

A. 1
B. -1
C. 0
D. -3

Q312.

Choose the output of this loop.
int s=0; for(int i=1;i<=7;i++) s += (i%2==0 ? 3 : 8); cout<<s;

A. 40
B. 42
C. 38
D. 41

Q313.

Evaluate the expression using integer arithmetic.
int x=15, y=6; cout << x%y + (x/y)*2;

A. 4
B. 6
C. 7
D. 8

Q314.

What is printed?
int x=17; int i=2; while(i--) x/=2; cout<<x;

A. 1
B. 4
C. 3
D. 5

IET, C-DAC

Q315.

Evaluate the expression using integer arithmetic.
int x=11, y=2; cout << x%y + (x/y)*2;

A. 8
B. 11
C. 10
D. 12

Q316.

What is the final value of s?
int s=0; for(int i=1;i<=2;++i) s+=i*i; cout<<s;

A. 5
B. 2
C. 6
D. 4

Q317.

Choose the output of this loop.
int s=0; for(int i=1;i<=3;i++) s += (i%2==0 ? 13 : 12); cout<<s;

A. 34
B. 37
C. 36
D. 38

Q318.

What is printed?
int x=16; int i=3; while(i--) x/=2; cout<<x;

A. 1
B. 2
C. 3
D. -1

Q319.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=8;++i) s += 2*i-9; cout<<s;

A. 1
B. 0
C. -1
D. -3

Q320.

What is the final value of s?
int s=0; for(int i=1;i<=2;++i) s+=i*i; cout<<s;

A. 4
B. 6
C. 2
D. 5

Q321.

What is the value printed?
int x=(15 << 2) ^ (7+3); cout<<x;

A. 55
B. 51
C. 53
D. 54

IET, C-DAC

Q322.

Choose the output of this loop.
int s=0; for(int i=1;i<=5;i++) s += (i%2==0 ? 10 : 2); cout<<s;

A. 25
B. 26
C. 23
D. 27

Q323.

What is the final value of s?
int s=0; for(int i=1;i<=6;++i) s+=i*i; cout<<s;

A. 88
B. 91
C. 90
D. 92

Q324.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=4;++i) s += 11*i-6; cout<<s;

A. 85
B. 86
C. 87
D. 83

Q325.

What is printed?
int x=2; int i=8; while(i--) x/=2; cout<<x;

A. -3
B. 1
C. -1
D. 0

Q326.

Find the output.
int x=14+12; int s=0; for(int i=0;i<2;++i) s+=x-i; cout<<s;

A. 52
B. 50
C. 48
D. 51

Q327.

Find the output.
int x=11+12; int s=0; for(int i=0;i<4;++i) s+=x-i; cout<<s;

A. 83
B. 86
C. 87
D. 85

Q328.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=2;++i) s += 9*i-8; cout<<s;

A. 12
B. 8
C. 10
D. 11

IET, C-DAC

Q329.

What is printed?
int x=5; int i=7; while(i--) x/=2; cout<<x;

A. -1
B. 0
C. -3
D. 1

Q330.

Find the output.
int x=9+2; int s=0; for(int i=0;i<3;++i) s+=x-i; cout<<s;

A. 27
B. 31
C. 30
D. 29

Q331.

What is the final value of s?
int s=0; for(int i=1;i<=5;++i) s+=i*i; cout<<s;

A. 52
B. 54
C. 56
D. 55

Q332.

Choose the output of this loop.
int s=0; for(int i=1;i<=5;i++) s += (i%2==0 ? 3 : 7); cout<<s;

A. 27
B. 24
C. 28
D. 26

Q333.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=4;++i) s += 14*i-4; cout<<s;

A. 124
B. 123
C. 121
D. 125

Q334.

Choose the output of this loop.
int s=0; for(int i=1;i<=6;i++) s += (i%2==0 ? 19 : 10); cout<<s;

A. 88
B. 87
C. 84
D. 86

Q335.

Find the output.
int x=4+5; int s=0; for(int i=0;i<8;++i) s+=x-i; cout<<s;

A. 41
B. 45
C. 43
D. 44

IET, C-DAC

Q336.

What is the value printed?
int x=(8 << 2) ^ (4+3); cout<<x;

A. 39
B. 38
C. 40
D. 36

Q337.

Determine the output.
int x=5; for(int i=0;i<3;++i) x=(x*6+i)%97; cout<<x;

A. 21
B. 20
C. 18
D. 22

Q338.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=2;++i) s += 19*i-3; cout<<s;

A. 51
B. 48
C. 50
D. 52

Q339.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=5;++i) s += 19*i-4; cout<<s;

A. 262
B. 266
C. 264
D. 265

Q340.

What is the value printed?
int x=(2 << 2) ^ (8+3); cout<<x;

A. 2
B. 3
C. 0
D. 4

Q341.

Choose the output of this loop.
int s=0; for(int i=1;i<=2;i++) s += (i%2==0 ? 19 : 11); cout<<s;

A. 27
B. 30
C. 31
D. 29

Q342.

Find the output.
int x=11+13; int s=0; for(int i=0;i<2;++i) s+=x-i; cout<<s;

A. 48
B. 44
C. 47
D. 46

IET, C-DAC

Q343.

What is the final value of s?
int s=0; for(int i=1;i<=6;++i) s+=i*i; cout<<s;

A. 90
B. 88
C. 92
D. 91

Q344.

What is the final value of s?
int s=0; for(int i=1;i<=8;++i) s+=i*i; cout<<s;

A. 205
B. 204
C. 203
D. 201

Q345.

What is the final value of s?
int s=0; for(int i=1;i<=6;++i) s+=i*i; cout<<s;

A. 91
B. 88
C. 92
D. 90

Q346.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=4;++i) s += 6*i-11; cout<<s;

A. 17
B. 13
C. 16
D. 15

Q347.

Find the output.
int x=3+13; int s=0; for(int i=0;i<4;++i) s+=x-i; cout<<s;

A. 57
B. 59
C. 58
D. 55

Q348.

What is printed?
int x=2; int i=4; while(i--) x/=2; cout<<x;

A. -1
B. 1
C. 0
D. -3

Q349.

What is the final value of s?
int s=0; for(int i=1;i<=2;++i) s+=i*i; cout<<s;

A. 6
B. 4
C. 5
D. 2

IET, C-DAC

Q350.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=6;++i) s += 15*i-11; cout<<s;

A. 250
B. 248
C. 249
D. 246

Q351.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=7;++i) s += 4*i-4; cout<<s;

A. 81
B. 85
C. 84
D. 83

Q352.

Choose the output of this loop.
int s=0; for(int i=1;i<=4;i++) s += (i%2==0 ? 13 : 3); cout<<s;

A. 33
B. 29
C. 31
D. 32

Q353.

What is printed?
int x=2; int i=5; while(i--) x/=2; cout<<x;

A. 0
B. -3
C. -1
D. 1

Q354.

What is printed?
int x=13; int i=7; while(i--) x/=2; cout<<x;

A. 0
B. -1
C. -3
D. 1

Q355.

Evaluate the expression using integer arithmetic.
int x=13, y=3; cout << x%y + (x/y)*2;

A. 9
B. 6
C. 8
D. 10

Q356.

Determine the output.
int x=9; for(int i=0;i<8;++i) x=(x*5+i)%97; cout<<x;

A. 22
B. 19
C. 23
D. 21

IET, C-DAC

Q357.

What is the final value of s?
int s=0; for(int i=1;i<=6;++i) s+=i*i; cout<<s;

A. 91
B. 92
C. 90
D. 88

Q358.

Find the output.
int x=13+12; int s=0; for(int i=0;i<6;++i) s+=x-i; cout<<s;

A. 136
B. 135
C. 134
D. 132

Q359.

What does std::move do by itself?

A. Calls the move constructor unconditionally
B. Casts an expression to an rvalue reference; it does not move resources alone
C. Always transfers memory immediately
D. Deletes the source object

Q360.

Evaluate the expression using integer arithmetic.
int x=2, y=2; cout << x%y + (x/y)*2;

A. -1
B. 1
C. 2
D. 3

Q361.

What is the value printed?
int x=(4 << 2) ^ (12+3); cout<<x;

A. 30
B. 32
C. 28
D. 31

Q362.

What is printed?
int x=10; int i=4; while(i--) x/=2; cout<<x;

A. -1
B. 1
C. 0
D. -3

Q363.

Choose the output of this loop.
int s=0; for(int i=1;i<=5;i++) s += (i%2==0 ? 16 : 4); cout<<s;

A. 41
B. 44
C. 45
D. 43

IET, C-DAC

Q364.

What is the final value of s?
int s=0; for(int i=1;i<=2;++i) s+=i*i; cout<<s;

A. 6
B. 5
C. 2
D. 4

Q365.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=4;++i) s += 4*i-3; cout<<s;

A. 25
B. 28
C. 27
D. 29

Q366.

Determine the output.
int x=9; for(int i=0;i<3;++i) x=(x*12+i)%97; cout<<x;

A. 43
B. 47
C. 45
D. 46

Q367.

What is the purpose of RAII?

A. Delay all object destruction until program exit
B. Tie resource lifetime to object lifetime
C. Replace constructors with macros
D. Disable exception handling

Q368.

Find the output.
int x=4+9; int s=0; for(int i=0;i<4;++i) s+=x-i; cout<<s;

A. 47
B. 43
C. 45
D. 46

Q369.

What is the value printed?
int x=(19 << 2) ^ (10+3); cout<<x;

A. 62
B. 65
C. 64
D. 66

Q370.

Evaluate the expression using integer arithmetic.
int x=18, y=4; cout << x%y + (x/y)*2;

A. 7
B. 9
C. 11
D. 10

IET, C-DAC

Q371.

What is the value printed?
int x=(14 << 2) ^ (4+3); cout<<x;

A. 60
B. 64
C. 62
D. 63

Q372.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=3;++i) s += 14*i-2; cout<<s;

A. 78
B. 75
C. 79
D. 77

Q373.

What is printed?
int x=6; int i=6; while(i--) x/=2; cout<<x;

A. 1
B. -3
C. 0
D. -1

Q374.

Choose the output of this loop.
int s=0; for(int i=1;i<=5;i++) s += (i%2==0 ? 11 : 2); cout<<s;

A. 25
B. 27
C. 29
D. 28

Q375.

Find the output.
int x=8+7; int s=0; for(int i=0;i<5;++i) s+=x-i; cout<<s;

A. 64
B. 65
C. 66
D. 62

Q376.

What is the value printed?
int x=(9 << 2) ^ (7+3); cout<<x;

A. 45
B. 43
C. 46
D. 47

Q377.

Evaluate the expression using integer arithmetic.
int x=6, y=12; cout << x%y + (x/y)*2;

A. 5
B. 3
C. 6
D. 7

IET, C-DAC

Q378.

Choose the output of this loop.
int s=0; for(int i=1;i<=5;i++) s += (i%2==0 ? 4 : 13); cout<<s;

A. 44
B. 48
C. 46
D. 47

Q379.

Find the output.
int x=3+13; int s=0; for(int i=0;i<3;++i) s+=x-i; cout<<s;

A. 45
B. 42
C. 44
D. 46

Q380.

What is the final value of s?
int s=0; for(int i=1;i<=4;++i) s+=i*i; cout<<s;

A. 29
B. 27
C. 31
D. 30

Q381.

Choose the output of this loop.
int s=0; for(int i=1;i<=7;i++) s += (i%2==0 ? 19 : 11); cout<<s;

A. 101
B. 98
C. 102
D. 100

Q382.

What is the value printed?
int x=(6 << 2) ^ (4+3); cout<<x;

A. 31
B. 28
C. 30
D. 32

Q383.

Find the output.
int x=7+3; int s=0; for(int i=0;i<5;++i) s+=x-i; cout<<s;

A. 37
B. 39
C. 40
D. 41

Q384.

Evaluate the expression using integer arithmetic.
int x=7, y=10; cout << x%y + (x/y)*2;

A. 7
B. 8
C. 4
D. 6

IET, C-DAC

Q385.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=5;++i) s += 13*i-10; cout<<s;

A. 145
B. 142
C. 146
D. 144

Q386.

Choose the output of this loop.
int s=0; for(int i=1;i<=7;i++) s += (i%2==0 ? 3 : 8); cout<<s;

A. 38
B. 41
C. 40
D. 42

Q387.

What is printed?
int x=16; int i=7; while(i--) x/=2; cout<<x;

A. 1
B. 0
C. -3
D. -1

Q388.

Determine the output.
int x=2; for(int i=0;i<4;++i) x=(x*3+i)%97; cout<<x;

A. 80
B. 82
C. 83
D. 84

Q389.

What is the final value of s?
int s=0; for(int i=1;i<=4;++i) s+=i*i; cout<<s;

A. 27
B. 29
C. 30
D. 31

Q390.

What is the final value of s?
int s=0; for(int i=1;i<=5;++i) s+=i*i; cout<<s;

A. 52
B. 56
C. 54
D. 55

Q391.

What is printed?
int x=3; int i=2; while(i--) x/=2; cout<<x;

A. 0
B. -3
C. -1
D. 1

IET, C-DAC

Q392.

What is printed?
int x=14; int i=6; while(i--) x/=2; cout<<x;

A. -3
B. -1
C. 0
D. 1

Q393.

Evaluate the expression using integer arithmetic.
int x=9, y=4; cout << x%y + (x/y)*2;

A. 2
B. 5
C. 6
D. 4

Q394.

Find the output.
int x=6+6; int s=0; for(int i=0;i<2;++i) s+=x-i; cout<<s;

A. 20
B. 24
C. 22
D. 23

Q395.

What is the final value of s?
int s=0; for(int i=1;i<=8;++i) s+=i*i; cout<<s;

A. 203
B. 205
C. 204
D. 201

Q396.

What is the value printed?
int x=(5 << 2) ^ (2+3); cout<<x;

A. 17
B. 16
C. 18
D. 14

Q397.

Evaluate the expression using integer arithmetic.
int x=9, y=12; cout << x%y + (x/y)*2;

A. 10
B. 8
C. 6
D. 9

Q398.

Choose the output of this loop.
int s=0; for(int i=1;i<=7;i++) s += (i%2==0 ? 14 : 4); cout<<s;

A. 55
B. 58
C. 59
D. 57

IET, C-DAC

Q399.

What is printed?
int x=3; int i=6; while(i--) x/=2; cout<<x;

A. -1
B. -3
C. 1
D. 0

Q400.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=7;++i) s += 16*i-3; cout<<s;

A. 426
B. 424
C. 428
D. 427

Q401.

Find the output.
int x=2+12; int s=0; for(int i=0;i<8;++i) s+=x-i; cout<<s;

A. 81
B. 85
C. 83
D. 84

Q402.

Find the output.
int x=13+4; int s=0; for(int i=0;i<4;++i) s+=x-i; cout<<s;

A. 59
B. 62
C. 61
D. 63

Q403.

What is the final value of s?
int s=0; for(int i=1;i<=7;++i) s+=i*i; cout<<s;

A. 139
B. 140
C. 137
D. 141

Q404.

What is the final value of s?
int s=0; for(int i=1;i<=2;++i) s+=i*i; cout<<s;

A. 5
B. 4
C. 6
D. 2

Q405.

Choose the output of this loop.
int s=0; for(int i=1;i<=6;i++) s += (i%2==0 ? 9 : 7); cout<<s;

A. 49
B. 48
C. 47
D. 45

IET, C-DAC

Q406.

Choose the output of this loop.
int s=0; for(int i=1;i<=4;i++) s += (i%2==0 ? 13 : 9); cout<<s;

A. 45
B. 41
C. 43
D. 44

Q407.

What is the final value of s?
int s=0; for(int i=1;i<=7;++i) s+=i*i; cout<<s;

A. 137
B. 140
C. 141
D. 139

Q408.

What is printed?
int x=11; int i=7; while(i--) x/=2; cout<<x;

A. -3
B. 0
C. 1
D. -1

Q409.

Evaluate the expression using integer arithmetic.
int x=18, y=2; cout << x%y + (x/y)*2;

A. 19
B. 15
C. 18
D. 17

Q410.

What is the value printed?
int x=(5 << 2) ^ (11+3); cout<<x;

A. 23
B. 27
C. 25
D. 26

Q411.

Evaluate the expression using integer arithmetic.
int x=13, y=13; cout << x%y + (x/y)*2;

A. 2
B. -1
C. 3
D. 1

Q412.

Evaluate the expression using integer arithmetic.
int x=18, y=11; cout << x%y + (x/y)*2;

A. 6
B. 9
C. 10
D. 8

IET, C-DAC

Q413.

Find the output.
int x=14+7; int s=0; for(int i=0;i<7;++i) s+=x-i; cout<<s;

A. 123
B. 125
C. 126
D. 127

Q414.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=8;++i) s += 18*i-13; cout<<s;

A. 545
B. 543
C. 544
D. 541

Q415.

Choose the output of this loop.
int s=0; for(int i=1;i<=4;i++) s += (i%2==0 ? 10 : 10); cout<<s;

A. 40
B. 41
C. 39
D. 37

Q416.

Find the output.
int x=9+11; int s=0; for(int i=0;i<5;++i) s+=x-i; cout<<s;

A. 91
B. 89
C. 87
D. 90

Q417.

Determine the output.
int x=12; for(int i=0;i<8;++i) x=(x*7+i)%97; cout<<x;

A. 7
B. 10
C. 11
D. 9

Q418.

Evaluate the expression using integer arithmetic.
int x=12, y=8; cout << x%y + (x/y)*2;

A. 5
B. 3
C. 6
D. 7

Q419.

Evaluate the expression using integer arithmetic.
int x=6, y=13; cout << x%y + (x/y)*2;

A. 6
B. 7
C. 5
D. 3

IET, C-DAC

Q420.

Evaluate the expression using integer arithmetic.
int x=17, y=2; cout << x%y + (x/y)*2;

A. 17
B. 14
C. 16
D. 18

Q421.

Choose the output of this loop.
int s=0; for(int i=1;i<=3;i++) s += (i%2==0 ? 15 : 7); cout<<s;

A. 29
B. 26
C. 28
D. 30

Q422.

What is printed?
int x=17; int i=4; while(i--) x/=2; cout<<x;

A. 2
B. 0
C. -2
D. 1

Q423.

Find the output.
int x=8+11; int s=0; for(int i=0;i<7;++i) s+=x-i; cout<<s;

A. 112
B. 109
C. 111
D. 113

Q424.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=8;++i) s += 12*i-9; cout<<s;

A. 359
B. 361
C. 357
D. 360

Q425.

Determine the output.
int x=18; for(int i=0;i<7;++i) x=(x*11+i)%97; cout<<x;

A. 4
B. 5
C. 1
D. 3

Q426.

Determine the output.
int x=16; for(int i=0;i<6;++i) x=(x*6+i)%97; cout<<x;

A. 7
B. 3
C. 6
D. 5

IET, C-DAC

Q427.

Determine the output.
int x=14; for(int i=0;i<7;++i) x=(x*6+i)%97; cout<<x;

A. 53
B. 51
C. 54
D. 55

Q428.

Determine the output.
int x=12; for(int i=0;i<2;++i) x=(x*3+i)%97; cout<<x;

A. 13
B. 11
C. 9
D. 12

Q429.

Find the output.
int x=17+13; int s=0; for(int i=0;i<5;++i) s+=x-i; cout<<s;

A. 140
B. 139
C. 141
D. 137

Q430.

Determine the output.
int x=4; for(int i=0;i<5;++i) x=(x*13+i)%97; cout<<x;

A. 60
B. 58
C. 62
D. 61

Q431.

What is printed?
int x=6; int i=3; while(i--) x/=2; cout<<x;

A. 0
B. -3
C. 1
D. -1

Q432.

Find the output.
int x=9+13; int s=0; for(int i=0;i<4;++i) s+=x-i; cout<<s;

A. 83
B. 82
C. 79
D. 81

Q433.

Choose the output of this loop.
int s=0; for(int i=1;i<=7;i++) s += (i%2==0 ? 6 : 2); cout<<s;

A. 26
B. 23
C. 27
D. 25

IET, C-DAC

Q434.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=3;++i) s += 6*i-4; cout<<s;

A. 25
B. 21
C. 23
D. 24

Q435.

Determine the output.
int x=2; for(int i=0;i<8;++i) x=(x*6+i)%97; cout<<x;

A. 84
B. 81
C. 83
D. 85

Q436.

What is the final value of s?
int s=0; for(int i=1;i<=5;++i) s+=i*i; cout<<s;

A. 55
B. 52
C. 54
D. 56

Q437.

What is the value printed?
int x=(14 << 2) ^ (3+3); cout<<x;

A. 59
B. 61
C. 63
D. 62

Q438.

What is printed?
int x=18; int i=4; while(i--) x/=2; cout<<x;

A. -2
B. 1
C. 2
D. 0

Q439.

Find the output.
int x=14+11; int s=0; for(int i=0;i<4;++i) s+=x-i; cout<<s;

A. 94
B. 95
C. 91
D. 93

Q440.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=3;++i) s += 5*i-6; cout<<s;

A. 13
B. 9
C. 11
D. 12

IET, C-DAC

Q441.

What is the value printed?
int x=(7 << 2) ^ (13+3); cout<<x;

A. 13
B. 12
C. 11
D. 9

Q442.

Choose the output of this loop.
int s=0; for(int i=1;i<=4;i++) s += (i%2==0 ? 18 : 6); cout<<s;

A. 47
B. 45
C. 48
D. 49

Q443.

What is the value printed?
int x=(19 << 2) ^ (7+3); cout<<x;

A. 67
B. 69
C. 70
D. 71

Q444.

Evaluate the expression using integer arithmetic.
int x=16, y=7; cout << x%y + (x/y)*2;

A. 3
B. 6
C. 7
D. 5

Q445.

Choose the output of this loop.
int s=0; for(int i=1;i<=5;i++) s += (i%2==0 ? 18 : 8); cout<<s;

A. 59
B. 60
C. 57
D. 61

Q446.

Which C++ feature allows a function to accept a variable number of compile-time type arguments?

A. Virtual inheritance
B. Friend declarations
C. Namespaces
D. Variadic templates

Q447.

What is the value printed?
int x=(19 << 2) ^ (13+3); cout<<x;

A. 92
B. 89
C. 93
D. 91

IET, C-DAC

Q448.

Choose the output of this loop.
int s=0; for(int i=1;i<=6;i++) s += (i%2==0 ? 11 : 5); cout<<s;

A. 48
B. 47
C. 49
D. 45

Q449.

What does the const qualifier on a member function promise?

A. The function cannot return a value
B. The function will not modify non-mutable data members
C. The object is stored in read-only memory
D. The function cannot be overloaded

Q450.

Find the output.
int x=2+12; int s=0; for(int i=0;i<5;++i) s+=x-i; cout<<s;

A. 61
B. 60
C. 57
D. 59

Q451.

Choose the output of this loop.
int s=0; for(int i=1;i<=2;i++) s += (i%2==0 ? 12 : 3); cout<<s;

A. 15
B. 16
C. 12
D. 14

Q452.

What is the value printed?
int x=(19 << 2) ^ (9+3); cout<<x;

A. 61
B. 65
C. 64
D. 63

Q453.

Determine the output.
int x=11; for(int i=0;i<8;++i) x=(x*10+i)%97; cout<<x;

A. 63
B. 66
C. 65
D. 67

Q454.

Choose the output of this loop.
int s=0; for(int i=1;i<=7;i++) s += (i%2==0 ? 2 : 12); cout<<s;

A. 54
B. 53
C. 55
D. 51

IET, C-DAC

Q455.

Find the output.
int x=6+12; int s=0; for(int i=0;i<3;++i) s+=x-i; cout<<s;

A. 48
B. 50
C. 51
D. 52

Q456.

What is the final value of s?
int s=0; for(int i=1;i<=4;++i) s+=i*i; cout<<s;

A. 30
B. 29
C. 27
D. 31

Q457.

What is the value printed?
int x=(9 << 2) ^ (5+3); cout<<x;

A. 41
B. 45
C. 44
D. 43

Q458.

Determine the output.
int x=19; for(int i=0;i<2;++i) x=(x*10+i)%97; cout<<x;

A. 58
B. 57
C. 55
D. 59

Q459.

What is the main risk of returning a reference to a local automatic variable?

A. The compiler extends its lifetime in all cases
B. The local variable becomes static
C. The reference dangles after the function returns
D. The reference is automatically copied

Q460.

Which STL algorithm requires a sorted range for its standard binary-search semantics?

A. std::reverse
B. std::binary_search
C. std::for_each
D. std::count

Q461.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=7;++i) s += 13*i-13; cout<<s;

A. 274
B. 273
C. 270
D. 272

IET, C-DAC

Q462.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=4;++i) s += 14*i-10; cout<<s;

A. 99
B. 97
C. 100
D. 101

Q463.

What is the value printed?
int x=(4 << 2) ^ (10+3); cout<<x;

A. 26
B. 30
C. 29
D. 28

Q464.

What is printed?
int x=17; int i=4; while(i--) x/=2; cout<<x;

A. -2
B. 0
C. 1
D. 2

Q465.

Find the output.
int x=4+13; int s=0; for(int i=0;i<7;++i) s+=x-i; cout<<s;

A. 99
B. 97
C. 98
D. 95

Q466.

Determine the output.
int x=5; for(int i=0;i<5;++i) x=(x*10+i)%97; cout<<x;

A. 32
B. 34
C. 35
D. 36

Q467.

What is printed?
int x=12; int i=4; while(i--) x/=2; cout<<x;

A. 1
B. -1
C. 0
D. -3

Q468.

Find the output.
int x=17+11; int s=0; for(int i=0;i<7;++i) s+=x-i; cout<<s;

A. 172
B. 174
C. 175
D. 176

IET, C-DAC

Q469.

Determine the output.
int x=13; for(int i=0;i<3;++i) x=(x*5+i)%97; cout<<x;

A. 79
B. 80
C. 81
D. 77

Q470.

Evaluate the expression using integer arithmetic.
int x=16, y=11; cout << x%y + (x/y)*2;

A. 8
B. 7
C. 4
D. 6

Q471.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=4;++i) s += 9*i-3; cout<<s;

A. 75
B. 77
C. 78
D. 79

Q472.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=2;++i) s += 3*i-13; cout<<s;

A. -18
B. -16
C. -20
D. -17

Q473.

Evaluate the expression using integer arithmetic.
int x=3, y=5; cout << x%y + (x/y)*2;

A. 0
B. 4
C. 2
D. 3

Q474.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=4;++i) s += 19*i-2; cout<<s;

A. 179
B. 182
C. 181
D. 183

Q475.

What is printed?
int x=8; int i=5; while(i--) x/=2; cout<<x;

A. 0
B. -3
C. 1
D. -1

IET, C-DAC

Q476.

Find the output.
int x=19+9; int s=0; for(int i=0;i<3;++i) s+=x-i; cout<<s;

A. 80
B. 78
C. 81
D. 82

Q477.

Determine the output.
int x=15; for(int i=0;i<3;++i) x=(x*6+i)%97; cout<<x;

A. 44
B. 46
C. 47
D. 48

Q478.

What is the value printed?
int x=(6 << 2) ^ (5+3); cout<<x;

A. 13
B. 17
C. 16
D. 15

Q479.

What is the value printed?
int x=(15 << 2) ^ (11+3); cout<<x;

A. 47
B. 49
C. 51
D. 50

Q480.

Evaluate the expression using integer arithmetic.
int x=18, y=9; cout << x%y + (x/y)*2;

A. 1
B. 4
C. 3
D. 5

Q481.

Choose the output of this loop.
int s=0; for(int i=1;i<=2;i++) s += (i%2==0 ? 17 : 13); cout<<s;

A. 30
B. 29
C. 31
D. 27

Q482.

Find the output.
int x=17+13; int s=0; for(int i=0;i<7;++i) s+=x-i; cout<<s;

A. 189
B. 190
C. 186
D. 188

IET, C-DAC

Q483.

What is printed?
int x=9; int i=3; while(i--) x/=2; cout<<x;

A. 2
B. 1
C. -2
D. 0

Q484.

Evaluate the expression using integer arithmetic.
int x=9, y=10; cout << x%y + (x/y)*2;

A. 6
B. 8
C. 9
D. 10

Q485.

What is the final value of s?
int s=0; for(int i=1;i<=4;++i) s+=i*i; cout<<s;

A. 31
B. 29
C. 30
D. 27

Q486.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=6;++i) s += 3*i-7; cout<<s;

A. 20
B. 18
C. 21
D. 22

Q487.

What is the value printed?
int x=(7 << 2) ^ (10+3); cout<<x;

A. 14
B. 16
C. 17
D. 18

Q488.

Choose the output of this loop.
int s=0; for(int i=1;i<=4;i++) s += (i%2==0 ? 11 : 13); cout<<s;

A. 49
B. 48
C. 45
D. 47

Q489.

What is the final value of s?
int s=0; for(int i=1;i<=4;++i) s+=i*i; cout<<s;

A. 29
B. 30
C. 31
D. 27

IET, C-DAC

Q490.

What is the value printed?
int x=(16 << 2) ^ (9+3); cout<<x;

A. 75
B. 77
C. 76
D. 73

Q491.

Evaluate the expression using integer arithmetic.
int x=18, y=12; cout << x%y + (x/y)*2;

A. 5
B. 9
C. 7
D. 8

Q492.

Determine the output.
int x=10; for(int i=0;i<8;++i) x=(x*8+i)%97; cout<<x;

A. 68
B. 67
C. 65
D. 69

Q493.

Which container invalidates iterators at and after an insertion point when vector capacity does not change?

A. std::vector
B. std::map
C. std::set
D. std::list

Q494.

What is the value printed?
int x=(5 << 2) ^ (13+3); cout<<x;

A. 5
B. 4
C. 3
D. 1

Q495.

Determine the output.
int x=7; for(int i=0;i<7;++i) x=(x*2+i)%97; cout<<x;

A. 46
B. 45
C. 43
D. 47

Q496.

Choose the output of this loop.
int s=0; for(int i=1;i<=8;i++) s += (i%2==0 ? 4 : 8); cout<<s;

A. 47
B. 48
C. 45
D. 49

IET, C-DAC

Q497.

What is printed?
int x=16; int i=6; while(i--) x/=2; cout<<x;

A. -3
B. -1
C. 1
D. 0

Q498.

What is the principal purpose of a virtual destructor in a polymorphic base class?

A. To make every member virtual
B. To allocate objects on the heap
C. To prevent object construction
D. To ensure derived destructors run when deleting through a base pointer

Q499.

Choose the output of this loop.
int s=0; for(int i=1;i<=7;i++) s += (i%2==0 ? 14 : 12); cout<<s;

A. 91
B. 90
C. 87
D. 89

Q500.

What is printed by the following C++ code?
int s=0; for(int i=1;i<=8;++i) s += 15*i-2; cout<<s;

A. 524
B. 521
C. 525
D. 523

IET, C-DAC

CONSOLIDATED ANSWER KEY

Answers are listed by question number. Each key corresponds to the option order shown in the question section.

1. A	2. B	3. C	4. A	5. B
6. B	7. D	8. C	9. C	10. C
11. B	12. B	13. B	14. B	15. A
16. D	17. D	18. D	19. C	20. B
21. B	22. D	23. D	24. D	25. D
26. A	27. C	28. B	29. C	30. A
31. D	32. B	33. C	34. A	35. C
36. A	37. B	38. A	39. D	40. A
41. D	42. A	43. D	44. A	45. C
46. A	47. B	48. B	49. C	50. B
51. D	52. C	53. D	54. B	55. A
56. A	57. D	58. B	59. C	60. A
61. B	62. A	63. B	64. C	65. A
66. C	67. C	68. C	69. D	70. A
71. B	72. C	73. A	74. B	75. A
76. A	77. D	78. C	79. A	80. D
81. D	82. C	83. B	84. D	85. B
86. C	87. C	88. B	89. C	90. B
91. A	92. A	93. C	94. A	95. A
96. C	97. D	98. A	99. B	100. B
101. B	102. D	103. D	104. A	105. C
106. B	107. A	108. D	109. C	110. C
111. C	112. C	113. D	114. B	115. A
116. A	117. A	118. D	119. C	120. A
121. A	122. C	123. C	124. B	125. C
126. C	127. A	128. B	129. C	130. C
131. A	132. C	133. A	134. D	135. B
136. A	137. D	138. B	139. D	140. B
141. C	142. A	143. D	144. D	145. A
146. A	147. A	148. D	149. A	150. D
151. C	152. C	153. B	154. C	155. B

156. A	157. C	158. B	159. D	160. A
161. B	162. A	163. B	164. B	165. C
166. D	167. D	168. A	169. C	170. C
171. C	172. B	173. A	174. D	175. D
176. A	177. A	178. A	179. D	180. C
181. B	182. A	183. D	184. A	185. D
186. B	187. A	188. A	189. A	190. A
191. D	192. B	193. D	194. B	195. B
196. B	197. A	198. B	199. C	200. B
201. B	202. D	203. A	204. A	205. B
206. A	207. A	208. C	209. D	210. A
211. D	212. C	213. D	214. D	215. A
216. A	217. B	218. A	219. C	220. C
221. C	222. B	223. D	224. D	225. D
226. B	227. C	228. D	229. C	230. B
231. C	232. C	233. A	234. A	235. D
236. D	237. C	238. C	239. B	240. B
241. D	242. A	243. B	244. B	245. B
246. A	247. A	248. A	249. B	250. D
251. D	252. B	253. C	254. B	255. C
256. C	257. C	258. C	259. B	260. B
261. A	262. C	263. C	264. B	265. C
266. B	267. C	268. A	269. A	270. D
271. D	272. C	273. B	274. A	275. B
276. A	277. D	278. B	279. C	280. C
281. A	282. C	283. B	284. A	285. D
286. C	287. D	288. B	289. B	290. D
291. C	292. B	293. C	294. B	295. A
296. C	297. B	298. C	299. C	300. D
301. C	302. C	303. A	304. A	305. A
306. A	307. B	308. A	309. B	310. A
311. C	312. D	313. C	314. B	315. B
316. A	317. B	318. B	319. B	320. D

321. D	322. B	323. B	324. B	325. D
326. D	327. B	328. D	329. B	330. C
331. D	332. A	333. A	334. B	335. D
336. A	337. A	338. A	339. D	340. B
341. B	342. C	343. D	344. B	345. A
346. C	347. C	348. C	349. C	350. C
351. C	352. D	353. A	354. A	355. A
356. A	357. A	358. B	359. B	360. C
361. D	362. C	363. B	364. B	365. B
366. D	367. B	368. D	369. B	370. D
371. D	372. A	373. C	374. D	375. B
376. C	377. C	378. D	379. A	380. D
381. A	382. A	383. C	384. A	385. A
386. B	387. B	388. C	389. C	390. D
391. A	392. C	393. B	394. D	395. C
396. A	397. D	398. B	399. D	400. D
401. D	402. B	403. B	404. A	405. B
406. D	407. B	408. B	409. C	410. D
411. A	412. B	413. C	414. C	415. A
416. D	417. B	418. C	419. A	420. A
421. A	422. D	423. A	424. D	425. A
426. C	427. C	428. D	429. A	430. D
431. A	432. B	433. A	434. D	435. A
436. A	437. D	438. B	439. A	440. D
441. B	442. C	443. C	444. B	445. B
446. D	447. A	448. A	449. B	450. B
451. A	452. C	453. B	454. A	455. C
456. A	457. C	458. A	459. C	460. B
461. B	462. C	463. C	464. C	465. C
466. C	467. C	468. C	469. B	470. B
471. C	472. D	473. D	474. B	475. A
476. C	477. C	478. C	479. D	480. B
481. A	482. A	483. B	484. C	485. C

486. C	**487. C**	**488. B**	**489. B**	**490. C**
491. D	**492. A**	**493. A**	**494. B**	**495. A**
496. B	**497. D**	**498. D**	**499. B**	**500. A**

Reference basis: C-DAC official PG-DAC/PGCP-AC course brochure and publicly available module outlines for topic coverage; publicly available C-DAC evaluation guidance for the objective-question format and difficulty framework. Questions in this booklet are independently authored practice items, not copied past-paper questions.

Official course outline: https://cdac.gov.in/index.aspx?courseid=0&id=DAC
C-DAC evaluation guideline reference: publicly available C-DAC evaluation guideline PDF (search result/source reference used during preparation).

IET, C-DAC