

# (A bit of) Advanced R

## Part 3 - a tour of the tidyverse

Julien Chiquet

<https://github.com/jchiquet/CourseAdvancedR>

Université Paris Dauphine, Juin 2018



# Outline

- ① Introduction to tidy data and tidyverse
- ② magrittr
- ③ tidyr
- ④ dplyr
- ⑤ tibble

# References

Many ideas/examples inspired/stolen there:

R for data science (Wickham & Grolemund, 2016), <http://r4ds.had.co.nz>



Tidyverse website, <https://www.tidyverse.org/>



# Prerequisites

## Data Structures in base R

- ① Atomic vector (integer, double, logical, character)
- ② Recursive vector (list)
- ③ Factor
- ④ Matrix and array
- ⑤ Data Frame

## R base programming

- ① Control Statements
- ② Functions
- ③ Functionals
- ④ Input/output
- ⑤ Rstudio API (application programming interface)

# Outline

- 1 Introduction to tidy data and tidyverse
- 2 magrittr
- 3 tidyr
- 4 dplyr
- 5 tibble

# Tidy data: motivation

Collected data are (never) under a proper canonical format

*“Happy families are all alike; every unhappy family is unhappy in its own way.” – Leo Tolstoy*

*“Tidy datasets are all alike, but every messy dataset is messy in its own way.” – Hadley Wickham<sup>1</sup>*

---

<sup>1</sup>Rstudio's chief scientific advisor

# Tidy data: motivation

Collected data are (never) under a proper canonical format

*“Happy families are all alike; every unhappy family is unhappy in its own way.” – Leo Tolstoy*

*“Tidy datasets are all alike, but every messy dataset is messy in its own way.” – Hadley Wickham<sup>1</sup>*

---

<sup>1</sup>Rstudio's chief scientific advisor

# Tidy data: what?

## First, a subjective question

What is the *observation/statistical unit* in your data?

## Definition

*Tidy data is a standard way of mapping the meaning of a dataset to its structure. A dataset is messy or tidy depending on how rows, columns and tables are matched up with observations, variables and types.*

In tidy data,

- ① each variable forms a column,
- ② each observation forms a row,
- ③ each type of observational unit forms a table.



# Tidy data: what?

## First, a subjective question

What is the *observation/statistical unit* in your data?

## Definition

*Tidy data is a standard way of mapping the meaning of a dataset to its structure. A dataset is messy or tidy depending on how rows, columns and tables are matched up with observations, variables and types.*

In tidy data,

- ① each variable forms a column,
- ② each observation forms a row,
- ③ each type of observational unit forms a table.

# Tidy data: what?

## First, a subjective question

What is the *observation/statistical unit* in your data?

## Definition

*Tidy data is a standard way of mapping the meaning of a dataset to its structure. A dataset is messy or tidy depending on how rows, columns and tables are matched up with observations, variables and types.*

In tidy data,

- ① each variable forms a column,
- ② each observation forms a row,
- ③ each type of observational unit forms a table.

# Tidy data: why?




Figure 1: Tidy data

- make manipulation, visualization and modelling easier
- a common structure for all packages
- a philosophy for data representation (beyond the R framework)

# Tidy or not ?

```
tidyr::table3
```

```
## # A tibble: 6 x 3
##   country      year rate
## * <chr>      <int> <chr>
## 1 Afghanistan 1999 745/19987071
## 2 Afghanistan 2000 2666/20595360
## 3 Brazil       1999 37737/172006362
## 4 Brazil       2000 80488/174504898
## 5 China        1999 212258/1272915272
## 6 China        2000 213766/1280428583
```

# Tidy or not ?

```
tidyr::table2
```

```
## # A tibble: 12 x 4
##   country      year type      count
##   <chr>      <int> <chr>    <int>
## 1 Afghanistan 1999 cases      745
## 2 Afghanistan 1999 population 19987071
## 3 Afghanistan 2000 cases      2666
## 4 Afghanistan 2000 population 20595360
## 5 Brazil      1999 cases      37737
## 6 Brazil      1999 population 172006362
## 7 Brazil      2000 cases      80488
## 8 Brazil      2000 population 174504898
## 9 China       1999 cases      212258
## 10 China      1999 population 1272915272
## 11 China      2000 cases      213766
## 12 China      2000 population 1280428583
```

# Tidy or not ?

```
tidyr::table1
```

```
## # A tibble: 6 x 4
##   country      year  cases population
##   <chr>      <int> <int>      <int>
## 1 Afghanistan 1999     745  19987071
## 2 Afghanistan 2000    2666  20595360
## 3 Brazil      1999   37737  172006362
## 4 Brazil      2000   80488  174504898
## 5 China       1999  212258 1272915272
## 6 China       2000  213766 1280428583
```

# The process of data analysis




Figure 2: scheme for data analysis process

- **import:** read/load the data
- **tidy:** formating (individuals/variables data frame)
- **transform:** suppression/creation/filtering/selection
- **visualization:** representation and validation
- **model:** statistical fits
- **communication:** diffusion (web/talk/article)

# The tidyverse

## Definition

- contraction of 'tidy' ("well arranged) and 'universe'.
- an *opinionated collection* of R packages designed for data science.
- all packages share an underlying *design philosophy, grammar, and data structures*

## Philosophy

*allows the user to focus on the important statistical questions rather than focusing on the technical aspects of data analysis*



# Let's have a look

The core tidyverse loads ggplot2, tibble, tidyr, readr, purrr, stringr, forcats, dplyr and others in a fancy and unconflicted way.

```
library(tidyverse)
tidyverse::tidyverse_conflicts()
```

```
## -- Conflicts -----
## x dplyr::filter() masks stats::filter()
## x dplyr::lag()     masks stats::lag()
```

```
tidyverse::tidyverse_deps()
```

```
## # A tibble: 25 x 4
##   package cran  local behind
##   <chr>   <chr> <chr> <lgl>
## 1 broom   0.4.4 0.4.3 TRUE
## 2 cli     1.0.0 1.0.0 FALSE
## 3 crayon  1.3.4 1.3.4 FALSE
## 4 dbplyr   1.2.1 1.2.1 FALSE
## 5 dplyr    0.7.5 0.7.4 TRUE
## 6 forcats 0.3.0 0.3.0 FALSE
## 7 ggplot2 2.2.1 2.2.1 FALSE
## 8 haven    1.1.1 1.1.1 FALSE
## 9 hms      0.4.2 0.4.2 FALSE
## 10 httr    1.3.1 1.3.1 FALSE
## # ... with 15 more rows
```

# Packages roles and overview I



tibble

a modern re-imagining of the data frame



tidyr

a set of functions that help you get to tidy data



dplyr

a consistent set of verbs that solve the most common data manipulation challenges

# Packages roles and overview II



readr

a fast and friendly way to read rectangular data (like csv, tsv, and fwf)



stringr

a cohesive set of functions designed to make working with strings as easy as possible



forcats

a suite of useful tools that solve common problems with factors

# Packages roles and overview III



a system for declaratively creating graphics, based on The Grammar of Graphics



enhances R's functional programming (FP) toolkit



offers a set of operators which make your code more readable

# Data analysis with the tidyverse




Figure 3: Updated scheme for data analysis process

# Outline

- 1 Introduction to tidy data and tidyverse
- 2 magrittr**
- 3 tidyr
- 4 dplyr
- 5 tibble

# Outline

- 1 Introduction to tidy data and tidyverse
- 2 magrittr
- 3 tidyr**
- 4 dplyr
- 5 tibble

# Outline

- 1 Introduction to tidy data and tidyverse
- 2 magrittr
- 3 tidyr
- 4 dplyr**
- 5 tibble



# Outline

- 1 Introduction to tidy data and tidyverse
- 2 magrittr
- 3 tidyr
- 4 dplyr
- 5 tibble**

# References

- R Core Team. (2017). *R: A language and environment for statistical computing*. Vienna, Austria: R Foundation for Statistical Computing. Retrieved from <https://www.R-project.org/>
- Wickham, H. (2014). *Advanced r*. CRC Press. Retrieved from <http://adv-r.had.co.nz/>
- Wickham, H., & Golemund, G. (2016). *R for data science: Import, tidy, transform, visualize, and model data*. "O'Reilly Media, Inc." Retrieved from <http://r4ds.had.co.nz>