Appendix F

Selected Solutions

F.10 Chapter 10 Solutions

10.1 The defining characteristic of a stack is the unique specification of how it is to be accessed. Stack is a LIFO (Last in First Out) structure. This means that the last thing that is put in the stack will be the first one to get out from the stack.

10.3 (a) PUSH R1

(b) POP R0

(c) PUSH R3

(d) POP R7

10.5 One way to check for overflow and underflow conditions is to keep track of a pointer that tracks the bottom of the stack. This pointer can be compared with the address of the first and last addresses of the space allocated for the stack.

```
;
; Subroutines for carrying out the PUSH and POP functions. This
; program works with a stack consisting of memory locations x3FFF
; (BASE) through x3FFB (MAX). R6 is the bottom of the stack.
;

POP             ST  R1, Save1 ; are needed by POP.
                ST  R2, Save2
                ST  R3, Save3
                LD  R1, NBASE   ; BASE contains -x3FFF.
                ADD R1, R1, #-1 ; R1 contains -x4000.
                ADD R2, R6, R1  ; Compare bottom of stack to x4000

                BRz fail_exit   ; Branch if stack is empty.
```

```
                LD  R1, BASE    ;Iterate from the top of
                                ;the stack
                LDI R0, BASE    ;Load the value from the
                NOT R3, R6      ;top of stack
                ADD R3, R3, #1  ;Generate the
                                ;negative of the
                                ;bottom-of-stack pointer
                ADD R6, R6, #1  ;Increment the
                                ;bottom-of-stack
                                ;pointer

pop_loop        ADD   R2, R1, R3  ;Compare iterating
                                  ;pointer to
                                  ;bottom-of-stack pointer
                BRz   success_exit;Branch if no more
                                  ;entries to shift
                LDR   R2, R1, #-1  ;Load the entry to shift
                STR   R2, R1, #0  ;Shift the entry
                ADD   R1, R1, #-1  ;Increment the
                                  ;iterating pointer
                BRnzp pop_loop

PUSH            ST  R1, Save1 ; Save registers that
                ST  R2, Save2 ; are needed by PUSH.
                ST  R3, Save3
                LD  R1, MAX   ; MAX contains -x3FFB
                ADD R2, R6, R1 ; Compare stack pointer to -x3FFB
                BRz fail_exit ; Branch if stack is full.

                ADD R1, R6, #0 ;Iterate from the bottom
                                 ;of stack
                LD  R3, NBASE    ;NBASE contains
                                 ;-x3FFF
                ADD R3, R3, #-1   ; R3 = -x4000

push_loop       ADD   R2, R1, R3  ;Compare iterating
                                  ;pointer to
                                  ;bottom-of-stack pointer
                BRz   push_entry  ;Branch if no more
                                  ;entries to shift
                LDR   R2, R1, #0  ;Load the entry to shift
                STR   R2, R1, #-1  ;Shift the entry
                ADD   R1, R1, #1 ;Decrement the
                                  ;iterating pointer
                BRnzp push_loop
```

```
push_entry      ADD   R6, R6, #-1   ;Increment the
                                    ;bottom-of-stack pointer
                STI   R0, BASE      ;Push a value onto stack
                BRnzp success_exit

success_exit    LD    R1, Save1     ;Restore original
                LD    R2, Save2     ;register values
                LD    R3, Save3
                AND   R5, R5, #0    ;R5 <--- success
                RET

fail_exit       LD    R1, Save1     ;Restore original
                LD    R2, Save2     ;register values
                LD    R3, Save3
                AND   R5, R5, #0
                ADD   R5, R5, #1    ;R5 <--- failure
                RET

BASE            .FILL x3FFF
NBASE           .FILL xC001 ; NBASE contains -x3FFF.
MAX             .FILL xC005

Save1           .FILL x0000
Save2           .FILL x0000
Save3           .FILL x0000
```

10.7

```
; Subroutines for carrying out the PUSH and POP functions. This
; program works with a stack consisting of memory locations x3FFF
; (BASE) through x3FFB (MAX). R6 is the stack pointer. R3 contains
; the size of the stack element. R4 is a pointer specifying the
; location of the element to PUSH from or the space to POP to
;
POP             ST      R2, Save2 ; are needed by POP.
                ST      R1, Save1
                ST      R0, Save0
                LD      R1, BASE ; BASE contains -x3FFF.
                ADD     R1, R1, #-1 ; R1 contains -x4000.
                ADD     R2, R6, R1 ; Compare stack pointer to x4000
                BRz     fail_exit ; Branch if stack is empty.
                ADD     R0, R4, #0
                ADD     R1, R3, #0
                ADD     R5, R6, R3
                ADD     R5, R5, #-1
                ADD     R6, R6, R3
```

感觉没有根据R4检查大小够不够。

```
pop_loop        LDR     R2, R5, #0
                STR     R2, R0, #0
                ADD     R0, R0, #1
                ADD     R5, R5, #-1
                ADD     R1, R1, #-1
                BRp     pop_loop
                BRnzp   success_exit

PUSH            ST      R2, Save2 ; Save registers that
                ST      R1, Save1 ; are needed by PUSH.
                ST      R0, Save0
                LD      R1,MAX ; MAX contains -x3FFB
                ADD     R2,R6,R1 ; Compare stack pointer to -x3FFB
                BRz     fail_exit ; Branch if stack is full.
                ADD     R0, R4, #0
                ADD     R1, R3, #0
                ADD     R5, R6, #-1

                NOT     R2, R3
                ADD     R2, R2, #1
                ADD     R6, R6, R2

push_loop       LDR     R2, R0, #0
                STR     R2, R5, #0
                ADD     R0, R0, #1
                ADD     R5, R5, #-1
                ADD     R1, R1, #-1
                BRp     push_loop

success_exit    LD      R0, Save0
                LD      R1, Save1 ; Restore original
                LD      R2, Save2 ; register values.
                AND     R5, R5, #0 ; R5 <-- success.
                RET
fail_exit       LD      R0, Save0
                LD      R1, Save1 ; Restore original
                LD      R2, Save2 ; register values.

                AND     R5, R5, #0
                ADD     R5, R5, #1 ; R5 <-- failure.
                RET
BASE            .FILL   xC001 ; BASE contains -x3FFF.
MAX             .FILL   xC005
Save0           .FILL   x0000
```

```
Save1           .FILL   x0000
Save2           .FILL   x0000
```

10.9 (a) BDECJKIHLG

(b)
```
Push Z
Push Y
Pop Y
Push X
Pop X
Push W
Push V
Pop V
Push U
Pop U
Pop W
Pop Z
Push T
Push S
Pop S
Push R
Pop R
Pop T
```

(c) 14 different output streams.

10.11 Correction, The question should have read:
In the example of Section 10.2.3, what are the contents of locations 0x01F1 and 0x01F2? They are part of a larger structure. Provide a name for that structure.

x01F1 - 0x6200
x01F2 - 0x6300

They are part of the Interrupt Vector Table.

10.13 (a) PC = x3006

Stack:

___

___

xxxxx - Saved SSP

(b) PC = x6200

Stack:

___

___

PSR of Program A - R6

x3007
xxxxx

(c) PC = x6300

Stack:
——
——

PSR for device B - R6
x6203
PSR of Program A
x3007
xxxxx

(d) PC = x6203

Stack:
——
——

PSR for device B
x6203
PSR of Program A - R6
x3007
xxxxx

(e) PC = x6400

Stack:
——
——

PSR for device B - R6
x6204
PSR of Program A
x3007
xxxxx

(f) PC = x6204

Stack:
——
——

PSR for device B

x6204
PSR of Program A - R6
x3007
xxxxx

(g) PC = x3007

Stack:
___
___

PSR for device B
x6204
PSR of Program A
x3007
xxxxx - Saved.SSP

10.14 Correction - If the buffer is full, a character has been stored in 0x40FE.

```
        LDI     R0, KBDR
        LDI     R1, PENDBF
        LD      R2, NEGEND
        ADD     R2, R1, R2
        BRz     ERR         ; Buffer is full
        STR     R0, R1, #0  ; Store the character
        ADD     R1, R1, #1
        STI     R1, PENDBF  ; Update next available empty
                            ; buffer location pointer
        BRnzp   DONE
ERR     LEA     R0, MSG
PUTS
DONE    RTI
KBDR    .FILL   xFE02
PBUF    .FILL   x4000
PENDBF  .FILL   x40FF
NEGEND  .FILL   xBF01 ; xBF01 = -(x40FF)
MSG     .STRINGZ  "Character cannot be accepted; input buffer full."
```

10.15 Note: This problem introduces the concept of a data structure called a queue. A queue has a First-In-First-Out(FIFO) property - Data is removed in the order as it is inserted. By having the pointer to the next available empty location wrap around to the beginning of the buffer in this problem, the queue becomes a circular queue. A circular queue is space efficient as it makes use of entries which have been removed by the consuming program. These concepts will be covered in detail in a data structure or algorithms course.

The solution to Problem 10.15 is not provided. Note that in this instance, we have provided a solution to 10.14, which should help with 10.15.

10.17 The Multiply step works by adding the multiplicand a number of times to an accumulator. The number of times to add is determined by the multiplier. The number of instructions executed to perform the Multiply step = 3 + 3*n, where n is the value of the multiplier. We will in general do better if we replace the core of the Multiply routine (lines 17 through 19 of Figure 10.14) with the following, doing the Multiply as a series of shifts and adds:

```
                AND    R0, R0, #0
                ADD    R4, R0, #1    ;R4 contains the bit mask (x0001)

Again           AND    R5, R2, R4    ;Is corresponding
                BRz    BitZero       ;bit of multiplier=1
                ADD    R0, R0, R1    ;Multiplier bit=1
                                     ;--> add
                                     ;shifted multiplicand
                BRn    Restore2      ;Product has already
                                     ;exceeded range
BitZero         ADD    R1, R1, R1    ;Shift the
                                     ;multiplicand bits
                BRn    Check         ;Mcand too big
                                     ;--> check if any
                                     ;higher mpy bits = 1
                ADD    R4, R4, R4    ;Set multiplier bit to
                                     ;next bit position
                BRn    DoRangeCheck  ;We have shifted mpy
                BRnzp  Again         ;bit into bit 15
                                     ;-->done.

Check           AND    R5, R2, R4
                BRp    Restore2
                ADD    R4, R4, R4
                BRp    Check
DoRangeCheck
```

10.19 This program assumes that hex digits are all capitalized.

```
        LD       R3, NEGASCII
        LD       R5, NEGHEX
        TRAP     x23
        ADD      R1, R0, R3   ;Remove ASCII template
        LD       R4, HEXTEST  ;Check if digit is hex
        ADD      R0, R1, R4
        BRnz     NEXT1
        ADD      R1, R1, R5   ;Remove extra
                              ;offset for hex
```

```
NEXT1           TRAP     x23
                ADD      R0, R0, R3   ;Remove ASCII template
                ADD      R2, R0, R4   ;Check if digit is hex
                BRnz     NEXT2
                ADD      R0, R0, R5   ;Remove extra
                                      ;offset for hex

NEXT2           ADD      R0, R1, R0   ;Add the numbers
                ADD      R1, R0, R4   ;Check if digit > 9
                BRnz     NEXT3
                LD       R2, HEX
                ADD      R0, R0, R2   ;Add offset for hex digits

NEXT3           LD       R2, ASCII
                ADD      R0, R0, R2   ;Add the ASCII template

DONE            TRAP     x21
                TRAP     x25

ASCII           .FILL    x0030
NEGASCII        .FILL    x-0030
HEXTEST         .FILL    #-9
HEX             .FILL    x0007
NEGHEX          .FILL    x-7
```

10.21

```
;
; R1 contains the number of digits including 'x'. Hex
; digits must be in CAPS.

ASCIItoBinary   AND R0, R0, #0 ; R0 will be used for our result
                ADD  R1, R1, #0 ; Test number of digits.
                BRz  DoneAtoB   ; There are no digits
;
                LD  R3, NegASCIIOffset ; R3 gets xFFD0, i.e., -x0030
                LEA  R2, ASCIIBUFF
                LD R6, NegXCheck
                LDR R4, R2, #0
                ADD R6, R4, R6
                BRz DoHexToBin

                ADD  R2, R2,R1
                ADD   R2, R2, #-1 ; R2 now points to "ones" digit
;
                LDR  R4, R2, #0 ; R4 <-- "ones" digit
                ADD  R4, R4, R3 ; Strip off the ASCII template
```

```
                ADD  R0, R0, R4 ; Add ones contribution
;
                ADD  R1, R1, #-1
                BRz  DoneAtoB ; The original number had one digit
                ADD  R2, R2, #-1 ; R2 now points to "tens" digit
;
                LDR  R4, R2, #0 ; R4 <-- "tens" digit
                ADD  R4, R4, R3 ; Strip off ASCII template
                LEA  R5, LookUp10 ; LookUp10 is BASE of tens values
                ADD  R5, R5, R4 ; R5 points to the right tens value
                LDR  R4, R5, #0
                ADD  R0, R0, R4 ; Add tens contribution to total
;
                ADD  R1, R1, #-1
                BRz  DoneAtoB ; The original number had two digits
                ADD  R2, R2, #-1 ; R2 now points to "hundreds" digit
;
                LDR  R4, R2, #0 ; R4 <-- "hundreds" digit
                ADD  R4, R4, R3 ; Strip off ASCII template
                LEA R5, LookUp100 ; LookUp100 is hundreds BASE
                ADD  R5, R5, R4 ; R5 points to hundreds value
                LDR  R4, R5, #0
                ADD  R0, R0, R4 ; Add hundreds contribution to total
                RET

DoHexToBin      ; R3 = NegASCIIOffset
                ; R2 = Buffer Pointer
                ; R1 = Num of digits + x
                ;
                ST R7, SaveR7
                LD R6, NumCheck
                ADD R1, R1, #-1

                ADD  R2, R2,R1
;
                LDR  R4, R2, #0 ; R4 <-- "ones" digit
                ADD  R4, R4, R3 ; Strip off the ASCII template
                ADD R7, R4, R6
                BRnz Cont1
                LD R7, NHexDiff
                ADD R4, R4, R7
Cont1           ADD  R0, R0, R4 ; Add ones contribution

;
                ADD  R1, R1, #-1
```

```
                BRz  DoneAtoB ; The original number had one digit
                ADD  R2, R2, #-1 ; R2 now points to "tens" digit
;
                LDR  R4, R2, #0 ; R4 <-- "tens" digit
                ADD  R4, R4, R3 ; Strip off ASCII template
                ADD R7, R4, R6
                BRnz Cont2
                LD R7, NHexDiff
                ADD R4, R4, R7

Cont2           LEA  R5, LookUp16
                ADD  R5, R5, R4
                LDR  R4, R5, #0
                ADD  R0, R0, R4
;
                ADD  R1, R1, #-1
                BRz  DoneAtoB ; The original number had two digits
                ADD  R2, R2, #-1 ; R2 now points to "hundreds" digit
;
                LDR  R4, R2, #0
                ADD  R4, R4, R3 ; Strip off ASCII template
                ADD R7, R4, R6
                BRnz Cont3
                LD R7, NHexDiff
                ADD R4, R4, R7

Cont3           LEA R5, LookUp256
                ADD  R5, R5, R4
                LDR  R4, R5, #0
                ADD  R0, R0, R4

;
DoneAtoB        LD R7, SaveR7
                RET

NegASCIIOffset  .FILL  xFFD0
NumCheck        .FILL  #-9
NHexDiff        .FILL #-7
NegXCheck       .FILL  xFF88
SaveR7          .FILL  x0000

ASCIIBUFF       .BLKW 4
LookUp10        .FILL #0
                .FILL #10
                .FILL #20
```

```
                .FILL #30
                .FILL #40
                .FILL #50
                .FILL #60
                .FILL #70
                .FILL #80
                .FILL #90
;
LookUp100       .FILL #0
                .FILL #100
                .FILL #200
                .FILL #300
                .FILL #400
                .FILL #500
                .FILL #600
                .FILL #700
                .FILL #800
                .FILL #900
LookUp16        .FILL     #0
                .FILL     #16
                .FILL     #32
                .FILL     #48
                .FILL     #64
                .FILL     #80
                .FILL     #96
                .FILL     #112
                .FILL     #128
                .FILL     #144
                .FILL     #160
                .FILL     #176
                .FILL     #192
                .FILL     #208
                .FILL     #224
                .FILL     #240

LookUp256       .FILL     #0
                .FILL     #256
                .FILL     #512
                .FILL     #768
                .FILL     #1024
                .FILL     #1280
                .FILL     #1536
                .FILL     #1792
                .FILL     #2048
                .FILL     #2304
```

```
.FILL     #2560
.FILL     #2816
.FILL     #3072
.FILL     #3328
.FILL     #3584
.FILL     #3840
```

10.23 This program reverses the input string. For example, given an input of “Howdy”, the output is “ydwoH”.

9.7 Note: This problem belongs in chapter 10.

The three errors that arose in the first student’s program are:

1. The stack is left unbalanced.

2. The privilege mode and condition codes are not restored.

3. Since the value in R7 is used for the return address instead of the value that was saved on the stack, the program will most likely not return to the correct place.