

main.c

Run ▶

```
1  #include<stdio.h>
2  int main()
3  {
4      float x , y;
5      char operator;
6
7
8      printf("_____ \n");
9      printf("| \n");
10     printf("|          CALCULATOR          | \n");
11     printf("|_____ \n");
12     printf("_____ \n");
13     printf("|          INSTRUCTIONS          | \n");
14     printf("| \n");
15     printf("|1. ENTER OPERATOR(+,-,*,/,q OR Q) | \n");
16     printf("|   note: Q or q is to quit       | \n");
17     printf("| \n");
18     printf("|2. ENTER TWO NUMBER              | \n");
19     printf("|_____ \n\n\n");
20
21     do
22     {
23         printf("enter operator(+,-,*,/,q or Q) : ");
24         scanf(" %c",&operator);
25         if (operator == '+' || operator == '-' || operator == '/' || operator == '*')
26         {
27             printf("enter two number : ");
28             scanf("%f%f",&x,&y);
29
30
31             switch(operator)
32             {
33                 case '+': printf("% 2f + % 2f = % 2f\n",x,y,x+y);
```

```
switch(operator)
{
    case '+' : printf("%.2f + %.2f \n = %.2f\n\n",x,y,x+y);
               break;
    case '-' : printf("%.2f - %.2f \n = %.2f\n\n",x,y,x-y);
               break;
    case '*' : printf("%.2f * %.2f \n = %.2f\n\n",x,y,x*y);
               break;
    case '/' : printf("%.2f / %.2f \n = %.2f\n\n",x,y,x/y);
               break;

}
```

```
}
else if(operator == 'q' || operator == 'Q' )
{}
```

```
else
{
    printf("\ninvalid operator\n\n");
}
```

```
} while( operator != 'q' && operator!= 'Q');
printf("SHUTTING DOWN CALCULATOR..... GOODBYE !");
```

```
}
```

CALCULATOR

INSTRUCTIONS

1. ENTER OPERATOR(+,-,*,/,q OR Q)
note: Q or q is to quit
2. ENTER TWO NUMBER

```
enter operator(+,-,*,/,q or Q) : *  
enter two number : 2 4  
2.00 * 4.00  
= 8.00
```

```
enter operator(+,-,*,/,q or Q) : +  
enter two number : 8 10  
8.00 + 10.00  
= 18.00
```

```
enter operator(+,-,*,/,q or Q) : q  
SHUTTING DOWN CALCULATOR..... GOODBYE !
```