




## Spesifikasi Teknis





DIMENSI (mm)	RKE 15	0	
WB, Wheelbase	3.500	3.850	
OL, Panjang total	6.258	7.153	
OW, Lebar total	2.206		
OH, Tinggi total	2.540		
Front tread	1.800		
Cabin to rear axle	2.713	7.153	
Ground clearance	180		
Front Overlang	1.198		
Rear over hang	1.710	2.105	
Box length	NA		

BERAT (kg)		
Berat kosong chasis	3.210	3.230
Axle depan	2.75	50
Axle belakang	5.75	50
GVW/GCW	8.50	00

PERFORMA			
Min. turning rad	5.75 m	7.00 m	
Max. speed	110 kr	m/h	
Max. grade ability	@ 40.	8%	
Max. tractive force	36.7	7	

MESIN		
Tipe	GH4E150E4	
Diameter x Stroke (mm)	100x120	
Volume	3.760 cc	
Output maksimum	150 hp 2.800 rpm	
Torsi maksimum	490 nm 1.400 - 1.800 rpm	
BRAKE		

Tipe	Dual circuit fully air brakes
SUSPENSI	Semi ellipticalV leaf spring with shock absorber
SPRING DEPAN	Semi elliptical leaf spring
Leaf Qty	10 x 8
Shock absorber	Double acting

	WB 2	
TRANSMISI		
Tipe		STO0506-1 ( 6 Forward 1 Reverse), overdrive
Gear ratio		
	I	6.38
	II	3.54
	III	2.09
	IV	1.38
	V	1.00
	VI	0.77
	R1	6.38
AXLE		
Front axle capacity		2.750 kg
Rear axle capacity		5.750 kg
Final gear ratio		4.88
CLUTCH		
Tipe		Ceramic facing with clutch booster
Diameter		330 mm
WHEEL & TIRE		
WHEEL & TIRE Front		7.5 x 16 - 14 PR
	=	7.5 x 16 - 14 PR 7.5 x 16 - 14 PR
Front		
Front Rear		7.5 x 16 - 14 PR
Front Rear Wheel rim		7.5 x 16 - 14 PR 6x16"
Front Rear Wheel rim Stud bolt		7.5 x 16 - 14 PR 6x16" 6 pcs
Front Rear Wheel rim Stud bolt FUEL TANK CAP.		7.5 x 16 - 14 PR 6x16" 6 pcs 190LTR
Front Rear Wheel rim Stud bolt FUEL TANK CAP. Baterry (AMP)	N	7.5 x 16 - 14 PR 6x16" 6 pcs 190LTR 24V-100 Ah amp
Front Rear Wheel rim Stud bolt FUEL TANK CAP. Baterry (AMP) Alternator SIDE RAIL DIMENSION Thicknes side rail	V	7.5 x 16 - 14 PR 6x16" 6 pcs 190LTR 24V-100 Ah amp 75 amp
Front Rear Wheel rim Stud bolt FUEL TANK CAP. Baterry (AMP) Alternator SIDE RAIL DIMENSION Thicknes side rail Web	N	7.5 x 16 - 14 PR 6x16" 6 pcs 190LTR 24V-100 Ah amp 75 amp 5 mm 210 mm
Front Rear Wheel rim Stud bolt  FUEL TANK CAP. Baterry (AMP) Alternator SIDE RAIL DIMENSION Thicknes side rail Web Flange	V	7.5 x 16 - 14 PR 6x16" 6 pcs 190LTR 24V-100 Ah amp 75 amp 5 mm 210 mm 76 mm
Front Rear Wheel rim Stud bolt FUEL TANK CAP. Baterry (AMP) Alternator SIDE RAIL DIMENSION Thicknes side rail Web	V	7.5 x 16 - 14 PR 6x16" 6 pcs 190LTR 24V-100 Ah amp 75 amp 5 mm 210 mm 76 mm Semi elliptical leaf spring
Front Rear Wheel rim Stud bolt  FUEL TANK CAP. Baterry (AMP) Alternator SIDE RAIL DIMENSION Thicknes side rail Web Flange	V	7.5 x 16 - 14 PR 6x16" 6 pcs 190LTR 24V-100 Ah amp 75 amp 5 mm 210 mm 76 mm
Front Rear Wheel rim Stud bolt  FUEL TANK CAP. Baterry (AMP) Alternator SIDE RAIL DIMENSION Thicknes side rail Web Flange SPRING REAR	N	7.5 x 16 - 14 PR 6x16" 6 pcs  190LTR 24V-100 Ah amp 75 amp  5 mm 210 mm 76 mm  Semi elliptical leaf spring Main leaf - 9
Front Rear Wheel rim Stud bolt  FUEL TANK CAP. Baterry (AMP) Alternator SIDE RAIL DIMENSION Thicknes side rail Web Flange SPRING REAR Leaf Qty	V	7.5 x 16 - 14 PR 6x16" 6 pcs 190LTR 24V-100 Ah amp 75 amp 5 mm 210 mm 76 mm Semi elliptical leaf spring Main leaf - 9 Helper leaf - 8
Front Rear Wheel rim Stud bolt  FUEL TANK CAP. Baterry (AMP) Alternator SIDE RAIL DIMENSION Thicknes side rail Web Flange SPRING REAR Leaf Qty Shock absorber	N	7.5 x 16 - 14 PR 6x16" 6 pcs 190LTR 24V-100 Ah amp 75 amp 5 mm 210 mm 76 mm Semi elliptical leaf spring Main leaf - 9 Helper leaf - 8
Front Rear Wheel rim Stud bolt  FUEL TANK CAP. Baterry (AMP) Alternator SIDE RAIL DIMENSION Thicknes side rail Web Flange SPRING REAR Leaf Qty Shock absorber Fog lamp		7.5 x 16 - 14 PR 6x16" 6 pcs 190LTR 24V-100 Ah amp 75 amp 5 mm 210 mm 76 mm Semi elliptical leaf spring Main leaf - 9 Helper leaf - 8

<sup>\*</sup>Aksesoris dan tipe kabin dalam ilustrasi gambar, mungkin tidak termasuk dalam paket penjualan. \*Kami berhak mengubah spesifikasi produk tanpa pemberitahuan sebelumnya.