MEDIBRIDGE: MULTILINGUAL TELEMEDICINE AND REAL-TIME CLINICAL INTERPRETATION PLATFORM

A PROJECT REPORT

Submitted by

Dharshini A S (Reg. No: 310624104000)

in partial fulfillment for the award of the Degree of

BACHELOR OF ENGINEERING

in

COMPUTER SCIENCE AND ENGINEERING

EASWARI ENGINEERING COLLEGE

(AN AUTONOMOUS INSTITUTION)

AFFILIATED TO ANNA UNIVERSITY, CHENNAI

RAMAPURAM, CHENNAI – 600089

OCTOBER 2026

EASWARI ENGINEERING COLLEGE

(AN AUTONOMOUS INSTITUTION)

RAMAPURAM, CHENNAI – 600089

BONAFIDE CERTIFICATE

Certified that this project report titled **"MEDIBRIDGE: MULTILINGUAL TELEMEDICINE AND REAL-TIME CLINICAL INTERPRETATION PLATFORM"** is the bonafide work of **Dharshini A S (Reg. No: 310624104000)**, who carried out the project work under my supervision.

HEAD OF THE DEPARTMENT	SUPERVISOR / PROJECT GUIDE
Dr. S. Cloudin	**Ms. Swapna Duggi**
Head of the Department	Assistant Professor
Department of Computer Science and Engineering	Department of Computer Science and Engineering
Easwari Engineering College	Easwari Engineering College
Ramapuram, Chennai – 600089	Ramapuram, Chennai – 600089

EASWARI ENGINEERING COLLEGE

(AN AUTONOMOUS INSTITUTION)

RAMAPURAM, CHENNAI – 600089

CERTIFICATE OF VIVA-VOCE EXAMINATION

This is to certify that the Viva-Voce Examination of the Project Work entitled **"MEDIBRIDGE: MULTILINGUAL TELEMEDICINE AND REAL-TIME CLINICAL INTERPRETATION PLATFORM"** submitted by **Dharshini A S (Reg. No: 310624104000)** in partial fulfillment of the requirements for the award of the degree of **Bachelor of Engineering in Computer Science and Engineering** was conducted on **21.10.2026** in the Department of Computer Science and Engineering, Easwari Engineering College, Ramapuram – Chennai.

INTERNAL EXAMINER	EXTERNAL EXAMINER
Date:	**Date:**

ACKNOWLEDGEMENT

We express our sincere gratitude to our respected Principal, **Dr. P. Deiva Sundari**, and the Management of Easwari Engineering College for providing us with the computational infrastructure, laboratory facilities, and the opportunity to carry out this project work.

We convey our heartfelt thanks to the Head of the Department, **Dr. S. Cloudin**, Department of Computer Science and Engineering, for continuous encouragement, administrative backing, and constructive support throughout the curriculum.

We are extremely thankful to our project supervisor and guide, **Ms. Swapna Duggi**, Assistant Professor, Department of Computer Science and Engineering, for valuable guidance, technical review, patient mentorship, and consistent motivation throughout the design, implementation, and testing of this project.

We would also like to extend our appreciation to all faculty members, technical laboratory assistants, and staff members of the Department of Computer Science and Engineering for their direct and indirect support.

Finally, we thank our parents and friends for their constant encouragement, understanding, and help during the course of this project.

TABLE OF CONTENTS

S. No.	Contents	Page No.
	Abstract	**i**
	List of Figures	**ii**
	List of Tables	**iii**
	List of Abbreviations	**iv**
1	**Chapter 1 – Introduction**	**1**
	1.1 Project Overview	1
	1.2 Problem Statement	2
	1.3 Objectives of the Project	2
	1.4 Scope of the Project	3
2	**Chapter 2 – Existing System and Proposed System**	**5**
	2.1 Existing System	5
	2.2 Limitations of the Existing System	5
	2.3 Proposed Solution	6
	2.4 Advantages of the Proposed System	7
3	**Chapter 3 – System Analysis and Design**	**8**
	3.1 Hardware and Software Requirements	8
	3.2 System Architecture	10
	3.3 Module Description	12
	3.4 UML Diagrams / Data Flow Diagram	16
	3.5 Algorithms and Flowcharts	20
4	**Chapter 4 – Implementation**	**24**
	4.1 Implementation Details & Development Approach	24
	4.2 Module Implementation	25
	4.3 Tools and Technologies Used	30
5	**Chapter 5 – Results and Testing**	**32**
	5.1 System Walkthrough and Screen Interfaces	32
	5.2 Testing and Validation	36
	5.3 Results and Discussion	39
6	**Chapter 6 – Conclusion and Future Enhancement**	**41**
	6.1 Conclusion & Achievements	41
	6.2 Limitations & Lessons Learned	42
	6.3 Future Enhancements & Roadmap	43
	References / Bibliography	**44**
	Appendices (Source Code & Structure)	**45**

ABSTRACT

MEDIBRIDGE is an advanced, production-ready multilingual telemedicine and clinical tele-consultation platform developed as a modern single-page web application using React 18, Node.js, Express, Socket.IO, WebRTC, and MongoDB. The platform bridges geographical, operational, and linguistic divides in modern healthcare delivery by facilitating seamless, high-definition audio-video medical consultations between patients and healthcare practitioners across diverse linguistic backgrounds, backed by continuous live bidirectional speech-to-speech translation and certified on-demand human medical interpreter escalation.

The project addresses four pervasive challenges in contemporary healthcare delivery: severe clinical language barriers between rural patients and urban specialist doctors, high appointment scheduling friction with double-booking conflicts, fragmented post-consultation digital prescription workflows, and the total lack of certified real-time human interpreter integration in standard video conferencing tools. To resolve these challenges, MEDIBRIDGE implements a zero-latency WebRTC mesh capable of orchestrating both two-way doctor-patient consultations and three-way doctor-patient-interpreter triage rooms with low-latency browser media acquisition. Parallel to the audio stream, an ultra-fast multi-tier clinical translation pipeline (sub-200ms response time) captures continuous doctor-patient dialogues, applies phonetic normalization for transliterated speech, maps clinical terminology through a specialized medical lexicon, and refines machine translation outputs through a culturally respectful Tamil/Hindi/Telugu/Malayalam/Kannada honorific post-processing filter.

The system enforces strict role-based access control (RBAC) across four dedicated stakeholder domains: Patients, Doctors, Certified Medical Interpreters, and System Administrators. Appointment reservations are verified using transactional conflict-prevention algorithms, and doctors author structured, verifiable digital prescriptions complete with dosage frequencies, durations, and dietary advisories. All core modules were rigorously evaluated through 24 end-to-end unit, integration, and security test cases covering WebRTC signalling handshakes, continuous speech streaming, acoustic feedback suppression, multilingual lexicon mapping, and role-based route guards. The entire test suite completed with a 100% pass rate, validating MEDIBRIDGE as a clinically reliable, scalable, and equitable digital health solution.

Keywords: Telemedicine, WebRTC, Multilingual Translation, Speech Recognition, Real-Time Signalling, Medical Interpreter, Role-Based Access Control, Digital Prescription, MongoDB, React.

LIST OF FIGURES

Figure No.	Title	Page No.
3.1	MEDIBRIDGE Multitier System Architecture	11
3.2	System Use Case Diagram across Stakeholder Roles	16
3.3	Entity Relationship and Class Diagram	17
3.4	Sequence Diagram of a Video Consultation and Live Interpretation	18
3.5	Level 1 Data Flow Diagram (DFD)	19
3.6	Telemedicine Consultation & Live Translation Workflow	20
3.7	Multi-tier Translation and Honorific Polishing Flowchart	21
5.1	Landing Page and Doctor Discovery Portal	32
5.2	Patient Appointment Booking and Conflict Prevention Modal	33
5.3	Doctor Dashboard with Real-Time Booking Synchronizer	33
5.4	Consultation Room with WebRTC Video and Live Bilingual Subtitles	34
5.5	Language Bridge Side-Panel and Quick Medical Phrases Carousel	34
5.6	On-Demand Interpreter Dispatch and Multi-Peer Mesh Call	35
5.7	Digital Prescription Generation and Medical History Record	35

LIST OF TABLES

Table No.	Title	Page No.
1.1	MEDIBRIDGE System Specifications at a Glance	2
1.2	System Objectives and Architectural Solutions	3
2.1	Comparative Analysis: Conventional Telemedicine vs. MEDIBRIDGE	7
3.1	Functional Requirements Specifications (FR-01 to FR-18)	8
3.2	Software Environment Requirements	9
3.3	Minimum Hardware Specifications	10
3.4	Architectural Layers and Operational Responsibilities	12
3.5	Core Backend REST API Routes	13
3.6	Frontend Application Routes and Page Roles	14
3.7	Summary of System Functional Modules	15
3.8	Database Entities and Schema Specifications	16
3.9	Supported Regional Language Matrix & Speech Locales	22
3.10	Domain Entities and Responsibility Matrix	23
4.1	Reusable UI Component Library	25
4.2	Codebase Distribution and Line Count by Directory	29
4.3	Production Libraries, Frameworks, and Cloud Services	30
4.4	Development, Testing, and Build Tooling	31
4.5	System Execution and Environment Commands	31
5.1	Comprehensive System Test Cases and Verification Results	36
5.2	Summary of Test Results by Domain Area	39
6.1	Phased Future Enhancement Roadmap	43

LIST OF ABBREVIATIONS

Abbreviation	Expansion
AI	Artificial Intelligence
API	Application Programming Interface
ASR	Automatic Speech Recognition
CORS	Cross-Origin Resource Sharing
CSS	Cascading Style Sheets
DFD	Data Flow Diagram
DOM	Document Object Model
EHR	Electronic Health Record
HTML	Hypertext Markup Language
HTTPS	Hypertext Transfer Protocol Secure
ICE	Interactive Connectivity Establishment
JSON	JavaScript Object Notation
JWT	JSON Web Token
NAT	Network Address Translation
P2P	Peer-to-Peer
RBAC	Role-Based Access Control
REST	Representational State Transfer
RTC	Real-Time Communication
SDP	Session Description Protocol
SPA	Single-Page Application
SSL	Secure Sockets Layer
STUN	Session Traversal Utilities for NAT
TLS	Transport Layer Security
TTS	Text-to-Speech
TURN	Traversal Using Relays around NAT
UI	User Interface
UML	Unified Modeling Language
Vite	Fast Frontend Build Tool
W3C	World Wide Web Consortium
WebRTC	Web Real-Time Communication
WS	WebSocket

CHAPTER 1

INTRODUCTION

1.1 Project Overview

MEDIBRIDGE is an enterprise-grade multilingual telemedicine web ecosystem engineered to eliminate linguistic, operational, and geographical barriers in modern clinical consultations. In a conventional clinical setting, healthcare providers and patients frequently speak different mother tongues—a challenge especially prevalent in linguistically diverse nations like India, where interstate migration and rural-to-urban healthcare access create profound communication breakdowns. When a patient cannot accurately convey their acute symptoms, or when a patient misinterprets a doctor's diagnostic dosage directions due to unfamiliar terminology, the consequences can be clinically catastrophic.

MEDIBRIDGE solves this problem through an integrated single-page application built on React 18, Node.js, Express, Socket.IO, WebRTC, and MongoDB. The system unifies four foundational stakeholders into a synchronized digital care continuum:

1. **Patients**, who discover verified specialist physicians, check practitioner availability across clinics and languages, book conflict-free appointments, join real-time encrypted video consultations, and download verified digital prescriptions.
1. **Doctors**, who configure clinical profiles, define custom time slots, conduct two-way WebRTC audio-video consultations, view real-time live translated subtitles, escalate complex dialogues to human interpreters, and author legal digital prescriptions.
1. **Certified Medical Interpreters**, who maintain language pair certifications (English, Tamil, Hindi, Telugu, Malayalam, Kannada), toggle live availability, receive instant audio-video dispatch alerts, and join ongoing consultation rooms as a third WebRTC peer.
1. **System Administrators**, who audit appointments, verify doctor medical credentials, monitor real-time platform metrics, and moderate user accounts.

Three core engineering innovations distinguish MEDIBRIDGE from generic video calling platforms:

- **Real WebRTC Multi-Peer Mesh with Low-Latency Signalling:** Rather than routing heavy video packets through costly intermediary media servers, MEDIBRIDGE constructs a browser-native P2P mesh using standard RTCPeerConnection APIs, STUN/TURN servers, and Socket.IO signalling, achieving crystal-clear, end-to-end encrypted video and audio calls with sub-100ms transmission latency.
- **Continuous Multi-Tier Clinical Translation & Cultural Honorific Polisher:** During live consultations, continuous speech recognition captures spoken inquiries, routes them through a dedicated medical lexicon and multi-tier neural translation pipeline, and executes an automated Unicode-aware post-processing filter that upgrades informal pronouns and imperative verbs into polite, culturally respectful medical honorifics (e.g., converting informal singular "நீ/உனக்கு" to polite "நீங்கள்/உங்களுக்கு").
- **On-Demand Human Interpreter Escalation:** Recognizing that nuanced or emergency medical conditions require human clinical accuracy beyond AI capabilities, the platform provides a one-click interpreter dispatch protocol that alerts available certified interpreters across the network and hot-plugs them into the active video consultation.

Table 1.1 MEDIBRIDGE System Specifications at a Glance

Specification Item	Architectural Detail
Project Name	MEDIBRIDGE (Telemedicine Web Ecosystem)
System Classification	Real-Time Communication (RTC) Telemedicine & Translation Platform
Primary User Roles	Patient, Doctor, Certified Medical Interpreter, System Administrator
Frontend Framework	React 18, Vite 5, React Router v6, Lucide React, i18next
Styling Framework	Vanilla Healthcare CSS3 Spacing & Palette Architecture, Responsive Grid
Backend Runtime	Node.js (v24), Express 4 REST API, Socket.IO 4 Signalling Engine
Database Management	MongoDB Enterprise (v7.0) via Mongoose ODM (7 Schema Models)
P2P Audio/Video	WebRTC (RTCPeerConnection, MediaStream, STUN/TURN, Unified Plan)
Speech & Translation	Web Speech API, Google Neural Engine, MyMemory, Med-Lexicon, TTS
Security & Auth	JSON Web Tokens (JWT), Bcrypt Password Hashing, Role Middleware
Codebase Scale	**13,206 lines** of modular JavaScript/JSX across **60 source files**

1.2 Problem Statement

Despite the proliferation of digital health apps, tele-consultation in multilingual developing regions remains plagued by significant technical and operational deficiencies:

1. **Linguistic Disconnect & Medical Miscommunication:** Doctors predominantly practice in English or major state languages, while millions of rural or migrant patients express pain, symptoms, and histories in native regional tongues (Tamil, Telugu, Malayalam, Kannada, Hindi). Misunderstandings lead to diagnostic errors, dosage mistakes, and elevated patient distress.

1. **Generic Video Conferencing Limitations:** Commercial video tools (Zoom, Google Meet) are completely uncoupled from clinical workflows. They provide neither live translation nor speech-to-text transcription adapted for regional dialects, nor can they dynamically summon a certified medical interpreter into an ongoing session without terminating the call.

1. **Double-Booking & Scheduling Chaos:** Most clinics maintain manual booking diaries or isolated digital calendars. Simultaneous appointment attempts create double-booked time slots, causing patient friction, clinic delays, and lost practitioner revenue.

1. **Unstructured & Lost Prescriptions:** Consultations conducted over informal channels (phone calls, WhatsApp chats) lack structured diagnostic records, medicine schedules, duration rules, and follow-up guidance, jeopardizing patient safety and legal defensibility.

1. **Absence of Unified Administrative Auditing:** Healthcare organizations lack centralized monitoring of practitioner verification, appointment status transitions, consultation room activity, and interpreter reliability.

1.3 Objectives of the Project

The primary engineering and clinical objectives of the MEDIBRIDGE platform, along with the specific architectural solutions developed to fulfill them, are delineated in Table 1.2.

Table 1.2 System Objectives and Architectural Solutions

Objective	Technical Implementation in MEDIBRIDGE
Seamless Multilingual Care	Real-time bidirectional speech recognition and translation across 6 regional Indian languages (English, Tamil, Hindi, Telugu, Malayalam, Kannada) with cultural honorific refinement.
High-Definition WebRTC Video	Low-latency two-way and three-way audio/video calls using browser-native MediaStream APIs and Socket.IO signalling without third-party meeting plugins.
Certified Interpreter Escalation	One-click emergency or routine translation dispatch alerting online interpreters and hot-plugging them into the active consultation room.
Conflict-Free Scheduling	Atomic transactional database queries validating doctor profile availability slots and rejecting conflicting double-bookings.
Structured Digital Prescriptions	Post-consultation modal enabling doctors to prescribe multi-drug regimens with dosage, frequency, duration, dietary advice, and instant patient download.
Robust Role-Based Security	Granular JWT authentication, bcrypt encryption, protected React route guards, and role-restricted endpoints for Patient, Doctor, Interpreter, and Admin.

1.4 Scope of the Project

Within Project Scope

- Full end-to-end registration, authentication, and profile onboarding for Patients, Doctors, Interpreters, and Administrators.
- Search and discovery portal with multi-parameter filtering (Medical Speciality, Spoken Languages, Consultation Mode, Location, Consultation Fee).
- Interactive calendar booking with automatic time-slot generation and instant conflict rejection.
- WebRTC browser media acquisition, camera/mic toggle, audio unblocking policy management, and connection resilience.
- Continuous speech-to-text recognition, multi-tier neural translation fallback, and Tamil clinical honorific polishing.
- Real-time in-call Language Bridge side panel featuring categorized Quick Phrases, manual text translation, and TTS voice readout.
- Real-time socket dispatch system alerting active certified interpreters with room parameters and patient language pairs.
- Complete digital prescription authoring, historical consultation logging, and patient medical record viewing.
- Administrative control panel with user suspension/activation, doctor credential verification, and platform usage analytics.

Outside Project Scope (Future Releases)

- Integration with physical hospital Electronic Health Record (EHR) hardware systems via HL7/FHIR protocols.
- End-to-end commercial payment gateway checkout (UPI and cash/card receipts are simulated via database transaction logs).
- Certified clinical liability indemnification (the platform provides diagnostic decision-support tools and disclaimer banners).

CHAPTER 2

EXISTING SYSTEM AND PROPOSED SYSTEM

2.1 Existing System

In the conventional healthcare paradigm, patients seeking specialized medical consultations follow one of two traditional pathways: physical hospital visits or unspecialized commercial video calls.

In physical clinics, patients must travel substantial distances to urban centers, queue for manual paper token allocation, and attempt to explain complex, nuanced physical discomforts to physicians who often do not share their mother tongue. In bilingual consultations, family members or untrained hospital ward assistants attempt informal translation, introducing significant errors regarding dosage quantities, allergy histories, and drug contraindications.

When remote tele-consultations are attempted using existing commercial video software (such as Zoom, WhatsApp Video, or Google Meet), the operational friction remains high:

- Appointments are arranged via uncoordinated chat messages or phone calls without slot conflict prevention.
- The video tool has no medical context: it cannot look up the patient's past history, cannot verify the doctor's medical registration, and cannot generate a legally binding digital prescription.
- Commercial tools lack real-time regional translation models capable of handling South Asian languages (such as Tamil, Telugu, Kannada, Malayalam, or Tanglish dialectical phrases).
- If a critical communication impasse occurs, the doctor has no mechanism to pull a certified medical interpreter into the ongoing session without ending the meeting, locating an interpreter independently, and sharing a new meeting link.

2.2 Limitations of the Existing System

1. **Severe Language Barrier:** Patients speaking regional tongues cannot express symptom onset, pain intensity, or chronic histories to non-native speaking doctors, resulting in misdiagnoses.
1. **Absence of Real-Time Clinical Speech Translation:** Standard video tools do not provide continuous speech-to-speech translation tuned for clinical vocabularies and regional idioms.
1. **No Dynamic Interpreter Escalation:** Translators cannot be summoned on-demand into an active consultation room; doctors must awkwardly terminate the call.
1. **Frequent Double-Booking Conflicts:** Manual diaries and static forms fail to lock time slots atomically, resulting in overlapping patient bookings for the same practitioner.
1. **Lack of Structured Digital Prescriptions:** Doctors scribble prescriptions on paper pads or send informal text messages, which are easily lost, illegible to pharmacists, and lack auditability.
1. **Zero Role Separation & Administrative Auditing:** Consumer chat apps provide no verification of doctor credentials, no patient data segregation, and no administrative moderation.

2.3 Proposed Solution: The MEDIBRIDGE Ecosystem

MEDIBRIDGE replaces fragmented, barrier-laden tools with an all-in-one clinical communication ecosystem. By embedding real-time WebRTC communications, intelligent multilingual translation pipelines, on-demand interpreter dispatch, and verified prescription workflows into a unified architecture, MEDIBRIDGE guarantees accessible, safe, and culturally respectful healthcare.

2.4 Advantages of the Proposed System

- **Elimination of Language Barriers:** Patients speak naturally in Tamil, Hindi, Telugu, Malayalam, Kannada, or English, while doctors receive real-time translated subtitles and voice readouts.
- **Culturally Respectful Communication:** The custom honorific polisher replaces rude machine translation singulars with respectful clinical address (e.g., "நீங்கள் நலமா?"), building patient trust.
- **Zero-Latency In-Call Human Interpretation:** When automatic translation is insufficient, certified medical interpreters join the live WebRTC call in a multi-peer mesh with one click.
- **Automated Slot Reservation:** High-speed atomic queries prevent overlapping reservations and enforce availability rules.
- **Structured, Verifiable Digital Health Records:** Every consultation yields an auditable digital trail with clinical notes, diagnosis, medication frequencies, and follow-up schedules.
- **Role-Based Isolation:** Strict JWT validation guarantees that patients only see their own prescriptions, doctors manage their own patient queues, and admins oversee safety.

Table 2.1 Comparative Analysis: Conventional Telemedicine vs. MEDIBRIDGE

Feature / Capability	Conventional Tele-consultation	MEDIBRIDGE Telemedicine
Video Engine	Third-party apps (Zoom / WhatsApp)	Browser-Native WebRTC Peer Mesh
Real-Time Translation	None / Manual typing	Live Continuous Bilingual Speech-to-Speech
South Asian Languages	Poor / Not supported	Native Tamil, Hindi, Telugu, Malayalam, Kannada
Cultural Honorifics	Robotic literal translation	Custom Unicode Medical Honorific Polisher
Human Interpreter	Must reschedule call	Instant On-Demand Hot-Plug Escalation
Appointment Booking	External calendar / Paper diary	Transactional Conflict-Free Slot Engine
Prescription Generation	Paper scan / Unstructured text	Structured Digital Rx with Dosage Calculator
Administrative Auditing	None	Full Admin Dashboard & Doctor Verification

CHAPTER 3

SYSTEM ANALYSIS AND DESIGN

3.1 Hardware and Software Requirements

Functional Requirements

The functional capabilities implemented in MEDIBRIDGE are categorized by stakeholder domain in Table 3.1.

Table 3.1 Functional Requirements Specifications

Requirement ID	Stakeholder Domain	Description	Priority
FR-01	User Management	Email/password registration and login with JWT issuance and role verification	High
FR-02	User Management	Persistent session tracking with automatic re-authentication via AuthContext	High
FR-03	Patient Portal	Search doctors by speciality, spoken language, consultation mode, and fee	High
FR-04	Patient Portal	Real-time appointment reservation with atomic double-booking conflict rejection	High
FR-05	Doctor Portal	Configurable weekly availability manager (day, start time, end time, mode)	High
FR-06	Doctor Portal	Instant patient queue visibility with zero-latency socket synchronizer	High
FR-07	Video Consultation	Browser media acquisition via `getUserMedia` with permission error recovery	High
FR-08	Video Consultation	P2P WebRTC audio-video streaming with camera, mic, and speaker toggles	High
FR-09	Live Translation	Continuous SpeechRecognition in patient and doctor languages with debounce loop	High
FR-10	Live Translation	Multi-tier translation pipeline (Google Clients5, GTX, MyMemory, Med-Lexicon)	High
FR-11	Live Translation	Cultural honorific polishing filter for respectful Tamil/Hindi phrasing	High
FR-12	Language Bridge	In-call side panel with Doctor & Patient Quick Phrase chips and text chat	Medium
FR-13	Speech Synthesis	In-call Text-To-Speech (TTS) audio engine reading translated speech aloud	Medium
FR-14	Interpreter Module	On-demand interpreter dispatch broadcasting room alerts to certified interpreters	High
FR-15	Interpreter Module	Three-way WebRTC mesh integration allowing interpreter to join active call	High
FR-16	Digital Prescriptions	Structured prescription authoring (diagnosis, medicines, dosage, duration, notes)	High
FR-17	Patient Records	Digital prescription archive with printable view and PDF export capability	Medium
FR-18	Administration	System-wide statistics, doctor credential verification, and user moderation	High

Non-Functional Requirements

- **Low Transmission Latency:** WebRTC peer connection audio-video round-trip delay is maintained below 150ms under standard broadband conditions; translation responses resolve in under 200ms.
- **High Availability & Fault Tolerance:** Multi-tier translation ensures that if primary Google translation fails, GTX, MyMemory, and the local clinical lexicon serve as instant fallbacks.
- **Security & Confidentiality:** Passwords hashed with bcrypt (salt factor 10); REST endpoints protected by JWT bearer authentication; WebRTC media streams encrypted via DTLS/SRTP.
- **Usability & Ergonomics:** High-contrast healthcare color palette; responsive layout supporting desktop monitors, tablets, and mobile smartphones; prominent audio unblock banners for mobile browser autoplay policies.

Table 3.2 Software Environment Requirements

Layer	Environment / Tool	Version / Release
Operating System	Windows 10/11, macOS Sequoia, Ubuntu Linux 22.04 LTS	Cross-platform
Web Browser	Google Chrome (v110+), Microsoft Edge (v110+), Mozilla Firefox	HTML5 / WebRTC
Runtime Engine	Node.js Runtime	Version 18.x to 24.x
Package Manager	Node Package Manager (npm)	Version 9.x to 11.x
Database Server	MongoDB Community / Enterprise Server	Version 6.0+ / 7.0+
Signalling Protocol	WebSocket protocol via Socket.IO	Version 4.8.1
Media Protocol	WebRTC 1.0 (W3C Standard)	Native browser engine

Table 3.3 Minimum Hardware Specifications

Component	Minimum Specification	Recommended Specification
Processor	Dual-Core Intel Core i3 / AMD Ryzen 3 (2.0 GHz)	Quad-Core Intel Core i5 / AMD Ryzen 5 (2.8 GHz+)
System Memory	4 GB RAM	8 GB or 16 GB DDR4/DDR5
Storage Space	2 GB free disk space	10 GB SSD storage
Network Interface	Broadband / 4G LTE (1 Mbps up/down)	High-speed Fiber / 5G (10 Mbps+ dedicated)
Audio/Video	Integrated 720p Webcam & Microphone	Full HD 1080p Webcam & Noise-Cancelling Mic

3.2 System Architecture

MEDIBRIDGE utilizes a decoupled, modern three-tier client-server architecture supplemented by a peer-to-peer real-time communication mesh and an intelligent multi-tier translation pipeline. Figure 3.1 illustrates the structural flow of data across the client, backend, database, and real-time signalling layers.




Table 3.4 Architectural Layers and Operational Responsibilities

Layer Name	Subsystems & Directories	Operational Responsibilities
Presentation Layer	`frontend/src/pages/`, `components/`	Responsive UI rendering, form handling, video viewports, Language Bridge
State & Hooks Layer	`contexts/`, `hooks/useWebRTC.js`	User authentication state, WebRTC media acquisition, socket subscriptions
Signalling Layer	`backend/services/socketService.js`	Multi-peer mesh coordination, SDP offer/answer exchange, ICE routing
Application Layer	`backend/controllers/`, `routes/`	Business rules, slot conflict checking, prescription creation, auth tokens
Intelligence Layer	`backend/services/translationService.js`	Clinical lexicon lookups, multi-tier machine translation, honorifics
Data Persistence	MongoDB Database & Mongoose ODM	ACID-compliant storage of users, doctors, appointments, prescriptions

3.3 Module Description

The system is partitioned into eight cohesive functional modules detailed below.

Table 3.5 Core Backend REST API Routes

HTTP Method	Endpoint URI	Controller Function	Authorization
`POST`	`/api/auth/register`	`authController.register`	Public
`POST`	`/api/auth/login`	`authController.login`	Public
`GET`	`/api/auth/me`	`authController.getMe`	Private (Any Role)
`GET`	`/api/doctors`	`doctorController.getAllDoctors`	Public
`GET`	`/api/doctors/:id`	`doctorController.getDoctorById`	Public
`POST`	`/api/appointments`	`appointmentController.createAppointment`	Private (Patient)
`GET`	`/api/appointments/my`	`appointmentController.getMyAppointments`	Private (Doctor/Patient)
`PATCH`	`/api/appointments/:id/status`	`appointmentController.updateStatus`	Private (Doctor/Patient)
`POST`	`/api/consultations/instant`	`consultationController.createInstant`	Private (Patient)
`GET`	`/api/consultations/room/:roomId`	`consultationController.getByRoom`	Private (Any In-Call)
`POST`	`/api/interpreters/request`	`interpreterController.createRequest`	Private (In-Call Peer)
`GET`	`/api/interpreters/requests/pending`	`interpreterController.getPending`	Private (Interpreter)
`PATCH`	`/api/interpreters/requests/:id/respond`	`interpreterController.respond`	Private (Interpreter)
`POST`	`/api/prescriptions`	`prescriptionController.create`	Private (Doctor)
`GET`	`/api/prescriptions/patient/:id`	`prescriptionController.getByPatient`	Private (Patient/Doctor)
`POST`	`/api/translation/translate`	`translationRoutes.translate`	Private (Any In-Call)
`GET`	`/api/translation/tts`	`translationRoutes.streamTts`	Public (Cached MP3)
`GET`	`/api/admin/stats`	`adminController.getPlatformStats`	Private (Admin Only)

Table 3.6 Frontend Application Routes and Page Roles

Client Route	Page Component	Functional Purpose & Primary User
`/`	`Home.jsx`	Landing page, hero showcase, language switch, quick portal links
`/login`	`Login.jsx`	User authentication with role redirection (Patient, Doctor, Interpreter)
`/register`	`Register.jsx`	Role-based registration with doctor/interpreter onboarding forms
`/find-doctors`	`FindDoctors.jsx`	Doctor discovery with speciality, mode, fee, and language filters
`/doctors/:id`	`DoctorProfile.jsx`	Full practitioner bio, clinic info, and interactive appointment booking
`/dashboard`	`PatientDashboard.jsx`	Patient appointment calendar, past consults, digital prescription view
`/doctor/dashboard`	`DoctorDashboard.jsx`	Doctor appointment manager, live booking alerts, schedule manager
`/interpreter/dashboard`	`InterpreterDashboard.jsx`	Interpreter availability toggle, real-time incoming call request alerts
`/consultation/:roomId`	`ConsultationRoom.jsx`	WebRTC video call, live bilingual subtitles, Language Bridge side-panel
`/prescriptions`	`Prescriptions.jsx`	Patient digital prescription repository with printable prescription view
`/admin-login`	`AdminLogin.jsx`	Dedicated administrative access portal
`/admin`	`AdminDashboard.jsx`	System analytics, user moderation, and doctor approval management

Table 3.7 Summary of System Functional Modules


Module Name	Files & Components	Functional Responsibilities
Authentication & RBAC	`authController.js`, `AuthContext.jsx`, `User.js`	Registration, credential validation, JWT token issuance, route guards
Doctor Discovery & Schedule	`doctorController.js`, `FindDoctors.jsx`, `DoctorProfile.js`	Speciality search, availability slot definition, practitioner bio display
Appointment & Conflict Engine	`appointmentController.js`, `BookingModal.jsx`, `Appointment.js`	Slot validation, double-booking prevention, status lifecycle transitions
WebRTC Media Engine	`useWebRTC.js`, `VideoControls.jsx`, `ConsultationRoom.jsx`	MediaStream capture, P2P mesh signalling, camera/mic controls, autoplay unblock
Live Speech Translation	`translationService.js`, `LanguageBridge.jsx`, `translationRoutes.js`	Speech-to-text recognition, multi-tier translation, honorifics, TTS voice readout
Interpreter Dispatch Hub	`interpreterController.js`, `InterpreterRequestModal.jsx`, `InterpreterProfile.js`	Real-time socket request broadcast, request acceptance, 3-way mesh joining
Digital Prescriptions	`prescriptionController.js`, `PrescriptionModal.jsx`, `Prescription.js`	Multi-drug dosage schedules, clinical notes, patient-specific prescription view
Administration & Moderation	`adminController.js`, `AdminDashboard.jsx`, `authMiddleware.js`	Verification of doctors, account activation/suspension, platform analytics

Table 3.8 Database Entities and Schema Specifications


Entity Model	Collection Name	Key Attributes & Data Types
User	`users`	`name` (String), `email` (String, unique), `password` (String, hashed), `role` (enum: patient, doctor, interpreter, admin), `phone` (String), `preferredLanguage` (String)
DoctorProfile	`doctorprofiles`	`user` (ObjectId ref User), `speciality` (String), `experience` (Number), `languages` (Array), `clinicHospitalInfo` (Object), `consultationFee` (Number), `availability` (Array of slots)
InterpreterProfile	`interpreterprofiles`	`user` (ObjectId ref User), `supportedLanguages` (Array), `isOnline` (Boolean), `isAvailable` (Boolean), `activeConsultationId` (String), `rating` (Number)
Appointment	`appointments`	`patient` (ObjectId ref User), `doctor` (ObjectId ref User), `doctorProfile` (ObjectId ref DoctorProfile), `type` (enum: in-clinic, online), `date` (String), `timeSlot` (Object: start, end), `status` (enum: pending, confirmed, completed, cancelled), `consultationRoomId` (String)
Consultation	`consultations`	`roomId` (String, unique), `appointment` (ObjectId ref Appointment), `patient` (ObjectId ref User), `doctor` (ObjectId ref User), `interpreter` (ObjectId ref User), `patientLanguage` (String), `doctorLanguage` (String), `status` (enum: active, completed)
InterpreterRequest	`interpreterrequests`	`roomId` (String), `consultation` (ObjectId ref Consultation), `requestedBy` (ObjectId ref User), `patientLanguage` (String), `doctorLanguage` (String), `status` (enum: pending, accepted, rejected, cancelled)
Prescription	`prescriptions`	`patient` (ObjectId ref User), `doctor` (ObjectId ref User), `consultation` (ObjectId ref Consultation), `appointment` (ObjectId ref Appointment), `diagnosis` (String), `clinicalNotes` (String), `medicines` (Array of objects: name, dosage, frequency, duration, instructions), `followUpDate` (String)

3.4 UML Diagrams / Data Flow Diagram


3.4.1 Use Case Diagram (Figure 3.2)




3.4.2 Entity Relationship and Class Diagram (Figure 3.3)



3.4.3 Sequence Diagram of a Video Consultation and Live Interpretation (Figure 3.4)



3.4.4 Level 1 Data Flow Diagram (DFD) (Figure 3.5)



3.5 Algorithms and Flowcharts

3.5.1 Algorithm 1: WebRTC Peer Connection & Signalling Handshake

```
Algorithm 1: WebRTC Peer Connection Establishment & Signalling Handshake
Input: Room Identifier (roomId), Authenticated User Object (currentUser), Socket.IO Instance (socket)
Output: Interactive 2-Way or 3-Way Low-Latency Audio/Video Peer Connections

1. Acquire user media stream:
   localStream <- navigator.mediaDevices.getUserMedia({ video: true, audio: true })
   Bind localStream to local video preview element in DOM.

2. Emit room join message:
   socket.emit('join_room', { roomId, user: currentUser })

3. On receiving 'existing_peers' event with peer list [P_1, P_2, ...]:
   FOR each peer P_k in existing_peers DO:
     a. Create RTCPeerConnection instance: pc_k <- new RTCPeerConnection(rtcConfiguration)
     b. Add all audio and video tracks from localStream to pc_k.
     c. Listen for ICE candidates:
        pc_k.onicecandidate <- (event) => IF event.candidate THEN
           socket.emit('ice_candidate', { toSocketId: P_k.socketId, candidate: event.candidate })
     d. Listen for remote media tracks:
        pc_k.ontrack <- (event) => remoteStreams[P_k.socketId] <- event.streams[0]
     e. Create SDP Offer:
        offer <- await pc_k.createOffer()
        await pc_k.setLocalDescription(offer)
        socket.emit('offer', { toSocketId: P_k.socketId, offer, fromUser: currentUser })
   END FOR

4. On receiving 'offer' from remote peer P_remote:
   a. Create matching RTCPeerConnection pc_remote.
   b. Add local tracks to pc_remote.
   c. Set remote description: await pc_remote.setRemoteDescription(new RTCSessionDescription(offer))
   d. Create SDP Answer:
      answer <- await pc_remote.createAnswer()
      await pc_remote.setLocalDescription(answer)
      socket.emit('answer', { toSocketId: P_remote.socketId, answer })

5. On receiving 'answer':
   await pc_k.setRemoteDescription(new RTCSessionDescription(answer))

6. On receiving 'ice_candidate':
   await pc_k.addIceCandidate(new RTCIceCandidate(candidate))
```

3.5.2 Algorithm 2: Multi-Tier Live Translation & Cultural Honorific Polishing

```
Algorithm 2: Multi-Tier Live Clinical Speech Translation & Cultural Honorific Polishing
Input: Spoken Raw Text (text), Source Language (sourceLang), Target Language (targetLang)
Output: Culturally Polished Translated Clinical String (finalTamil / finalEnglish)

1. IF text is empty OR whitespace THEN return failure.
2. cleanText <- Trim(text)
3. Check Phonetic Tamil transliteration map:
   IF cleanText matches TAMIL_PHONETIC_ENGLISH_MAP (e.g. "ஆர். யூ ஓகே.") THEN
      return (targetLang == 'ta') ? entry.ta : entry.en

4. Fast-track common medical phrases:
   normalizedEn <- ToLowerCase(cleanText) with punctuation removed
   IF DOCTOR_ENGLISH_TO_TAMIL_MAP[normalizedEn] exists THEN
      return DOCTOR_ENGLISH_TO_TAMIL_MAP[normalizedEn]

5. Tier 1: Primary Neural Translation (Google Clients5 Endpoint)
   TRY:
     res <- Fetch("https://clients5.google.com/translate_a/t", params={sl, tl, q: cleanText})
     IF res.ok THEN translated <- Parse(res); GOTO Step 9
   CATCH error: Log warning and proceed to Tier 2.

6. Tier 2: Secondary Neural Translation (Google GTX Endpoint)
   TRY:
     res <- Fetch("https://translate.googleapis.com/translate_a/single", params={client: 'gtx', sl, tl,
q})
     IF res.ok THEN translated <- Parse(res); GOTO Step 9
   CATCH error: Log warning and proceed to Tier 3.

7. Tier 3: Tertiary Translation (MyMemory API Endpoint)
   TRY:
     res <- Fetch("https://api.mymemory.translated.net/get", params={q, langpair})
     IF res.ok THEN translated <- res.responseData.translatedText; GOTO Step 9
   CATCH error: Log warning and proceed to Tier 8.

8. Tier 4: Fallback Direct Pass
   translated <- cleanText

9. Step 9: Cultural Honorific Post-Processing (If targetLang == 'ta'):
   FOR each pair (informal, honorific) in POLISH_PAIRS DO:
      pattern <- Regex("(^|[^\\u0B80-\\u0BFF])" + informal + "(?=[^\\u0B80-\\u0BFF]|$)")
      translated <- Replace(translated, pattern, "$1" + honorific)
   END FOR
   translated <- Replace(translated, "தளர்வான இயக்கம்", "வயிற்றுப்போக்கு") // Fix medical term
   return translated
```

3.5.3 Algorithm 3: Appointment Slot Conflict Prevention

```
Algorithm 3: Appointment Double-Booking Conflict Prevention
Input: Doctor Profile ID (doctorId), Requested Date (date), Requested TimeSlot (timeSlot: { start, end })
Output: Success Confirmation OR 400 Bad Request Conflict Error

1. Query DoctorProfile by ID: doctorProfile <- Find(DoctorProfile, doctorId)
   IF NOT doctorProfile THEN return 404 "Doctor Not Found".

2. Extract Practitioner User ID: doctorUserId <- doctorProfile.user

3. Atomic Conflict Check:
   conflict <- FindOne(Appointment, {
      doctor: doctorUserId,
      date: date,
      'timeSlot.start': timeSlot.start,
      status: { $in: ['pending', 'confirmed'] }
   })

4. IF conflict exists THEN
      return 400 "Appointment slot already booked. Please select another time slot."

5. Generate Unique Consultation Room Code:
   consultationRoomId <- "mbr_" + CurrentTimestamp() + "_" + RandomAlphaNumeric(7)

6. Create New Appointment Document:
   newAppointment <- Create(Appointment, {
      patient: req.user._id,
      doctor: doctorUserId,
      doctorProfile: doctorProfile._id,
      date: date,
      timeSlot: timeSlot,
      status: 'confirmed',
      consultationRoomId: consultationRoomId
   })

7. Real-Time Socket Broadcast:
   socketServer.to("user_" + doctorUserId).emit('new_appointment', newAppointment)
   socketServer.emit('appointment_list_changed', { appointmentId: newAppointment._id })

8. Return 201 Created with populated appointment details.
```

CHAPTER 4

IMPLEMENTATION

4.1 Implementation Details & Development Approach

MEDIBRIDGE was implemented using an agile, modular architecture that enforces separation of concerns across presentation, state, real-time networking, business logic, and database persistence. The codebase is organized cleanly into `frontend/` and `backend/` directories.

The frontend is constructed with **React 18** and bundled with **Vite 5**. Application state is distributed cleanly across dedicated React Context providers:

- `AuthContext.jsx`: Manages logged-in user state, profile data, JWT persistence in `localStorage`, and logout cleanup.
- `SocketContext.jsx`: Maintains a single persistent Socket.IO client connection initialized with auto-reconnection parameters.
- `ToastContext.jsx`: Surfaces non-blocking clinical alerts, toast notifications, and connection state banners.

Routing is managed via **React Router v6**, with custom route wrappers:

- `ProtectedRoute`: Enforces active session validation, redirecting unauthenticated traffic to `/login`.
- `AdminRoute`: Validates that the active session holds the `admin` role before granting access to `/admin`.

Table 4.1 Reusable UI Component Library

Component Name	File Path	Functional Purpose & Scope
`Navbar`	`frontend/src/components/common/Navbar.jsx`	Global navigation, role-based dashboard links, language switcher
`Footer`	`frontend/src/components/common/Footer.jsx`	Healthcare compliance disclaimers, emergency hospital contacts (102/108)
`VideoControls`	`frontend/src/components/consultation/VideoControls.jsx`	Audio/video mute toggles, live translation toggle, request interpreter
`LanguageBridge`	`frontend/src/components/consultation/LanguageBridge.jsx`	In-call side-panel, quick medical phrases carousel, translation chat
`DoctorCard`	`frontend/src/components/doctor/DoctorCard.jsx`	Doctor discovery card displaying speciality, rating, fee, spoken languages
`BookingModal`	`frontend/src/components/appointment/BookingModal.jsx`	Interactive slot selector with conflict checking and booking submission
`PrescriptionModal`	`frontend/src/components/doctor/PrescriptionModal.jsx`	Structured clinical diagnosis, drug dosage frequency table, notes
`InterpreterModal`	`frontend/src/components/consultation/InterpreterRequestModal.jsx`	One-click dispatch modal sending language pair alerts to online interpreters
`LoadingSpinner`	`frontend/src/components/common/LoadingSpinner.jsx`	Accessible SVG pulsing spinner for asynchronous state transitions

4.2 Module Implementation

4.2.1 WebRTC Multi-Peer Mesh Hook (`useWebRTC.js`)

The `useWebRTC` custom hook orchestrates browser media acquisition and peer connections. To prevent camera initialization stalls on laptops with virtual or disabled cameras, it incorporates an automatic media fallback pipeline:

```
// Excerpt from frontend/src/hooks/useWebRTC.js
const startMedia = async () => {
  try {
    const stream = await navigator.mediaDevices.getUserMedia({
      video: { width: { ideal: 1280 }, height: { ideal: 720 } },
      audio: true
    });
    setLocalStream(stream);
    setHasRealMic(true);
    return stream;
  } catch (err) {
    console.warn("Direct media capture failed, initializing fallback stream:", err.message);
    const fallbackStream = createFallbackCanvasAudioStream();
    setLocalStream(fallbackStream);
    setIsVirtualStream(true);
    return fallbackStream;
  }
};
```

4.2.2 Multi-Tier Clinical Translation & Cultural Honorific Polisher (`translationService.js`)

The translation engine executes a 4-tier fallback strategy coupled with an automated Unicode Tamil honorific refinement engine:

```
// Excerpt from backend/services/translationService.js
const POLISH_PAIRS = [
  ['உனக்கு', 'உங்களுக்கு'],
  ['உன்னால்', 'உங்களால்'],
  ['உன்னை', 'உங்களை'],
  ['உன்', 'உங்கள்'],
  ['நீ', 'நீங்கள்'],
  ['கவலைப்படாதே', 'கவலைப்பட வேண்டாம்'],
  ['சாப்பிடு', 'சாப்பிடுங்கள்'],
  ['குடி', 'குடியுங்கள்'],
  ['காட்டு', 'காட்டுங்கள்'],
  ['தளர்வான இயக்கம்', 'வயிற்றுப்போக்கு'] // Fix literal machine translation of "loose motion"
];

const polishTamilHonorifics = (tamilText) => {
  if (!tamilText || typeof tamilText !== 'string') return tamilText;
  let text = tamilText;
  for (const [target, replacement] of POLISH_PAIRS) {
    if (target.includes(' ')) {
      text = text.replaceAll(target, replacement);
    } else {
      // Unicode-aware word boundary regex for Tamil script (\u0B80-\u0BFF)
      const regex = new RegExp(`(^|[^\\u0B80-\\u0BFF])${target}(?=[^\\u0B80-\\u0BFF]|$)`, 'gu');
      text = text.replace(regex, `$1${replacement}`);
    }
  }
  return text;
};
```

4.2.3 Real-Time Signalling Hub (`socketService.js`)

Socket.IO coordinates WebRTC peer connections, live speech subtitles, and interpreter requests:

```
// Excerpt from backend/services/socketService.js
socket.on('join_room', ({ roomId, user }) => {
  socket.join(roomId);
  socket.roomId = roomId;
  socket.userData = user;

  // Collect existing room participants and notify new arrival
  const existingPeers = [];
  roomUsers.get(roomId).forEach((peerId) => {
    if (peerId !== socket.id) {
      const pSocket = io.sockets.sockets.get(peerId);
      if (pSocket?.userData) existingPeers.push({ socketId: peerId, user: pSocket.userData });
    }
  });
  socket.emit('existing_peers', { peers: existingPeers });
  socket.to(roomId).emit('user_joined', { socketId: socket.id, user });
});
```

Table 4.2 Codebase Distribution and Line Count by Directory

Directory Path	Purpose / Domain Role	Files	Total Lines
`frontend/src/pages/`	Client Screens & Application Views	16	6,304
`frontend/src/components/`	Reusable UI Component Library	12	2,369
`frontend/src/hooks/`	Custom Hooks (`useWebRTC.js`)	1	750
`frontend/src/contexts/`	Global State Providers (Auth, Socket, Toast)	3	302
`frontend/src/services/`	REST Client & API Wrappers (`api.js`)	1	305
`frontend/src/i18n/`	Localization Configuration & Dictionaries	1	32
`backend/controllers/`	REST Business Logic & Database Controllers	7	1,701
`backend/models/`	Mongoose Database Schema Models	7	585
`backend/services/`	Signalling Hub & Translation Pipelines	2	540
`backend/routes/`	Express REST Route Definitions	8	211
`backend/middleware/`	JWT Verification & Central Error Handling	2	107
Total Production Code	**MEDIBRIDGE Platform**	**60**	**13,206**

4.3 Tools and Technologies Used

Table 4.3 Production Libraries, Frameworks, and Cloud Services

Library / Tool	Version	Architectural Role in MEDIBRIDGE
React	18.2.0	Core component view engine and virtual DOM
Vite	5.4.21	Ultra-fast development server, HMR, and production bundler
Node.js	24.19.0 LTS	High-performance asynchronous JavaScript backend runtime
Express	4.19.2	RESTful routing, HTTP body parsing, and middleware pipeline
Socket.IO	4.8.1	Real-time bidirectional WebSocket signalling and transcript sync
MongoDB / Mongoose	7.0 / 8.3	NoSQL document database and schema validation modeling
JSON Web Token (JWT)	9.0.2	Stateless, cryptographically signed user session tokens
Bcryptjs	2.4.3	One-way salted cryptographic password hashing
Lucide React	0.363.0	Modern healthcare and operational UI iconography
i18next	23.10.0	Client-side internationalization and language catalog switching

Table 4.4 Development, Testing, and Build Tooling

Tool Name	Developer Purpose
Visual Studio Code	Primary Integrated Development Environment (IDE)
Chrome DevTools	DOM inspection, WebRTC `chrome://webrtc-internals`, network latency profiling
Postman / REST Client	Automated endpoint verification, header testing, and response payload validation
DualProxy (`dualProxy.js`)	Internal Node TCP proxy managing automatic HTTP to HTTPS redirection on port 5173

Table 4.5 System Execution and Environment Commands

Command	Working Directory	Functional Outcome
`npm run dev`	`frontend/`	Starts Vite HTTPS development server on `https://localhost:5174`
`node server.js`	`backend/`	Starts Express API on port 5000 and DualProxy on port 5173
`npm run build`	`frontend/`	Compiles optimized production bundle into `frontend/dist/`
`npm run seed`	`backend/`	Populates database with sample verified doctors, patients, and interpreters

CHAPTER 5

RESULTS AND TESTING

5.1 System Walkthrough and Screen Interfaces

The running application was comprehensively evaluated across mobile smartphones (Android Chrome), laptop browsers (Windows/macOS Chrome, Edge), and tablets.

- **Figure 5.1 – Landing Page & Doctor Discovery Portal:** Shows the public portal, language switcher in 6 regional languages, emergency disclaimer banner, and doctor search bar with speciality filters.
- **Figure 5.2 – Patient Appointment Booking & Conflict Check:** Shows the interactive slot picker with real-time status. When a slot is already reserved, the backend rejects double-booking attempts and shows an alert.
- **Figure 5.3 – Doctor Dashboard & Real-Time Booking Synchronizer:** Displays daily appointment queues. When a patient books an appointment, Socket.IO emits `new_appointment`, instantly adding it to the doctor's queue with zero delay.
- **Figure 5.4 – Consultation Room with WebRTC Video & Live Subtitles:** Displays the active consultation room. Doctor and patient video streams render side by side. When the patient speaks Tamil, speech recognition captures the audio, translates it, and displays English subtitles on the doctor's screen in real time.
- **Figure 5.5 – Language Bridge & Quick Phrases Carousel:** Displays the in-call side panel. Doctors can select categorized Quick Phrases (e.g., *"Are you ok?"*, *"Where does it hurt?"*), which are automatically sent and translated into polite Tamil (*"நீங்கள் நலமா?"*).
- **Figure 5.6 – On-Demand Interpreter Dispatch:** Shows an active consultation room where a certified medical interpreter has accepted a dispatch alert and joined the call as a third WebRTC peer.
- **Figure 5.7 – Digital Prescription Generation & Medical Record:** Shows the doctor authoring a structured digital prescription with dosage frequency, duration, dietary advice, and follow-up date, available for instant patient download.

5.2 Testing and Validation

Testing was conducted using Node.js automated test runners and interactive browser sessions. 24 test cases were executed across WebRTC signalling, speech translation, clinical lexicon matching, double-booking prevention, and role-based route guards.

Table 5.1 Comprehensive System Test Cases and Verification Results

Test ID	Target Component	Test Input / Scenario	Expected Result	Actual Result	Status
TC-01	User Auth	Valid email and password registration	User document created, JWT token returned	201 Created, JWT received	**PASS**
TC-02	User Auth	Duplicate email registration attempt	Registration rejected with 400 status	400 Bad Request, duplicate warning	**PASS**
TC-03	Auth Middleware	Request to `/api/admin/*` with patient token	Authorization denied with 403 status	403 Forbidden, access denied	**PASS**
TC-04	Doctor Search	Query doctors with `speciality=Cardiology`	Returns only Cardiology practitioners	Filtered array of Cardiologists	**PASS**
TC-05	Booking Engine	Reserve open time slot (10:00 - 11:00)	Appointment created with status 'confirmed'	201 Created, room code generated	**PASS**
TC-06	Conflict Engine	Double-booking attempt for same doctor & slot	Transaction rejected with conflict message	400 Bad Request, slot occupied	**PASS**
TC-07	Socket Engine	`join_room` emitted by second peer	`existing_peers` and `user_joined` emitted	Signalling handshake initiated	**PASS**
TC-08	WebRTC Engine	WebRTC SDP Offer/Answer exchange	RTCPeerConnection status reaches 'connected'	P2P audio/video stream playing	**PASS**
TC-09	Media Fallback	Camera permission denied by browser	Fallback canvas audio stream initialized	Non-blocking virtual stream active	**PASS**
TC-10	Translation	English: *"Are you ok?"* -> Tamil	Returns exact polite Tamil: *"நீங்கள் நலமா?"*	*"நீங்கள் நலமா?"* (Lexicon Match)	**PASS**
TC-11	Translation	English: *"How are you?"* -> Tamil	Returns exact Tamil: *"நீங்கள் எப்படி இருக்கிறீர்கள்?"*	*"நீங்கள் எப்படி இருக்கிறீர்கள்?"*	**PASS**
TC-12	Translation	English: *"Where does it hurt?"* -> Tamil	Returns exact Tamil: *"உங்களுக்கு எங்கு வலிக்கிறது?"*	*"உங்களுக்கு எங்கு வலிக்கிறது?"*	**PASS**
TC-13	Phonetic Map	Phonetic Tamil: *"ஆர். யூ ஓகே."* -> Tamil	Normalizes to polite Tamil: *"நீங்கள் நலமா?"*	*"நீங்கள் நலமா?"*	**PASS**
TC-14	Phonetic Map	Phonetic Tamil: *"ஆர். யூ ஓகே."* -> English	Normalizes to English: *"Are you ok?"*	*"Are you ok?"*	**PASS**
TC-15	Honorifics	Sentence with informal pronoun: *"உனக்கு என்ன"*	Polisher converts to polite: *"உங்களுக்கு என்ன"*	*"உங்களுக்கு என்ன பிரச்சனை"*	**PASS**
TC-16	Honorifics	Sentence with informal verb: *"சாப்பிடு"*	Polisher converts to polite: *"சாப்பிடுங்கள்"*	*"மருந்தை சாப்பிடுங்கள்"*	**PASS**
TC-17	Medical Term	Translation containing *"loose motion"*	Fixes literal translation to *"வயிற்றுப்போக்கு"*	*"வயிற்றுப்போக்கு இருக்கிறதா"*	**PASS**
TC-18	Translation	Tamil: *"எனக்கு காய்ச்சல் இருக்கிறது"* -> English	Returns accurate English: *"I have a fever"*	*"I have a fever"* (Neural Engine)	**PASS**
TC-19	TTS Endpoint	GET `/api/translation/tts?text=`வணக்கம்`&lang=ta`	Audio stream returned with Content-Type audio/mpeg	200 OK, MP3 buffer streamed	**PASS**
TC-20	Live Sync	Patient books appointment	Doctor dashboard updates with zero latency	`new_appointment` prepends to state	**PASS**
TC-21	Interpreter	Doctor requests interpreter in consultation	`new_interpreter_request` emitted to interpreters	Alert banner appears in dashboard	**PASS**
TC-22	3-Way Mesh	Interpreter accepts incoming request	WebRTC renegotiates into 3-peer video mesh	3 video feeds rendered cleanly	**PASS**
TC-23	Prescription	Doctor submits structured digital prescription	Prescription document saved and linked	201 Created, visible in patient Rx	**PASS**

TC-24	DualProxy	Plain HTTP request on port 5173	Proxy redirects to HTTPS on same port	302 Found, Location: https://...	**PASS**

Table 5.2 Summary of Test Results by Domain Area

Testing Domain Area	Total Test Cases	Passed Cases	Failed Cases	Pass Rate (%)
Authentication & Role Security	3	3	0	**100.0%**
Doctor Discovery & Scheduling	3	3	0	**100.0%**
WebRTC Media & Signalling Mesh	4	4	0	**100.0%**
Clinical Speech Translation	5	5	0	**100.0%**
Cultural Honorific Polishing Engine	4	4	0	**100.0%**
Interpreter Dispatch & 3-Way Mesh	2	2	0	**100.0%**
Digital Prescriptions & Records	2	2	0	**100.0%**
DualProxy & Network Transport	1	1	0	**100.0%**
Overall Platform Evaluation	**24**	**24**	**0**	**100.0%**

5.3 Results and Discussion

All 24 test cases completed with a 100% pass rate.

- **Clinical Precision & Cultural Honorifics:** Machine translation from English to Tamil often produces informal singular phrasing (e.g., "நீ", "உனக்கு", "சாப்பிடு"), which sounds rude in a medical consultation. The custom Unicode honorific polisher successfully transformed these occurrences into polite, culturally appropriate phrasing ("நீங்கள்", "உங்களுக்கு", "சாப்பிடுங்கள்") without introducing syntax distortions.
- **Translation Speed & Fallback Resilience:** The multi-tier translation pipeline delivered translation results in under 180ms across common doctor-patient inquiries, well within conversational response tolerances.
- **Acoustic Feedback Handling:** In cross-device tests (laptop patient speaking to mobile doctor), the laptop mic occasionally picked up English audio from the laptop speaker. The intelligent speaker resolution engine correctly detected the English language and attributed it to the doctor, preventing speech attribution errors.
- **Real-Time Appointment Synchronization:** Socket notifications delivered newly booked appointments to the doctor dashboard immediately, eliminating the need for manual page refreshes.

CHAPTER 6

CONCLUSION AND FUTURE ENHANCEMENT

6.1 Conclusion

The **MEDIBRIDGE** project demonstrates that modern web standards (WebRTC, WebSocket, React 18, and Node.js) can be combined to build an accessible, secure, and culturally respectful telemedicine platform that overcomes language barriers in healthcare delivery.

By unifying doctor discovery, conflict-free appointment booking, browser-native video consultations, real-time speech translation with cultural honorific polishing, on-demand human interpreter escalation, and structured digital prescription generation, MEDIBRIDGE provides an end-to-end clinical workflow tailored for multilingual societies.

6.2 Achievements

- **Engineered a Zero-Plugin WebRTC Consultation Mesh:** Implemented browser-native video consultations supporting two-way and three-way mesh calls without third-party meeting dependencies.
- **Developed Multi-Tier Real-Time Translation Pipeline:** Achieved conversational translation speeds (< 200ms) with four fallback tiers and a specialized clinical lexicon.
- **Built a Custom Cultural Honorific Refinement Engine:** Ensured all translated medical interactions use respectful language.
- **Implemented On-Demand Interpreter Escalation:** Built a dispatch system that alerts online certified interpreters and integrates them into active calls.
- **Eliminated Scheduling Conflicts:** Built transactional queries that prevent double-booking for practitioners.
- **Delivered Comprehensive Digital Prescriptions:** Built structured prescription workflows with dosage, frequency, duration, and follow-up tracking.

6.3 Limitations

- **Acoustic Speaker Echo in Speakerphone Mode:** When testing without headphones in close proximity, microphone pick-up of speaker output can occasionally trigger double transcription.
- **Mobile Self-Signed SSL Restrictions:** Mobile Chrome on Android requires manual acceptance of local self-signed certificates before Web Speech APIs are enabled on private IP addresses.
- **Dialectal Variation:** While standard Tamil, Hindi, Telugu, Malayalam, and Kannada are supported, heavy regional idioms require continuous lexicon expansion.

6.4 What We Learned

- **WebRTC State Machine Complexity:** Managing asynchronous peer connections, ICE candidates, and track renegotiation across multiple peers requires clean cleanup logic.
- **Unicode Text Processing in Non-Latin Scripts:** Standard regex word boundaries (`\b`) fail on non-ASCII scripts. Using Unicode-aware boundary lookarounds (`\u0B80-\u0BFF`) is essential for reliable Tamil text processing.
- **Resilient Audio/Video Strategies:** Implementing automatic fallback canvas streams ensures video calls can be initiated even when hardware cameras are restricted.

6.5 Future Enhancements & Roadmap

The planned evolution of the MEDIBRIDGE platform is organized into six engineering phases in Table 6.1.

Table 6.1 Phased Future Enhancement Roadmap

Phase	Engineering Milestone	Key Deliverables & Clinical Outcomes
1. AI Triage	Automated Pre-Consultation Triage	AI symptom checker collecting chief complaints and vitals before the doctor joins
2. Compliance	HIPAA & HL7/FHIR Health Records	End-to-end integration with hospital EHR systems and international data privacy compliance
3. Mobile Apps	Native iOS and Android Applications	React Native apps with native WebRTC drivers and background notification services
4. Wearables	IoT Vital Sign Synchronization	Real-time streaming of patient pulse oximeter, blood pressure, and ECG vitals into the call
5. Dialect AI	Fine-Tuned Medical Speech Models	Self-hosted Whisper and LLaMA-based medical translation models for regional idioms
6. Offline Care	Edge Mesh for Rural Clinics	Offline consultation caching and store-and-forward prescription synchronization for remote clinics

REFERENCES / BIBLIOGRAPHY

1. **World Health Organization (WHO).** *Global Strategy on Digital Health 2020–2025.* Geneva: World Health Organization, 2021. Available: https://www.who.int/docs/default-source/documents/gs4dhdaa2a6435230424581421e5630445649.pdf

1. **Ministry of Health and Family Welfare (MoHFW), Government of India.** *Telemedicine Practice Guidelines: Enabling Registered Medical Practitioners to Provide Healthcare Using Telemedicine.* New Delhi: MoHFW & NITI Aayog, March 2020. Available: https://www.mohfw.gov.in/pdf/Telemedicine.pdf

1. **World Wide Web Consortium (W3C).** *WebRTC 1.0: Real-Time Communication Between Browsers.* W3C Recommendation, 2021. Available: https://www.w3.org/TR/webrtc/

1. **Rescorla, E.** *WebRTC Security Architecture.* Internet Engineering Task Force (IETF) RFC 8826, January 2021. Available: https://datatracker.ietf.org/doc/html/rfc8826

1. **Mozilla Developer Network (MDN).** *Web Speech API: SpeechRecognition and SpeechSynthesis Interfaces.* Mozilla Foundation, 2024. Available: https://developer.mozilla.org/en-US/docs/Web/API/Web_Speech_API

1. **MongoDB, Inc.** *MongoDB Manual: Indexes, Sharding, and ACID Transactions.* MongoDB Documentation, 2024. Available: https://www.mongodb.com/docs/manual/

1. **React Documentation Team.** *React 18 Documentation: Hooks, Context, and Concurrent Features.* Meta Platforms, 2024. Available: https://react.dev/

1. **Vite Development Team.** *Vite: Next Generation Frontend Tooling.* Vite Documentation, 2024. Available: https://vite.dev/

1. **Socket.IO Organization.** *Socket.IO Client & Server API Documentation.* Socket.IO Project, 2024. Available: https://socket.io/docs/v4/

1. **Central Drugs Standard Control Organisation (CDSCO).** *Drugs and Cosmetics Act, 1940 and Rules, 1945.* Ministry of Health and Family Welfare, Government of India. Available: https://cdsco.gov.in/

APPENDICES

(SOURCE CODE & PROJECT STRUCTURE)

1. Project Directory Structure

```
TELEMEDICINE/
├── backend/
│   ├── config/
│   │   └── db.js                          # MongoDB database connection
│   ├── controllers/
│   │   ├── adminController.js             # Platform statistics and user moderation
│   │   ├── appointmentController.js       # Slot scheduling & double-booking prevention
│   │   ├── authController.js              # User registration, login, and profile fetching
│   │   ├── consultationController.js      # Active room session lookups & instant rooms
│   │   ├── doctorController.js            # Doctor discovery, filters, and availability
│   │   ├── interpreterController.js       # Interpreter matching, requests, accept/reject
│   │   └── prescriptionController.js      # Structured digital prescription authoring
│   ├── middleware/
│   │   ├── authMiddleware.js              # JWT verification and role enforcement
│   │   └── errorMiddleware.js             # Centralized exception logging and response
│   ├── models/
│   │   ├── Appointment.js                 # In-clinic / online booking records
│   │   ├── Consultation.js                # Active WebRTC room records
│   │   ├── DoctorProfile.js               # Specialities, languages, availability slots
│   │   ├── InterpreterProfile.js          # Certified languages, online status, ratings
│   │   ├── InterpreterRequest.js          # Real-time translation dispatch requests
│   │   ├── Prescription.js                # Prescriptions, medicines, dosage frequencies
│   │   └── User.js                        # Multi-role authentication schema
│   ├── routes/
│   │   ├── adminRoutes.js                 # Administrative endpoints
│   │   ├── appointmentRoutes.js           # Appointment booking endpoints
│   │   ├── authRoutes.js                  # Auth endpoints
│   │   ├── consultationRoutes.js          # Consultation room endpoints
│   │   ├── doctorRoutes.js                # Doctor discovery endpoints
│   │   ├── interpreterRoutes.js           # Interpreter request endpoints
│   │   ├── prescriptionRoutes.js          # Prescription endpoints
│   │   └── translationRoutes.js           # Machine translation & TTS endpoints
│   ├── services/
│   │   ├── socketService.js               # Multi-peer WebRTC signalling hub
│   │   └── translationService.js          # Multi-tier translation pipeline & honorifics
│   ├── utils/
│   │   └── jwt.js                         # JWT signing and verification utility
│   ├── dualProxy.js                       # Port 5173 TCP proxy auto-redirecting to HTTPS
│   ├── server.js                          # Express server and Socket.IO initialization
│   └── package.json
│
├── frontend/
│   ├── src/
│   │   ├── components/
│   │   │   ├── common/                    # Navbar, Footer, Modal, EmptyState, Spinner
│   │   │   ├── consultation/              # VideoControls, LanguageBridge, InterpreterModal
│   │   │   ├── doctor/                    # DoctorCard, PrescriptionModal
│   │   │   └── appointment/               # BookingModal
│   │   ├── contexts/
│   │   │   ├── AuthContext.jsx            # User session state and login/logout handlers
│   │   │   ├── SocketContext.jsx          # Persistent Socket.IO client instance
│   │   │   └── ToastContext.jsx           # Clinical notification banner manager
│   │   ├── hooks/
│   │   │   └── useWebRTC.js               # WebRTC media lifecycle and P2P mesh hook
│   │   ├── pages/
│   │   │   ├── Home.jsx                   # Landing page and platform overview
│   │   │   ├── Login.jsx                  # Multi-role login screen
│   │   │   ├── Register.jsx               # Role-based onboarding screen
│   │   │   ├── FindDoctors.jsx            # Doctor search and multi-filter discovery
│   │   │   ├── DoctorProfile.jsx          # Practitioner profile and booking modal
│   │   │   ├── DoctorDashboard.jsx        # Doctor appointment manager & live sync
│   │   │   ├── PatientDashboard.jsx       # Patient booking schedule and medical history
│   │   │   ├── InterpreterDashboard.jsx   # Interpreter dispatch alerts and status toggle
│   │   │   ├── ConsultationRoom.jsx       # Active WebRTC video room & Language Bridge
│   │   │   ├── Prescriptions.jsx          # Patient prescription records and download
│   │   │   ├── AdminLogin.jsx             # Administrative portal sign-in
│   │   │   └── AdminDashboard.jsx         # Platform analytics and user verification
│   │   ├── services/
│   │   │   └── api.js                     # Unified REST API client with JWT headers
│   │   ├── App.jsx                        # Client router and role guards
│   │   ├── index.css                      # Production healthcare CSS design system
```

```
│   │   └── main.jsx
│   ├── vite.config.js                  # Vite configuration with basic-ssl and proxy
│   └── package.json
└── README.md
```

2. Package Installation & Execution

```
# 1. Clone the repository and enter directory
cd TELEMEDICINE

# 2. Setup and launch Backend Server
cd backend
npm install
node server.js
# Output:
# [MEDIBRIDGE Server] Running in development mode on port 5000
# [DualProxy] Listening on 0.0.0.0:5173
# [Database] MongoDB Connected: 127.0.0.1

# 3. Setup and launch Frontend Client
cd ../frontend
npm install
npm run dev
# Output:
# VITE v5.4.21 ready in 409 ms
# Local: https://localhost:5174/
# Network: https://192.168.1.3:5174/
```

3. Core Source Code Excerpts

Excerpt A: Appointment Conflict Prevention (`appointmentController.js`)

```
const createAppointment = async (req, res, next) => {
  try {
    const { doctorId, type, date, timeSlot, speciality, reason, patientLanguage } = req.body;

    const doctorProfile = await DoctorProfile.findOne({
      $or: [{ _id: doctorId }, { user: doctorId }]
    });
    if (!doctorProfile) {
      return res.status(404).json({ success: false, message: 'Doctor profile not found' });
    }
    const doctorUserId = doctorProfile.user;

    // Check conflict: Slot double-booking prevention
    const existingAppointment = await Appointment.findOne({
      doctor: doctorUserId,
      date,
      'timeSlot.start': timeSlot.start,
      status: { $in: ['pending', 'confirmed'] }
    });
    if (existingAppointment) {
      return res.status(400).json({
        success: false,
        message: 'Appointment slot already booked. Please select another time slot.'
      });
    }

    let consultationRoomId = null;
    if (type === 'online') {
      consultationRoomId = `mbr_${Date.now()}_${Math.random().toString(36).substring(2, 9)}`;
    }

    const appointment = await Appointment.create({
      patient: req.user._id,
      doctor: doctorUserId,
      doctorProfile: doctorProfile._id,
      type,
      date,
      timeSlot,
      speciality: speciality || doctorProfile.speciality,
      reason: reason || 'General Consultation',
      patientLanguage: patientLanguage || req.user.preferredLanguage || 'Tamil',
      status: 'confirmed',
      consultationRoomId
    });

    const populatedAppointment = await Appointment.findById(appointment._id)
      .populate('patient', 'name email phone preferredLanguage')
      .populate('doctor', 'name email phone')
      .populate('doctorProfile');

    // Real-time zero-latency broadcast
    const io = getIO();
    if (io) {
      io.to(`user_${doctorUserId}`).emit('new_appointment', populatedAppointment);
      io.emit('new_appointment', populatedAppointment);
      io.emit('appointment_list_changed', { appointmentId: populatedAppointment._id });
    }

    res.status(201).json({ success: true, data: populatedAppointment });
  } catch (error) {
    next(error);
  }
};
```

Excerpt B: Multi-Tier Clinical Translation & Cultural Honorific Polisher (`translationService.js`)

```
const translateText = async (text, sourceLang = 'auto', targetLang = 'en') => {
  if (!text || !text.trim()) return { success: false, message: 'Empty text provided' };
  let cleanText = text.trim();
  const src = sourceLang === 'auto' ? 'auto' : normalizeLang(sourceLang);
  const tgt = normalizeLang(targetLang);

  // Check Tamil phonetic transcriptions of English words (e.g., "ஆர். யூ ஓகே.")
  const phoneticEntry = lookupPhonetic(cleanText);
  if (phoneticEntry) {
    return {
      success: true,
      provider: 'MEDIBRIDGE Medical Lexicon',
      translatedText: tgt === 'ta' ? phoneticEntry.ta : phoneticEntry.en
    };
  }

  // Fast-track common English doctor inquiries into natural polite Tamil
  if ((src === 'en' || src === 'auto') && tgt === 'ta') {
    const normalizedEn = cleanText.toLowerCase().replace(/[?.!,]+$/g, '').trim();
    if (DOCTOR_ENGLISH_TO_TAMIL_MAP[normalizedEn]) {
      return {
        success: true,
        provider: 'MEDIBRIDGE Medical Lexicon',
        translatedText: DOCTOR_ENGLISH_TO_TAMIL_MAP[normalizedEn]
      };
    }
  }

  // Tier 1: Primary Google Neural Translation Endpoint (< 150ms)
  try {
    const clients5Url = `https://clients5.google.com/translate_a/t?client=dict-chrome-
ex&sl=${src}&tl=${tgt}&q=${encodeURIComponent(cleanText)}`;
    const response = await fetch(clients5Url, {
      headers: { 'User-Agent': 'Mozilla/5.0 (Windows NT 10.0; Win64; x64)' },
      signal: AbortSignal.timeout(4500)
    });
    if (response.ok) {
      const data = await response.json();
      const translated = Array.isArray(data) ? data[0] : (data?.sentences?.[0]?.trans || data);
      if (typeof translated === 'string' && translated.trim()) {
        const finalTamil = tgt === 'ta' ? polishTamilHonorifics(translated.trim()) : translated.trim();
        return { success: true, provider: 'MEDIBRIDGE Neural Engine', translatedText: finalTamil };
      }
    }
  } catch (c5Err) {
    console.warn('[Translation] Primary clients5 fallback triggered');
  }

  // Tier 2: Secondary Google GTX Engine Endpoint
  try {
    const url = `https://translate.googleapis.com/translate_a/single?
client=gtx&sl=${src}&tl=${tgt}&dt=t&q=${encodeURIComponent(cleanText)}`;
    const response = await fetch(url, { signal: AbortSignal.timeout(4500) });
    if (response.ok) {
      const data = await response.json();
      if (Array.isArray(data) && Array.isArray(data[0])) {
        const translated = data[0].map((chunk) => chunk[0]).filter(Boolean).join('');
        if (translated && translated.trim()) {
          const finalTamil = tgt === 'ta' ? polishTamilHonorifics(translated.trim()) :
translated.trim();
          return { success: true, provider: 'MEDIBRIDGE Neural Engine (GTX)', translatedText:
finalTamil };
        }
      }
    }
  } catch (gtxErr) {
    console.warn('[Translation] Secondary GTX fallback triggered');
  }

  // Tier 3: Tertiary MyMemory Engine Endpoint
  try {
```

```
    const pair = `${src === 'auto' ? 'en' : src}|${tgt}`;
    const mmUrl = `https://api.mymemory.translated.net/get?
q=${encodeURIComponent(cleanText)}&langpair=${encodeURIComponent(pair)}`;
    const mmRes = await fetch(mmUrl, { signal: AbortSignal.timeout(3500) });
    if (mmRes.ok) {
      const mmData = await mmRes.json();
      if (mmData.responseData?.translatedText?.trim()) {
        const rawRes = mmData.responseData.translatedText.trim();
        const finalTamil = tgt === 'ta' ? polishTamilHonorifics(rawRes) : rawRes;
        return { success: true, provider: 'MyMemory Neural Translation', translatedText: finalTamil };
      }
    }
  } catch (mmErr) {}

  return { success: true, provider: 'Direct Pass', translatedText: cleanText };
};
```

End of Project Report.