A

Attributes

Operations
- A():

Abstract

Attributes

Operations
~ Abstract():

AbstractClass

Attributes

Operations
+ AbstractClass():

AbstractClass

Attributes

Operations
+ AbstractClass():

Address

Attributes

Operations
- Address():

AddressValidator

Attributes

Operations
+ AddressValidator():
+ postDeserialize(Address): void

Amount<Q>

Attributes

Operations
+ Amount():

Annotations

Attributes

- descriptor: FileDescriptor
descriptor: FileDescriptor
Operations
- Annotations():
+ registerAllExtensions(ExtensionRegistry): void
+ registerAllExtensions(ExtensionRegistryLite): void

Api

Attributes

Operations
- Api():
+ values(): Api[]
~ newParser(): Parser
+ valueOf(String): Api

AppendableWriter

Attributes

Operations
~ AppendableWriter(Appendable):
+ append(CharSequence): Writer
+ write(String, int, int): void
+ flush(): void
+ write(int): void
+ close(): void
+ append(CharSequence, int, int): Writer
+ write(char[], int, int): void

ArrayOfArrays

Attributes

expectedJson: String
Operations
+ ArrayOfArrays():

ArrayOfObjects

Attributes

expectedJson: String
Operations
+ ArrayOfObjects():

ArrayTest

Attributes

Operations
+ ArrayTest():
+ testMultidimensionalArraysDeserialization(): void
+ setUp(): void
+ testArrayOfPrimitivesAsObjectsDeserialization(): void
+ testArrayOfCollectionDeserialization(): void
+ testTopLevelArrayOfIntsSerialization(): void
+ testArrayOfStringsSerialization(): void
+ testArrayOfCollectionSerialization(): void
+ testMultidimensionalPrimitiveArraysDeserialization(): void
+ testArrayOfNullSerialization(): void
+ testEmptyArrayDeserialization(): void
+ testSingleStringArraySerialization(): void
+ testMixingTypesInObjectArraySerialization(): void
+ testInvalidArrayDeserialization(): void
+ testNullsInArrayWithSerializeNullPropertySetSerialization(): void
+ testMultidimensionalArraysSerialization(): void
+ testSingleStringArrayDeserialization(): void
+ testMultidimensionalObjectArraysSerialization(): void
+ testSingleNullInArraySerialization(): void
+ testArrayOfPrimitivesAsObjectsSerialization(): void
+ testArrayOfNullDeserialization(): void
+ testTopLevelArrayOfIntsDeserialization(): void
+ testNullsInArraySerialization(): void
+ testMultidimensionalPrimitiveArraysSerialization(): void
+ testArrayOfStringsDeserialization(): void
+ testArrayElementsAreArrays(): void
+ testObjectArrayWithNonPrimitivesSerialization(): void
+ testEmptyArraySerialization(): void
+ testSingleNullInArrayDeserialization(): void
+ testNullsInArrayDeserialization(): void

Assignment<T>

Attributes

Operations
+ Assignment(Id<Assignment<T>>, T):
- Assignment():

AtomicIntegerTypeAdapter

Attributes

Operations
- AtomicIntegerTypeAdapter():
+ deserialize(JsonElement, Type, JsonDeserializationContext): AtomicInteger
+ serialize(AtomicInteger, Type, JsonSerializationContext): JsonElement

B

Attributes

Operations
- B():

Bag

Attributes

- descriptor: FileDescriptor
descriptor: FileDescriptor
Operations
- Bag():
+ registerAllExtensions(ExtensionRegistryLite): void
+ registerAllExtensions(ExtensionRegistry): void

BagOfPrimitiveWrappers

Attributes

expectedJson: String
Operations
+ BagOfPrimitiveWrappers(Long, Integer, Boolean):

BagOfPrimitives

Attributes
+ intValue: int
intValue: int
expectedJson: String
Operations
+ BagOfPrimitives(long, int, boolean, String):
+ BagOfPrimitives():
+ hashCode(): int
+ equals(Object): boolean
+ toString(): String

BagOfPrimitives

Attributes
+ intValue: int
intValue: int
expectedJson: String
Operations
+ BagOfPrimitives():
+ BagOfPrimitives(long, int, boolean, String):
+ toString(): String
+ equals(Object): boolean
+ hashCode(): int

BankTransfer

Attributes

Operations
~ BankTransfer(String, String):

Bar<T>

Attributes

Operations
~ Bar(T):

Base

Attributes

Operations
~ Base(int):

Base

Attributes

Operations
- Base():

Base

Attributes

Operations
+ Base():

Base

Attributes

Operations
- Base():

Base<T>

Attributes

Operations
~ Base(T):

BaseCollection<U, C>

Attributes

Operations
- BaseCollection():

BaseIntegerAdapter

Attributes

Operations
- BaseIntegerAdapter():
+ serialize(Base<Integer>, Type, JsonSerializationContext): JsonElement

BaseSerializer

Attributes

Operations
+ BaseSerializer():
+ serialize(Base, Type, JsonSerializationContext): JsonElement

BaseStringAdapter

Attributes

Operations
- BaseStringAdapter():
+ serialize(Base<String>, Type, JsonSerializationContext): JsonElement

BaseTypeAdapter

Attributes

Operations
- BaseTypeAdapter():
+ deserialize(JsonElement, Type, JsonDeserializationContext): Base

BigClass

Attributes

Operations
- BigClass():

BillingInstrument

Attributes

Operations
~ BillingInstrument(String):

Builder

Attributes

descriptorForType: Descriptor
defaultInstanceForType: InnerMessage
dataBuilderList: List<Builder>
dataOrBuilderList: List<DataOrBuilder>
NIdCt: int
content: Type
dataCount: int
dataList: List<Data>
descriptor: Descriptor
initialized: boolean

Operations
- Builder():
- Builder(BuilderParent):
+ addData(Data): Builder
+ buildPartial(): InnerMessage
+ clearContent(): Builder
+ addData(int, Data): Builder
+ mergeFrom(Message): Builder
+ addData(Builder): Builder
- ensureDataIsMutable(): void
+ getDataOrBuilder(int): DataOrBuilder
+ addDataBuilder(): Builder
+ build(): InnerMessage
+ mergeFrom(InnerMessage): Builder
# internalGetFieldAccessorTable(): FieldAccessorTable
+ addDataBuilder(int): Builder
+ mergeFrom(CodedInputStream, ExtensionRegistryLite): Builder
+ clear(): Builder
- buildPartialRepeatedFields(InnerMessage): void
+ hasContent(): boolean
+ setData(int, Data): Builder
+ hasNIdCt(): boolean
+ removeData(int): Builder
+ addData(int, Builder): Builder
+ clearNIdCt(): Builder
+ addAllData(Iterable<Data>): Builder
+ clearData(): Builder
- buildPartial0(InnerMessage): void
+ getDataBuilder(int): Builder
+ getData(int): Data
+ setData(int, Builder): Builder
- internalGetDataFieldBuilder(): RepeatedFieldBuilder<Data, Builder, DataOrBuilder>

Builder

Attributes

descriptorForType: Descriptor
countryCode5F55: String
countryCode5F55Bytes: ByteString
month: int
longTimestamp: long
defaultInstanceForType: OuterMessage
year: int
descriptor: Descriptor
initialized: boolean

Operations
- Builder(BuilderParent):
- Builder():
+ hasMonth(): boolean
+ buildPartial(): OuterMessage
- buildPartial0(OuterMessage): void
+ mergeFrom(CodedInputStream, ExtensionRegistryLite): Builder
+ clear(): Builder
# internalGetFieldAccessorTable(): FieldAccessorTable
+ build(): OuterMessage
+ clearLongTimestamp(): Builder
+ mergeFrom(OuterMessage): Builder
+ hasYear(): boolean
+ mergeFrom(Message): Builder
+ clearYear(): Builder
+ hasLongTimestamp(): boolean
+ clearCountryCode5F55(): Builder
+ clearMonth(): Builder
+ hasCountryCode5F55(): boolean

Builder

Attributes

descriptorForType: Descriptor
numbersCount: int
name: String
defaultInstanceForType: ProtoWithRepeatedFields
simplesOrBuilderList: List<SimpleProtoOrBuilder>
numbersList: List<Long>
nameBytes: ByteString
simplesCount: int
simplesList: List<SimpleProto>
simplesBuilderList: List<Builder>
descriptor: Descriptor
initialized: boolean

Operations
- Builder(BuilderParent):
- Builder():
+ buildPartial(): ProtoWithRepeatedFields
- buildPartial0(ProtoWithRepeatedFields): void
+ getSimplesOrBuilder(int): SimpleProtoOrBuilder
+ addSimples(int, SimpleProto): Builder
- ensureSimplesIsMutable(): void
+ addAllSimples(Iterable<SimpleProto>): Builder
+ clear(): Builder
+ addSimples(Builder): Builder
+ addSimples(SimpleProto): Builder
+ mergeFrom(ProtoWithRepeatedFields): Builder
+ addSimples(int, Builder): Builder
+ setSimples(int, Builder): Builder
+ hasName(): boolean
+ getNumbers(int): long
+ addSimplesBuilder(int): Builder
# internalGetFieldAccessorTable(): FieldAccessorTable
+ getSimplesBuilder(int): Builder
+ addSimplesBuilder(): Builder
- buildPartialRepeatedFields(ProtoWithRepeatedFields): void
+ addAllNumbers(Iterable<Long>): Builder
+ setNumbers(int, long): Builder
- ensureNumbersIsMutable(): void
+ mergeFrom(CodedInputStream, ExtensionRegistryLite): Builder
+ addNumbers(long): Builder
- internalGetSimplesFieldBuilder(): RepeatedFieldBuilder<SimpleProto, Builder, SimpleProtoOrBuilder>
+ clearNumbers(): Builder
+ mergeFrom(Message): Builder
+ build(): ProtoWithRepeatedFields
+ clearSimples(): Builder
+ getSimples(int): SimpleProto
+ clearName(): Builder
+ removeSimples(int): Builder
+ setSimples(int, SimpleProto): Builder

Builder

Attributes

descriptorForType: Descriptor
width: int
defaultInstanceForType: Data
dataBytes: ByteString
height: int
descriptor: Descriptor
data: String
initialized: boolean

Operations
- Builder():
- Builder(BuilderParent):
+ clearWidth(): Builder
+ hasData(): boolean
+ clearData(): Builder
+ mergeFrom(Data): Builder
+ clear(): Builder
+ mergeFrom(CodedInputStream, ExtensionRegistryLite): Builder
+ build(): Data
+ clearHeight(): Builder
+ hasHeight(): boolean
# internalGetFieldAccessorTable(): FieldAccessorTable
+ mergeFrom(Message): Builder
+ buildPartial(): Data
- buildPartial0(Data): void
+ hasWidth(): boolean

Builder

Attributes
- enumSerialization: EnumSerialization
- shouldUseJsonNameFieldOption: boolean
shouldUseJsonNameFieldOption: boolean
enumSerialization: EnumSerialization

Operations
- Builder(EnumSerialization, CaseFormat, CaseFormat):
+ setFieldNameSerializationFormat(CaseFormat, CaseFormat): Builder
+ build(): ProtoTypeAdapter
+ addSerializedEnumValueExtension(Extension<EnumValueOptions ...): Builder
+ addSerializedNameExtension(Extension<FieldOptions, String>): Builder

Builder

Builder

Attributes

descriptorForType: Descriptor
msgBytes: ByteString
defaultInstanceForType: SimpleProto
count: int
descriptor: Descriptor
msg: String
initialized: boolean

Operations
- Builder(BuilderParent):
- Builder():
+ buildPartial(): SimpleProto
+ clearMsg(): Builder
- buildPartial0(SimpleProto): void
+ hasMsg(): boolean
# internalGetFieldAccessorTable(): FieldAccessorTable
+ hasCount(): boolean
+ build(): SimpleProto
+ mergeFrom(CodedInputStream, ExtensionRegistryLite): Builder
+ mergeFrom(SimpleProto): Builder
+ clear(): Builder
+ clearCount(): Builder
+ mergeFrom(Message): Builder

Builder

Attributes

descriptorForType: Descriptor
anotherField: String
nameThatTestsCaseFormatList: ProtocolStringList
nameThatTestsCaseFormatCount: int
defaultInstanceForType: ProtoWithDifferentCaseFormat
descriptor: Descriptor
anotherFieldBytes: ByteString
initialized: boolean

Operations
- Builder():
- Builder(BuilderParent):
+ getNameThatTestsCaseFormat(int): String
+ setNameThatTestsCaseFormat(int, String): Builder
- ensureNameThatTestsCaseFormatIsMutable(): void
+ clearAnotherField(): Builder
+ build(): ProtoWithDifferentCaseFormat
+ addNameThatTestsCaseFormat(String): Builder
# internalGetFieldAccessorTable(): FieldAccessorTable
+ getNameThatTestsCaseFormatBytes(int): ByteString
+ buildPartial(): ProtoWithDifferentCaseFormat
+ addNameThatTestsCaseFormatBytes(ByteString): Builder
+ mergeFrom(CodedInputStream, ExtensionRegistryLite): Builder
+ clearNameThatTestsCaseFormat(): Builder
+ addAllNameThatTestsCaseFormat(Iterable<String>): Builder
+ mergeFrom(Message): Builder
+ mergeFrom(ProtoWithDifferentCaseFormat): Builder
+ hasAnotherField(): boolean
- buildPartial0(ProtoWithDifferentCaseFormat): void
+ clear(): Builder

Builder

Attributes

outerMessageBuilder: Builder
idBytes: ByteString
defaultInstanceForType: ProtoWithAnnotations
descriptor: Descriptor
outerMessage: OuterMessage
id: String
innerMessage1OrBuilder: InnerMessageOrBuilder
descriptorForType: Descriptor
innerMessage2OrBuilder: InnerMessageOrBuilder
innerMessage1Builder: Builder
innerMessage2Builder: Builder
innerMessage2: InnerMessage
innerMessage1: InnerMessage
outerMessageOrBuilder: OuterMessageOrBuilder
initialized: boolean

Operations
- Builder(BuilderParent):
- Builder():
+ setInnerMessage2(InnerMessage): Builder
+ mergeOuterMessage(OuterMessage): Builder
- buildPartial0(ProtoWithAnnotations): void
+ clearInnerMessage1(): Builder
+ hasInnerMessage2(): boolean
+ clear(): Builder
+ mergeFrom(CodedInputStream, ExtensionRegistryLite): Builder
- internalGetOuterMessageFieldBuilder(): SingleFieldBuilder<OuterMessage, Builder, OuterMessageOrBuilder>
+ clearId(): Builder
+ hasOuterMessage(): boolean
+ clearInnerMessage2(): Builder
+ hasInnerMessage1(): boolean
- internalGetInnerMessage2FieldBuilder(): SingleFieldBuilder<InnerMessage, Builder, InnerMessageOrBuilder>
+ mergeFrom(ProtoWithAnnotations): Builder
- maybeForceBuilderInitialization(): void
- internalGetInnerMessage1FieldBuilder(): SingleFieldBuilder<InnerMessage, Builder, InnerMessageOrBuilder>
+ hasId(): boolean
+ setOuterMessage(OuterMessage): Builder
+ buildPartial(): ProtoWithAnnotations
+ mergeInnerMessage1(InnerMessage): Builder
# internalGetFieldAccessorTable(): FieldAccessorTable
+ build(): ProtoWithAnnotations
+ mergeInnerMessage2(InnerMessage): Builder
+ mergeFrom(Message): Builder
+ setInnerMessage1(InnerMessage): Builder
+ clearOuterMessage(): Builder

Builder

Attributes

descriptorForType: Descriptor
neitherBytes: ByteString
annotationOnly: String
both: String
bothBytes: ByteString
jsonNameOnlyBytes: ByteString
defaultInstanceForType: ProtoWithAnnotationsAndJsonNames
jsonNameOnly: String
descriptor: Descriptor
annotationOnlyBytes: ByteString
initialized: boolean
neither: String
Operations
- Builder():
- Builder(BuilderParent):
+ clearAnnotationOnly(): Builder
+ buildPartial(): ProtoWithAnnotationsAndJsonNames
+ hasAnnotationOnly(): boolean
+ mergeFrom(Message): Builder
+ mergeFrom(CodedInputStream, ExtensionRegistryLite): Builder
# internalGetFieldAccessorTable(): FieldAccessorTable
+ clearJsonNameOnly(): Builder
+ hasNeither(): boolean
+ clearNeither(): Builder
+ hasBoth(): boolean
- buildPartial0(ProtoWithAnnotationsAndJsonNames): void
+ mergeFrom(ProtoWithAnnotationsAndJsonNames): Builder
+ build(): ProtoWithAnnotationsAndJsonNames
+ clear(): Builder
+ clearBoth(): Builder
+ hasJsonNameOnly(): boolean

BuiltInOverwriting

Attributes

Operations
- BuiltInOverwriting():

C

Attributes

Operations
- C():

CEO

Attributes

Operations
~ CEO():

Car

Attributes

Operations
~ Car(String, int):
~ Car():
+ hashCode(): int
+ equals(Object): boolean

Circle

Attributes

Operations
~ Circle(int):

ClassExtendingJdkClass

Attributes

Operations
- ClassExtendingJdkClass():
+ read(char[], int, int): int
+ close(): void

ClassOverridingEquals

Attributes

expectedJson: String
Operations
+ ClassOverridingEquals():
+ equals(Object): boolean
+ hashCode(): int

ClassSatisfyingBounds

Attributes

Operations
~ ClassSatisfyingBounds():

ClassWithAMap

Attributes

Operations
- ClassWithAMap():

ClassWithArray

Attributes

Operations
+ ClassWithArray(Object[]):
+ ClassWithArray():

ClassWithBaseArray

Attributes

Operations
- ClassWithBaseArray():

ClassWithBaseArrayField

Attributes

Operations
+ ClassWithBaseArrayField(Base[]):

ClassWithBaseCollectionField

Attributes

Operations
+ ClassWithBaseCollectionField(Collection<Base>):

ClassWithBaseField

Attributes

Operations
+ ClassWithBaseField(Base):

ClassWithBigDecimal

Attributes

expectedJson: String
Operations
~ ClassWithBigDecimal(String):

ClassWithBigInteger

Attributes

expectedJson: String
Operations
~ ClassWithBigInteger(String):

ClassWithCollectionField

Attributes

Operations
- ClassWithCollectionField():

ClassWithCustomTypeConverter

Attributes
- value: int
- bag: BagOfPrimitives
bag: BagOfPrimitives
expectedJson: String
value: int

Operations
+ ClassWithCustomTypeConverter(BagOfPrimitives, int):
+ ClassWithCustomTypeConverter():
+ ClassWithCustomTypeConverter(int):

ClassWithEnumFields

Attributes

expectedJson: String
Operations
- ClassWithEnumFields():

ClassWithExposedField

Attributes

Operations
~ ClassWithExposedField():
~ ClassWithExposedField(String):

ClassWithExposedFields

Attributes

expectedJson: String
Operations
+ ClassWithExposedFields(Integer, Integer):
+ ClassWithExposedFields(Integer, Integer, long, double, char ...):

ClassWithField

Attributes

Operations
~ ClassWithField():
+ ClassWithField(String):

ClassWithHasArgsConstructor

Attributes

Operations
+ ClassWithHasArgsConstructor(int):

ClassWithInitializedMembers

Attributes

Operations
+ ClassWithInitializedMembers():

ClassWithInterfaceField

Attributes

Operations
+ ClassWithInterfaceField(SomeInterface):

ClassWithJsonAdapterAnnotation

Attributes

Operations
+ ClassWithJsonAdapterAnnotation():
+ ClassWithJsonAdapterAnnotation(int, int, int, int):
+ toString(): String

ClassWithList

Attributes

Operations
~ ClassWithList():
~ ClassWithList(String):

ClassWithListOfObjects

Attributes

Operations
~ ClassWithListOfObjects(String):
~ ClassWithListOfObjects():

ClassWithMap

Attributes

Operations
- ClassWithMap():

ClassWithMembers

Attributes

Operations
- ClassWithMembers():

ClassWithNamedFields

Attributes

Operations
+ ClassWithNamedFields(int):

ClassWithNoArgsConstructor

Attributes

Operations
+ ClassWithNoArgsConstructor():

ClassWithNoExposedFields

Attributes

Operations
- ClassWithNoExposedFields():

ClassWithNoFields

Attributes

Operations
+ ClassWithNoFields():
+ equals(Object): boolean

ClassWithNullWrappedPrimitive

Attributes

Operations
- ClassWithNullWrappedPrimitive():

ClassWithObjects

Attributes

Operations
+ ClassWithObjects():
+ ClassWithObjects(BagOfPrimitives):

ClassWithObjectsSerializer

Attributes

Operations
- ClassWithObjectsSerializer():
+ serialize(ClassWithObjects, Type, JsonSerializationContext): JsonElement

ClassWithPrivateField

Attributes

Operations
- ClassWithPrivateField():

ClassWithPrivateNoArgsConstructor

Attributes

Operations
- ClassWithPrivateNoArgsConstructor():

ClassWithPrivateNoArgsConstructor

Attributes

Operations
- ClassWithPrivateNoArgsConstructor():

ClassWithSerializedName

Attributes

Operations
+ ClassWithSerializedName(int):

ClassWithSerializedNameFields

Attributes

expectedJson: String
Operations
+ ClassWithSerializedNameFields(int, int):
+ ClassWithSerializedNameFields():

ClassWithStaticField

Attributes

Operations
- ClassWithStaticField():

ClassWithStaticFinalField

Attributes

Operations
~ ClassWithStaticFinalField():

ClassWithSubInterfacesOfCollection

Attributes

expectedJson: String
Operations
+ ClassWithSubInterfacesOfCollection(List<Integer>, Queue< ...):
~ sortedSetContains(char[]): boolean
- append(StringBuilder, Collection<?>): StringBuilder
~ setContains(float[]): boolean
~ listContains(int[]): boolean
~ queueContains(long[]): boolean

ClassWithThrowingConstructor

Attributes

Operations
+ ClassWithThrowingConstructor():

ClassWithTransientFields<T>

Attributes

expectedJson: String
Operations
+ ClassWithTransientFields(long):
+ ClassWithTransientFields():

ClassWithUnreferencedHasArgsConstructor

Attributes

Operations
+ ClassWithUnreferencedHasArgsConstructor(int):

ClassWithUnreferencedNoArgsConstructor

Attributes

Operations
+ ClassWithUnreferencedNoArgsConstructor():

ClassWithUrlField

Attributes

Operations
- ClassWithUrlField():

ClassWithVersionAnnotations

Attributes

Operations
+ ClassWithVersionAnnotations():

ClassWithoutNoArgsConstructor

Attributes

Operations
+ ClassWithoutNoArgsConstructor(String):

ClassWithoutNoArgsConstructor

Attributes

Operations
+ ClassWithoutNoArgsConstructor(String):

CollectionEntry

Attributes

Operations
- CollectionEntry():
~ CollectionEntry(String, String):

CollectionTest

Attributes

Operations
+ CollectionTest():
+ testRawCollectionOfIntegersSerialization(): void
+ testWildcardPrimitiveCollectionDeserilaization(): void
+ testLinkedListSerialization(): void
+ testNullsInListSerialization(): void
+ testNullsInListDeserialization(): void
+ testFieldIsArrayList(): void
+ testQueueDeserialization(): void
+ testRawCollectionOfBagOfPrimitivesNotAllowed(): void
+ testTopLevelCollectionOfIntegersSerialization(): void
+ testIssue1107(): void
+ testTopLevelCollectionOfIntegersDeserialization(): void
+ testStack(): void
+ testCollectionOfStringsDeserialization(): void
+ testSetSerialization(): void
- toIntArray(Collection<?>): int[]
+ testUserCollectionTypeAdapter(): void
+ testSetDeserialization(): void
+ testCollectionOfStringsSerialization(): void
+ testWildcardPrimitiveCollectionSerilaization(): void
+ testLinkedListDeserialization(): void
+ setUp(): void
+ testRawCollectionDeserializationNotAllowed(): void
+ testPriorityQueue(): void
+ testCollectionOfObjectWithNullSerialization(): void
+ testObjectCollectionSerialization(): void
+ testCollectionWithoutNoArgsConstructor(): void
+ testWildcardCollectionField(): void
+ testTopLevelListOfIntegerCollectionsDeserialization(): void
+ testCollectionOfObjectSerialization(): void
+ testQueueSerialization(): void
+ testCollectionOfBagOfPrimitivesSerialization(): void
+ testVector(): void

CollectionWithoutNoArgsConstructor<E>

Attributes

Operations
+ CollectionWithoutNoArgsConstructor(int):
+ add(E): boolean
+ size(): int
+ iterator(): Iterator<E>

CollectionsDeserializationBenchmark

Attributes

Operations
+ CollectionsDeserializationBenchmark():
+ main(String[]): void
+ timeCollectionsDefault(int): void
~ setUp(): void
+ timeCollectionsReflectionStreaming(int): void
+ timeCollectionsStreaming(int): void

Color

Attributes

Operations
- Color(String, int):
+ values(): Color[]
+ valueOf(String): Color

CommentsTest

Attributes

Operations
+ CommentsTest():
+ testParseComments(): void

Company

Attributes

Operations
~ Company():

Computer

Attributes

Operations
~ Computer(User):

Computer

Attributes

Operations
~ Computer(User, User, User):

Computer2

Attributes

Operations
~ Computer2(User2):

Computer2

Attributes

Operations
~ Computer2(User):

Concrete

Attributes

Operations
~ Concrete():

ConcreteClass

Attributes

Operations
+ ConcreteClass():

ConstructorConstructorTest

Attributes

Operations
+ ConstructorConstructorTest():
+ testGet_AbstractClassNoArgConstructor(): void
+ testCustomCollectionCreation(): void
+ testGet_Interface(): void
+ testStringMapCreation(): void
+ testCustomMapInterfaceCreation(): void
+ testCustomMapCreation(): void
+ testCustomCollectionInterfaceCreation(): void

Container

Attributes

Operations
~ Container(String, int):

Content

Attributes

Operations
~ Content():
+ toString(): String

Course<T>

Attributes
~ students: List<Student>
students: List<Student>
id: Id<Course<T>>

Operations
- Course():
+ Course(Id<Course<T>>, int, Assignment<T>, List<Student>):

CrazyLongTypeAdapter

Attributes

Operations
+ CrazyLongTypeAdapter():
+ serialize(Long, Type, JsonSerializationContext): JsonElement
+ deserialize(JsonElement, Type, JsonDeserializationContext): Long

CreditCard

Attributes

Operations
~ CreditCard(String, int):

CurrentWrite

Attributes

- chars: char[]
chars: char[]
Operations
- CurrentWrite():
+ length(): int
+ charAt(int): char
+ toString(): String
+ subSequence(int, int): CharSequence

CustomClass1

Attributes

Operations
- CustomClass1():

CustomClass1

Attributes

Operations
~ CustomClass1():

CustomClass2

Attributes

Operations
- CustomClass2():

CustomClass2

Attributes

Operations
~ CustomClass2():

CustomClass3

Attributes

Operations
+ CustomClass3(String):
+ CustomClass3():

CustomClass3

Attributes

Operations
+ CustomClass3():
+ CustomClass3(String):

CustomCollectionInterface

<<interface>>

Attributes

Operations

CustomConcurrentMap<K, V>

Attributes

Operations
~ CustomConcurrentMap(Void):

CustomConcurrentNavigableMap<K, V>

Attributes

Operations
~ CustomConcurrentNavigableMap(Void):

CustomDeserializerTest

Attributes

+ ...): void
Operations
+ CustomDeserializerTest():
+ testJsonTypeFieldBasedDeserialization(): void
+ testDefaultConstructorNotCalledOnField(): void
+ testCustomDeserializerReturnsNull(): void
+ setUp(): void
+ testCustomDeserializerReturnsNullForArrayElements(): void
+ testCustomDeserializerReturnsNullForTopLevelObject(): void
+ testDefaultConstructorNotCalledOnObject(): void

CustomEnumMap<K, V>

Attributes

Operations
~ CustomEnumMap(Void):

CustomLinkedHashMap<K, V>

Attributes

Operations
~ CustomLinkedHashMap(Void):

CustomList<E>

Attributes

Operations
~ CustomList(Void):

CustomListInterface

<<interface>>

Attributes

Operations

CustomMapInterface

<<interface>>

Attributes

Operations

CustomQueue<E>

Attributes

Operations
~ CustomQueue(Void):

CustomSet<E>

Attributes

Operations
~ CustomSet(Void):

CustomSetInterface

<<interface>>

Attributes

Operations

CustomSortedMap<K, V>

Attributes

Operations
~ CustomSortedMap(Void):

CustomSortedSet<E>

Attributes

Operations
~ CustomSortedSet(Void):

CustomToString

Attributes

Operations
- CustomToString():
+ valueOf(String): CustomToString
+ toString(): String
+ values(): CustomToString[]

CustomTypeAdaptersTest

Attributes

+ ...): void
+ testCustomAdapterInvokedForCollectionElementDeserialization ...): void
+ ...): void
Operations
+ CustomTypeAdaptersTest():
+ testCustomDeserializers(): void
+ testCustomSerializerInvokedForPrimitives(): void
+ testCustomAdapterInvokedForCollectionElementSerialization(): void
+ testCustomAdapterInvokedForMapElementSerialization(): void
+ testCustomNestedDeserializers(): void
- createGsonObjectWithFooTypeAdapter(): Gson
+ testCustomNestedSerializers(): void
+ setUp(): void
+ testCustomSerializers(): void
+ testCustomTypeAdapterDoesNotAppliesToSubClasses(): void
+ testCustomByteArraySerializer(): void
+ testEnsureCustomSerializerNotInvokedForNullValues(): void
+ testCustomAdapterInvokedForMapElementSerializationWithType(...): void
+ testCustomAdapterInvokedForMapElementDeserialization(): void
+ disable_testCustomDeserializersOfSelf(): void
+ testRegisterHierarchyAdapterForDate(): void
+ testCustomByteArrayDeserializerAndInstanceCreator(): void
+ testEnsureCustomDeserializerNotInvokedForNullValues(): void
+ testCustomDeserializerInvokedForPrimitives(): void
+ disable_testCustomSerializersOfSelf(): void

Data

Attributes

- DEFAULT_INSTANCE: Data
serializedSize: int
width: int
parserForType: Parser<Data>
defaultInstanceForType: Data
dataBytes: ByteString
height: int
DEFAULT_INSTANCE: Data
descriptor: Descriptor
data: String
initialized: boolean

Operations
- Data():
- Data(Builder<?>):
+ parseFrom(ByteString): Data
# internalGetFieldAccessorTable(): FieldAccessorTable
+ hasHeight(): boolean
+ parseFrom(ByteString, ExtensionRegistryLite): Data
+ parseFrom(InputStream): Data
+ equals(Object): boolean
+ parseFrom(ByteBuffer, ExtensionRegistryLite): Data
+ newBuilderForType(): Builder
+ parseDelimitedFrom(InputStream, ExtensionRegistryLite): Data
+ parseFrom(byte[]): Data
+ parseFrom(CodedInputStream, ExtensionRegistryLite): Data
+ parseFrom(InputStream, ExtensionRegistryLite): Data
+ parseDelimitedFrom(InputStream): Data
# newBuilderForType(BuilderParent): Builder
+ hashCode(): int
+ parseFrom(CodedInputStream): Data
+ writeTo(CodedOutputStream): void
+ newBuilder(Data): Builder
+ parseFrom(byte[], ExtensionRegistryLite): Data
+ parseFrom(ByteBuffer): Data
+ parser(): Parser<Data>
+ toBuilder(): Builder
+ hasData(): boolean
+ newBuilder(): Builder
+ hasWidth(): boolean

DataHolder

Attributes

Operations
+ DataHolder(String):

DataHolder

Attributes

- data: String
data: String
Operations
+ DataHolder(String):
- DataHolder():

DataHolderDeserializer

Attributes

Operations
- DataHolderDeserializer():
+ deserialize(JsonElement, Type, JsonDeserializationContext): DataHolder

DataHolderDeserializer

Attributes

Operations
- DataHolderDeserializer():
+ deserialize(JsonElement, Type, JsonDeserializationContext): DataHolder

DataHolderSerializer

Attributes

Operations
- DataHolderSerializer():
+ serialize(DataHolder, Type, JsonSerializationContext): JsonElement

DataHolderWrapper

Attributes

Operations
+ DataHolderWrapper(DataHolder):

DataHolderWrapper

Attributes

- wrappedData: DataHolder
wrappedData: DataHolder
Operations
- DataHolderWrapper():
+ DataHolderWrapper(DataHolder):

DataOrBuilder

<<interface>>

Attributes

dataBytes: ByteString
height: int
width: int
data: String
Operations
+ hasData(): boolean
+ hasWidth(): boolean
+ hasHeight(): boolean

DateParserTest

Attributes

Operations
+ DateParserTest():
+ testParseComplete(): void
+ testParseNullDate(): void
+ testParseWithTimeZoneOffset(): void
+ testParseInvalidTimezone(): void
+ testParseWithoutMillis(): void
+ testParseInvalidFormat(): void

DateTypeAdapter

Attributes

Operations
- DateTypeAdapter():
+ serialize(Date, Type, JsonSerializationContext): JsonElement
+ deserialize(JsonElement, Type, JsonDeserializationContext): Date

DefaultDateTypeAdapterTest

Attributes

Operations
+ DefaultDateTypeAdapterTest():
+ testParsingDatesFormattedWithUsLocale(): void
+ testFormattingInFr(): void
+ testParsingDatesFormattedWithSystemLocale(): void
+ testDateDeserializationISO8601(): void
+ testUnexpectedToken(): void
- dateAdapter(TypeAdapterFactory): TypeAdapter<Date>
+ testNullValue(): void
+ testFormatUsesDefaultTimezone(): void
+ testGsonDateFormat(): void
- assertFormatted(String, TypeAdapterFactory): void
+ testFormattingInEnUs(): void
- assertFormattingAlwaysEmitsUsLocale(Locale): void
+ testDatePattern(): void
- assertParsed(String, TypeAdapterFactory): void
+ testInvalidDatePattern(): void
- toLiteral(String): String

DefaultInetAddressTypeAdapterTest

Attributes

Operations
+ DefaultInetAddressTypeAdapterTest():
+ testInetAddressSerializationAndDeserialization(): void
+ setUp(): void

DefaultMapJsonSerializerTest

Attributes

Operations
+ DefaultMapJsonSerializerTest():
+ testEmptyMapNoTypeSerialization(): void
+ testNonEmptyMapSerialization(): void
+ testEmptyMapSerialization(): void

DefaultTypeAdaptersTest

Attributes

Operations
+ DefaultTypeAdaptersTest():
+ testNullSerialization(): void
+ testStringBufferDeserialization(): void
+ testUrlNullSerialization(): void
+ testJsonArraySerialization(): void
+ testBadValueForBigDecimalDeserialization(): void
+ testUrlNullDeserialization(): void
+ testLocaleSerializationWithLanguageCountryVariant(): void
+ testUriDeserialization(): void
+ testDefaultGregorianCalendarDeserialization(): void
+ testLocaleDeserializationWithLanguageCountry(): void
+ testDefaultDateDeserialization(): void
+ testStringBufferSerialization(): void
+ testUrlSerialization(): void
+ testDateSerializationInCollection(): void
+ assertEqualsTime(Date, int, int, int): void
+ testDefaultGregorianCalendarSerialization(): void
+ testDateSerializationWithStyle(): void
+ testDefaultCalendarDeserialization(): void
+ testBigDecimalFieldSerialization(): void
+ testDateSerializationWithPattern(): void
+ testClassSerialization(): void
+ testLocaleDeserializationWithLanguageCountryVariant(): void
+ testOverrideBigDecimalTypeAdapter(): void
+ testDefaultDateDeserializationUsingBuilder(): void
+ testSetSerialization(): void
+ testBigIntegerFieldSerialization(): void
+ testLocaleDeserializationWithLanguage(): void
+ testTreeSetSerialization(): void
+ testUrlDeserialization(): void
+ testJsonArrayDeserialization(): void
+ testPropertiesDeserialization(): void
+ testLocaleSerializationWithLanguage(): void
+ testJsonPrimitiveDeserialization(): void
+ setUp(): void
+ tearDown(): void
+ testDateDeserializationWithPattern(): void
+ testTreeSetDeserialization(): void
+ testDefaultDateSerializationUsingBuilder(): void
+ testLocaleSerializationWithLanguageCountry(): void
+ testUuidSerialization(): void
+ testStringBuilderSerialization(): void
+ testBigDecimalFieldDeserialization(): void
+ testJsonNullSerialization(): void
+ testDateSerializationWithDateStyle(): void
+ testJsonElementTypeMismatch(): void
+ testBitSetDeserialization(): void
+ testDateStyleOverwritesPattern(): void
+ testUuidDeserialization(): void
+ testClassDeserialization(): void
+ testJsonObjectDeserialization(): void
+ testJsonObjectSerialization(): void
+ testBigIntegerFieldDeserialization(): void
+ testBitSetSerialization(): void
+ testDefaultDateSerialization(): void
+ assertEqualsDate(Date, int, int, int): void
+ testDefaultCalendarSerialization(): void
+ testUriSerialization(): void
- testNullSerializationAndDeserialization(Class<?>): void
+ testNullSerializationAndDeserialization(Gson, Class<?>): void
+ testDateSerializationWithPatternNotOverridenByTypeAdapter(): void
+ testOverrideBigIntegerTypeAdapter(): void
+ testJsonPrimitiveSerialization(): void
+ testNullJsonElementSerialization(): void
+ testStringBuilderDeserialization(): void
+ testJsonNullDeserialization(): void
+ testPropertiesSerialization(): void

DelegatingAdapterFactory

Attributes

Operations
~ DelegatingAdapterFactory():
+ create(Gson, TypeToken<T>): TypeAdapter<T>

DelegatingAndOverwriting

Attributes

Operations
- DelegatingAndOverwriting():

Derived

Attributes

Operations
- Derived():

Derived1

Attributes

Operations

~ Derived1(): Derived2

Attributes

Operations
~ Derived2():

Deserializer

Attributes

Operations
~ Deserializer():
+ deserialize(JsonElement, Type, JsonDeserializationContext): DummyClass

Deserializer

Attributes

Operations
~ Deserializer():
+ deserialize(JsonElement, Type, JsonDeserializationContext): WithJsonDeserializer

Deserializer

Attributes

Operations
~ Deserializer():
+ deserialize(JsonElement, Type, JsonDeserializationContext): List<Integer>

Document

Attributes

Operations
- Document(TypeToken<?>, TypeReference<?>):
+ values(): Document[]
+ valueOf(String): Document

DummyClass

Attributes

Operations
~ DummyClass(String):
+ toString(): String

DummyClass

Attributes

Operations
- DummyClass():

DummyTypeAdapterFactory

Attributes

Operations
- DummyTypeAdapterFactory():
+ create(Gson, TypeToken<T>): TypeAdapter<T>

Employee

Attributes

Operations
~ Employee(String, long):
~ Employee():

EmployeeAdapter

Attributes

Operations
~ EmployeeAdapter():
+ deserialize(JsonElement, Type, JsonDeserializationContext): Employee
+ serialize(Employee, Type, JsonSerializationContext): JsonElement

Entry

Attributes

Operations
~ Entry(int):

EntrySet

Attributes

Operations
~ EntrySet():
+ contains(Object): boolean
+ remove(Object): boolean
+ iterator(): Iterator<Entry<K, V>>
+ clear(): void
+ size(): int

EnumClass

Attributes

Operations
- EnumClass():
+ valueOf(String): EnumClass
+ values(): EnumClass[]

EnumClassWithSerializedName

Attributes

Operations
- EnumClassWithSerializedName():
+ values(): EnumClassWithSerializedName[]
+ valueOf(String): EnumClassWithSerializedName

EnumSerialization

Attributes

Operations
- EnumSerialization():
+ values(): EnumSerialization[]
+ valueOf(String): EnumSerialization

EnumTest

Attributes

Operations
+ EnumTest():
+ testEnumMap(): void
+ testEnumSubclassWithRegisteredTypeAdapter(): void
+ testEnumToStringRead(): void
+ testTopLevelEnumDeserialization(): void
+ setUp(): void
+ testEnumClassWithFields(): void
+ testEnumSubclassAsParameterizedType(): void
+ testEnumSubclass(): void
+ testEnumCaseMapping(): void
+ testTopLevelEnumSerialization(): void
+ testCollectionOfEnumsDeserialization(): void
+ testJdkEnum(): void
+ testClassWithEnumFieldDeserialization(): void
+ testEnumToStringReadInterchanged(): void
+ testClassWithEnumFieldSerialization(): void
+ testEnumSet(): void
+ testCollectionOfEnumsSerialization(): void

EnumWithObfuscatedTest

Attributes

Operations
+ EnumWithObfuscatedTest():
+ setUp(): void
+ testEnumClassWithObfuscated(): void

EscapingTest

Attributes

Operations
+ EscapingTest():
+ testEscapeAllHtmlCharacters(): void
+ testGsonDoubleDeserialization(): void
+ testEscapingObjectFields(): void
+ testEscapingQuotesInStringArray(): void
+ testGsonAcceptsEscapedAndNonEscapedJsonDeserialization(): void
+ setUp(): void

Event

Attributes

Operations
- Event(String, String):
+ toString(): String

ExceptionHolder

Attributes

Operations
+ ExceptionHolder(String, String):
- ExceptionHolder():

ExceptionTypeAdapter

Attributes

Operations
- ExceptionTypeAdapter():
+ serialize(AtomicLong, Type, JsonSerializationContext): JsonElement
+ deserialize(JsonElement, Type, JsonDeserializationContext): AtomicLong

ExclusionStrategy

<<interface>>

Attributes

Operations
+ shouldSkipField(FieldAttributes): boolean
+ shouldSkipClass(Class<?>): boolean

ExclusionStrategyFunctionalTest

Attributes

+ ...): void
+ ...): void
+ ...): void
+ ...): void
Operations
+ ExclusionStrategyFunctionalTest():
- createGson(ExclusionStrategy, boolean): Gson
+ testExclusionStrategyWithMode(): void
+ testExcludeTopLevelClassDeserialization(): void
+ setUp(): void
+ testExclusionStrategyDeserialization(): void
+ testExclusionStrategySerialization(): void
+ testExcludeTopLevelClassSerialization(): void

ExportedPackagesTest

Attributes

Operations
+ ExportedPackagesTest():
+ testInaccessiblePackage(): void
+ testReflectionInternalField(): void
+ testMainPackage(): void
+ testReflectPackage(): void
+ testAnnotationsPackage(): void
+ testStreamPackage(): void

Expose

Attributes

Operations
+ serialize(): boolean
+ deserialize(): boolean

ExposeFieldsTest

Attributes

Operations
+ ExposeFieldsTest():
+ testArrayWithOneNullExposeFieldObjectSerialization(): void
+ testNullExposeFieldSerialization(): void
+ testNoExposedFieldSerialization(): void
+ testExposeAnnotationDeserialization(): void
+ testExposeAnnotationSerialization(): void
+ setUp(): void
+ testExposedInterfaceFieldDeserialization(): void
+ testNoExposedFieldDeserialization(): void
+ testExposedInterfaceFieldSerialization(): void

ExtendingClassWithPrivateField

Attributes

Operations
- ExtendingClassWithPrivateField():

Factory

Attributes

Operations
~ Factory():
+ create(Gson, TypeToken<T>): TypeAdapter<T>

Factory

Attributes

Operations
~ Factory():
+ create(Gson, TypeToken<T>): TypeAdapter<T>

Factory

Attributes

Operations
~ Factory():
+ create(Gson, TypeToken<T>): TypeAdapter<T>

Factory

Attributes

Operations
~ Factory():
+ create(Gson, TypeToken<T>): TypeAdapter<T>

Feed

Attributes

Operations
~ Feed():
+ toString(): String

Field<T>

<<interface>>

Attributes

Operations

FieldAttributes

Attributes

name: String
annotations: Collection<Annotation>
declaringClass: Class<?>
declaredType: Type
declaredClass: Class<?>

Operations
+ FieldAttributes(Field):
+ hasModifier(int): boolean
+ getAnnotation(Class<T>): T
+ toString(): String

FieldAttributesTest

Attributes

Operations
+ FieldAttributesTest():
+ testDeclaringClass(): void
+ testNullField(): void
+ testName(): void
+ setUp(): void
+ testModifiers(): void
+ testDeclaredTypeAndClass(): void

FieldExclusionTest

Attributes

Operations
+ FieldExclusionTest():
+ setUp(): void
+ testInnerClassExclusion(): void
+ testDefaultNestedStaticClassIncluded(): void
+ testDefaultInnerClassExclusion(): void

FieldNamingPolicyTest

Attributes

Operations
+ FieldNamingPolicyTest():
+ testSeparateCamelCase(): void
+ testUpperCasingLocaleIndependent(): void
+ testUpperCaseFirstLetter(): void
+ testLowerCasingLocaleIndependent(): void

FilterResult

Attributes

Operations
- FilterResult():
+ values(): FilterResult[]
+ valueOf(String): FilterResult

Foo

Attributes

Operations
+ Foo():
+ Foo(int, long):

Foo

Attributes

Operations
- Foo():

Foo

Attributes

Operations
~ Foo(int):

Foo

Attributes

Operations

Foo1<A>

Attributes

Operations
- Foo1():

Foo2<B>

Attributes

Operations
- Foo2():

FooTypeAdapter

Attributes

Operations
+ FooTypeAdapter():
+ serialize(Foo, Type, JsonSerializationContext): JsonElement
+ deserialize(JsonElement, Type, JsonDeserializationContext): Foo

FormattingStyleTest

Attributes

Operations
+ FormattingStyleTest():
- buildExpected(String, String, boolean): String
+ testDefault(): void
+ testFormat(): void
+ testStyleValidations(): void
+ testFormatCompact(): void
- createInput(): Map<String, List<Integer>>
+ testFormatPretty(): void
- toJson(Object, FormattingStyle): String
+ testCompactToPretty(): void
+ testPrettyToCompact(): void
+ testVariousCombinationsParse(): void
+ testFormatPrettySingleLine(): void

Gadget

Attributes

Operations
~ Gadget(Part):

GadgetWithOptionalPart

Attributes

Operations
- GadgetWithOptionalPart(Part):

GadgetWithPrimitivePart

Attributes

Operations
- GadgetWithPrimitivePart(long):

GadgetWithTwoParts

Attributes

Operations
~ GadgetWithTwoParts(Part, Part):

Gender

Attributes

Operations
- Gender():
+ valueOf(String): Gender
+ values(): Gender[]

Gender

Attributes

Operations
- Gender():
+ values(): Gender[]
+ valueOf(String): Gender

GenericArrayTypeTest

Attributes

Operations
+ GenericArrayTypeTest():
+ testNotEquals(): void
+ testOurTypeFunctionality(): void
+ setUp(): void

GenericWithBound<T>

Attributes

Operations
~ GenericWithBound():

GenericWithMultiBound<T>

Attributes

Operations
~ GenericWithMultiBound():

GetAdapterDelegation

Attributes

Operations
~ GetAdapterDelegation(String):

Gizmo

Attributes

Operations
~ Gizmo(Part):

Gizmo2

Attributes

Operations
~ Gizmo2(List<Part>):

Gizmo2PartTypeAdapterFactory

Attributes

Operations
- Gizmo2PartTypeAdapterFactory():
+ create(Gson, TypeToken<T>): TypeAdapter<T>
GizmoPartTypeAdapterFactory

Attributes

Operations
- GizmoPartTypeAdapterFactory():
+ create(Gson, TypeToken<T>): TypeAdapter<T>

GraphAdapterFactory

Attributes

graph: Graph
Operations
+ GraphAdapterFactory(Map<Type, InstanceCreator<?>>):
+ create(Gson, TypeToken<T>): TypeAdapter<T>
+ clearGraph(): void
+ createInstance(Type): Object

GsonBindParser

Attributes

Operations
- GsonBindParser():
+ parse(char[], Document): void

GsonBuildConfig

Attributes

Operations
- GsonBuildConfig():

GsonBuildConfigTest

Attributes

Operations
+ GsonBuildConfigTest():
+ testEnsureGsonBuildConfigGetsUpdatedToMavenVersion(): void

GsonBuilder

Attributes

- objectToNumberStrategy: ToNumberStrategy
- fieldNamingPolicy: FieldNamingStrategy
- numberToNumberStrategy: ToNumberStrategy
- formattingStyle: FormattingStyle
- longSerializationPolicy: LongSerializationPolicy
- strictness: Strictness
exclusionStrategies: ExclusionStrategy[]
fieldNamingPolicy: FieldNamingPolicy
formattingStyle: FormattingStyle
dateFormat: int
objectToNumberStrategy: ToNumberStrategy
longSerializationPolicy: LongSerializationPolicy
fieldNamingStrategy: FieldNamingStrategy
strictness: Strictness
numberToNumberStrategy: ToNumberStrategy
version: double

Operations
~ GsonBuilder(Gson):
+ GsonBuilder():
+ disableHtmlEscaping(): GsonBuilder
+ enableComplexMapKeySerialization(): GsonBuilder
+ registerTypeAdapter(Type, Object): GsonBuilder
+ excludeFieldsWithModifiers(int[]): GsonBuilder
- hasNonOverridableAdapter(Type): boolean
+ addSerializationExclusionStrategy(ExclusionStrategy): GsonBuilder
- addTypeAdaptersForDate(String, int, int, List< ...): void
+ setPrettyPrinting(): GsonBuilder
+ setLenient(): GsonBuilder
+ registerTypeAdapterFactory(TypeAdapterFactory): GsonBuilder
+ create(): Gson
+ disableJdkUnsafe(): GsonBuilder
+ addReflectionAccessFilter(ReflectionAccessFilter): GsonBuilder
+ serializeNulls(): GsonBuilder
+ serializeSpecialFloatingPointValues(): GsonBuilder
+ addDeserializationExclusionStrategy(ExclusionStrategy): GsonBuilder
+ setDateFormat(String): GsonBuilder
+ disableInnerClassSerialization(): GsonBuilder
+ excludeFieldsWithoutExposeAnnotation(): GsonBuilder
- checkDateFormatStyle(int): int
+ registerTypeHierarchyAdapter(Class<?>, Object): GsonBuilder
+ setDateFormat(int, int): GsonBuilder
+ generateNonExecutableJson(): GsonBuilder

GsonBuilderTest

Attributes

Operations
+ GsonBuilderTest():
+ testSetDateFormatNullPattern(): void
+ testDefaultStrictness(): void
+ testSetDateFormatWithInvalidPattern(): void
+ testModificationAfterCreate(): void
+ testTransientFieldExclusion(): void
+ testSetDateFormatEmptyPattern(): void
+ testSetDateFormatValidStyle(): void
+ testSetDateFormatWithValidPattern(): void
+ testRegisterTypeHierarchyAdapterJsonElements_Allowed(): void
+ testRegisterTypeAdapterForCoreType(): void
+ testCreatingMoreThanOnce(): void
+ testRegisterTypeHierarchyAdapterJsonElements(): void
+ testSetLenient(): void
+ testSetStrictness(): void
+ testRegisterTypeAdapterForJsonElements(): void
+ testExcludeFieldsWithModifiers(): void
- assertCustomGson(Gson): void
+ testDisableJdkUnsafe(): void
+ testSetDateFormatInvalidStyle(): void
+ testRegisterTypeAdapterForObjectAndJsonElements(): void
- assertDefaultGson(Gson): void
+ testSetVersionInvalid(): void

GsonDomParser

Attributes

Operations
- GsonDomParser():
+ parse(char[], Document): void

GsonPreconditions

Attributes

Operations
- GsonPreconditions():
+ checkArgument(boolean): void
+ checkArgument(boolean, String): void
+ checkNotNull(T): T
+ checkNotNull(T, String): T

GsonSkipParser

Attributes

Operations
- GsonSkipParser():
+ parse(char[], Document): void

GsonStreamParser

Attributes

Operations
- GsonStreamParser():
+ parse(char[], Document): void
- readToken(JsonReader): void

GsonTest

Attributes

Operations
+ GsonTest():
+ testNewJsonReader_Custom(): void
+ testNewJsonWriter_Custom(): void
+ testGetDelegateAdapter(): void
+ testDefaultGsonNewBuilderModification(): void
+ testFromJson_WrongResultType(): void
+ testGetAdapter_Concurrency(): void
+ testGetAdapter_FutureAdapterConcurrency(): void
+ testNewJsonReader_Default(): void
- assertDefaultGson(Gson): void
+ testOverridesDefaultExcluder(): void
- assertCustomGson(Gson): void
+ testStrictnessDefault(): void
+ testClonedTypeAdapterFactoryListsAreIndependent(): void
+ testNewJsonWriter_Default(): void
+ testNewBuilderModification(): void
+ testGetAdapter_Null(): void

GsonTypeAdapterTest

Attributes

Operations
+ GsonTypeAdapterTest():
+ testTypeAdapterThrowsException(): void
+ testTypeAdapterDoesNotAffectNonAdaptedTypes(): void
+ testTypeAdapterProperlyConvertsTypes(): void
+ testDefaultTypeAdapterThrowsParseException(): void
+ testDeserializerForAbstractClass(): void
+ setUp(): void
- assertSerialized(String, Class<?>, boolean, boolean, Object ...): void

GsonTypesTest

Attributes

Operations
+ GsonTypesTest():
+ testNewParameterizedTypeWithoutOwner(): void
+ getFirstTypeArgument(Type): Type
+ testEqualsOnConstructorParameterTypeVariables(): void
+ testEqualsOnMethodTypeVariables(): void
+ testGetFirstTypeArgument(): void
+ testGetMapKeyAndValueTypesForPropertiesSubclass(): void

HasArrayListField

Attributes

Operations
~ HasArrayListField():

HasModifiers

Attributes

Operations
~ HasModifiers():

HasObjectMap

Attributes

Operations
~ HasObjectMap():

HasTransients

Attributes

Operations
~ HasTransients():

HistoryCourse

Attributes

Operations
- HistoryCourse():

ISO8601Utils

Attributes

Operations
- ISO8601Utils():
+ format(Date, boolean): String
- indexOfNonDigit(String, int): int
- parseInt(String, int, int): int
- padInt(StringBuilder, int, int): void
+ format(Date, boolean, TimeZone): String
+ parse(String, ParsePosition): Date
+ format(Date): String
- checkOffset(String, int, char): boolean

Id<R>

Attributes

~ value: String
value: String
Operations
- Id(String, Type):

IdTreeTypeAdapter

Attributes

Operations
- IdTreeTypeAdapter():
+ deserialize(JsonElement, Type, JsonDeserializationContext): Id<?>
+ serialize(Id<?>, Type, JsonSerializationContext): JsonElement

Immutable

<<interface>>

Attributes

Operations

Implementation

Attributes

value: String
Operations
+ Implementation():

InheritanceTest

Attributes

+ ...): void
+ ...): void
Operations
+ InheritanceTest():
+ testSubClassDeserialization(): void
+ testSubInterfacesOfCollectionSerialization(): void
+ testBaseSerializedAsSubWhenSpecifiedWithExplicitType(): void
+ testClassWithBaseArrayFieldSerialization(): void
+ testSubClassSerialization(): void
+ testBaseSerializedAsSubForToJsonMethod(): void
+ testClassWithBaseCollectionFieldSerialization(): void
+ testBaseSerializedAsSub(): void
+ setUp(): void
+ testBaseSerializedAsBaseWhenSpecifiedWithExplicitType(): void
+ testSubInterfacesOfCollectionDeserialization(): void

Inner

Attributes

Operations
+ Inner(String):

InnerClass

Attributes

Operations
~ InnerClass():

InnerClassExclusionStrategyTest

Attributes

Operations
+ InnerClassExclusionStrategyTest():
+ testIncludeStaticNestedClassField(): void
+ testExcludeInnerClassObject(): void
- assertIncludesField(Field): void
- assertExcludesClass(Class<?>): void
+ testExcludeInnerClassField(): void
- assertExcludesField(Field): void
- assertIncludesClass(Class<?>): void
+ testIncludeStaticNestedClassObject(): void

InnerMessage

Attributes

- DEFAULT_INSTANCE: InnerMessage
serializedSize: int
defaultInstanceForType: InnerMessage
parserForType: Parser<InnerMessage>
dataOrBuilderList: List<DataOrBuilder>
NIdCt: int
content: Type
dataCount: int
dataList: List<Data>
descriptor: Descriptor
initialized: boolean
DEFAULT_INSTANCE: InnerMessage
Operations
- InnerMessage(Builder<?>):
- InnerMessage():
+ getDataOrBuilder(int): DataOrBuilder
+ newBuilderForType(): Builder
+ hasContent(): boolean
+ parseFrom(ByteString): InnerMessage
+ parseFrom(ByteString, ExtensionRegistryLite): InnerMessage
+ parseFrom(ByteBuffer): InnerMessage
+ parseFrom(ByteBuffer, ExtensionRegistryLite): InnerMessage
+ parseDelimitedFrom(InputStream, ExtensionRegistryLite): InnerMessage
+ equals(Object): boolean
# internalGetFieldAccessorTable(): FieldAccessorTable
+ parser(): Parser<InnerMessage>
+ parseFrom(CodedInputStream, ExtensionRegistryLite): InnerMessage
+ parseFrom(InputStream): InnerMessage
+ parseFrom(byte[]): InnerMessage
+ parseFrom(InputStream, ExtensionRegistryLite): InnerMessage
+ newBuilder(): Builder
+ hasNIdCt(): boolean
+ hashCode(): int
+ toBuilder(): Builder
+ writeTo(CodedOutputStream): void
+ parseFrom(CodedInputStream): InnerMessage
+ parseFrom(byte[], ExtensionRegistryLite): InnerMessage
+ parseDelimitedFrom(InputStream): InnerMessage
+ getData(int): Data
# newBuilderForType(BuilderParent): Builder
+ newBuilder(InnerMessage): Builder

InnerMessageOrBuilder

<<interface>>

Attributes
dataList: List<Data>
dataOrBuilderList: List<DataOrBuilder>
NIdCt: int
content: Type
dataCount: int

Operations
+ getDataOrBuilder(int): DataOrBuilder
+ hasContent(): boolean
+ hasNIdCt(): boolean
+ getData(int): Data

InstanceCreator<T>

<<interface>>

Attributes

Operations
+ createInstance(Type): T

InstanceCreatorTest

Attributes

Operations
+ InstanceCreatorTest():
+ testInstanceCreatorReturnsSubTypeForTopLevelObject(): void
+ testInstanceCreatorForParametrizedType(): void
+ testInstanceCreatorReturnsSubTypeForField(): void
+ testInstanceCreatorForCollectionType(): void
+ testInstanceCreatorReturnsBaseType(): void

Intercept

Attributes

Operations
+ postDeserialize(): Class<JsonPostDeserializer<?>>

InterceptorTest

Attributes

Operations
+ InterceptorTest():
+ testCollection(): void
+ testMapKeyAndValues(): void
+ testExceptionsPropagated(): void
+ testList(): void
+ testField(): void
+ testCustomTypeAdapter(): void
+ testDirectInvocationOfTypeAdapter(): void
+ setUp(): void
+ testTopLevelClass(): void

InterchangedToString

Attributes

Operations
- InterchangedToString(String):
+ toString(): String
+ values(): InterchangedToString[]
+ valueOf(String): InterchangedToString

Interface

<<interface>>

Attributes

Operations

Interface

<<interface>>

Attributes

Operations

InterfaceWithImplementation

<<interface>>

Attributes

value: String
Operations

InternationalizationTest

Attributes

+ ...): void
Operations
+ InternationalizationTest():
+ testStringsWithUnicodeChineseCharactersDeserialization(): void
+ testSupplementaryUnicodeSerialization(): void
+ setUp(): void
+ testSupplementaryUnicodeDeserialization(): void
+ testSupplementaryUnicodeEscapedDeserialization(): void
+ testStringsWithUnicodeChineseCharactersSerialization(): void

Item

Attributes

Operations
~ Item():
+ toString(): String

JacksonBindParser

Attributes

Operations
- JacksonBindParser():
+ parse(char[], Document): void

JacksonStreamParser

Attributes

Operations
- JacksonStreamParser():
+ parse(char[], Document): void

Java17RecordTest

Attributes

Operations
+ Java17RecordTest():
+ testFieldExclusionStrategy(): void
+ testMultipleNamesDeserializedCorrectly(): void
+ testSerializedNameOnAccessor(): void
+ testJsonAdapterAnnotation(): void
+ testStaticFieldDeserialization(): void
+ testStaticFieldSerialization(): void
+ testUnknownJsonProperty(): void
+ testPrimitiveDefaultValues(): void
+ testMultipleNamesInTheSameString(): void
+ testConstructorRuns(): void
+ testRecordNull(): void
+ testExposeAnnotation(): void
+ testObjectDefaultValue(): void
+ testThrowingConstructor(): void
+ testThrowingAccessor(): void
+ testDuplicateJsonProperties(): void
+ testAccessorIsCalled(): void
+ testReflectionFilterBlockInaccessible(): void
+ testEmptyRecord(): void
+ testFieldNamingStrategy(): void
+ testPrimitiveJsonNullValue(): void
+ testPrimitiveAdapterNullValue(): void
+ testRecordBaseClass(): void
+ testClassReflectionFilter(): void
+ testFirstNameIsChosenForSerialization(): void

Java17ReflectionHelperTest

Attributes

Operations
+ Java17ReflectionHelperTest():
+ testJava17Record(): void
+ testJava17RecordAccessors(): void

Java17ReflectiveTypeAdapterFactoryTest

Attributes

Operations
+ Java17ReflectiveTypeAdapterFactoryTest():
+ setUp(): void
+ testSerializeRecords(): void
+ testCustomAdapterForRecords(): void

JavaSerializationTest

Attributes

Operations
+ JavaSerializationTest():
+ testListIsSerializable(): void
- serializedCopy(T): T
+ testMapIsSerializable(): void
+ testNumberIsSerializable(): void

JavaUtilConcurrentAtomicTest

Attributes

Operations
+ JavaUtilConcurrentAtomicTest():
+ testAtomicLongArrayWithStringSerializationPolicy(): void
+ setUp(): void
+ testAtomicInteger(): void
+ testAtomicLongWithStringSerializationPolicy(): void
+ testAtomicIntegerArray(): void
+ testAtomicBoolean(): void
+ testAtomicLong(): void
+ testAtomicLongArray(): void

JavaVersion

Attributes

- majorJavaVersion: int
majorJavaVersion: int
java9OrLater: boolean
Operations
- JavaVersion():
~ parseMajorJavaVersion(String): int
- determineMajorJavaVersion(): int
- extractLeadingInt(String): int
- parseDotted(String): int

JavaVersionTest

Attributes

Operations
+ JavaVersionTest():
+ testJava7(): void
+ testJava10(): void
+ testJava8(): void
+ testUnknownVersionFormat(): void
+ testJava6(): void
+ testJava9(): void
+ testGetMajorJavaVersion(): void

JsonAdapterAnnotationOnFieldsTest

Attributes

+ testFieldAnnotationTakesPrecedenceOverRegisteredTypeAdapter ...): void
+ ...): void
+ testClassAnnotationAdapterFactoryTakesPrecedenceOverDefault ...): void
Operations
+ JsonAdapterAnnotationOnFieldsTest():
+ testJsonSerializer(): void
+ testOverwriteBuiltIn(): void
+ testPrimitiveFieldAnnotationTakesPrecedenceOverDefault(): void
+ testClassAnnotationAdapterTakesPrecedenceOverDefault(): void
+ testExcludePrecedence(): void
+ testJsonDeserializer(): void
+ testExcludeSerializePrecedence(): void
+ testNonPrimitiveFieldAnnotationTakesPrecedenceOverDefault(): void
+ testExcludeDeserializePrecedence(): void
+ testDelegatingAdapterFactory(): void
+ testDelegatingAdapterFactory_Delayed(): void
+ testJsonAdapterInvokedOnlyForAnnotatedFields(): void
+ testGetAdapterDelegation(): void
+ testJsonAdapterWrappedInNullSafeAsRequested(): void
+ testFieldAnnotationWorksForParameterizedType(): void
+ testFieldAnnotationTakesPrecedenceOverClassAnnotation(): void

JsonAdapterAnnotationTypeAdapterFactory

Attributes

Operations
+ JsonAdapterAnnotationTypeAdapterFactory(...):
~ getTypeAdapter(ConstructorConstructor, Gson, TypeToken<?>, ...): TypeAdapter<?>
+ create(Gson, TypeToken<T>): TypeAdapter<T>
- putFactoryAndGetCurrent(Class<?>, TypeAdapterFactory): TypeAdapterFactory
- getAnnotation(Class<?>): JsonAdapter
- createAdapter(ConstructorConstructor, Class<?>): Object
+ isClassJsonAdapterFactory(TypeToken<?>, TypeAdapterFactory): boolean

JsonAdapterFactory

Attributes

Operations
+ JsonAdapterFactory():

JsonAdapterSerializerDeserializerTest

Attributes

Operations
+ JsonAdapterSerializerDeserializerTest():
+ testDifferentJsonAdaptersForGenericFieldsOfSameRawType(): void
+ testJsonAdapterNullSafe(): void
+ testJsonSerializerDeserializerBasedJsonAdapterOnFields(): void
+ testJsonSerializerDeserializerBasedJsonAdapterOnClass(): void

JsonArray

Attributes
asNumber: Number
asBigInteger: BigInteger
asFloat: float
asByte: byte
asCharacter: char
asShort: short
asBigDecimal: BigDecimal
empty: boolean
asString: String
asBoolean: boolean
asInt: int
asDouble: double
asSingleElement: JsonElement
asLong: long
Operations
+ JsonArray():
+ JsonArray(int):
+ add(Boolean): void
+ remove(int): JsonElement
+ set(int, JsonElement): JsonElement
+ contains(JsonElement): boolean
+ addAll(JsonArray): void
+ add(String): void
+ deepCopy(): JsonArray
+ add(Character): void
+ add(Number): void
+ add(JsonElement): void
+ equals(Object): boolean
+ get(int): JsonElement
+ hashCode(): int
+ size(): int
+ remove(JsonElement): boolean
+ iterator(): Iterator<JsonElement>
+ asList(): List<JsonElement>

JsonArrayAsListSuiteTest

Attributes

Operations
+ JsonArrayAsListSuiteTest():
+ suite(): Test

JsonDeserializer<T>

<<interface>>

Attributes

Operations
+ deserialize(JsonElement, Type, JsonDeserializationContext): T

JsonElement

Attributes
asNumber: Number
asBigInteger: BigInteger
asFloat: float
asByte: byte
asCharacter: char
asShort: short
asBigDecimal: BigDecimal
asJsonNull: JsonNull
asJsonArray: JsonArray
jsonObject: boolean
asString: String
asBoolean: boolean
asInt: int
asDouble: double
jsonNull: boolean
asJsonPrimitive: JsonPrimitive
jsonArray: boolean
asJsonObject: JsonObject
jsonPrimitive: boolean
asLong: long
Operations
+ JsonElement():
+ deepCopy(): JsonElement
+ toString(): String

JsonIOException

Attributes

Operations
+ JsonIOException(String):
+ JsonIOException(String, Throwable):
+ JsonIOException(Throwable):

JsonNull

Attributes

Operations
+ JsonNull():
+ equals(Object): boolean
+ hashCode(): int
+ deepCopy(): JsonNull

JsonNullTest

Attributes

Operations
+ JsonNullTest():
+ testDeepCopy(): void
+ testEqualsAndHashcode(): void
+ testToString(): void

JsonObject

Attributes

empty: boolean
Operations
+ JsonObject():
+ deepCopy(): JsonObject
+ addProperty(String, Number): void
+ hashCode(): int
+ getAsJsonObject(String): JsonObject
+ get(String): JsonElement
+ getAsJsonPrimitive(String): JsonPrimitive
+ equals(Object): boolean
+ add(String, JsonElement): void
+ size(): int
+ remove(String): JsonElement
+ asMap(): Map<String, JsonElement>
+ addProperty(String, String): void
+ keySet(): Set<String>
+ has(String): boolean
+ addProperty(String, Boolean): void
+ getAsJsonArray(String): JsonArray
+ entrySet(): Set<Entry<String, JsonElement>>
+ addProperty(String, Character): void

JsonObjectAsMapSuiteTest

Attributes

Operations
+ JsonObjectAsMapSuiteTest():
+ suite(): Test

JsonParseException

Attributes

Operations
+ JsonParseException(Throwable):
+ JsonParseException(String):
+ JsonParseException(String, Throwable):

JsonParser

Attributes

Operations
+ JsonParser():
+ parse(JsonReader): JsonElement
+ parseReader(JsonReader): JsonElement
+ parse(String): JsonElement
+ parse(Reader): JsonElement
+ parseString(String): JsonElement
+ parseReader(Reader): JsonElement

JsonParserParameterizedTest

Attributes

Operations
+ JsonParserParameterizedTest():
+ data(): Iterable<String>
+ testParse(): void

JsonParserTest

Attributes

Operations
+ JsonParserTest():
+ testParseDeeplyNestedArrays(): void
+ testParseEmptyString(): void
+ testParseUnquotedSingleWordStringFails(): void
+ testParseString(): void
+ testParseEmptyWhitespaceInput(): void
+ testLegacyStrict(): void
+ testParseInvalidJson(): void
+ testParseUnquotedMultiWordStringFails(): void
+ testParseDeeplyNestedObjects(): void
+ testParseMixedArray(): void
+ testParseReader(): void
+ testReadWriteTwoObjects(): void
+ testStrict(): void
+ testParseUnquotedStringArrayFails(): void

JsonPostDeserializer<T>

<<interface>>

Attributes

Operations
+ postDeserialize(T): void

JsonPrimitive

Attributes
asNumber: Number
string: boolean
asBigInteger: BigInteger
asFloat: float
asByte: byte
asCharacter: char
number: boolean
asShort: short
asBigDecimal: BigDecimal
asString: String
asBoolean: boolean
asInt: int
asDouble: double
boolean: boolean
asLong: long
Operations
+ JsonPrimitive(Number):
+ JsonPrimitive(Boolean):
+ JsonPrimitive(String):
+ JsonPrimitive(Character):
+ deepCopy(): JsonPrimitive
- isIntegral(JsonPrimitive): boolean
+ hashCode(): int
+ equals(Object): boolean

JsonPrimitiveTest

Attributes

Operations
+ JsonPrimitiveTest():
+ testDeepCopy(): void
+ testNulls(): void
+ testEquals(): void
+ testFloatEqualsBigDecimal(): void
+ testShortEqualsLong(): void
+ testParsingStringAsBoolean(): void
+ testEqualsIntegerAndBigInteger(): void
+ testEqualsDoubleNaNAndBigDecimal(): void
+ testByteEqualsLong(): void
+ testDoubleEqualsBigDecimal(): void
+ testBigDecimalEqualsZero(): void
+ testBoolean(): void
+ testParsingStringAsNumber(): void
+ testExponential(): void
+ testByteEqualsBigInteger(): void
+ testStringsAndChar(): void
+ testToString(): void
+ testByteEqualsInteger(): void
+ testShortEqualsInteger(): void
+ testFloatEqualsDouble(): void
+ testEqualsDoesNotEquateStringAndNonStringTypes(): void
+ testByteEqualsShort(): void
+ testBigDecimalEqualsTransitive(): void
+ testAsNumber_Boolean(): void
+ testIntegerEqualsLong(): void
+ testEqualsAcrossTypes(): void
+ testShortEqualsBigInteger(): void
+ testIntegerEqualsBigInteger(): void
+ testLongEqualsBigInteger(): void
+ testBigDecimalEquals(): void

JsonReader

Attributes

- nestingLimit: int
- strictness: Strictness
previousPath: String
strictness: Strictness
path: String
nestingLimit: int
lenient: boolean

Operations
+ JsonReader(Reader):
+ endArray(): void
+ beginArray(): void
+ close(): void
+ nextLong(): long
- readEscapeCharacter(): char
- checkLenient(): void
- skipTo(String): boolean
~ locationString(): String
- push(int): void
- syntaxError(String): MalformedJsonException
+ toString(): String
- consumeNonExecutePrefix(): void
- nextQuotedValue(char): String
- nextNonWhitespace(boolean): int
+ hasNext(): boolean
- skipQuotedValue(char): void
- nextUnquotedValue(): String
+ skipValue(): void
+ beginObject(): void
- peekNumber(): int
+ endObject(): void
+ nextName(): String
~ doPeek(): int
+ nextString(): String
- unexpectedTokenError(String): IllegalStateException
- skipToEndOfLine(): void
+ nextBoolean(): boolean
+ nextNull(): void
+ nextDouble(): double
+ nextInt(): int
- isLiteral(char): boolean
- getPath(boolean): String
+ peek(): JsonToken
- peekKeyword(): int
- skipUnquotedValue(): void
- fillBuffer(int): boolean

JsonReaderInternalAccess

Attributes

Operations
+ JsonReaderInternalAccess():
+ promoteNameToValue(JsonReader): void

JsonReaderTest

Attributes

Operations
+ JsonReaderTest():
+ testStrictVeryLongNumber(): void
+ testFailWithPositionDeepPath(): void
+ testEscapedNewlineAllowedInDefaultMode(): void
+ testPeekLongMaxValue(): void
+ testInvalidJsonInput(): void
+ testStringNullIsNotNull(): void
+ testReadObject(): void
+ testFailWithPositionOverCStyleComment(): void
+ testDeeplyNestedArrays(): void
+ testFailWithEscapedNewlineCharacter(): void
- assertUnexpectedStructureError(IllegalStateException, ...): void
- assertStrictError(MalformedJsonException, String): void
+ testSkipArrayAfterPeek(): void
+ testQuotedNumberWithEscape(): void
+ testLenientMultipleTopLevelValues(): void
+ testSetStrictnessNull(): void
+ testHelloWorld(): void
+ testMixedCaseLiterals(): void
+ testNonStrictModeParsesUnescapedControlCharacter(): void
+ testUnescapingInvalidCharacters(): void
+ testPeekLongMinValue(): void
+ testSkipObjectAfterPeek(): void
+ testFailWithPositionGreaterThanBufferSize(): void
+ testCapitalizedFalseFailWhenStrict(): void
+ testNestingLimit(): void
+ testReadAcrossBuffers(): void
+ testVeryLongUnquotedString(): void
+ testSkipObjectNameUnquoted(): void
+ testSkipTopLevelObject(): void
+ testLenientNameValueSeparator(): void
+ testEmptyString(): void
+ testPeekLargerThanLongMaxValue(): void
+ testBooleans(): void
+ testSetStrictness(): void
+ testMalformedDocuments(): void
+ testFailWithPositionOverHashEndOfLineComment(): void
+ testUnterminatedStringFailure(): void
+ testStrictSemicolonDelimitedNameValuePairWithSkipValue(): void
+ testStrictMultipleTopLevelValues(): void
+ testIntegerMismatchFailuresDoNotAdvance(): void
+ testLenientSemicolonDelimitedNameValuePair(): void
+ testFailWithPositionOverSlashSlashEndOfLineComment(): void
+ testEscapeCharacterQuoteInStrictMode(): void
+ testVeryLongUnquotedLiteral(): void
+ testLenientNonExecutePrefix(): void
+ testUnescapingTruncatedCharacters(): void
+ testSkipArray(): void
+ testCharacterUnescaping(): void
+ testTopLevelValueTypeWithSkipValue(): void
+ testLenientUnquotedStrings(): void
+ testStrictUnquotedNamesWithSkipValue(): void
+ testCapitalizedNullFailWhenStrict(): void
+ testPeekingUnquotedStringsPrefixedWithBooleans(): void
- assertDocument(String, Object[]): void
+ testPeekLargerThanLongMinValue(): void
+ testVeryLongQuotedString(): void
- testFailWithPosition(String, String): void
+ testNestingLimitDefault(): void
+ testSkipVeryLongUnquotedString(): void
+ testPeekingUnquotedStringsPrefixedWithIntegers(): void
+ testStrictNameValueSeparatorWithSkipValue(): void
+ testLenientNonExecutePrefixWithLeadingWhitespace(): void
+ testStrictUnquotedNames(): void
+ testStrictUnnecessaryArraySeparatorsWithSkipValue(): void
+ testLenientUnquotedNames(): void
+ testLongLargerThanMaxLongThatWrapsAround(): void
+ testTopLevelValueTypes(): void
+ testSkipValueAfterEndOfDocument(): void
+ testMalformedNumbers(): void
+ testSkipInteger(): void
+ testEmptyStringName(): void
+ testStrictNonExecutePrefix(): void
+ testNullLiteralIsNotAString(): void
+ testEscapedNewlineNotAllowedInStrictMode(): void
+ testLenientVeryLongNumber(): void
+ testUnterminatedObject(): void
+ testStrictExtraCommasInMaps(): void
+ testLenientExtraCommasInMaps(): void
+ testStrictUnquotedStrings(): void
+ testFailWithPositionOverUnquotedString(): void
- reader(String): Reader
+ testStrictUnquotedStringsWithSkipValue(): void
+ testFailWithPosition(): void
+ testDocumentWithCommentEndingInSlash(): void
+ testReaderDoesNotTreatU2028U2029AsNewline(): void
+ testSetLenientFalse(): void
+ testStrictSingleQuotedNames(): void
+ testDeeplyNestedObjects(): void
+ testStrictSemicolonDelimitedArray(): void
+ testStrictNonExecutePrefixWithSkipValue(): void
+ testStrictSingleQuotedStringsWithSkipValue(): void
+ testNumberWithOctalPrefix(): void
+ testReadEmptyArray(): void
+ testStrictNonFiniteDoublesWithSkipValue(): void
+ testStringAsNumberWithTruncatedExponent(): void
+ testLenientSingleQuotedStrings(): void
+ testNextFailuresDoNotAdvance(): void
+ testSkipTopLevelUnquotedString(): void
+ testLenientUnnecessaryArraySeparators(): void
+ testPeekMuchLargerThanLongMinValue(): void
+ testSkipObject(): void
+ testSkipObjectNameSingleQuoted(): void
+ testSkipValueAtArrayEnd(): void
+ testStringAsNumberWithDigitAndNonDigitExponent(): void
+ testReadArray(): void
+ testSkipTopLevelQuotedString(): void
+ testSetLenientTrue(): void
+ testLenientSemicolonDelimitedArray(): void
+ testLenientComments(): void
+ testStrictModeAllowsOtherControlCharacters(): void
+ testPrematurelyClosed(): void
+ testStrictNonFiniteDoubles(): void
+ testVeryLongUnterminatedString(): void
+ testReadEmptyObject(): void
+ testStrictNameValueSeparator(): void
+ testBomForbiddenAsOtherCharacterInDocument(): void
+ testLenientSingleQuotedNames(): void
+ testStringEndingInSlash(): void
+ testStrictModeFailsToParseUnescapedControlCharacter(): void
+ testFailWithPositionIsOffsetByBom(): void
+ testSkipValueAtObjectEnd(): void
+ testNulls(): void
- repeat(char, int): String
+ testHasNextEndOfDocument(): void
+ testLongs(): void
+ testLenientNonFiniteDoubles(): void
+ testDoubles(): void
+ testStringAsNumberWithNonDigitExponent(): void
+ testFailWithPositionOverQuotedString(): void
+ testStrictSingleQuotedStrings(): void
+ testLenientPartialNonExecutePrefix(): void
+ testUnescapingTruncatedSequence(): void
+ testStrictUnnecessaryArraySeparators(): void
+ testStrictMultipleTopLevelValuesWithSkipValue(): void
- assertNotANumber(String): void
+ testHighPrecisionLong(): void
+ testCapitalizedTrueFailWhenStrict(): void
+ testPrematureEndOfInput(): void
+ testSkipObjectName(): void
+ testStrictSemicolonDelimitedArrayWithSkipValue(): void
+ testBomIgnoredAsFirstCharacterOfDocument(): void
+ testStringWithLeadingSlash(): void
+ testSkipVeryLongQuotedString(): void
+ testStrictSemicolonDelimitedNameValuePair(): void
+ testIntegersWithFractionalPartSpecified(): void
+ testStrictQuotedNonFiniteDoubles(): void
+ testStrictCommentsWithSkipValue(): void
+ testDefaultStrictness(): void
+ testEscapeCharacterQuoteWithoutStrictMode(): void
+ testLongLargerThanMinLongThatWrapsAround(): void
+ testSkipDouble(): void
+ testNegativeZero(): void
+ testStrictComments(): void
+ testCommentsInStringValue(): void
+ testStrictSingleQuotedNamesWithSkipValue(): void
+ testLenientQuotedNonFiniteDoubles(): void
+ testMissingValue(): void

JsonScope

Attributes

Operations
- JsonScope():

JsonSerializer<T>

<<interface>>

Attributes

Operations
+ serialize(T, Type, JsonSerializationContext): JsonElement

JsonStack

Attributes

pathName: String
pathIndex: int
empty: boolean
Operations
~ JsonStack(int):
- buildPath(StringBuilder, boolean): void
~ pop(): Object
~ incrementPathIndex(): void
~ clear(): void
- ensureCapacity(): void
- appendObjectPath(StringBuilder, int): void
- appendArrayPath(StringBuilder, int, boolean): void
~ peek(): Object
~ isSecondFromTopInstanceOf(Class<?>): boolean
~ push(Object): void
~ getPath(boolean): String

JsonStreamParser

Attributes

Operations
+ JsonStreamParser(String):
+ JsonStreamParser(Reader):
+ remove(): void
+ hasNext(): boolean
+ next(): JsonElement

JsonSyntaxException

Attributes

Operations
+ JsonSyntaxException(String):
+ JsonSyntaxException(String, Throwable):
+ JsonSyntaxException(Throwable):

JsonTreeReader

Attributes

previousPath: String
path: String
Operations
+ JsonTreeReader(JsonElement):
- nextNumeric(JsonValueExtractor<T>): T
- expect(JsonToken): void
- handleIterator(Iterator<?>): JsonToken
+ endArray(): void
+ nextInt(): int
+ close(): void
+ hasNext(): boolean
+ nextDouble(): double
+ toString(): String
+ nextLong(): long
+ skipValue(): void
- determineJsonPrimitiveType(JsonPrimitive): JsonToken
+ nextNull(): void
+ nextName(): String
- nextName(boolean): String
+ beginArray(): void
+ endObject(): void
+ nextBoolean(): boolean
+ nextString(): String
+ beginObject(): void
- determineTokenType(Object): JsonToken
~ nextJsonElement(): JsonElement
+ peek(): JsonToken
- locationString(): String
+ promoteNameToValue(): void

JsonTreeTest

Attributes

Operations
+ JsonTreeTest():
+ testToJsonTree(): void
+ testJsonTreeNull(): void
- assertContains(JsonObject, JsonPrimitive): void
+ testJsonTreeToString(): void
+ testToJsonTreeObjectType(): void
+ setUp(): void

JsonTreeWriter

Attributes

Operations
+ JsonTreeWriter():
+ close(): void
- peek(): JsonElement
+ jsonValue(String): JsonWriter
+ flush(): void
+ get(): JsonElement
- put(JsonElement): void
+ endArray(): JsonWriter
+ value(double): JsonWriter
+ name(String): JsonWriter
+ endObject(): JsonWriter
+ beginObject(): JsonWriter
+ value(Number): JsonWriter
+ beginArray(): JsonWriter
+ value(long): JsonWriter
+ value(boolean): JsonWriter
+ value(Boolean): JsonWriter
+ value(float): JsonWriter
+ value(String): JsonWriter
+ nullValue(): JsonWriter

JsonValueExtractor<T>

<<interface>>

Attributes

Operations
+ extract(JsonPrimitive): T

JsonWriter

Attributes
- strictness: Strictness
- formattingStyle: FormattingStyle
- htmlSafe: boolean
- serializeNulls: boolean
htmlSafe: boolean
indent: String
formattingStyle: FormattingStyle
strictness: Strictness
lenient: boolean
serializeNulls: boolean

Operations
+ JsonWriter(Writer):
+ endArray(): JsonWriter
+ endObject(): JsonWriter
+ value(boolean): JsonWriter
- alwaysCreatesValidJsonNumber(Class<Number>): boolean
- peek(): int
+ flush(): void
- newline(): void
+ nullValue(): JsonWriter
- beforeValue(): void
+ close(): void
+ beginObject(): JsonWriter
+ value(Boolean): JsonWriter
- writeDeferredName(): void
- push(int): void
+ value(Number): JsonWriter
+ value(String): JsonWriter
+ value(float): JsonWriter
- beforeName(): void
+ beginArray(): JsonWriter
- openScope(int, char): JsonWriter
+ name(String): JsonWriter
- replaceTop(int): void
+ value(long): JsonWriter
- string(String): void
+ jsonValue(String): JsonWriter
- closeScope(int, int, char): JsonWriter
+ value(double): JsonWriter

KeySet

Attributes

Operations
~ KeySet():
+ contains(Object): boolean
+ remove(Object): boolean
+ iterator(): Iterator<K>
+ clear(): void
+ size(): int

LazilyParsedNumberTest

Attributes

Operations
+ LazilyParsedNumberTest():
+ testHashCode(): void
+ testJavaSerialization(): void
+ testEquals(): void

LeniencyTest

Attributes

Operations
+ LeniencyTest():
+ testLenientFromJson(): void
+ setUp(): void

Link

Attributes

Operations
~ Link():
+ toString(): String

LinkedTreeMap<K, V>

Attributes

Operations
+ LinkedTreeMap(Comparator<K>, boolean):
+ LinkedTreeMap():
+ LinkedTreeMap(boolean):
+ remove(Object): V
+ put(K, V): V?
+ clear(): void
~ findByObject(Object): Node<K, V>
+ size(): int
+ keySet(): Set<K>
- replaceInParent(Node<K, V>, Node<K, V>): void
- rotateRight(Node<K, V>): void
- rebalance(Node<K, V>, boolean): void
- writeReplace(): Object
~ removeInternal(Node<K, V>, boolean): void
+ get(Object): V
+ containsKey(Object): boolean
- equal(Object, Object): boolean
+ entrySet(): Set<Entry<K, V>>
- rotateLeft(Node<K, V>): void
- readObject(ObjectInputStream): void
~ find(K, boolean): Node<K, V>
~ findByEntry(Entry<?, ?>): Node<K, V>
~ removeInternalByKey(Object): Node<K, V>

LinkedTreeMapIterator<T>

Attributes

Operations
~ LinkedTreeMapIterator():
+ hasNext(): boolean
+ remove(): void
~ nextNode(): Node<K, V>

LinkedTreeMapSuiteTest

Attributes

Operations
+ LinkedTreeMapSuiteTest():
- createFeatures(Feature<?>[]): Feature<?>[]
+ suite(): Test

LinkedTreeMapTest

Attributes

Operations
+ LinkedTreeMapTest():
+ testEmptyStringValues(): void
+ testPutNullValue(): void
+ testLargeSetOfRandomKeys(): void
+ testPutNonComparableKeyFails(): void
+ testPutNullKeyFails(): void
+ testEntrySetValueNull_Forbidden(): void
+ testRemoveRootDoesNotDoubleUnlink(): void
+ testPutOverrides(): void
+ testEqualsAndHashCode(): void
+ testIterationOrder(): void
+ testPutNullValue_Forbidden(): void
+ testEntrySetValueNull(): void
+ testClear(): void
+ testContainsNullKeyIsAlwaysFalse(): void
+ testContainsNonComparableKeyReturnsFalse(): void
+ testJavaSerialization(): void

ListGenerator

Attributes

Operations
- ListGenerator():
+ samples(): SampleElements<JsonElement>
+ order(List<JsonElement>): Iterable<JsonElement>
+ createArray(int): JsonElement[]
+ create(Object[]): List<JsonElement>

LongSerializationPolicyTest

Attributes

Operations
+ LongSerializationPolicyTest():
+ testDefaultLongSerialization(): void
+ testDefaultLongSerializationIntegration(): void
+ testStringLongSerialization(): void
+ testDefaultLongSerializationNull(): void
+ testStringLongSerializationNull(): void
+ testStringLongSerializationIntegration(): void

LongToStringTypeAdapterFactory

Attributes

Operations
- LongToStringTypeAdapterFactory():
+ create(Gson, TypeToken<T>): TypeAdapter<T>

Main

Attributes

Operations
- Main():
- testSerializedName(BiConsumer<String, String>): void
- testUnreferencedConstructorHasArgs(BiConsumer<String): void

MalformedJsonException

Attributes

Operations
+ MalformedJsonException(String):
+ MalformedJsonException(Throwable):
+ MalformedJsonException(String, Throwable):

Manager

Attributes

Operations
~ Manager():

ManagerAdapter

Attributes

Operations
~ ManagerAdapter():
+ deserialize(JsonElement, Type, JsonDeserializationContext): Manager
+ serialize(Manager, Type, JsonSerializationContext): JsonElement

MapClass

Attributes

Operations
~ MapClass():
+ addBase(String, Base): void
+ addSub(String, Sub): void

MapGenerator

Attributes

Operations
+ MapGenerator(boolean):
# create(Entry<String, String>[]): Map<String, String>

MapGenerator

Attributes

Operations
- MapGenerator():
+ samples(): SampleElements<Entry<String, JsonElement>>
+ createArray(int): Entry<String, JsonElement>[]
+ createKeyArray(int): String[]
+ order(List<Entry<String, JsonElement>>): Iterable<Entry<String, JsonElement>>
+ createValueArray(int): JsonElement[]
+ create(Object[]): Map<String, JsonElement>

MapTest

Attributes

Operations
+ MapTest():
+ testMapDeserializationEmpty(): void
+ testMapDeserializationWithIntegerKeys(): void
+ testMapDeserializationWithUnquotedIntegerKeys(): void
+ testMapStringSupertypeKeyDeserialization(): void
+ testHashMapDeserialization(): void
+ testMapWithoutNoArgsConstructor(): void
+ testCustomSerializerForSpecificMapType(): void
+ testMapOfMapSerialization(): void
+ testMapSerializationWithNullValue(): void
+ testMapDeserializationWithLongKeys(): void
+ testBooleanKeyDeserialization(): void
+ testMapWithQuotes(): void
+ testMapStringKeyDeserialization(): void
+ testNumberKeyDeserialization(): void
+ testMapSerializationWithIntegerKeys(): void
+ testMapStandardSubclassDeserialization(): void
+ testComplexKeysSerialization(): void
+ testConcurrentNavigableMap(): void
+ testMapSerializationWithNullValueButSerializeNulls(): void
+ testMapSubclassDeserialization(): void
+ testSerializeMaps(): void
+ testSerializeMapOfMaps(): void
+ testConcurrentHashMap(): void
+ testMapSubclassSerialization(): void
+ testWriteMapsWithEmptyStringKey(): void
+ testInterfaceTypeMap(): void
+ testConcurrentSkipListMap(): void
+ testMapOfMapDeserialization(): void
+ testMapNonStringKeyDeserialization(): void
+ testObjectMapSerialization(): void
+ testMapSerializationWithNullKey(): void
+ testMapSerializationWithNullValuesSerialized(): void
+ testConcurrentMap(): void
- newMap(K, V, K, V): Map<K, V>
+ testMapDeserializationWithNullValue(): void
+ testMapDeserializationWithUnquotedLongKeys(): void
+ testMapSerializationWithWildcardValues(): void
+ testReadMapsWithEmptyStringKey(): void
+ testMapDeserializationWithWildcardValues(): void
+ testComplexKeysDeserialization(): void
+ testMapSerialization(): void
+ testMapNamePromotionWithJsonElementReader(): void
+ testStringKeyDeserialization(): void
+ testParameterizedMapSubclassSerialization(): void
+ testMapDeserializationWithNullKey(): void
+ testDeserializeMapOfMaps(): void
+ setUp(): void
+ testSortedMap(): void
+ testInterfaceTypeMapWithSerializer(): void
+ testMapSerializationEmpty(): void
+ testMapSerializationWithNullValues(): void
+ testMapDeserializationWithDuplicateKeys(): void
+ testMapDeserialization(): void
+ testGeneralMapField(): void

MapWithGeneralMapParameters

Attributes

Operations
~ MapWithGeneralMapParameters():

MapWithoutNoArgsConstructor<K, V>

Attributes

Operations
+ MapWithoutNoArgsConstructor(int):
+ put(K, V): V?
+ entrySet(): Set<Entry<K, V>>

Measurable<T>

<<interface>>

Attributes

Operations

MixedStreamTest

Attributes

Operations
+ MixedStreamTest():
+ testReadNulls(): void
+ testWriteNulls(): void
+ testReadDoesNotMutateState(): void
+ testWriteDoesNotMutateState(): void
+ testWriteInvalidState(): void
+ testReadInvalidState(): void
+ testWriteLenient(): void
+ testWriteHtmlSafeWithoutEscaping(): void
+ testWriteHtmlSafeWithEscaping(): void
+ testReadMixedStreamed(): void
+ testWriteClosed(): void
+ testWriteMixedStreamed(): void
+ testReadClosed(): void

MockClassBoth

Attributes

Operations
- MockClassBoth():

MockClassSince

Attributes

Operations
- MockClassSince():

MultiParameters<A, B, C, D, E>

Attributes

Operations
~ MultiParameters(A, B, C, D, E):
- MultiParameters():
+ hashCode(): int
+ equals(Object): boolean

MultipleSandwiches

Attributes

Operations
+ MultipleSandwiches(List<Sandwich>):
+ equals(Object): boolean
+ hashCode(): int

MyBase

Attributes

Operations
- MyBase():

MyClass

Attributes

Operations
~ MyClass(String, String):

MyClass

Attributes

Operations
- MyClass():

MyClassTypeAdapter

Attributes

Operations
- MyClassTypeAdapter():
+ read(JsonReader): Class<?>
+ write(JsonWriter, Class<?>): void

MyEnum

Attributes

Operations
- MyEnum():
+ values(): MyEnum[]
+ valueOf(String): MyEnum

MyEnum

Attributes

Operations
- MyEnum():
+ valueOf(String): MyEnum
+ values(): MyEnum[]

MyEnumTypeAdapter

Attributes

Operations
- MyEnumTypeAdapter():
+ serialize(Roshambo, Type, JsonSerializationContext): JsonElement
+ deserialize(JsonElement, Type, JsonDeserializationContext): Roshambo

MyExclusionStrategy

Attributes

Operations
- MyExclusionStrategy(Class<?>):
+ shouldSkipClass(Class<?>): boolean
+ shouldSkipField(FieldAttributes): boolean

MyMap

Attributes

Operations
- MyMap():

MyParameterizedMap<K, V>

Attributes

Operations
~ MyParameterizedMap(int):

MyParameterizedType<T>

Attributes
+ value: T
expectedJson: String
value: T

Operations
+ MyParameterizedType(T):
+ hashCode(): int
+ equals(Object): boolean
- getExpectedJson(Object): String

MyParameterizedTypeAdapter<T>

Attributes

Operations
+ MyParameterizedTypeAdapter():
+ serialize(MyParameterizedType<T>, Type, ...): JsonElement
+ deserialize(JsonElement, Type, JsonDeserializationContext): MyParameterizedType<T>
+ getExpectedJson(MyParameterizedType<T>): String

MyParameterizedTypeInstanceCreator<T>

Attributes

Operations
+ MyParameterizedTypeInstanceCreator(T):
+ createInstance(Type): MyParameterizedType<T>

MyQuantity

Attributes

Operations
- MyQuantity():

Nested

Attributes

expectedJson: String
Operations
+ Nested():
+ Nested(BagOfPrimitives, BagOfPrimitives):
+ appendFields(StringBuilder): void

NestedClass

Attributes

Operations
+ NestedClass(String):
+ toJson(): String

NoSerializedNameMain

Attributes

Operations
- NoSerializedNameMain():
+ runTestNoJdkUnsafe(): String
+ runTestNoArgsConstructor(): String
+ runTestHasArgsConstructor(): String

Node

Attributes

Operations
~ Node(String):

Node<K, V>

Attributes
~ value: V
~ key: K
value: V
key: K
Operations
~ Node(boolean, Node<K, V>, K, Node<K, V>, Node<K, V>):
~ Node(boolean):
+ hashCode(): int
+ last(): Node<K, V>
+ toString(): String
+ setValue(V): V
+ equals(Object): boolean
+ first(): Node<K, V>

NonStaticInner<T>

Attributes

Operations
- NonStaticInner():

NonUploadingCaliperRunner

Attributes

Operations
- NonUploadingCaliperRunner():
+ run(Class<?>, String[]): void
- concat(String, String[]): String[]

NullObjectAndFieldTest

Attributes

Operations
+ NullObjectAndFieldTest():
+ testNullWrappedPrimitiveMemberSerialization(): void
+ testAbsentJsonElementsAreSetToNull(): void
+ testCustomSerializationOfNulls(): void
+ testPrintPrintingArraysWithNulls(): void
+ testPrintPrintingObjectWithNulls(): void
+ testExplicitDeserializationOfNulls(): void
+ testExplicitSerializationOfNullStringMembers(): void
+ testCustomTypeAdapterPassesNullSerialization(): void
+ testExplicitSerializationOfNullArrayMembers(): void
+ testExplicitSerializationOfNulls(): void
+ testExplicitNullSetsFieldToNullDuringDeserialization(): void
+ testNullWrappedPrimitiveMemberDeserialization(): void
+ setUp(): void
+ testTopLevelNullObjectSerialization(): void
+ testTopLevelNullObjectDeserialization(): void
+ testExplicitSerializationOfNullCollectionMembers(): void
+ testCustomTypeAdapterPassesNullDeserialization(): void

NumberAsStringAdapter

Attributes

Operations
~ NumberAsStringAdapter(Class<Number>):
+ write(JsonWriter, Number): void
+ read(JsonReader): Number

NumberLimits

Attributes

Operations
- NumberLimits():
- checkLength(String): void
+ parseBigDecimal(String): BigDecimal
+ parseBigInteger(String): BigInteger
- preview(String): String

ObjectConstructor<T>

<<interface>>

ObjectTest

Attributes

+ ...): void
Operations
+ ObjectTest():
+ testThrowingDefaultConstructor(): void
+ testClassWithTransientFieldsDeserialization(): void
+ testNullArraysDeserialization(): void
+ testTruncatedDeserialization(): void
+ testArrayOfObjectsDeserialization(): void
+ testObjectFieldNamesWithoutQuotesDeserialization(): void
+ testNullFieldsDeserialization(): void
+ testStaticFieldSerialization(): void
+ testInnerClassDeserialization(): void

ObjectTypeAdapterTest

Attributes

Operations
+ ObjectTypeAdapterTest():
+ testSerialize(): void
+ testDeserialize(): void
+ testDeserializeNullValue(): void
+ testSerializeObject(): void
+ testSerializeNullValue(): void
+ testDeserializeDeeplyNestedArrays(): void
+ testDeserializeDeeplyNestedObjects(): void

ObjectWithField

Attributes

Operations
- ObjectWithField():

ObjectWithTypeVariables<T>

Attributes

expectedJson: String
Operations
+ ObjectWithTypeVariables(T, T[], List<T>, List<T>[], List<T> ...):
- ObjectWithTypeVariables():
+ toString(T): String
- appendObjectsToBuilder(StringBuilder, Iterable<T>): void
- appendObjectsToBuilder(StringBuilder, List<T>[]): void

ObjectWithWildcardCollection

Attributes

- collection: Collection<BagOfPrimitives>
collection: Collection<BagOfPrimitives>
Operations
+ ObjectWithWildcardCollection(Collection<BagOfPrimitives>):

OperationType

Attributes

Operations
- OperationType():
+ valueOf(String): OperationType
+ values(): OperationType[]

OtherClass

Attributes

Operations
- OtherClass():

Outer

Attributes

Operations
- Outer():

OuterMessage

Attributes

- DEFAULT_INSTANCE: OuterMessage
countryCode5F55: String
countryCode5F55Bytes: ByteString
serializedSize: int
parserForType: Parser<OuterMessage>
month: int
longTimestamp: long
year: int
defaultInstanceForType: OuterMessage
DEFAULT_INSTANCE: OuterMessage
descriptor: Descriptor
initialized: boolean

Operations
- OuterMessage(Builder<?>):
- OuterMessage():
+ writeTo(CodedOutputStream): void
+ parseFrom(InputStream, ExtensionRegistryLite): OuterMessage
+ parseFrom(InputStream): OuterMessage
+ parseFrom(ByteString, ExtensionRegistryLite): OuterMessage
+ newBuilderForType(): Builder
+ hashCode(): int
+ hasMonth(): boolean
+ parseFrom(byte[], ExtensionRegistryLite): OuterMessage
+ newBuilder(): Builder
# newBuilderForType(BuilderParent): Builder
+ parser(): Parser<OuterMessage>
+ parseFrom(byte[]): OuterMessage
+ parseFrom(CodedInputStream, ExtensionRegistryLite): OuterMessage
+ newBuilder(OuterMessage): Builder
+ parseFrom(CodedInputStream): OuterMessage
+ hasYear(): boolean
+ hasLongTimestamp(): boolean
+ parseFrom(ByteBuffer, ExtensionRegistryLite): OuterMessage
+ parseDelimitedFrom(InputStream): OuterMessage
+ parseFrom(ByteString): OuterMessage
+ toBuilder(): Builder
+ hasCountryCode5F55(): boolean
+ parseDelimitedFrom(InputStream, ExtensionRegistryLite): OuterMessage
# internalGetFieldAccessorTable(): FieldAccessorTable
+ parseFrom(ByteBuffer): OuterMessage
+ equals(Object): boolean

OuterMessageOrBuilder

<<interface>>

Attributes

countryCode5F55: String
countryCode5F55Bytes: ByteString
month: int
longTimestamp: long
year: int
Operations
+ hasLongTimestamp(): boolean
+ hasCountryCode5F55(): boolean
+ hasYear(): boolean
+ hasMonth(): boolean

OverrideCoreTypeAdaptersTest

Attributes

Operations
+ OverrideCoreTypeAdaptersTest():
+ testOverrideStringAdapter(): void
+ testOverrideWrapperBooleanAdapter(): void
+ testOverridePrimitiveBooleanAdapter(): void

ParameterizedTypeFixtures

Attributes

Operations
- ParameterizedTypeFixtures():

ParameterizedTypeTest

Attributes

Operations
+ ParameterizedTypeTest():
+ setUp(): void
+ testOurTypeFunctionality(): void
+ testNotEquals(): void

ParameterizedTypesTest

Attributes

Operations
+ ParameterizedTypesTest():
+ testVariableTypeArrayDeserialization(): void
+ testParameterizedTypeGenericArraysSerialization(): void
+ testParameterizedTypeDeserialization(): void
+ testParameterizedTypeWithCustomSerializer(): void
+ testParameterizedTypesWithWriterSerialization(): void
+ testParameterizedTypeWithReaderDeserialization(): void
+ testParameterizedTypeWithVariableTypeDeserialization(): void
+ testGsonFromJsonTypeToken(): void
+ testTypesWithMultipleParametersSerialization(): void
+ testVariableTypeFieldsAndGenericArraysSerialization(): void
+ testDeepParameterizedTypeDeserialization(): void
+ testParameterizedTypesSerialization(): void
+ testDeepParameterizedTypeSerialization(): void
+ testTypesWithMultipleParametersDeserialization(): void
+ testParameterizedTypesWithCustomDeserializer(): void
+ testVariableTypeFieldsAndGenericArraysDeserialization(): void
- assertCorrectlyDeserialized(Object): void
+ testVariableTypeDeserialization(): void
- arrayOf(T[]): T[]
+ testParameterizedTypeGenericArraysDeserialization(): void
+ setUp(): void

ParseBenchmark

Attributes

Operations
+ ParseBenchmark():
- getResourceFile(String): File
- resourceToString(String): String
+ main(String[]): void
~ setUp(): void
+ timeParse(int): void

Parser

<<interface>>

Attributes

Operations
+ parse(char[], Document): void

Part

Attributes

Operations
+ Part(String):

PerformanceTest

Attributes

Operations
+ PerformanceTest():
+ testByteArrayDeserialization(): void
+ testDeserializeClasses(): void
- buildJsonForClassWithList(): String
- parseLongJson(String): void
+ testDeserializeExposedClasses(): void
+ testLargeGsonMapRoundTrip(): void
+ testSerializeClasses(): void
+ testByteArraySerialization(): void
+ setUp(): void
+ testLargeCollectionSerialization(): void
+ testDummy(): void
+ testSerializeExposedClasses(): void
+ testStringDeserialization(): void
+ testLargeObjectSerializationAndDeserialization(): void
+ testLargeCollectionDeserialization(): void

Person

Attributes

Operations
~ Person(String, int):
+ equals(Object): boolean
+ hashCode(): int

Point

Attributes

Operations
~ Point(int, int):
+ equals(Object): boolean
+ toString(): String
+ hashCode(): int

PostConstructAdapterFactoryTest

Attributes

Operations
+ PostConstructAdapterFactoryTest():
+ testInvalidSandwichThrowsException(): void
+ testMultipleSandwichesDeserialization(): void
+ testMultipleSandwichesSerialization(): void
+ testNullInputHandling(): void
+ testValidSandwichDeserialization(): void
+ setUp(): void

PreJava9DateFormatProvider

Attributes

Operations
- PreJava9DateFormatProvider():
+ getUsDateTimeFormat(int, int): DateFormat

PrettyPrintingTest

Attributes

Operations
+ PrettyPrintingTest():
+ testPrettyPrintArrayOfPrimitiveArrays(): void
+ testPrettyPrintArrayOfPrimitives(): void
+ setUp(): void
+ testPrettyPrintListOfPrimitiveArrays(): void
+ testPrettyPrintList(): void
+ testPrettyPrintArrayOfObjects(): void
+ testMultipleArrays(): void
+ testMap(): void
+ testEmptyMapField(): void

PrimitiveArray

Attributes

expectedJson: String
Operations
+ PrimitiveArray():
+ PrimitiveArray(long[]):

PrimitiveCharacterTest

Attributes

Operations
+ PrimitiveCharacterTest():
+ setUp(): void
+ testPrimitiveCharacterAutoboxedSerialization(): void
+ testPrimitiveCharacterAutoboxedDeserialization(): void

PrimitiveTypeAdapter

Attributes

Operations
~ PrimitiveTypeAdapter():
+ adaptType(Object, Class<T>): T

PrincipalImpl

Attributes

- name: String
name: String
Operations
+ PrincipalImpl(String):
+ equals(Object): boolean
+ hashCode(): int

PrintFormattingTest

Attributes

Operations
+ PrintFormattingTest():
+ setUp(): void
+ testJsonObjectWithNullValues(): void
+ testCompactFormattingLeavesNoWhiteSpace(): void
+ testJsonObjectWithNullValuesSerialized(): void
- assertContainsNoWhiteSpace(String): void

PrivateRecord

Attributes

Operations
- PrivateRecord(int):
+ i(): int

ProtoTypeAdapter

Attributes

Operations
- ProtoTypeAdapter(EnumSerialization, CaseFormat, CaseFormat ...):
+ serialize(Message, Type, JsonSerializationContext): JsonElement
- findValueByNameAndExtension(EnumDescriptor, JsonElement): EnumValueDescriptor
- getCachedMethod(Class<?>, String, Class<?>[]): Method
+ deserialize(JsonElement, Type, JsonDeserializationContext): Message
- getCustSerializedEnumValue(EnumValueOptions, String): String
+ newBuilder(): Builder
- getCustSerializedName(FieldDescriptor): String
- getEnumValue(EnumValueDescriptor): Object

ProtoWithAnnotations

Attributes

- DEFAULT_INSTANCE: ProtoWithAnnotations
idBytes: ByteString
serializedSize: int
defaultInstanceForType: ProtoWithAnnotations
descriptor: Descriptor
outerMessage: OuterMessage
id: String
innerMessage1OrBuilder: InnerMessageOrBuilder
DEFAULT_INSTANCE: ProtoWithAnnotations
innerMessage2OrBuilder: InnerMessageOrBuilder
parserForType: Parser<ProtoWithAnnotations>
innerMessage2: InnerMessage
innerMessage1: InnerMessage
outerMessageOrBuilder: OuterMessageOrBuilder
initialized: boolean

Operations
- ProtoWithAnnotations():
- ProtoWithAnnotations(Builder<?>):
+ parseFrom(CodedInputStream, ExtensionRegistryLite): ProtoWithAnnotations
+ parseFrom(byte[]): ProtoWithAnnotations
+ hashCode(): int
+ parseFrom(InputStream): ProtoWithAnnotations
+ parseFrom(byte[], ExtensionRegistryLite): ProtoWithAnnotations
+ hasId(): boolean
+ parseFrom(CodedInputStream): ProtoWithAnnotations
+ parseFrom(ByteString): ProtoWithAnnotations
+ hasInnerMessage1(): boolean
+ parseDelimitedFrom(InputStream, ExtensionRegistryLite): ProtoWithAnnotations
+ writeTo(CodedOutputStream): void
+ parseFrom(InputStream, ExtensionRegistryLite): ProtoWithAnnotations
+ parser(): Parser<ProtoWithAnnotations>
# internalGetFieldAccessorTable(): FieldAccessorTable
+ equals(Object): boolean
+ newBuilder(): Builder
+ newBuilderForType(): Builder
+ toBuilder(): Builder
+ parseFrom(ByteBuffer, ExtensionRegistryLite): ProtoWithAnnotations
+ hasInnerMessage2(): boolean
# newBuilderForType(BuilderParent): Builder
+ hasOuterMessage(): boolean
+ parseDelimitedFrom(InputStream): ProtoWithAnnotations
+ newBuilder(ProtoWithAnnotations): Builder
+ parseFrom(ByteBuffer): ProtoWithAnnotations
+ parseFrom(ByteString, ExtensionRegistryLite): ProtoWithAnnotations

ProtoWithAnnotationsAndJsonNames

Attributes

- DEFAULT_INSTANCE: ProtoWithAnnotationsAndJsonNames
neitherBytes: ByteString
both: String
serializedSize: int
DEFAULT_INSTANCE: ProtoWithAnnotationsAndJsonNames
jsonNameOnly: String
defaultInstanceForType: ProtoWithAnnotationsAndJsonNames
descriptor: Descriptor
annotationOnlyBytes: ByteString
neither: String
annotationOnly: String
parserForType: Parser<ProtoWithAnnotationsAndJsonNames>
bothBytes: ByteString
jsonNameOnlyBytes: ByteString
initialized: boolean

Operations
- ProtoWithAnnotationsAndJsonNames(Builder<?>):
- ProtoWithAnnotationsAndJsonNames():
+ parseFrom(ByteString): ProtoWithAnnotationsAndJsonNames
+ newBuilder(): Builder
+ hasJsonNameOnly(): boolean
+ hasAnnotationOnly(): boolean
+ parseFrom(byte[], ExtensionRegistryLite): ProtoWithAnnotationsAndJsonNames
# internalGetFieldAccessorTable(): FieldAccessorTable
+ hasBoth(): boolean
+ parseFrom(CodedInputStream, ExtensionRegistryLite): ProtoWithAnnotationsAndJsonNames
+ hasNeither(): boolean
+ parseFrom(ByteBuffer, ExtensionRegistryLite): ProtoWithAnnotationsAndJsonNames
+ parseFrom(byte[]): ProtoWithAnnotationsAndJsonNames
+ parser(): Parser<ProtoWithAnnotationsAndJsonNames>
+ parseDelimitedFrom(InputStream): ProtoWithAnnotationsAndJsonNames
+ parseFrom(CodedInputStream): ProtoWithAnnotationsAndJsonNames
+ hashCode(): int
+ newBuilder(ProtoWithAnnotationsAndJsonNames): Builder
+ parseFrom(InputStream, ExtensionRegistryLite): ProtoWithAnnotationsAndJsonNames
+ parseFrom(ByteString, ExtensionRegistryLite): ProtoWithAnnotationsAndJsonNames
+ newBuilderForType(): Builder
+ equals(Object): boolean
+ toBuilder(): Builder
# newBuilderForType(BuilderParent): Builder
+ parseFrom(ByteBuffer): ProtoWithAnnotationsAndJsonNames
+ parseDelimitedFrom(InputStream, ExtensionRegistryLite): ProtoWithAnnotationsAndJsonNames
+ parseFrom(InputStream): ProtoWithAnnotationsAndJsonNames
+ writeTo(CodedOutputStream): void

ProtoWithAnnotationsAndJsonNamesOrBuilder

<<interface>>

Attributes

neitherBytes: ByteString
annotationOnly: String
both: String
bothBytes: ByteString
jsonNameOnlyBytes: ByteString
jsonNameOnly: String
annotationOnlyBytes: ByteString
neither: String
Operations
+ hasBoth(): boolean
+ hasNeither(): boolean
+ hasAnnotationOnly(): boolean
+ hasJsonNameOnly(): boolean

ProtoWithAnnotationsOrBuilder

<<interface>>

Attributes

idBytes: ByteString
innerMessage2OrBuilder: InnerMessageOrBuilder
innerMessage2: InnerMessage
innerMessage1: InnerMessage
outerMessage: OuterMessage
id: String
outerMessageOrBuilder: OuterMessageOrBuilder
innerMessage1OrBuilder: InnerMessageOrBuilder
Operations
+ hasId(): boolean
+ hasInnerMessage1(): boolean
+ hasOuterMessage(): boolean
+ hasInnerMessage2(): boolean

ProtoWithDifferentCaseFormat

Attributes

- DEFAULT_INSTANCE: ProtoWithDifferentCaseFormat
anotherField: String
DEFAULT_INSTANCE: ProtoWithDifferentCaseFormat
serializedSize: int
parserForType: Parser<ProtoWithDifferentCaseFormat>
nameThatTestsCaseFormatList: ProtocolStringList
nameThatTestsCaseFormatCount: int
defaultInstanceForType: ProtoWithDifferentCaseFormat
descriptor: Descriptor
anotherFieldBytes: ByteString
initialized: boolean

Operations
- ProtoWithDifferentCaseFormat(Builder<?>):
- ProtoWithDifferentCaseFormat():
+ parseFrom(ByteString): ProtoWithDifferentCaseFormat
+ parseFrom(CodedInputStream): ProtoWithDifferentCaseFormat
+ parseFrom(ByteString, ExtensionRegistryLite): ProtoWithDifferentCaseFormat
# internalGetFieldAccessorTable(): FieldAccessorTable
+ parseFrom(ByteBuffer): ProtoWithDifferentCaseFormat
+ parseFrom(CodedInputStream, ExtensionRegistryLite): ProtoWithDifferentCaseFormat
+ getNameThatTestsCaseFormat(int): String
+ parseFrom(byte[], ExtensionRegistryLite): ProtoWithDifferentCaseFormat
# newBuilderForType(BuilderParent): Builder
+ newBuilder(): Builder
+ parser(): Parser<ProtoWithDifferentCaseFormat>
+ getNameThatTestsCaseFormatBytes(int): ByteString
+ toBuilder(): Builder
+ parseFrom(InputStream, ExtensionRegistryLite): ProtoWithDifferentCaseFormat
+ hasAnotherField(): boolean
+ hashCode(): int
+ parseFrom(byte[]): ProtoWithDifferentCaseFormat
+ newBuilder(ProtoWithDifferentCaseFormat): Builder
+ parseFrom(ByteBuffer, ExtensionRegistryLite): ProtoWithDifferentCaseFormat
+ parseDelimitedFrom(InputStream, ExtensionRegistryLite): ProtoWithDifferentCaseFormat
+ equals(Object): boolean
+ newBuilderForType(): Builder
+ writeTo(CodedOutputStream): void
+ parseDelimitedFrom(InputStream): ProtoWithDifferentCaseFormat
+ parseFrom(InputStream): ProtoWithDifferentCaseFormat

ProtoWithDifferentCaseFormatOrBuilder

<<interface>>

Attributes

anotherField: String
nameThatTestsCaseFormatCount: int
nameThatTestsCaseFormatList: List<String>
anotherFieldBytes: ByteString
Operations
+ hasAnotherField(): boolean
+ getNameThatTestsCaseFormatBytes(int): ByteString
+ getNameThatTestsCaseFormat(int): String

ProtoWithRepeatedFields

Attributes

- DEFAULT_INSTANCE: ProtoWithRepeatedFields
serializedSize: int
defaultInstanceForType: ProtoWithRepeatedFields
simplesOrBuilderList: List<SimpleProtoOrBuilder>
numbersList: List<Long>
simplesCount: int
nameBytes: ByteString
descriptor: Descriptor
DEFAULT_INSTANCE: ProtoWithRepeatedFields
numbersCount: int
name: String
parserForType: Parser<ProtoWithRepeatedFields>
simplesList: List<SimpleProto>
initialized: boolean

Operations
- ProtoWithRepeatedFields(Builder<?>):
- ProtoWithRepeatedFields():
+ parseFrom(ByteString): ProtoWithRepeatedFields
+ parseFrom(CodedInputStream, ExtensionRegistryLite): ProtoWithRepeatedFields
+ parseFrom(ByteString, ExtensionRegistryLite): ProtoWithRepeatedFields
+ parseDelimitedFrom(InputStream): ProtoWithRepeatedFields
# newBuilderForType(BuilderParent): Builder
+ getSimplesOrBuilder(int): SimpleProtoOrBuilder
+ equals(Object): boolean
+ getSimples(int): SimpleProto
+ hasName(): boolean
+ parseFrom(InputStream, ExtensionRegistryLite): ProtoWithRepeatedFields
+ newBuilderForType(): Builder
+ parseDelimitedFrom(InputStream, ExtensionRegistryLite): ProtoWithRepeatedFields
# internalGetFieldAccessorTable(): FieldAccessorTable
+ newBuilder(ProtoWithRepeatedFields): Builder
+ parseFrom(byte[], ExtensionRegistryLite): ProtoWithRepeatedFields
+ getNumbers(int): long
+ newBuilder(): Builder
+ parseFrom(InputStream): ProtoWithRepeatedFields
+ writeTo(CodedOutputStream): void
+ parseFrom(ByteBuffer): ProtoWithRepeatedFields
+ parseFrom(byte[]): ProtoWithRepeatedFields
+ toBuilder(): Builder
+ parseFrom(ByteBuffer, ExtensionRegistryLite): ProtoWithRepeatedFields
+ parser(): Parser<ProtoWithRepeatedFields>
+ hashCode(): int
+ parseFrom(CodedInputStream): ProtoWithRepeatedFields

ProtoWithRepeatedFieldsOrBuilder

<<interface>>

Attributes
numbersCount: int
name: String
simplesOrBuilderList: List<SimpleProtoOrBuilder>
numbersList: List<Long>
nameBytes: ByteString
simplesCount: int
simplesList: List<SimpleProto>
Operations
+ getSimplesOrBuilder(int): SimpleProtoOrBuilder
+ hasName(): boolean
+ getNumbers(int): long
+ getSimples(int): SimpleProto

ProtosWithAnnotationsAndJsonNamesTest

Attributes

+ ...): void
+ ...): void
Operations
+ ProtosWithAnnotationsAndJsonNamesTest():
- roundTrip(Gson, Gson, String): String
+ testProtoWithAnnotationsAndJsonNames_basicRoundTrips(): void
+ testProtoWithAnnotationsAndJsonNames_fieldWithJsonName(): void
- roundTrip(Gson, Gson, ProtoWithAnnotationsAndJsonNames): ProtoWithAnnotationsAndJsonNames
+ testProtoWithAnnotationsAndJsonNames_basicConversions(): void
+ testProtoWithAnnotationsAndJsonNames_unannotatedField(): void

ProtosWithAnnotationsTest

Attributes

Operations
+ ProtosWithAnnotationsTest():
+ testProtoWithAnnotations_serialize(): void
+ testProtoWithAnnotations_deserializeWithEnumNumbers(): void
+ testProtoWithAnnotations_deserializeUnknownEnumValue(): void
+ testProtoWithAnnotations_deserializeUnrecognizedEnumValue(): void
+ testProtoWithAnnotations_deserializeUnrecognizedEnumNumber(...): void
+ setUp(): void
+ testProtoWithAnnotations_deserialize(): void

ProtosWithPrimitiveTypesTest

Attributes

Operations
+ ProtosWithPrimitiveTypesTest():
+ testDeserializeProto(): void
+ testDeserializeWithExplicitNullValue(): void
+ setUp(): void
+ testSerializeEmptyProto(): void
+ testSerializeProto(): void
+ testDeserializeEmptyProto(): void

PublicRecord

Attributes

Operations
+ PublicRecord(int):
+ i(): int

Quantity

Attributes

Operations
- Quantity():

RawCollectionsExample

Attributes

Operations
+ RawCollectionsExample():
+ main(String[]): void

RawSerializationTest

Attributes

Operations
+ RawSerializationTest():
+ testCollectionOfObjects(): void
+ testThreeLevelParameterizedObject(): void
+ setUp(): void
+ testTwoLevelParameterizedObject(): void
+ testCollectionOfPrimitives(): void
+ testParameterizedObject(): void

ReaderUser

Attributes

Operations
~ ReaderUser():
+ toString(): String

RecordHelper

Attributes

Operations
- RecordHelper():
~ getCanonicalRecordConstructor(Class<T>): Constructor<T>
~ isRecord(Class<?>): boolean
~ getRecordComponentNames(Class<?>): String[]
+ getAccessor(Class<?>, Field): Method

RecordNotSupportedHelper

Attributes

Operations
- RecordNotSupportedHelper():
~ getRecordComponentNames(Class<?>): String[]
~ getCanonicalRecordConstructor(Class<T>): Constructor<T>
+ getAccessor(Class<?>, Field): Method
~ isRecord(Class<?>): boolean

RecordSupportedHelper

Attributes

Operations
- RecordSupportedHelper():
~ isRecord(Class<?>): boolean
+ getCanonicalRecordConstructor(Class<T>): Constructor<T>
+ getAccessor(Class<?>, Field): Method
~ getRecordComponentNames(Class<?>): String[]

RecordWithCustomNames

Attributes

Operations
- RecordWithCustomNames(String, String):
+ b(): String
+ a(): String

RecordWithPrimitives

Attributes

Operations
- RecordWithPrimitives(String, byte, short, int, long, float ...):
+ aDouble(): double
+ aFloat(): float
+ aLong(): long
+ anInt(): int
+ aChar(): char
+ aBoolean(): boolean
+ aByte(): byte
+ aString(): String
+ aShort(): short

RecordWithStaticField

Attributes

Operations
- RecordWithStaticField():

RecursiveTypesResolveTest

Attributes

Operations
+ RecursiveTypesResolveTest():
+ testRecursiveTypeVariablesResolve1(): void
+ testRecursiveTypeVariablesResolve12(): void
+ testSubSupertype(): void
+ testRecursiveResolveSimple(): void
+ testSuperSubtype(): void
+ testDoubleSupertype(): void
+ testDoubleSubtype(): void

ReflectionAccessFilter

<<interface>>

Attributes

Operations
+ check(Class<?>): FilterResult

ReflectionAccessFilterTest

Attributes

Operations
+ ReflectionAccessFilterTest():
+ testBlockAllJavaExtendingJdkClass(): void
+ testAllowForSupertype(): void
+ testBlockInaccessibleInterface(): void
+ testDelegation(): void
+ testClassWithoutNoArgsConstructor(): void
+ testBlockAllCollectionImplementation(): void
+ testBlockInaccessibleStaticField(): void
+ testConstantsToString(): void
+ testBlockAllJava(): void
+ testInaccessibleNoArgsConstructor(): void
+ testBlockAllCollectionInterface(): void
+ testBlockInaccessibleJavaExtendingJdkClass(): void
+ testBlockInaccessibleJava(): void
+ testDontBlockAccessibleJava(): void
+ testBlockAllPartial(): void

ReflectionHelper

Attributes

Operations
- ReflectionHelper():
+ getCanonicalRecordConstructor(Class<T>): Constructor<T>
+ constructorToString(Constructor<?>): String
+ tryMakeAccessible(Constructor<?>): String
+ getAccessibleObjectDescription(AccessibleObject, boolean): String
- getInaccessibleTroubleshootingSuffix(Exception): String
+ getAccessor(Class<?>, Field): Method
+ createExceptionForUnexpectedIllegalAccess(...): RuntimeException
+ isStatic(Class<?>): boolean
- appendExecutableParameters(AccessibleObject, StringBuilder): void
- createExceptionForRecordReflectionException(...): RuntimeException
+ getRecordComponentNames(Class<?>): String[]
+ isAnonymousOrNonStaticLocal(Class<?>): boolean
+ makeAccessible(AccessibleObject): void
+ fieldToString(Field): String
+ isRecord(Class<?>): boolean

ReflectionInaccessibleTest

Attributes

Operations
+ ReflectionInaccessibleTest():
+ testSerialization(): void
+ testDeserialization(): void

ReusedTypeVariablesFullyResolveTest

Attributes

Operations
+ ReusedTypeVariablesFullyResolveTest():
+ setUp(): void
+ testGenericsPreservation(): void

Roshambo

Attributes

Operations
- Roshambo():
+ values(): Roshambo[]
~ defeats(): Roshambo
+ valueOf(String): Roshambo

RuntimeType

Attributes

Operations
- RuntimeType():

RuntimeTypeAdapterFactory<T>

Attributes

Operations
RuntimeTypeAdapterFactory(Class<?>, String):
+ of(Class<T>, String): RuntimeTypeAdapterFactory<T>
+ create(Gson, TypeToken<R>): TypeAdapter<R>
+ of(Class<T>): RuntimeTypeAdapterFactory<T>
+ registerSubtype(Class<T>, String): RuntimeTypeAdapterFactory<T>
+ registerSubtype(Class<T>): RuntimeTypeAdapterFactory<T>

RuntimeTypeAdapterFactoryFunctionalTest

Attributes

Operations
+ RuntimeTypeAdapterFactoryFunctionalTest():
+ testSubclassesAutomaticallySerialized(): void

RuntimeTypeAdapterFactoryTest

Attributes

Operations
+ RuntimeTypeAdapterFactoryTest():
+ setUp(): void
+ testBasicSerialization(): void
+ testMissingTypeField(): void
+ testBasicDeserialization(): void
+ testUnregisteredType(): void

SampleObjectForTest

Attributes

Operations
+ SampleObjectForTest(int, String, long):
+ SampleObjectForTest():

Sandwich

Attributes

Operations
+ Sandwich(String, String):
+ hashCode(): int
- validate(): void
+ equals(Object): boolean

SerializationBenchmark

Attributes

Operations
+ SerializationBenchmark():
+ main(String[]): void
+ timeObjectSerialization(int): void
~ setUp(): void

SerializedName

Attributes

Operations
+ value(): String
+ alternate(): String[]

SerializedNameTest

Attributes

Operations
+ SerializedNameTest():
+ testMultipleNamesDeserializedCorrectly(): void
+ testMultipleNamesInTheSameString(): void
+ testFirstNameIsChosenForSerialization(): void

Serializer

Attributes

Operations
~ Serializer():
+ serialize(DummyClass, Type, JsonSerializationContext): JsonElement

Serializer

Attributes

Operations
+ Serializer():
+ Serializer(String):
+ serialize(CreatedByInstanceCreator, Type, ...): JsonElement

Serializer

Attributes

Operations
~ Serializer():
+ serialize(List<Integer>, Type, JsonSerializationContext): JsonElement

Serializer

Attributes

Operations
+ Serializer(int):
+ serialize(CreatedByJdkUnsafe, Type, ...): JsonElement

Serializer

Attributes

Operations
~ Serializer():
+ serialize(WithJsonSerializer, Type, ...): JsonElement

SetCollection<T>

Attributes

Operations
- SetCollection():

Shape

Attributes

Operations
~ Shape(ShapeType):

ShapeType

Attributes

Operations
- ShapeType():
+ values(): ShapeType[]
+ valueOf(String): ShapeType

SimpleProto

Attributes

- DEFAULT_INSTANCE: SimpleProto
DEFAULT_INSTANCE: SimpleProto
msgBytes: ByteString
serializedSize: int
parserForType: Parser<SimpleProto>
defaultInstanceForType: SimpleProto
count: int
descriptor: Descriptor
msg: String
initialized: boolean

Operations
- SimpleProto(Builder<?>):
- SimpleProto():
+ parseFrom(CodedInputStream): SimpleProto
+ toBuilder(): Builder
+ hasCount(): boolean
+ equals(Object): boolean
+ hasMsg(): boolean
+ parseFrom(ByteBuffer): SimpleProto
+ parseFrom(InputStream, ExtensionRegistryLite): SimpleProto
+ newBuilder(): Builder
+ newBuilderForType(): Builder
+ parseFrom(CodedInputStream, ExtensionRegistryLite): SimpleProto
# internalGetFieldAccessorTable(): FieldAccessorTable
+ parseFrom(ByteString, ExtensionRegistryLite): SimpleProto
+ parser(): Parser<SimpleProto>
+ hashCode(): int
+ writeTo(CodedOutputStream): void
# newBuilderForType(BuilderParent): Builder
+ parseDelimitedFrom(InputStream, ExtensionRegistryLite): SimpleProto
+ newBuilder(SimpleProto): Builder
+ parseDelimitedFrom(InputStream): SimpleProto
+ parseFrom(InputStream): SimpleProto
+ parseFrom(ByteString): SimpleProto
+ parseFrom(byte[]): SimpleProto
+ parseFrom(byte[], ExtensionRegistryLite): SimpleProto
+ parseFrom(ByteBuffer, ExtensionRegistryLite): SimpleProto

SimpleProtoOrBuilder

<<interface>>

Attributes

msgBytes: ByteString
count: int
msg: String
Operations
+ hasMsg(): boolean
+ hasCount(): boolean

Since

Attributes

Operations
+ value(): double

SinceUntilMixing

Attributes

Operations
- SinceUntilMixing():

SmallClass

Attributes

Operations
- SmallClass():

SomeInterface

<<interface>>

Attributes

Operations

SomeInterfaceInstanceCreator

Attributes

Operations
- SomeInterfaceInstanceCreator():
+ createInstance(Type): SomeInterface

SomeObject

Attributes

Operations
- SomeObject():

SqlTypesSupport

Attributes

Operations
- SqlTypesSupport():
- checkSqlTypesSupport(): boolean
- createTimestampDateType(): DateType<Date>
- createSqlDateType(): DateType<Date>

SqlTypesSupportTest

Attributes

Operations
+ SqlTypesSupportTest():
+ testSupported(): void

Square

Attributes

Operations
~ Square(int):

StaticNestedClass

Attributes

Operations
~ StaticNestedClass():

StreamingTypeAdaptersTest

Attributes

Operations
+ StreamingTypeAdaptersTest():
+ testSerializeRecursive(): void
+ testDeserialize1dArray(): void
+ testNullSafe(): void
+ testDeserializeNullField(): void
+ testSerialize2dArray(): void
+ testSerializeNullObject(): void
+ testFromJsonTree(): void
+ testDeserialize2dArray(): void
+ testSerialize(): void
+ testDeserialize(): void
- usePersonNameAdapter(): void
+ testSerializeMap(): void
+ testDeserializeMap(): void
+ testSerializeWithCustomTypeAdapter(): void
+ testDeserializeWithCustomTypeAdapter(): void
+ testSerializeNullField(): void
+ testDeserializeNullObject(): void
+ testSerialize1dArray(): void

Streams

Attributes

Operations
- Streams():
+ parse(JsonReader): JsonElement
+ writerForAppendable(Appendable): Writer
+ write(JsonElement, JsonWriter): void

StreamsTest

Attributes

Operations
+ StreamsTest():
+ testWriterForAppendable(): void

Strictness

Attributes

Operations
- Strictness():
+ values(): Strictness[]
+ valueOf(String): Strictness

StringHolder

Attributes

Operations
+ StringHolder(String):
+ StringHolder(String, String):

StringHolderTypeAdapter

Attributes

Operations
- StringHolderTypeAdapter():
+ createInstance(Type): StringHolder
+ deserialize(JsonElement, Type, JsonDeserializationContext): StringHolder
+ serialize(StringHolder, Type, JsonSerializationContext): JsonElement

StringWrapper

Attributes

Operations
+ StringWrapper(String):

Student

Attributes

Operations
+ Student(Id<Student>, String):
- Student():

Sub

Attributes

Operations
~ Sub(int, int):

Sub

Attributes

Operations
+ Sub():

SubSerializer

Attributes

Operations
+ SubSerializer():
+ serialize(Sub, Type, JsonSerializationContext): JsonElement

SubTestClass

Attributes

Operations
- SubTestClass():

SubType1

Attributes

Operations
- SubType1():

SubType2

Attributes

Operations
- SubType2():

SubTypeOfBagOfPrimitives

Attributes

Operations
+ SubTypeOfBagOfPrimitives(long, int, boolean, String, float):

SubTypeOfNested

Attributes

Operations
+ SubTypeOfNested(BagOfPrimitives, BagOfPrimitives):
+ appendFields(StringBuilder): void

SubTypes

Attributes

subclass: Type
Operations
- SubTypes(Type):
+ valueOf(String): SubTypes
+ values(): SubTypes[]

SuperTestClass

Attributes

Operations
- SuperTestClass():

TestClassHasArgsConstructor

Attributes

Operations
+ TestClassHasArgsConstructor(String):

TestClassNoArgsConstructor

Attributes

Operations
~ TestClassNoArgsConstructor():

TestClassNotAbstract

Attributes

Operations
~ TestClassNotAbstract():

TestEnum

Attributes

Operations
- TestEnum():
+ values(): TestEnum[]
+ valueOf(String): TestEnum

TestEnumSetCollection

Attributes

Operations
- TestEnumSetCollection():

TestType2<X, Y>

Attributes

Operations
- TestType2():

TestType<X>

Attributes

Operations
- TestType():

TestTypeAdapter

Attributes

Operations
- TestTypeAdapter():
+ write(JsonWriter, Object): void
+ read(JsonReader): Object

TestTypes

Attributes

Operations
- TestTypes():

ToNumberPolicy

Attributes

Operations
- ToNumberPolicy():
+ valueOf(String): ToNumberPolicy
+ values(): ToNumberPolicy[]

ToNumberStrategy

<<interface>>

Attributes

Operations
+ readNumber(JsonReader): Number

TreeTypeAdaptersTest

Attributes

Operations
+ TreeTypeAdaptersTest():
+ testSerializeId(): void
+ setUp(): void
+ testDeserializeId(): void

TroubleshootingGuide

Attributes

Operations
- TroubleshootingGuide():
+ createUrl(String): String

Truck

Attributes

Operations
~ Truck():

Tweet

Attributes

Operations
~ Tweet():

Type

Attributes

descriptor: EnumDescriptor
number: int
descriptorForType: EnumDescriptor
valueDescriptor: EnumValueDescriptor
Operations
- Type(int):
+ forNumber(int): Type?
+ values(): Type[]
+ valueOf(int): Type
+ internalGetValueMap(): EnumLiteMap<Type>
+ valueOf(EnumValueDescriptor): Type
+ valueOf(String): Type

TypeAdapterTest

Attributes

Operations
+ TypeAdapterTest():
+ testToJson_ThrowingIOException(): void
+ testFromJson_String_TrailingData(): void
+ testNullSafe_ReturningSameInstanceOnceNullSafe(): void
+ testNullSafe(): void
+ testFromJson_Reader_TrailingData(): void
+ testNullSafe_ToString(): void

TypeHierarchyAdapterTest

Attributes

Operations
+ TypeHierarchyAdapterTest():
+ testRegisterSuperTypeFirst(): void
+ testRegisterSubTypeFirstAllowed(): void
+ testTypeHierarchy(): void

TypeVariableTest

Attributes

Operations
+ TypeVariableTest(T):
+ method(): T

UncategorizedTest

Attributes

Operations
+ UncategorizedTest():
+ testStaticFieldsAreNotSerialized(): void
+ testInvalidJsonDeserializationFails(): void
+ testGsonInstanceReusableForSerializationAndDeserialization(...): void
+ setUp(): void
+ testTrailingWhitespace(): void
+ testObjectEqualButNotSameSerialization(): void
+ testReturningDerivedClassesDuringDeserialization(): void

UnreadableReader

Attributes

Operations
- UnreadableReader():
+ close(): void
+ read(char[], int, int): int

UnsafeAllocator

Attributes

Operations
- UnsafeAllocator():
- create(): UnsafeAllocator
- assertInstantiable(Class<?>): void
+ newInstance(Class<T>): T

UnsafeAllocatorInstantiationTest

Attributes

Operations
+ UnsafeAllocatorInstantiationTest():
+ testAbstractClassInstantiation(): void
+ testConcreteClassInstantiation(): void
+ testInterfaceInstantiation(): void

UnusedClass

Attributes

Operations
+ UnusedClass():

User

Attributes

Operations
- User(String):

User

Attributes

Operations
+ User(String, String):

User

Attributes

Operations
~ User():

User2

Attributes

Operations
- User2(String):

UserDeserializer

Attributes

Operations
- UserDeserializer():
+ deserialize(JsonElement, Type, JsonDeserializationContext): User

UserGroup

Attributes

Operations
- UserGroup():

UserSerializer

Attributes

Operations
- UserSerializer():
+ serialize(User, Type, JsonSerializationContext): JsonElement

UserSerializerDeserializer

Attributes

Operations
- UserSerializerDeserializer():
+ serialize(User, Type, JsonSerializationContext): JsonElement
+ deserialize(JsonElement, Type, JsonDeserializationContext): User

UserSerializerDeserializer2

Attributes

Operations
- UserSerializerDeserializer2():
+ serialize(User2, Type, JsonSerializationContext): JsonElement
+ deserialize(JsonElement, Type, JsonDeserializationContext): User2

UserValidator

Attributes

Operations
+ UserValidator():
+ postDeserialize(User): void

UtcDateTypeAdapterTest

Attributes

Operations
+ UtcDateTypeAdapterTest():
+ testNullValue(): void
+ testDeserializeDate(): void
+ setUp(): void
+ testDeserializeWithoutMillis(): void
+ testDeserializeWithTimeZoneOffset(): void
+ testSerializeDate(): void
+ testInvalidFormat(): void

Version1

Attributes

Operations
- Version1():

Version1_1

Attributes

Operations

- Version1_1(): Version1_2

Attributes

Operations
- Version1_2():

VersionExclusionStrategyTest

Attributes

Operations
+ VersionExclusionStrategyTest():
- assertExcludesClass(Excluder, Class<?>): void
- assertIncludesField(Excluder, Field): void
+ testSameVersion(): void
- assertExcludesField(Excluder, Field): void
+ testNewerVersion(): void
- assertIncludesClass(Excluder, Class<?>): void
+ testOlderVersion(): void

VersioningTest

Attributes

Operations
+ VersioningTest():
+ testVersionedClassesSerialization(): void
+ testVersionedGsonWithUnversionedClassesDeserialization(): void
+ testVersionedGsonWithUnversionedClassesSerialization(): void
+ testVersionedGsonMixingSinceAndUntilDeserialization(): void
+ testIgnoreLaterVersionClassDeserialization(): void
+ testVersionedUntilDeserialization(): void
+ testIgnoreLaterVersionClassSerialization(): void
+ testVersionedClassesDeserialization(): void
- gsonWithVersion(double): Gson
+ testVersionedGsonMixingSinceAndUntilSerialization(): void
+ testVersionedUntilSerialization(): void

WithDelayedDelegatingFactory

Attributes

Operations
- WithDelayedDelegatingFactory():

WithDelegatingFactory<T>

Attributes

Operations
- WithDelegatingFactory():

WithJsonDeserializer

Attributes

Operations
~ WithJsonDeserializer(List<Integer>):

WithJsonSerializer

Attributes

Operations
- WithJsonSerializer():

WithNullSafe

Attributes

Operations
~ WithNullSafe(User, User, User, User):