File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMARTCITY

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main ⊗ 0 ⚠ 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main ⊗ 0 ⚠ 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main ⊗ 0 ⚠ 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main ⊗ 0 ⚠ 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main ⊗ 0 ⚠ 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main ⊗ 0 ⚠ 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main ⊗ 0 ⚠ 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

C:\projects\smartcity\backend

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

C:\projects\smartcity\backend

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main ⊗ 0 ⚠ 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main ⊗ 0 ⚠ 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main ⊗ 0 ⚠ 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main ⊗ 0 ⚠ 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

Show All Commands Ctrl + Shift + P

Go to File Ctrl + P

Open Chat Ctrl + Alt + I

Find in Files Ctrl + Shift + F

Start Debugging F5

main 0 0

Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

test.py

backend > ai_model > test.py > ...

```python
import google.generativeai as genai
import os

# ✅ Configure Gemini
genai.configure(api_key=os.getenv("GOOGLE_API_KEY"))
model = genai.GenerativeModel('gemini-1.5-flash')

# ✅ Generate Eco Tips
def gentip(keyword: str) -> str:
    prompt = f"Give one practical eco-friendly tip related to: {keyword}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Answer General Query
def answer_q(query: str) -> str:
    prompt = f"Answer this question concisely: {query}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Summarize Text
def summarize_text(text: str) -> str:
    prompt = f"Summarize the following policy/document:\n\n{text}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Forecast KPI (based on natural language)
def forecast_kpi_description(kpi_csv_summary: str) -> str:
    prompt = f"Given this KPI trend summary, predict the next logical value or trend:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Detect Anomalies Description
def detect_anomalies_description(kpi_csv_summary: str) -> str:
    prompt = f"Analyze the following KPI data and highlight any potential anomalies:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()
```

main ⊗ 0 ⚠ 0 Ln 5, Col 53 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

test.py

backend > ai_model > test.py > ...

```python
import google.generativeai as genai
import os

# ✅ Configure Gemini
genai.configure(api_key=os.getenv("GOOGLE_API_KEY"))
model = genai.GenerativeModel('gemini-1.5-flash')

# ✅ Generate Eco Tips
def gentip(keyword: str) -> str:
    prompt = f"Give one practical eco-friendly tip related to: {keyword}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Answer General Query
def answer_q(query: str) -> str:
    prompt = f"Answer this question concisely: {query}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Summarize Text
def summarize_text(text: str) -> str:
    prompt = f"Summarize the following policy/document:\n\n{text}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Forecast KPI (based on natural language)
def forecast_kpi_description(kpi_csv_summary: str) -> str:
    prompt = f"Given this KPI trend summary, predict the next logical value or trend:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Detect Anomalies Description
def detect_anomalies_description(kpi_csv_summary: str) -> str:
    prompt = f"Analyze the following KPI data and highlight any potential anomalies:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()
```

main ⊗ 0 ⚠ 0 Ln 5, Col 53 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

test.py

backend > ai_model > test.py > ...

```python
import google.generativeai as genai
import os

# ✅ Configure Gemini
genai.configure(api_key=os.getenv("GOOGLE_API_KEY"))
model = genai.GenerativeModel('gemini-1.5-flash')

# ✅ Generate Eco Tips
def gentip(keyword: str) -> str:
    prompt = f"Give one practical eco-friendly tip related to: {keyword}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Answer General Query
def answer_q(query: str) -> str:
    prompt = f"Answer this question concisely: {query}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Summarize Text
def summarize_text(text: str) -> str:
    prompt = f"Summarize the following policy/document:\n\n{text}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Forecast KPI (based on natural language)
def forecast_kpi_description(kpi_csv_summary: str) -> str:
    prompt = f"Given this KPI trend summary, predict the next logical value or trend:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Detect Anomalies Description
def detect_anomalies_description(kpi_csv_summary: str) -> str:
    prompt = f"Analyze the following KPI data and highlight any potential anomalies:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()
```

main ⊗ 0 ⚠ 0 PAVANTECH-06 (3 minutes ago) Ln 5, Col 53 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

test.py

backend > ai_model > test.py > ...

```python
import google.generativeai as genai
import os

# ✅ Configure Gemini
genai.configure(api_key=os.getenv("GOOGLE_API_KEY"))
model = genai.GenerativeModel('gemini-1.5-flash')

# ✅ Generate Eco Tips
def gentip(keyword: str) -> str:
    prompt = f"Give one practical eco-friendly tip related to: {keyword}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Answer General Query
def answer_q(query: str) -> str:
    prompt = f"Answer this question concisely: {query}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Summarize Text
def summarize_text(text: str) -> str:
    prompt = f"Summarize the following policy/document:\n\n{text}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Forecast KPI (based on natural language)
def forecast_kpi_description(kpi_csv_summary: str) -> str:
    prompt = f"Given this KPI trend summary, predict the next logical value or trend:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Detect Anomalies Description
def detect_anomalies_description(kpi_csv_summary: str) -> str:
    prompt = f"Analyze the following KPI data and highlight any potential anomalies:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()
```

main ⊗ 0 ⚠ 0 PAVANTECH-06 (3 minutes ago) Ln 5, Col 53 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

test.py

backend > ai_model > test.py > ...

```python
import google.generativeai as genai
import os

# ✅ Configure Gemini
genai.configure(api_key=os.getenv("GOOGLE_API_KEY"))
model = genai.GenerativeModel('gemini-1.5-flash')

# ✅ Generate Eco Tips
def gentip(keyword: str) -> str:
    prompt = f"Give one practical eco-friendly tip related to: {keyword}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Answer General Query
def answer_q(query: str) -> str:
    prompt = f"Answer this question concisely: {query}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Summarize Text
def summarize_text(text: str) -> str:
    prompt = f"Summarize the following policy/document:\n\n{text}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Forecast KPI (based on natural language)
def forecast_kpi_description(kpi_csv_summary: str) -> str:
    prompt = f"Given this KPI trend summary, predict the next logical value or trend:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Detect Anomalies Description
def detect_anomalies_description(kpi_csv_summary: str) -> str:
    prompt = f"Analyze the following KPI data and highlight any potential anomalies:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()
```

main ⊗ 0 ⚠ 0 PAVANTECH-06 (3 minutes ago) Ln 5, Col 53 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

test.py

backend > ai_model > test.py > ...

```python
import google.generativeai as genai
import os

# ✅ Configure Gemini
genai.configure(api_key=os.getenv("GOOGLE_API_KEY"))
model = genai.GenerativeModel('gemini-1.5-flash')

# ✅ Generate Eco Tips
def gentip(keyword: str) -> str:
    prompt = f"Give one practical eco-friendly tip related to: {keyword}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Answer General Query
def answer_q(query: str) -> str:
    prompt = f"Answer this question concisely: {query}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Summarize Text
def summarize_text(text: str) -> str:
    prompt = f"Summarize the following policy/document:\n\n{text}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Forecast KPI (based on natural language)
def forecast_kpi_description(kpi_csv_summary: str) -> str:
    prompt = f"Given this KPI trend summary, predict the next logical value or trend:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Detect Anomalies Description
def detect_anomalies_description(kpi_csv_summary: str) -> str:
    prompt = f"Analyze the following KPI data and highlight any potential anomalies:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()
```

main ⊗ 0 ⚠ 0 PAVANTECH-06 (3 minutes ago) Ln 5, Col 53 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

test.py

backend > ai_model > test.py > ...

```python
import google.generativeai as genai
import os

# ✅ Configure Gemini
genai.configure(api_key=os.getenv("GOOGLE_API_KEY"))
model = genai.GenerativeModel('gemini-1.5-flash')

# ✅ Generate Eco Tips
def gentip(keyword: str) -> str:
    prompt = f"Give one practical eco-friendly tip related to: {keyword}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Answer General Query
def answer_q(query: str) -> str:
    prompt = f"Answer this question concisely: {query}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Summarize Text
def summarize_text(text: str) -> str:
    prompt = f"Summarize the following policy/document:\n\n{text}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Forecast KPI (based on natural language)
def forecast_kpi_description(kpi_csv_summary: str) -> str:
    prompt = f"Given this KPI trend summary, predict the next logical value or trend:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Detect Anomalies Description
def detect_anomalies_description(kpi_csv_summary: str) -> str:
    prompt = f"Analyze the following KPI data and highlight any potential anomalies:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()
```

main ⊗ 0 ⚠ 0 PAVANTECH-06 (3 minutes ago) Ln 5, Col 53 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

test.py

backend > ai_model > test.py > ...

```python
import google.generativeai as genai
import os

# ✅ Configure Gemini
genai.configure(api_key=os.getenv("GOOGLE_API_KEY"))
model = genai.GenerativeModel('gemini-1.5-flash')

# ✅ Generate Eco Tips
def gentip(keyword: str) -> str:
    prompt = f"Give one practical eco-friendly tip related to: {keyword}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Answer General Query
def answer_q(query: str) -> str:
    prompt = f"Answer this question concisely: {query}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Summarize Text
def summarize_text(text: str) -> str:
    prompt = f"Summarize the following policy/document:\n\n{text}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Forecast KPI (based on natural language)
def forecast_kpi_description(kpi_csv_summary: str) -> str:
    prompt = f"Given this KPI trend summary, predict the next logical value or trend:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Detect Anomalies Description
def detect_anomalies_description(kpi_csv_summary: str) -> str:
    prompt = f"Analyze the following KPI data and highlight any potential anomalies:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()
```

main ⊗ 0 ⚠ 0 PAVANTECH-06 (3 minutes ago) Ln 5, Col 53 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

test.py

backend > ai_model > test.py > ...

```python
import google.generativeai as genai
import os

# ✅ Configure Gemini
genai.configure(api_key=os.getenv("GOOGLE_API_KEY"))
model = genai.GenerativeModel('gemini-1.5-flash')

# ✅ Generate Eco Tips
def gentip(keyword: str) -> str:
    prompt = f"Give one practical eco-friendly tip related to: {keyword}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Answer General Query
def answer_q(query: str) -> str:
    prompt = f"Answer this question concisely: {query}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Summarize Text
def summarize_text(text: str) -> str:
    prompt = f"Summarize the following policy/document:\n\n{text}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Forecast KPI (based on natural language)
def forecast_kpi_description(kpi_csv_summary: str) -> str:
    prompt = f"Given this KPI trend summary, predict the next logical value or trend:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Detect Anomalies Description
def detect_anomalies_description(kpi_csv_summary: str) -> str:
    prompt = f"Analyze the following KPI data and highlight any potential anomalies:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()
```

main ⊗ 0 ⚠ 0 PAVANTECH-06 (3 minutes ago) Ln 5, Col 53 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

test.py

backend > ai_model > test.py > ...

```python
import google.generativeai as genai
import os

# ✅ Configure Gemini
genai.configure(api_key=os.getenv("GOOGLE_API_KEY"))
model = genai.GenerativeModel('gemini-1.5-flash')

# ✅ Generate Eco Tips
def gentip(keyword: str) -> str:
    prompt = f"Give one practical eco-friendly tip related to: {keyword}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Answer General Query
def answer_q(query: str) -> str:
    prompt = f"Answer this question concisely: {query}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Summarize Text
def summarize_text(text: str) -> str:
    prompt = f"Summarize the following policy/document:\n\n{text}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Forecast KPI (based on natural language)
def forecast_kpi_description(kpi_csv_summary: str) -> str:
    prompt = f"Given this KPI trend summary, predict the next logical value or trend:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Detect Anomalies Description
def detect_anomalies_description(kpi_csv_summary: str) -> str:
    prompt = f"Analyze the following KPI data and highlight any potential anomalies:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()
```

main ⊗ 0 ⚠ 0 PAVANTECH-06 (3 minutes ago) Ln 5, Col 53 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

test.py

backend > ai_model > test.py > ...

```python
import google.generativeai as genai
import os

# ✅ Configure Gemini
genai.configure(api_key=os.getenv("GOOGLE_API_KEY"))
model = genai.GenerativeModel('gemini-1.5-flash')

# ✅ Generate Eco Tips
def gentip(keyword: str) -> str:
    prompt = f"Give one practical eco-friendly tip related to: {keyword}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Answer General Query
def answer_q(query: str) -> str:
    prompt = f"Answer this question concisely: {query}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Summarize Text
def summarize_text(text: str) -> str:
    prompt = f"Summarize the following policy/document:\n\n{text}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Forecast KPI (based on natural language)
def forecast_kpi_description(kpi_csv_summary: str) -> str:
    prompt = f"Given this KPI trend summary, predict the next logical value or trend:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Detect Anomalies Description
def detect_anomalies_description(kpi_csv_summary: str) -> str:
    prompt = f"Analyze the following KPI data and highlight any potential anomalies:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()
```

main ⊗ 0 ⚠ 0 PAVANTECH-06 (3 minutes ago) Ln 5, Col 53 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

test.py

backend > ai_model > test.py > ...

```python
import google.generativeai as genai
import os

# ✅ Configure Gemini
genai.configure(api_key=os.getenv("GOOGLE_API_KEY"))
model = genai.GenerativeModel('gemini-1.5-flash')

# ✅ Generate Eco Tips
def gentip(keyword: str) -> str:
    prompt = f"Give one practical eco-friendly tip related to: {keyword}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Answer General Query
def answer_q(query: str) -> str:
    prompt = f"Answer this question concisely: {query}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Summarize Text
def summarize_text(text: str) -> str:
    prompt = f"Summarize the following policy/document:\n\n{text}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Forecast KPI (based on natural language)
def forecast_kpi_description(kpi_csv_summary: str) -> str:
    prompt = f"Given this KPI trend summary, predict the next logical value or trend:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Detect Anomalies Description
def detect_anomalies_description(kpi_csv_summary: str) -> str:
    prompt = f"Analyze the following KPI data and highlight any potential anomalies:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()
```

main ⊗ 0 ⚠ 0 PAVANTECH-06 (3 minutes ago) Ln 5, Col 53 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

test.py

backend > ai_model > test.py > ...

```python
import google.generativeai as genai
import os

# ✅ Configure Gemini
genai.configure(api_key=os.getenv("GOOGLE_API_KEY"))
model = genai.GenerativeModel('gemini-1.5-flash')

# ✅ Generate Eco Tips
def gentip(keyword: str) -> str:
    prompt = f"Give one practical eco-friendly tip related to: {keyword}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Answer General Query
def answer_q(query: str) -> str:
    prompt = f"Answer this question concisely: {query}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Summarize Text
def summarize_text(text: str) -> str:
    prompt = f"Summarize the following policy/document:\n\n{text}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Forecast KPI (based on natural language)
def forecast_kpi_description(kpi_csv_summary: str) -> str:
    prompt = f"Given this KPI trend summary, predict the next logical value or trend:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Detect Anomalies Description
def detect_anomalies_description(kpi_csv_summary: str) -> str:
    prompt = f"Analyze the following KPI data and highlight any potential anomalies:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()
```

main ⊗ 0 ⚠ 0 PAVANTECH-06 (3 minutes ago) Ln 5, Col 53 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

test.py

backend > ai_model > test.py > ...

```python
import google.generativeai as genai
import os

# ✅ Configure Gemini
genai.configure(api_key=os.getenv("GOOGLE_API_KEY"))
model = genai.GenerativeModel('gemini-1.5-flash')

# ✅ Generate Eco Tips
def gentip(keyword: str) -> str:
    prompt = f"Give one practical eco-friendly tip related to: {keyword}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Answer General Query
def answer_q(query: str) -> str:
    prompt = f"Answer this question concisely: {query}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Summarize Text
def summarize_text(text: str) -> str:
    prompt = f"Summarize the following policy/document:\n\n{text}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Forecast KPI (based on natural language)
def forecast_kpi_description(kpi_csv_summary: str) -> str:
    prompt = f"Given this KPI trend summary, predict the next logical value or trend:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Detect Anomalies Description
def detect_anomalies_description(kpi_csv_summary: str) -> str:
    prompt = f"Analyze the following KPI data and highlight any potential anomalies:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()
```

main ⊗ 0 ⚠ 0 PAVANTECH-06 (3 minutes ago) Ln 5, Col 53 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

test.py

backend > ai_model > test.py > ...

```python
import google.generativeai as genai
import os

# ✅ Configure Gemini
genai.configure(api_key=os.getenv("GOOGLE_API_KEY"))
model = genai.GenerativeModel('gemini-1.5-flash')

# ✅ Generate Eco Tips
def gentip(keyword: str) -> str:
    prompt = f"Give one practical eco-friendly tip related to: {keyword}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Answer General Query
def answer_q(query: str) -> str:
    prompt = f"Answer this question concisely: {query}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Summarize Text
def summarize_text(text: str) -> str:
    prompt = f"Summarize the following policy/document:\n\n{text}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Forecast KPI (based on natural language)
def forecast_kpi_description(kpi_csv_summary: str) -> str:
    prompt = f"Given this KPI trend summary, predict the next logical value or trend:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Detect Anomalies Description
def detect_anomalies_description(kpi_csv_summary: str) -> str:
    prompt = f"Analyze the following KPI data and highlight any potential anomalies:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()
```

main ⊗ 0 ⚠ 0 PAVANTECH-06 (3 minutes ago) Ln 5, Col 53 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

test.py

backend > ai_model > test.py > ...

```python
import google.generativeai as genai
import os

# ✅ Configure Gemini
genai.configure(api_key=os.getenv("GOOGLE_API_KEY"))
model = genai.GenerativeModel('gemini-1.5-flash')

# ✅ Generate Eco Tips
def gentip(keyword: str) -> str:
    prompt = f"Give one practical eco-friendly tip related to: {keyword}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Answer General Query
def answer_q(query: str) -> str:
    prompt = f"Answer this question concisely: {query}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Summarize Text
def summarize_text(text: str) -> str:
    prompt = f"Summarize the following policy/document:\n\n{text}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Forecast KPI (based on natural language)
def forecast_kpi_description(kpi_csv_summary: str) -> str:
    prompt = f"Given this KPI trend summary, predict the next logical value or trend:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Detect Anomalies Description
def detect_anomalies_description(kpi_csv_summary: str) -> str:
    prompt = f"Analyze the following KPI data and highlight any potential anomalies:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()
```

main ⊗ 0 ⚠ 0 PAVANTECH-06 (3 minutes ago) Ln 5, Col 53 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

test.py

backend > ai_model > test.py > ...

```python
import google.generativeai as genai
import os

# ✅ Configure Gemini
genai.configure(api_key=os.getenv("GOOGLE_API_KEY"))
model = genai.GenerativeModel('gemini-1.5-flash')

# ✅ Generate Eco Tips
def gentip(keyword: str) -> str:
    prompt = f"Give one practical eco-friendly tip related to: {keyword}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Answer General Query
def answer_q(query: str) -> str:
    prompt = f"Answer this question concisely: {query}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Summarize Text
def summarize_text(text: str) -> str:
    prompt = f"Summarize the following policy/document:\n\n{text}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Forecast KPI (based on natural language)
def forecast_kpi_description(kpi_csv_summary: str) -> str:
    prompt = f"Given this KPI trend summary, predict the next logical value or trend:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Detect Anomalies Description
def detect_anomalies_description(kpi_csv_summary: str) -> str:
    prompt = f"Analyze the following KPI data and highlight any potential anomalies:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()
```

main ⊗ 0 ⚠ 0 PAVANTECH-06 (3 minutes ago) Ln 5, Col 53 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

test.py

backend > ai_model > test.py > ...

```python
import google.generativeai as genai
import os

# ✅ Configure Gemini
genai.configure(api_key=os.getenv("GOOGLE_API_KEY"))
model = genai.GenerativeModel('gemini-1.5-flash')

# ✅ Generate Eco Tips
def gentip(keyword: str) -> str:
    prompt = f"Give one practical eco-friendly tip related to: {keyword}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Answer General Query
def answer_q(query: str) -> str:
    prompt = f"Answer this question concisely: {query}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Summarize Text
def summarize_text(text: str) -> str:
    prompt = f"Summarize the following policy/document:\n\n{text}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Forecast KPI (based on natural language)
def forecast_kpi_description(kpi_csv_summary: str) -> str:
    prompt = f"Given this KPI trend summary, predict the next logical value or trend:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Detect Anomalies Description
def detect_anomalies_description(kpi_csv_summary: str) -> str:
    prompt = f"Analyze the following KPI data and highlight any potential anomalies:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()
```

main ⊗ 0 ⚠ 0 PAVANTECH-06 (3 minutes ago) Ln 5, Col 53 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

test.py

backend > ai_model > test.py > ...

```python
import google.generativeai as genai
import os

# ✅ Configure Gemini
genai.configure(api_key=os.getenv("GOOGLE_API_KEY"))
model = genai.GenerativeModel('gemini-1.5-flash')

# ✅ Generate Eco Tips
def gentip(keyword: str) -> str:
    prompt = f"Give one practical eco-friendly tip related to: {keyword}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Answer General Query
def answer_q(query: str) -> str:
    prompt = f"Answer this question concisely: {query}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Summarize Text
def summarize_text(text: str) -> str:
    prompt = f"Summarize the following policy/document:\n\n{text}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Forecast KPI (based on natural language)
def forecast_kpi_description(kpi_csv_summary: str) -> str:
    prompt = f"Given this KPI trend summary, predict the next logical value or trend:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Detect Anomalies Description
def detect_anomalies_description(kpi_csv_summary: str) -> str:
    prompt = f"Analyze the following KPI data and highlight any potential anomalies:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()
```

main ⊗ 0 ⚠ 0 PAVANTECH-06 (3 minutes ago) Ln 5, Col 53 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

test.py

backend > ai_model > test.py > ...

```python
import google.generativeai as genai
import os

# ✅ Configure Gemini
genai.configure(api_key=os.getenv("GOOGLE_API_KEY"))
model = genai.GenerativeModel('gemini-1.5-flash')

# ✅ Generate Eco Tips
def gentip(keyword: str) -> str:
    prompt = f"Give one practical eco-friendly tip related to: {keyword}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Answer General Query
def answer_q(query: str) -> str:
    prompt = f"Answer this question concisely: {query}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Summarize Text
def summarize_text(text: str) -> str:
    prompt = f"Summarize the following policy/document:\n\n{text}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Forecast KPI (based on natural language)
def forecast_kpi_description(kpi_csv_summary: str) -> str:
    prompt = f"Given this KPI trend summary, predict the next logical value or trend:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Detect Anomalies Description
def detect_anomalies_description(kpi_csv_summary: str) -> str:
    prompt = f"Analyze the following KPI data and highlight any potential anomalies:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()
```

main ⊗ 0 ⚠ 0 PAVANTECH-06 (3 minutes ago) Ln 5, Col 53 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

test.py

backend > ai_model > test.py > ...

```python
import google.generativeai as genai
import os

# ✅ Configure Gemini
genai.configure(api_key=os.getenv("GOOGLE_API_KEY"))
model = genai.GenerativeModel('gemini-1.5-flash')

# ✅ Generate Eco Tips
def gentip(keyword: str) -> str:
    prompt = f"Give one practical eco-friendly tip related to: {keyword}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Answer General Query
def answer_q(query: str) -> str:
    prompt = f"Answer this question concisely: {query}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Summarize Text
def summarize_text(text: str) -> str:
    prompt = f"Summarize the following policy/document:\n\n{text}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Forecast KPI (based on natural language)
def forecast_kpi_description(kpi_csv_summary: str) -> str:
    prompt = f"Given this KPI trend summary, predict the next logical value or trend:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Detect Anomalies Description
def detect_anomalies_description(kpi_csv_summary: str) -> str:
    prompt = f"Analyze the following KPI data and highlight any potential anomalies:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()
```

main ⊗ 0 ⚠ 0 PAVANTECH-06 (3 minutes ago) Ln 5, Col 53 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

test.py

backend > ai_model > test.py > ...

```python
import google.generativeai as genai
import os

# ✅ Configure Gemini
genai.configure(api_key=os.getenv("GOOGLE_API_KEY"))
model = genai.GenerativeModel('gemini-1.5-flash')

# ✅ Generate Eco Tips
def gentip(keyword: str) -> str:
    prompt = f"Give one practical eco-friendly tip related to: {keyword}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Answer General Query
def answer_q(query: str) -> str:
    prompt = f"Answer this question concisely: {query}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Summarize Text
def summarize_text(text: str) -> str:
    prompt = f"Summarize the following policy/document:\n\n{text}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Forecast KPI (based on natural language)
def forecast_kpi_description(kpi_csv_summary: str) -> str:
    prompt = f"Given this KPI trend summary, predict the next logical value or trend:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Detect Anomalies Description
def detect_anomalies_description(kpi_csv_summary: str) -> str:
    prompt = f"Analyze the following KPI data and highlight any potential anomalies:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()
```

main ⊗ 0 ⚠ 0 PAVANTECH-06 (3 minutes ago) Ln 5, Col 53 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

test.py

backend > ai_model > test.py > ...

```python
import google.generativeai as genai
import os

# ✅ Configure Gemini
genai.configure(api_key=os.getenv("GOOGLE_API_KEY"))
model = genai.GenerativeModel('gemini-1.5-flash')

# ✅ Generate Eco Tips
def gentip(keyword: str) -> str:
    prompt = f"Give one practical eco-friendly tip related to: {keyword}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Answer General Query
def answer_q(query: str) -> str:
    prompt = f"Answer this question concisely: {query}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Summarize Text
def summarize_text(text: str) -> str:
    prompt = f"Summarize the following policy/document:\n\n{text}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Forecast KPI (based on natural language)
def forecast_kpi_description(kpi_csv_summary: str) -> str:
    prompt = f"Given this KPI trend summary, predict the next logical value or trend:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Detect Anomalies Description
def detect_anomalies_description(kpi_csv_summary: str) -> str:
    prompt = f"Analyze the following KPI data and highlight any potential anomalies:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()
```

main ⊗ 0 ⚠ 0 PAVANTECH-06 (3 minutes ago) Ln 5, Col 53 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

test.py

backend > ai_model > test.py > ...

```python
import google.generativeai as genai
import os

# ✅ Configure Gemini
genai.configure(api_key=os.getenv("GOOGLE_API_KEY"))
model = genai.GenerativeModel('gemini-1.5-flash')

# ✅ Generate Eco Tips
def gentip(keyword: str) -> str:
    prompt = f"Give one practical eco-friendly tip related to: {keyword}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Answer General Query
def answer_q(query: str) -> str:
    prompt = f"Answer this question concisely: {query}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Summarize Text
def summarize_text(text: str) -> str:
    prompt = f"Summarize the following policy/document:\n\n{text}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Forecast KPI (based on natural language)
def forecast_kpi_description(kpi_csv_summary: str) -> str:
    prompt = f"Given this KPI trend summary, predict the next logical value or trend:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Detect Anomalies Description
def detect_anomalies_description(kpi_csv_summary: str) -> str:
    prompt = f"Analyze the following KPI data and highlight any potential anomalies:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()
```

main ⊗ 0 ⚠ 0 PAVANTECH-06 (3 minutes ago) Ln 5, Col 53 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

test.py

backend > ai_model > test.py > ...

```python
import google.generativeai as genai
import os

# ✅ Configure Gemini
genai.configure(api_key=os.getenv("GOOGLE_API_KEY"))
model = genai.GenerativeModel('gemini-1.5-flash')

# ✅ Generate Eco Tips
def gentip(keyword: str) -> str:
    prompt = f"Give one practical eco-friendly tip related to: {keyword}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Answer General Query
def answer_q(query: str) -> str:
    prompt = f"Answer this question concisely: {query}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Summarize Text
def summarize_text(text: str) -> str:
    prompt = f"Summarize the following policy/document:\n\n{text}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Forecast KPI (based on natural language)
def forecast_kpi_description(kpi_csv_summary: str) -> str:
    prompt = f"Given this KPI trend summary, predict the next logical value or trend:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Detect Anomalies Description
def detect_anomalies_description(kpi_csv_summary: str) -> str:
    prompt = f"Analyze the following KPI data and highlight any potential anomalies:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()
```

main ⊗ 0 ⚠ 0 PAVANTECH-06 (3 minutes ago) Ln 5, Col 53 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

test.py

backend > ai_model > test.py > ...

```python
import google.generativeai as genai
import os

# ✅ Configure Gemini
genai.configure(api_key=os.getenv("GOOGLE_API_KEY"))
model = genai.GenerativeModel('gemini-1.5-flash')

# ✅ Generate Eco Tips
def gentip(keyword: str) -> str:
    prompt = f"Give one practical eco-friendly tip related to: {keyword}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Answer General Query
def answer_q(query: str) -> str:
    prompt = f"Answer this question concisely: {query}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Summarize Text
def summarize_text(text: str) -> str:
    prompt = f"Summarize the following policy/document:\n\n{text}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Forecast KPI (based on natural language)
def forecast_kpi_description(kpi_csv_summary: str) -> str:
    prompt = f"Given this KPI trend summary, predict the next logical value or trend:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()

# ✅ Detect Anomalies Description
def detect_anomalies_description(kpi_csv_summary: str) -> str:
    prompt = f"Analyze the following KPI data and highlight any potential anomalies:\n\n{kpi_csv_summary}"
    response = model.generate_content(prompt)
    return response.text.strip()
```

main ⊗ 0 ⚠ 0 PAVANTECH-06 (3 minutes ago) Ln 5, Col 53 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_ge...py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

schemas.py

backend > models > schemas.py > ...

```python
from pydantic import BaseModel

class Feedback(BaseModel):
    name: str
    message: str
    category: str
```

main 0 0 Ln 7, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_ge...py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

schemas.py

backend > models > schemas.py > ...

```python
from pydantic import BaseModel

class Feedback(BaseModel):
    name: str
    message: str
    category: str
```

main 0 0 Ln 7, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_ge...py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

schemas.py

backend > models > schemas.py > ...

```python
from pydantic import BaseModel

class Feedback(BaseModel):
    name: str
    message: str
    category: str
```

main 0 0 Ln 7, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_ge...py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

schemas.py

backend > models > schemas.py > ...

```python
from pydantic import BaseModel

class Feedback(BaseModel):
    name: str
    message: str
    category: str
```

main 0 0 Ln 7, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

schemas.py

backend > models > schemas.py > ...

```python
from pydantic import BaseModel

class Feedback(BaseModel):
    name: str
    message: str
    category: str
```

main 0 0 Ln 7, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

schemas.py

backend > models > schemas.py > ...

```python
from pydantic import BaseModel

class Feedback(BaseModel):
    name: str
    message: str
    category: str
```

main 0 0 Ln 7, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

schemas.py

backend > models > schemas.py > ...

```python
from pydantic import BaseModel

class Feedback(BaseModel):
    name: str
    message: str
    category: str
```

main 0 0 Ln 7, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

schemas.py

backend > models > schemas.py > ...

```python
from pydantic import BaseModel

class Feedback(BaseModel):
    name: str
    message: str
    category: str
```

main 0 0 Ln 7, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

schemas.py

backend > models > schemas.py > ...

```python
from pydantic import BaseModel

class Feedback(BaseModel):
    name: str
    message: str
    category: str
```

main 0 0 Ln 7, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

schemas.py

backend > models > schemas.py > ...

```python
from pydantic import BaseModel

class Feedback(BaseModel):
    name: str
    message: str
    category: str
```

main 0 0 Ln 7, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

schemas.py

backend > models > schemas.py > ...

```python
from pydantic import BaseModel

class Feedback(BaseModel):
    name: str
    message: str
    category: str
```

main 0 0 Ln 7, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

main 0 0 Ln 7, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main 0 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main 0 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main 0 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main 0 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main 0 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main 0 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main 0 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - servic
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1   Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
    Start typing to dismiss or don't show this again.
```

main 0 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - servic
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main 0 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - service
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main 0 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - service
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main 0 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - service
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main 0 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - service
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main 0 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - servic
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main 0 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - servic
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main 0 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - servic
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main 0 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - servic
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main 0 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - servic
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main 0 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - servic
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main 0 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main 0 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main ⊗ 0 ⚠ 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main ⊗ 0 ⚠ 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main ⊗ 0 ⚠ 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main ⊗ 0 ⚠ 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main ⊗ 0 ⚠ 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main 0 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main ⊗ 0 ⚠ 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main ⊗ 0 ⚠ 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main ⊗ 0 ⚠ 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main ⊗ 0 ⚠ 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main ⊗ 0 ⚠ 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main ⊗ 0 ⚠ 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tip_gen.py

backend > models > tip_gen.py

```
1  Open chat (Ctrl+I), or select a language (Ctrl+K M), or fill with template to get started.
   Start typing to dismiss or don't show this again.
```

main ⊗ 0 ⚠ 0 Ln 1, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

anomaly.py

backend > routes > anomaly.py > ...

```python
from fastapi import APIRouter, UploadFile
import pandas as pd
from services.gemini_utils import detect_anomalies_description

router = APIRouter()

@router.post("/anomaly")
def anomaly(file: UploadFile):
    df = pd.read_csv(file.file)
    summary = df.describe().to_string()
    anomalies = detect_anomalies_description(summary)
    return {"anomalies": anomalies}
```

main 0 0 Ln 13, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

anomaly.py

backend > routes > anomaly.py > ...

```python
from fastapi import APIRouter, UploadFile
import pandas as pd
from services.gemini_utils import detect_anomalies_description

router = APIRouter()

@router.post("/anomaly")
def anomaly(file: UploadFile):
    df = pd.read_csv(file.file)
    summary = df.describe().to_string()
    anomalies = detect_anomalies_description(summary)
    return {"anomalies": anomalies}
```

main 0 0 Ln 13, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

anomaly.py

backend > routes > anomaly.py > ...

```python
from fastapi import APIRouter, UploadFile
import pandas as pd
from services.gemini_utils import detect_anomalies_description

router = APIRouter()

@router.post("/anomaly")
def anomaly(file: UploadFile):
    df = pd.read_csv(file.file)
    summary = df.describe().to_string()
    anomalies = detect_anomalies_description(summary)
    return {"anomalies": anomalies}
```

main 0 0 Ln 13, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chats
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

anomaly.py

backend > routes > anomaly.py > ...

```python
from fastapi import APIRouter, UploadFile
import pandas as pd
from services.gemini_utils import detect_anomalies_description

router = APIRouter()

@router.post("/anomaly")
def anomaly(file: UploadFile):
    df = pd.read_csv(file.file)
    summary = df.describe().to_string()
    anomalies = detect_anomalies_description(summary)
    return {"anomalies": anomalies}
```

main 0 0 Ln 13, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

anomaly.py

backend > routes > anomaly.py > ...

```python
from fastapi import APIRouter, UploadFile
import pandas as pd
from services.gemini_utils import detect_anomalies_description

router = APIRouter()

@router.post("/anomaly")
def anomaly(file: UploadFile):
    df = pd.read_csv(file.file)
    summary = df.describe().to_string()
    anomalies = detect_anomalies_description(summary)
    return {"anomalies": anomalies}
```

main 0 0 Ln 13, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

anomaly.py

backend > routes > anomaly.py > ...

```python
from fastapi import APIRouter, UploadFile
import pandas as pd
from services.gemini_utils import detect_anomalies_description

router = APIRouter()

@router.post("/anomaly")
def anomaly(file: UploadFile):
    df = pd.read_csv(file.file)
    summary = df.describe().to_string()
    anomalies = detect_anomalies_description(summary)
    return {"anomalies": anomalies}
```

main 0 0 Ln 13, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

anomaly.py

backend > routes > anomaly.py > ...

```python
from fastapi import APIRouter, UploadFile
import pandas as pd
from services.gemini_utils import detect_anomalies_description

router = APIRouter()

@router.post("/anomaly")
def anomaly(file: UploadFile):
    df = pd.read_csv(file.file)
    summary = df.describe().to_string()
    anomalies = detect_anomalies_description(summary)
    return {"anomalies": anomalies}
```

main 0 0 Ln 13, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

anomaly.py

backend > routes > anomaly.py > ...

```python
from fastapi import APIRouter, UploadFile
import pandas as pd
from services.gemini_utils import detect_anomalies_description

router = APIRouter()

@router.post("/anomaly")
def anomaly(file: UploadFile):
    df = pd.read_csv(file.file)
    summary = df.describe().to_string()
    anomalies = detect_anomalies_description(summary)
    return {"anomalies": anomalies}
```

main 0 0 Ln 13, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

anomaly.py

backend > routes > anomaly.py > ...

```python
from fastapi import APIRouter, UploadFile
import pandas as pd
from services.gemini_utils import detect_anomalies_description

router = APIRouter()

@router.post("/anomaly")
def anomaly(file: UploadFile):
    df = pd.read_csv(file.file)
    summary = df.describe().to_string()
    anomalies = detect_anomalies_description(summary)
    return {"anomalies": anomalies}
```

main 0 0 Ln 13, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

anomaly.py

backend > routes > anomaly.py > ...

```python
from fastapi import APIRouter, UploadFile
import pandas as pd
from services.gemini_utils import detect_anomalies_description

router = APIRouter()

@router.post("/anomaly")
def anomaly(file: UploadFile):
    df = pd.read_csv(file.file)
    summary = df.describe().to_string()
    anomalies = detect_anomalies_description(summary)
    return {"anomalies": anomalies}
```

main 0 0 Ln 13, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

anomaly.py

backend > routes > anomaly.py > ...

```python
from fastapi import APIRouter, UploadFile
import pandas as pd
from services.gemini_utils import detect_anomalies_description

router = APIRouter()

@router.post("/anomaly")
def anomaly(file: UploadFile):
    df = pd.read_csv(file.file)
    summary = df.describe().to_string()
    anomalies = detect_anomalies_description(summary)
    return {"anomalies": anomalies}
```

main 0 0 Ln 13, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

anomaly.py

backend > routes > anomaly.py > ...

```python
from fastapi import APIRouter, UploadFile
import pandas as pd
from services.gemini_utils import detect_anomalies_description

router = APIRouter()

@router.post("/anomaly")
def anomaly(file: UploadFile):
    df = pd.read_csv(file.file)
    summary = df.describe().to_string()
    anomalies = detect_anomalies_description(summary)
    return {"anomalies": anomalies}
```

main 0 0 Ln 13, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

chat.py

backend > routes > chat.py

```python
from pydantic import BaseModel
from services.gemini_utils import answer_q

router = APIRouter()

class ChatRequest(BaseModel):
    query: str

@router.post("/chat")
def chat(data: ChatRequest):
    reply = answer_q(data.query)
    return {"response": reply}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF Python Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

chat.py

backend > routes > chat.py > ...

```python
from pydantic import BaseModel
from services.gemini_utils import answer_q

router = APIRouter()

class ChatRequest(BaseModel):
    query: str

@router.post("/chat")
def chat(data: ChatRequest):
    reply = answer_q(data.query)
    return {"response": reply}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

chat.py

backend > routes > chat.py > ...

```python
from pydantic import BaseModel
from services.gemini_utils import answer_q

router = APIRouter()

class ChatRequest(BaseModel):
    query: str

@router.post("/chat")
def chat(data: ChatRequest):
    reply = answer_q(data.query)
    return {"response": reply}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

chat.py

backend > routes > chat.py > ...

```python
from pydantic import BaseModel
from services.gemini_utils import answer_q

router = APIRouter()

class ChatRequest(BaseModel):
    query: str

@router.post("/chat")
def chat(data: ChatRequest):
    reply = answer_q(data.query)
    return {"response": reply}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

chat.py

backend > routes > chat.py > ...

```python
from pydantic import BaseModel
from services.gemini_utils import answer_q

router = APIRouter()

class ChatRequest(BaseModel):
    query: str

@router.post("/chat")
def chat(data: ChatRequest):
    reply = answer_q(data.query)
    return {"response": reply}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

chat.py

backend > routes > chat.py > ...

```python
from pydantic import BaseModel
from services.gemini_utils import answer_q

router = APIRouter()

class ChatRequest(BaseModel):
    query: str

@router.post("/chat")
def chat(data: ChatRequest):
    reply = answer_q(data.query)
    return {"response": reply}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

chat.py

backend > routes > chat.py > ...

```python
from pydantic import BaseModel
from services.gemini_utils import answer_q

router = APIRouter()

class ChatRequest(BaseModel):
    query: str

@router.post("/chat")
def chat(data: ChatRequest):
    reply = answer_q(data.query)
    return {"response": reply}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

chat.py

backend > routes > chat.py > ...

```python
from pydantic import BaseModel
from services.gemini_utils import answer_q

router = APIRouter()

class ChatRequest(BaseModel):
    query: str

@router.post("/chat")
def chat(data: ChatRequest):
    reply = answer_q(data.query)
    return {"response": reply}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

chat.py

backend > routes > chat.py > ...

```python
from pydantic import BaseModel
from services.gemini_utils import answer_q

router = APIRouter()

class ChatRequest(BaseModel):
    query: str

@router.post("/chat")
def chat(data: ChatRequest):
    reply = answer_q(data.query)
    return {"response": reply}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

chat.py

backend > routes > chat.py > ...

```python
from pydantic import BaseModel
from services.gemini_utils import answer_q

router = APIRouter()

class ChatRequest(BaseModel):
    query: str

@router.post("/chat")
def chat(data: ChatRequest):
    reply = answer_q(data.query)
    return {"response": reply}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

chat.py

backend > routes > chat.py > ...

```python
from pydantic import BaseModel
from services.gemini_utils import answer_q

router = APIRouter()

class ChatRequest(BaseModel):
    query: str

@router.post("/chat")
def chat(data: ChatRequest):
    reply = answer_q(data.query)
    return {"response": reply}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

chat.py

backend > routes > chat.py > ...

```python
from pydantic import BaseModel
from services.gemini_utils import answer_q

router = APIRouter()

class ChatRequest(BaseModel):
    query: str

@router.post("/chat")
def chat(data: ChatRequest):
    reply = answer_q(data.query)
    return {"response": reply}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

chat.py

backend > routes > chat.py > ...

```python
from pydantic import BaseModel
from services.gemini_utils import answer_q

router = APIRouter()

class ChatRequest(BaseModel):
    query: str

@router.post("/chat")
def chat(data: ChatRequest):
    reply = answer_q(data.query)
    return {"response": reply}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

chat.py

backend > routes > chat.py > ...

```python
from pydantic import BaseModel
from services.gemini_utils import answer_q

router = APIRouter()

class ChatRequest(BaseModel):
    query: str

@router.post("/chat")
def chat(data: ChatRequest):
    reply = answer_q(data.query)
    return {"response": reply}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

chat.py

backend > routes > chat.py > ...

```python
from pydantic import BaseModel
from services.gemini_utils import answer_q

router = APIRouter()

class ChatRequest(BaseModel):
    query: str

@router.post("/chat")
def chat(data: ChatRequest):
    reply = answer_q(data.query)
    return {"response": reply}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

chat.py

backend > routes > chat.py > ...

```python
from pydantic import BaseModel
from services.gemini_utils import answer_q

router = APIRouter()

class ChatRequest(BaseModel):
    query: str

@router.post("/chat")
def chat(data: ChatRequest):
    reply = answer_q(data.query)
    return {"response": reply}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecas
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

C:\projects\smartcity\backend\routes\feedback.py

OUTLINE

TIMELINE

chat.py

backend > routes > chat.py > ...

```python
from pydantic import BaseModel
from services.gemini_utils import answer_q

router = APIRouter()

class ChatRequest(BaseModel):
    query: str

@router.post("/chat")
def chat(data: ChatRequest):
    reply = answer_q(data.query)
    return {"response": reply}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

chat.py

backend > routes > chat.py > ...

```python
from pydantic import BaseModel
from services.gemini_utils import answer_q

router = APIRouter()

class ChatRequest(BaseModel):
    query: str

@router.post("/chat")
def chat(data: ChatRequest):
    reply = answer_q(data.query)
    return {"response": reply}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

chat.py

backend > routes > chat.py > ...

```python
from pydantic import BaseModel
from services.gemini_utils import answer_q

router = APIRouter()

class ChatRequest(BaseModel):
    query: str

@router.post("/chat")
def chat(data: ChatRequest):
    reply = answer_q(data.query)
    return {"response": reply}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

feedback.py

backend > routes > feedback.py

main 0 0

Ln 14, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

feedback.py

backend > routes > feedback.py > submit_feedback

```python
from fastapi import APIRouter
from models.schemas import Feedback

router = APIRouter()
feedback_db = []

@router.post("/feedback")
def submit_feedback(data: Feedback):
    feedback_db.append(data.dict())
    return {"message": "Feedback submitted"}
```

main 0 0 Ln 10, Col 45 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

feedback.py

backend > routes > feedback.py > submit_feedback

```python
from fastapi import APIRouter
from models.schemas import Feedback

router = APIRouter()
feedback_db = []

@router.post("/feedback")
def submit_feedback(data: Feedback):
    feedback_db.append(data.dict())
    return {"message": "Feedback submitted"}
```

main 0 0 Ln 10, Col 45 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

feedback.py

backend > routes > feedback.py > submit_feedback

```python
from fastapi import APIRouter
from models.schemas import Feedback

router = APIRouter()
feedback_db = []

@router.post("/feedback")
def submit_feedback(data: Feedback):
    feedback_db.append(data.dict())
    return {"message": "Feedback submitted"}
```

main 0 0 Ln 10, Col 45 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

feedback.py

backend > routes > feedback.py > submit_feedback

```python
from fastapi import APIRouter
from models.schemas import Feedback

router = APIRouter()
feedback_db = []

@router.post("/feedback")
def submit_feedback(data: Feedback):
    feedback_db.append(data.dict())
    return {"message": "Feedback submitted"}
```

main 0 0 Ln 10, Col 45 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

feedback.py

backend > routes > feedback.py > submit_feedback

```python
from fastapi import APIRouter
from models.schemas import Feedback

router = APIRouter()
feedback_db = []

@router.post("/feedback")
def submit_feedback(data: Feedback):
    feedback_db.append(data.dict())
    return {"message": "Feedback submitted"}
```

main 0 0 Ln 10, Col 45 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

feedback.py

backend > routes > feedback.py > submit_feedback

```python
from fastapi import APIRouter
from models.schemas import Feedback

router = APIRouter()
feedback_db = []

@router.post("/feedback")
def submit_feedback(data: Feedback):
    feedback_db.append(data.dict())
    return {"message": "Feedback submitted"}
```

main 0 0 PAVANTECH-06 (2 days ago) Ln 10, Col 45 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

feedback.py

backend > routes > feedback.py > submit_feedback

```python
from fastapi import APIRouter
from models.schemas import Feedback

router = APIRouter()
feedback_db = []

@router.post("/feedback")
def submit_feedback(data: Feedback):
    feedback_db.append(data.dict())
    return {"message": "Feedback submitted"}
```

main 0 0 PAVANTECH-06 (2 days ago) Ln 10, Col 45 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

feedback.py

backend > routes > feedback.py > submit_feedback

```python
from fastapi import APIRouter
from models.schemas import Feedback

router = APIRouter()
feedback_db = []

@router.post("/feedback")
def submit_feedback(data: Feedback):
    feedback_db.append(data.dict())
    return {"message": "Feedback submitted"}
```

main 0 0 PAVANTECH-06 (2 days ago) Ln 10, Col 45 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

feedback.py

backend > routes > feedback.py > submit_feedback

```python
from fastapi import APIRouter
from models.schemas import Feedback

router = APIRouter()
feedback_db = []

@router.post("/feedback")
def submit_feedback(data: Feedback):
    feedback_db.append(data.dict())
    return {"message": "Feedback submitted"}
```

main 0 0 PAVANTECH-06 (2 days ago) Ln 10, Col 45 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

feedback.py

backend > routes > feedback.py > submit_feedback

```python
from fastapi import APIRouter
from models.schemas import Feedback

router = APIRouter()
feedback_db = []

@router.post("/feedback")
def submit_feedback(data: Feedback):
    feedback_db.append(data.dict())
    return {"message": "Feedback submitted"}
```

main 0 0 PAVANTECH-06 (2 days ago) Ln 10, Col 45 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

feedback.py

backend > routes > feedback.py > submit_feedback

```python
from fastapi import APIRouter
from models.schemas import Feedback

router = APIRouter()
feedback_db = []

@router.post("/feedback")
def submit_feedback(data: Feedback):
    feedback_db.append(data.dict())
    return {"message": "Feedback submitted"}
```

main 0 0 PAVANTECH-06 (2 days ago) Ln 10, Col 45 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

feedback.py

backend > routes > feedback.py > submit_feedback

```python
from fastapi import APIRouter
from models.schemas import Feedback

router = APIRouter()
feedback_db = []

@router.post("/feedback")
def submit_feedback(data: Feedback):
    feedback_db.append(data.dict())
    return {"message": "Feedback submitted"}
```

main 0 0 PAVANTECH-06 (2 days ago) Ln 10, Col 45 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

feedback.py

backend > routes > feedback.py > submit_feedback

```python
from fastapi import APIRouter
from models.schemas import Feedback

router = APIRouter()
feedback_db = []

@router.post("/feedback")
def submit_feedback(data: Feedback):
    feedback_db.append(data.dict())
    return {"message": "Feedback submitted"}
```

main 0 0 PAVANTECH-06 (2 days ago) Ln 10, Col 45 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

forecast.py

backend > routes > forecast.py > ...

```python
from fastapi import APIRouter, UploadFile
import pandas as pd
from services.gemini_utils import forecast_kpi_description

router = APIRouter()

@router.post("/forecast")
def forecast(file: UploadFile):
    df = pd.read_csv(file.file)
    summary = df.describe().to_string()
    prediction = forecast_kpi_description(summary)
    return {"forecast": prediction}
```

main 0 0 Ln 13, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

forecast.py

backend > routes > forecast.py > ...

```python
from fastapi import APIRouter, UploadFile
import pandas as pd
from services.gemini_utils import forecast_kpi_description

router = APIRouter()

@router.post("/forecast")
def forecast(file: UploadFile):
    df = pd.read_csv(file.file)
    summary = df.describe().to_string()
    prediction = forecast_kpi_description(summary)
    return {"forecast": prediction}
```

main 0 0 Ln 13, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

forecast.py

backend > routes > forecast.py > ...

```python
from fastapi import APIRouter, UploadFile
import pandas as pd
from services.gemini_utils import forecast_kpi_description

router = APIRouter()

@router.post("/forecast")
def forecast(file: UploadFile):
    df = pd.read_csv(file.file)
    summary = df.describe().to_string()
    prediction = forecast_kpi_description(summary)
    return {"forecast": prediction}
```

main 0 0 Ln 13, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

forecast.py

backend > routes > forecast.py > ...

```python
from fastapi import APIRouter, UploadFile
import pandas as pd
from services.gemini_utils import forecast_kpi_description

router = APIRouter()

@router.post("/forecast")
def forecast(file: UploadFile):
    df = pd.read_csv(file.file)
    summary = df.describe().to_string()
    prediction = forecast_kpi_description(summary)
    return {"forecast": prediction}
```

main 0 0 Ln 13, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

forecast.py

backend > routes > forecast.py > ...

```python
from fastapi import APIRouter, UploadFile
import pandas as pd
from services.gemini_utils import forecast_kpi_description

router = APIRouter()

@router.post("/forecast")
def forecast(file: UploadFile):
    df = pd.read_csv(file.file)
    summary = df.describe().to_string()
    prediction = forecast_kpi_description(summary)
    return {"forecast": prediction}
```

main 0 0 Ln 13, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

forecast.py

backend > routes > forecast.py > ...

```python
from fastapi import APIRouter, UploadFile
import pandas as pd
from services.gemini_utils import forecast_kpi_description

router = APIRouter()

@router.post("/forecast")
def forecast(file: UploadFile):
    df = pd.read_csv(file.file)
    summary = df.describe().to_string()
    prediction = forecast_kpi_description(summary)
    return {"forecast": prediction}
```

main 0 0 Ln 13, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

forecast.py

backend > routes > forecast.py > ...

```python
from fastapi import APIRouter, UploadFile
import pandas as pd
from services.gemini_utils import forecast_kpi_description

router = APIRouter()

@router.post("/forecast")
def forecast(file: UploadFile):
    df = pd.read_csv(file.file)
    summary = df.describe().to_string()
    prediction = forecast_kpi_description(summary)
    return {"forecast": prediction}
```

main 0 0 Ln 13, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

forecast.py

backend > routes > forecast.py > ...

```python
from fastapi import APIRouter, UploadFile
import pandas as pd
from services.gemini_utils import forecast_kpi_description

router = APIRouter()

@router.post("/forecast")
def forecast(file: UploadFile):
    df = pd.read_csv(file.file)
    summary = df.describe().to_string()
    prediction = forecast_kpi_description(summary)
    return {"forecast": prediction}
```

main 0 0 Ln 13, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

forecast.py

backend > routes > forecast.py > ...

```python
from fastapi import APIRouter, UploadFile
import pandas as pd
from services.gemini_utils import forecast_kpi_description

router = APIRouter()

@router.post("/forecast")
def forecast(file: UploadFile):
    df = pd.read_csv(file.file)
    summary = df.describe().to_string()
    prediction = forecast_kpi_description(summary)
    return {"forecast": prediction}
```

main 0 0 Ln 13, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

C:\projects\smartcity\backend\routes\summarization.py

OUTLINE

TIMELINE

forecast.py

backend > routes > forecast.py > ...

```python
from fastapi import APIRouter, UploadFile
import pandas as pd
from services.gemini_utils import forecast_kpi_description

router = APIRouter()

@router.post("/forecast")
def forecast(file: UploadFile):
    df = pd.read_csv(file.file)
    summary = df.describe().to_string()
    prediction = forecast_kpi_description(summary)
    return {"forecast": prediction}
```

main 0 0 Ln 13, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

C:\projects\smartcity\backend\routes\summarization.py

OUTLINE

TIMELINE

forecast.py

backend > routes > forecast.py > ...

```python
from fastapi import APIRouter, UploadFile
import pandas as pd
from services.gemini_utils import forecast_kpi_description

router = APIRouter()

@router.post("/forecast")
def forecast(file: UploadFile):
    df = pd.read_csv(file.file)
    summary = df.describe().to_string()
    prediction = forecast_kpi_description(summary)
    return {"forecast": prediction}
```

main 0 0 Ln 13, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

C:\projects\smartcity\backend\routes\summarization.py

OUTLINE

TIMELINE

forecast.py

backend > routes > forecast.py > ...

```python
from fastapi import APIRouter, UploadFile
import pandas as pd
from services.gemini_utils import forecast_kpi_description

router = APIRouter()

@router.post("/forecast")
def forecast(file: UploadFile):
    df = pd.read_csv(file.file)
    summary = df.describe().to_string()
    prediction = forecast_kpi_description(summary)
    return {"forecast": prediction}
```

main 0 0 Ln 13, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

summarization.py

backend > routes > summarization.py

main 0 0 Ln 13, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

summarization.py

backend > routes > summarization.py > ...

```python
from fastapi import APIRouter
from pydantic import BaseModel
from services.gemini_utils import summarize_text

router = APIRouter()

class SummarizeRequest(BaseModel):
    text: str

@router.post("/summarize")
def summarize(data: SummarizeRequest):
    result = summarize_text(data.text)
    return {"summary": result}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

summarization.py

backend > routes > summarization.py > ...

```python
from fastapi import APIRouter
from pydantic import BaseModel
from services.gemini_utils import summarize_text

router = APIRouter()

class SummarizeRequest(BaseModel):
    text: str

@router.post("/summarize")
def summarize(data: SummarizeRequest):
    result = summarize_text(data.text)
    return {"summary": result}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

summarization.py

backend > routes > summarization.py > ...

```python
from fastapi import APIRouter
from pydantic import BaseModel
from services.gemini_utils import summarize_text

router = APIRouter()

class SummarizeRequest(BaseModel):
    text: str

@router.post("/summarize")
def summarize(data: SummarizeRequest):
    result = summarize_text(data.text)
    return {"summary": result}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

summarization.py

backend > routes > summarization.py > ...

```python
from fastapi import APIRouter
from pydantic import BaseModel
from services.gemini_utils import summarize_text

router = APIRouter()

class SummarizeRequest(BaseModel):
    text: str

@router.post("/summarize")
def summarize(data: SummarizeRequest):
    result = summarize_text(data.text)
    return {"summary": result}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

summarization.py

backend > routes > summarization.py > ...

```python
from fastapi import APIRouter
from pydantic import BaseModel
from services.gemini_utils import summarize_text

router = APIRouter()

class SummarizeRequest(BaseModel):
    text: str

@router.post("/summarize")
def summarize(data: SummarizeRequest):
    result = summarize_text(data.text)
    return {"summary": result}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

summarization.py

backend > routes > summarization.py > ...

```python
from fastapi import APIRouter
from pydantic import BaseModel
from services.gemini_utils import summarize_text

router = APIRouter()

class SummarizeRequest(BaseModel):
    text: str

@router.post("/summarize")
def summarize(data: SummarizeRequest):
    result = summarize_text(data.text)
    return {"summary": result}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

summarization.py

backend > routes > summarization.py > ...

```python
from fastapi import APIRouter
from pydantic import BaseModel
from services.gemini_utils import summarize_text

router = APIRouter()

class SummarizeRequest(BaseModel):
    text: str

@router.post("/summarize")
def summarize(data: SummarizeRequest):
    result = summarize_text(data.text)
    return {"summary": result}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

summarization.py

backend > routes > summarization.py > ...

```python
from fastapi import APIRouter
from pydantic import BaseModel
from services.gemini_utils import summarize_text

router = APIRouter()

class SummarizeRequest(BaseModel):
    text: str

@router.post("/summarize")
def summarize(data: SummarizeRequest):
    result = summarize_text(data.text)
    return {"summary": result}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

summarization.py

backend > routes > summarization.py > ...

```python
from fastapi import APIRouter
from pydantic import BaseModel
from services.gemini_utils import summarize_text

router = APIRouter()

class SummarizeRequest(BaseModel):
    text: str

@router.post("/summarize")
def summarize(data: SummarizeRequest):
    result = summarize_text(data.text)
    return {"summary": result}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tips.py

backend > routes > tips.py

```python
from fastapi import APIRouter
from pydantic import BaseModel
from services.gemini_utils import gentip

router = APIRouter()

class TipRequest(BaseModel):
    keyword: str

@router.post("/tips")
def eco_tips(data: TipRequest):
    tip = gentip(data.keyword)
    return {"tips": tip}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF {} Python Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tips.py

backend > routes > tips.py > ...

```python
from fastapi import APIRouter
from pydantic import BaseModel
from services.gemini_utils import gentip

router = APIRouter()

class TipRequest(BaseModel):
    keyword: str

@router.post("/tips")
def eco_tips(data: TipRequest):
    tip = gentip(data.keyword)
    return {"tips": tip}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tips.py

backend > routes > tips.py > ...

```python
from fastapi import APIRouter
from pydantic import BaseModel
from services.gemini_utils import gentip

router = APIRouter()

class TipRequest(BaseModel):
    keyword: str

@router.post("/tips")
def eco_tips(data: TipRequest):
    tip = gentip(data.keyword)
    return {"tips": tip}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tips.py

backend > routes > tips.py > ...

```python
from fastapi import APIRouter
from pydantic import BaseModel
from services.gemini_utils import gentip

router = APIRouter()

class TipRequest(BaseModel):
    keyword: str

@router.post("/tips")
def eco_tips(data: TipRequest):
    tip = gentip(data.keyword)
    return {"tips": tip}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tips.py

backend > routes > tips.py > ...

```python
from fastapi import APIRouter
from pydantic import BaseModel
from services.gemini_utils import gentip

router = APIRouter()

class TipRequest(BaseModel):
    keyword: str

@router.post("/tips")
def eco_tips(data: TipRequest):
    tip = gentip(data.keyword)
    return {"tips": tip}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tips.py

backend > routes > tips.py > ...

```python
from fastapi import APIRouter
from pydantic import BaseModel
from services.gemini_utils import gentip

router = APIRouter()

class TipRequest(BaseModel):
    keyword: str

@router.post("/tips")
def eco_tips(data: TipRequest):
    tip = gentip(data.keyword)
    return {"tips": tip}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tips.py

backend > routes > tips.py > ...

```python
from fastapi import APIRouter
from pydantic import BaseModel
from services.gemini_utils import gentip

router = APIRouter()

class TipRequest(BaseModel):
    keyword: str

@router.post("/tips")
def eco_tips(data: TipRequest):
    tip = gentip(data.keyword)
    return {"tips": tip}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tips.py

backend > routes > tips.py > ...

```python
from fastapi import APIRouter
from pydantic import BaseModel
from services.gemini_utils import gentip

router = APIRouter()

class TipRequest(BaseModel):
    keyword: str

@router.post("/tips")
def eco_tips(data: TipRequest):
    tip = gentip(data.keyword)
    return {"tips": tip}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tips.py

backend > routes > tips.py > ...

```python
from fastapi import APIRouter
from pydantic import BaseModel
from services.gemini_utils import gentip

router = APIRouter()

class TipRequest(BaseModel):
    keyword: str

@router.post("/tips")
def eco_tips(data: TipRequest):
    tip = gentip(data.keyword)
    return {"tips": tip}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore
- README.md
- requirements.txt

OUTLINE

TIMELINE

tips.py

backend > routes > tips.py > ...

```python
from fastapi import APIRouter
from pydantic import BaseModel
from services.gemini_utils import gentip

router = APIRouter()

class TipRequest(BaseModel):
    keyword: str

@router.post("/tips")
def eco_tips(data: TipRequest):
    tip = gentip(data.keyword)
    return {"tips": tip}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
    - __pycache__
    - ai_response.py
    - gemini_utils.py
    - ml_utils.py
    - watsonx.py
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore

OUTLINE

TIMELINE

tips.py

backend > routes > tips.py > ...

```python
from fastapi import APIRouter
from pydantic import BaseModel
from services.gemini_utils import gentip

router = APIRouter()

class TipRequest(BaseModel):
    keyword: str

@router.post("/tips")
def eco_tips(data: TipRequest):
    tip = gentip(data.keyword)
    return {"tips": tip}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
    - __pycache__
    - ai_response.py
    - gemini_utils.py
    - ml_utils.py
    - watsonx.py
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore

OUTLINE

TIMELINE

tips.py

backend > routes > tips.py > ...

```python
from fastapi import APIRouter
from pydantic import BaseModel
from services.gemini_utils import gentip

router = APIRouter()

class TipRequest(BaseModel):
    keyword: str

@router.post("/tips")
def eco_tips(data: TipRequest):
    tip = gentip(data.keyword)
    return {"tips": tip}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live

File Edit Selection View Go Run Terminal Help

smartcity

EXPLORER

SMAR...

- backend
  - __pycache__
  - ai_model
    - __pycache__
    - test.py
  - models
    - __pycache__
    - schemas.py
    - tip_gen.py
  - routes
    - __pycache__
    - anomaly.py
    - chat.py
    - feedback.py
    - forecast.py
    - summarization.py
    - tips.py
  - services
    - __pycache__
    - ai_response.py
    - gemini_utils.py
    - ml_utils.py
    - watsonx.py
  - utils
  - main.py
- frontend
- screenshots
- venv
- .env
- .gitignore

OUTLINE

TIMELINE

tips.py

backend > routes > tips.py > ...

```python
from fastapi import APIRouter
from pydantic import BaseModel
from services.gemini_utils import gentip

router = APIRouter()

class TipRequest(BaseModel):
    keyword: str

@router.post("/tips")
def eco_tips(data: TipRequest):
    tip = gentip(data.keyword)
    return {"tips": tip}
```

main 0 0 Ln 14, Col 1 Spaces: 4 UTF-8 CRLF {} Python 3.11.9 (Microsoft Store) Go Live