HIGH-TEMPERATURE ALUMINIUM FOIL LABEL

DURABLETAG

AUL 6055

ALUMINIUM FOIL LABEL | 175 TOTAL THICKNESS | MATTE WHITE | SPSA



Product Code: AUL 6055

Product Name: ALUMINIUM FOIL LABEL | 175 TOTAL THICKNESS | MATTE WHITE | SPSA

Facestock: AUL 6055 is a white aluminum foil label featuring a silicone-based pressure-sensitive adhesive and a heat-resistant surface coating. It is specifically designed for identification labels used in the high-temperature steel casting industry. The label is compatible with thermal transfer printing using a premium high-temperature wax resin ribbon, or it can be processed through laser engraving.

Basis Weight: 183.6 g/m² ±10% ISO 536

Caliper: 68 µm ISO 534

Adhesive: SPSA is a high-temperature silicone pressure-sensitive adhesive with excellent heat and chemical resistance.

Liner: Clear PET release liner.

Basis Weight: 70g/m² ISO 536

Caliper: 50 µm ISO 534

Total Caliper: 175 µm±10% ISO 534

Minimum Application Surface Temperature: +300 °C (+572 °F)

Service Temperature: - 40 °F to 1112 °F (-40 °C to 600 °C)

Short-Term Exposure (<2 min): +600 °C (+1112 °F)

Continuous Operating Temperature: –40 °C to +300 °C (–40 °F to +572 °F)

Suitable for identification applications involving short-term exposure to temperatures up to 600 °C (1112 °F), for less than 2 minutes.

ALUMINIUM FOIL LABEL | 175 TOTAL THICKNESS | MATTE WHITE | SPSA is used for identification purposes in the metal industry. Barcode or alphanumeric identification of hot metal items. Aluminum and steel mills, heat treatment of coil springs, nameplates on industrial equipment.
The product shows excellent heat resistance. It is also resistant to UV light and outdoor conditions. It is suitable for the applications that labels are exposed to high temperatures up to + 600 °C / short term.

Application tests are highly recommended.

-40 °C to +300 °C continuous

Up to +600 °C for <2 min

RoHS	PPWR	REACH
SUBSTANCE TESTING	HEAVY-METAL SCREENING	SVHC SCREENING
TESTED COMPONENT ONLY	ARTICLE 5(4) — HEAVY METALS ONLY	TESTED SAMPLE / GROUP ONLY

Shelf Life: To obtain optimal performance, use this product within one year of the date of manufacture, under storage conditions as defined by FINAT (20–25 °C; 40–50% RH). Prolonged storage outside these conditions may reduce the shelf life.

Warranty: © 2023, DURABLETAG

DURABLETAG products are sold on the understanding that the Buyer will test them under actual conditions of use and determine their suitability for the intended application.

DURABLETAG warrants to the Buyer that its products are free from defects in materials and workmanship. DURABLETAG's obligations under this warranty are limited to replacing products demonstrated to the satisfaction of DURABLETAG to have been defective, provided that the Buyer has complied with the handling, storage and shelf life requirements specified in the applicable DURABLETAG material specifications.
The above warranties extend solely to the Buyer, and all warranty claims must be made by the Buyer. Rework or replacement shall not alter the original warranty period. In all cases, the warranty period shall not exceed thirty (30) days from the date of the original shipment.

THE ABOVE WARRANTIES ARE EXCLUSIVE OF AND IN LIEU OF ALL OTHER WARRANTIES, WRITTEN OR ORAL, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE. NO IMPLIED STATUTORY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE SHALL APPLY. DURABLETAG SHALL NOT BE LIABLE, EITHER IN TORT OR IN CONTRACT, FOR ANY LOSS OR DAMAGE, DIRECT, INCIDENTAL OR CONSEQUENTIAL, ARISING OUT OF THE USE OF OR INABILITY TO USE THE PRODUCT, OR FROM DELAY IN THE REPLACEMENT OR REPAIR OF PRODUCTS UNDER THE ABOVE WARRANTY.

Rev. 02 | 01 Nov 2026

www.durabletag.com