CL-206151

Matt Chrome PET Film Label

HIGH-TACK ADHESIVE

Topcoated matt chrome PET film with backside metallisation and a high-tack adhesive for demanding substrates, including low-surface-energy plastics. Designed for durable product, equipment and component identification.

TECHNICAL SPECIFICATIONS

Product Code	CL-206151
Facestock	Topcoated matt chrome PET film with backside metallisation
Facestock Basis Weight	72 g/m² (ISO 536)
Facestock Caliper	50 µm (ISO 534)
Adhesive	
Adhesive Coat Weight	Rubber-hybridised acrylic adhesive
Release Liner	27 g/m² (FTM 12)
	White supercalendered glassine release paper
Liner Basis Weight	70 g/m² (ISO 536)
Liner Caliper	61 µm (ISO 534)
Total Caliper	138 µm ±10%, including liner (ISO 534)
Initial Tack	20 N/25 mm; FTM 9, glass
90° Peel Adhesion	21 N/25 mm; FTM 2, stainless steel, 24 h dwell
Min. Application Temperature	+5 °C (+41 °F)
Service Temperature	-40 °C to +150 °C (-40 °F to +302 °F)
Shelf Life	1 year; see storage conditions below

MATERIAL CONSTRUCTION

50 µm matt chrome PET film

27 g/m² high-tack adhesive

61 µm glassine release liner

Schematic only; layers are not to scale.

APPLICATIONS

- Automotive parts and lacquered surfaces
- Low-surface-energy plastic components
- Electronics and household appliances
- Durable identification and warning labels

PRINTING & CONVERTING

Resin-ribbon thermal transfer, flexographic, UV letterpress and screen printing; selected UV inkjet systems. Metallic reflection can reduce barcode contrast. Verify readability with the intended printer, ribbon and scanner.

APPLICATION & STORAGE NOTES

Material data report BS 5609:1986 Section 2 marine-immersion compliance. Section 3 for the printed label requires separate ink or ribbon evaluation.

Verify adhesion and print durability under actual conditions. Avoid sharp corners during die-cutting. Store in protective packaging under the conditions below.

Shelf Life: To obtain optimal performance, use this product within one year of the date of manufacture, under storage conditions as defined by FINAT (20-25 °C; 40-50% RH). Prolonged storage outside these conditions may reduce the shelf life.

Warranty: © 2023, codeLINE

codeLINE products are sold on the understanding that the Buyer will test them under actual conditions of use and determine their suitability for the intended application.

codeLINE warrants to the Buyer that its products are free from defects in materials and workmanship. codeLINE's obligations under this warranty are limited to replacing products demonstrated to the satisfaction of codeLINE to have been defective, provided that the Buyer has complied with the handling, storage and shelf life requirements specified in the applicable codeLINE material specifications.

The above warranties extend solely to the Buyer, and all warranty claims must be made by the Buyer. Rework or replacement shall not alter the original warranty period. In all cases, the warranty period shall not exceed thirty (30) days from the date of the original shipment.

THE ABOVE WARRANTIES ARE EXCLUSIVE OF AND IN LIEU OF ALL OTHER WARRANTIES, WRITTEN OR ORAL, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE. NO IMPLIED STATUTORY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE SHALL APPLY. codeLINE SHALL NOT BE LIABLE, EITHER IN TORT OR IN CONTRACT, FOR ANY LOSS OR DAMAGE, DIRECT, INCIDENTAL OR CONSEQUENTIAL, ARISING OUT OF THE USE OF OR INABILITY TO USE THE PRODUCT, OR FROM DELAY IN THE REPLACEMENT OR REPAIR OF PRODUCTS UNDER THE ABOVE WARRANTY.