CL-207029

White PE Film Label

FLEXIBLE CONTAINER LABELLING

Flexible, topcoated white polyethylene label film with a clear permanent emulsion acrylic adhesive. Designed for squeezable bottles, flexible containers and industrial packaging, including HDPE oil cans.

TECHNICAL SPECIFICATIONS

Product Code	CL-207029
Facestock	Topcoated white polyethylene (PE) film
Facestock Basis Weight	91 g/m² (ISO 536)
Facestock Caliper	93 µm (ISO 534)
Adhesive	Clear permanent emulsion acrylic adhesive
Adhesive Coat Weight	Not specified
Release Liner	White supercalendered glassine release paper
Liner Basis Weight	57 g/m² (ISO 536)
Liner Caliper	50 µm (ISO 534)
Total Caliper	166 µm ±10%, including liner (ISO 534)
Initial Tack	16 N/25 mm; FTM 9, glass
90° Peel Adhesion	10 N/25 mm; FTM 2, stainless steel
Min. Application Temperature	0 °C (+32 °F)
Service Temperature	-20 °C to +80 °C (-4 °F to +176 °F)
Shelf Life	1 year; see storage conditions below

MATERIAL CONSTRUCTION

93 µm topcoated white PE film

Permanent emulsion acrylic adhesive

50 µm glassine release liner

Schematic only; layers are not to scale.

APPLICATIONS

- Squeezable bottles and flexible containers
- Home and personal care packaging
- HDPE oil cans and industrial packaging
- Large labels and complex label shapes

PRINTING & CONVERTING

Suitable for UV flexo, UV inkjet, screen, offset, letterpress, gravure, foiling and thermal transfer. Select compatible inks and ribbons. On-press corona treatment is not advised; heavy ink coverage may embrittle the PE film.

APPLICATION & STORAGE NOTES

Material meets BS 5609:1986 Section 2 marine-immersion requirements. Section 3 for the printed label requires specific ink or ribbon evaluation.

Developed for in-house oil-can labelling; external use requires testing. Food-contact suitability requires a construction-specific statement. Values are typical; validate actual use.

Shelf Life: To obtain optimal performance, use this product within one year of the date of manufacture, under storage conditions as defined by FINAT (20-25 °C; 40-50% RH). Prolonged storage outside these conditions may reduce the shelf life.

Warranty: © 2023, codeLINE

codeLINE products are sold on the understanding that the Buyer will test them under actual conditions of use and determine their suitability for the intended application.

codeLINE warrants to the Buyer that its products are free from defects in materials and workmanship. codeLINE's obligations under this warranty are limited to replacing products demonstrated to the satisfaction of codeLINE to have been defective, provided that the Buyer has complied with the handling, storage and shelf life requirements specified in the applicable codeLINE material specifications.

The above warranties extend solely to the Buyer, and all warranty claims must be made by the Buyer. Rework or replacement shall not alter the original warranty period. In all cases, the warranty period shall not exceed thirty (30) days from the date of the original shipment.

THE ABOVE WARRANTIES ARE EXCLUSIVE OF AND IN LIEU OF ALL OTHER WARRANTIES, WRITTEN OR ORAL, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE. NO IMPLIED STATUTORY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE SHALL APPLY. codeLINE SHALL NOT BE LIABLE, EITHER IN TORT OR IN CONTRACT, FOR ANY LOSS OR DAMAGE, DIRECT, INCIDENTAL OR CONSEQUENTIAL, ARISING OUT OF THE USE OF OR INABILITY TO USE THE PRODUCT, OR FROM DELAY IN THE REPLACEMENT OR REPAIR OF PRODUCTS UNDER THE ABOVE WARRANTY.