codeLINE
QUALITY BUILDS CONFIDENCE

CL-210289

Matt White HDPE Freezer Label

COLD STORAGE & PALLET TRACKING

Matt white HDPE film with an absorbent, paper-like print coating and a permanent rubber-based freezer adhesive. Designed for cold-storage tracking, packaging and stretch- or shrink-wrapped pallet identification.

TECHNICAL SPECIFICATIONS

Product Code	CL-210289
Facestock	Matt white high-density polyethylene (HDPE) film with absorbent topcoat
Facestock Basis Weight	60 g/m² (ISO 536)
Facestock Caliper	85 µm (ISO 534)
Adhesive	Permanent rubber-based freezer adhesive
Adhesive Coat Weight	Not specified
Release Liner	White supercalendered glassine release paper
Liner Basis Weight	57 g/m² (ISO 536)
Liner Caliper	50 µm (ISO 534)
Total Caliper	157 µm ±10%, including liner (ISO 534)
Initial Tack	14 N/25 mm; FTM 9, glass
90° Peel Adhesion	7.5 N/25 mm; FTM 2, stainless steel
Min. Application Temperature	-25 °C (-13 °F)
Service Temperature	-50 °C to +70 °C (-58 °F to +158 °F)
Shelf Life	1 year; see storage conditions below

MATERIAL CONSTRUCTION

85 µm matt white HDPE film

Rubber-based freezer adhesive

50 µm glassine release liner

Schematic only; layers are not to scale.

APPLICATIONS

- Cold-storage packaging and tracking
- Paper, cardboard and film packaging
- Stretch- or shrink-wrapped pallets
- Chemical drums; indoor or mid-term outdoor

PRINTING & CONVERTING

Suitable for thermal transfer with compatible wax, wax/resin or resin ribbons, dot-matrix printing and conventional preprinting. Use sharp dies; rotary and magnetic die-cutting require additional care due to film extensibility.

APPLICATION & STORAGE NOTES

Adhesion can be achieved on slightly frosted surfaces; validate actual frost, moisture and substrate conditions.

The cavitated film may delaminate on removal. Food-contact use requires a construction-specific statement. Values are typical; test the complete label in actual use and store rolls as specified below.

Shelf Life: To obtain optimal performance, use this product within one year of the date of manufacture, under storage conditions as defined by FINAT (20-25 °C; 40-50% RH). Prolonged storage outside these conditions may reduce the shelf life.

Warranty: © 2023, codeLINE

codeLINE products are sold on the understanding that the Buyer will test them under actual conditions of use and determine their suitability for the intended application.

codeLINE warrants to the Buyer that its products are free from defects in materials and workmanship. codeLINE's obligations under this warranty are limited to replacing products demonstrated to the satisfaction of codeLINE to have been defective, provided that the Buyer has complied with the handling, storage and shelf life requirements specified in the applicable codeLINE material specifications.

The above warranties extend solely to the Buyer, and all warranty claims must be made by the Buyer. Rework or replacement shall not alter the original warranty period. In all cases, the warranty period shall not exceed thirty (30) days from the date of the original shipment.

THE ABOVE WARRANTIES ARE EXCLUSIVE OF AND IN LIEU OF ALL OTHER WARRANTIES, WRITTEN OR ORAL, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE. NO IMPLIED STATUTORY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE SHALL APPLY. codeLINE SHALL NOT BE LIABLE, EITHER IN TORT OR IN CONTRACT, FOR ANY LOSS OR DAMAGE, DIRECT, INCIDENTAL OR CONSEQUENTIAL, ARISING OUT OF THE USE OF OR INABILITY TO USE THE PRODUCT, OR FROM DELAY IN THE REPLACEMENT OR REPAIR OF PRODUCTS UNDER THE ABOVE WARRANTY.