HIGH-TEMPERATURE IDENTIFICATION TAG

DURABLETAG

HCT 7090

HYBRID 155 CONSTRUCTION | DOUBLE-SIDED COATING | WHITE TAG



Product Code: HCT 7090

Product Name: HYBRID 155 CONSTRUCTION | DOUBLE-SIDED COATING | WHITE TAG

Facestock: HCT 7090 is a hybrid tag material with a nominal caliper of 155 µm and a white coating on both sides. It is intended for demanding identification applications. Material performance, chemical compatibility and printed-image durability must be verified under the intended application conditions.

Basis Weight : 280 g/m² ±10%

Caliper : 155 µm ±10%

Construction: Non-adhesive tag

Temperature Limits, Including Short-Term Exposure: -80 °C to +800 °C (-112 °F to +1472 °F)

Short-Term Exposure: (<15 min): +800 °C (+1472 °F)

Continuous Operating Temperature: -40 °C to +600 °C (-40 °F to +1112 °F)

HYBRID 155 CONSTRUCTION | DOUBLE-SIDED COATING | WHITE TAG It is a hang tag used for identification purposes in the metal industry.
The product shows excellent heat resistance. It is also resistant to UV light and outdoor conditions. It is suitable for applications in which tags are exposed to temperatures up to +800 °C for less than 15 minutes.

-40 °C to +600 °C continuous
Up to +800 °C for <15 min

Typical applications include identification tags in the steel industry when high heat resistance is required.

- Application tests are highly recommended.

RoHS SUBSTANCE TESTING — TESTED COMPONENT ONLY

PPWR HEAVY-METAL SCREENING — ARTICLE 5(4) — HEAVY METALS ONLY

REACH SVHC SCREENING — TESTED SAMPLE / GROUP ONLY

Shelf Life: To obtain optimal performance, use this product within one year of the date of manufacture, under storage conditions as defined by FINAT (20–25 °C; 40–50% RH). Prolonged storage outside these conditions may reduce the shelf life.

Warranty: © 2023, DURABLETAG

DURABLETAG products are sold on the understanding that the Buyer will test them under actual conditions of use and determine their suitability for the intended application.

DURABLETAG warrants to the Buyer that its products are free from defects in materials and workmanship. DURABLETAG's obligations under this warranty are limited to replacing products demonstrated to the satisfaction of DURABLETAG to have been defective, provided that the Buyer has complied with the handling, storage and shelf life requirements specified in the applicable DURABLETAG material specifications.
The above warranties extend solely to the Buyer, and all warranty claims must be made by the Buyer. Rework or replacement shall not alter the original warranty period. In all cases, the warranty period shall not exceed thirty (30) days from the date of the original shipment.

THE ABOVE WARRANTIES ARE EXCLUSIVE OF AND IN LIEU OF ALL OTHER WARRANTIES, WRITTEN OR ORAL, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE. NO IMPLIED STATUTORY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE SHALL APPLY. DURABLETAG SHALL NOT BE LIABLE, EITHER IN TORT OR IN CONTRACT, FOR ANY LOSS OR DAMAGE, DIRECT, INCIDENTAL OR CONSEQUENTIAL, ARISING OUT OF THE USE OF OR INABILITY TO USE THE PRODUCT, OR FROM DELAY IN THE REPLACEMENT OR REPAIR OF PRODUCTS UNDER THE ABOVE WARRANTY.

Rev. 02 | 01 Nov 2026

www.durabletag.com