HIGH-TACK CROSS-LAMİNATED HDPE LABEL

DURABLETAG

HDL 5250

TC HDPE 105 HM 45 -BG FSC



Product Code: HDL 5250

Product Name: TC HDPE 105 HM 45 -BG FSC

Facestock: White cross-laminated high-density polyethylene (HDPE) film with a matt, topcoated printing surface on one side. The construction comprises multiple oriented film layers laminated together for resistance to tearing, puncture and tear propagation.

Basis Weight: 80 g/m² ISO 536

Caliper: 105 µm ISO 534

Adhesive: Special-purpose permanent rubber-based adhesive.

Liner: White, a supercalendered glassine paper.

Basis Weight: 54 g/m² ISO 536

Caliper: 47 µm ISO 534

Total Caliper: 183 µm±10% ISO 534

Initial Tack: 33 N/25 mm — FTM 9, glass

90° Peel Adhesion: 17 N/25 mm — FTM 2, steel

Service Temperature: -40 °C to +70 °C (-40 °F to +158 °F)

Minimum Application Temperature: -5 °C (+23 °F)

Adhesive Performance: The aggressive nature of the adhesive provides excellent performance on rough or apolar substrates, as well as at low temperatures.

Applications and Use: The multilayer facestock is intended for applications requiring resistance to tearing and puncture. The HM45 adhesive is designed for challenging substrates such as rubber, cardboard, wood, fibre drums and plastic containers. Suitability must be verified on the actual surface.

Adhesive Coat Weight
(30 ±5) g/m²

Strong Adhesive

Shelf Life: To obtain optimal performance, use this product within one year of the date of manufacture, under storage conditions as defined by FINAT (20–25 °C; 40–50% RH). Prolonged storage outside these conditions may reduce the shelf life.

Warranty: © 2023, DURABLETAG

DURABLETAG products are sold on the understanding that the Buyer will test them under actual conditions of use and determine their suitability for the intended application.

DURABLETAG warrants to the Buyer that its products are free from defects in materials and workmanship. DURABLETAG's obligations under this warranty are limited to replacing products demonstrated to the satisfaction of DURABLETAG to have been defective, provided that the Buyer has complied with the handling, storage and shelf life requirements specified in the applicable DURABLETAG material specifications. The above warranties extend solely to the Buyer, and all warranty claims must be made by the Buyer. Rework or replacement shall not alter the original warranty period. In all cases, the warranty period shall not exceed thirty (30) days from the date of the original shipment.

THE ABOVE WARRANTIES ARE EXCLUSIVE OF AND IN LIEU OF ALL OTHER WARRANTIES, WRITTEN OR ORAL, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE. NO IMPLIED STATUTORY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE SHALL APPLY. DURABLETAG SHALL NOT BE LIABLE, EITHER IN TORT OR IN CONTRACT, FOR ANY LOSS OR DAMAGE, DIRECT, INCIDENTAL OR CONSEQUENTIAL, ARISING OUT OF THE USE OF OR INABILITY TO USE THE PRODUCT, OR FROM DELAY IN THE REPLACEMENT OR REPAIR OF PRODUCTS UNDER THE ABOVE WARRANTY.

Rev. 02 | 01 Nov 2026

www.durabletag.com