HIGH-TEMPERATURE POLYIMIDE LABEL

DURABLETAG

PML 6062

POLYIMIDE 75 TC MATT WHITE SILICONE ADHESIVE WG ANTISTATIC



Product Code: PML 6062

Product Name: POLYIMIDE 75 TC MATT WHITE SILICONE ADHESIVE WG ANTISTATIC

Facestock: This product is a PI antistatic label with a permanent silicone pressure-sensitive adhesive. The product is electrostatic safe, with a surface resistance and adhesive resistance of 106-1010 ohms and a moving peel voltage of less than 100 volts.

Basis Weight: 120 g/m² ISO 536

Caliper: 75 µm ISO 534

Adhesive: High-temperature silicone adhesive with excellent heat and chemical resistance.

Liner: White , a supercalendered glassine paper.

Basis Weight: 90g/m² ISO 536

Caliper: 80 µm ISO 534

Total Caliper: 185 µm±10% ISO 534

Minimum Application Temperature: +5 °C (+41 °F)

Service Temperature: -4 °C to 260°C (+500 °F)

Adhesion to Stainless Steel: Tested according to ASTM D1000, American Society for Testing and Materials
Test speed: 300 mm/min; dwell time: 20 min / ≥3N/inch

Initial Tack: National Standard GB-4852 test method ≥1#

Holding Power: National Standard GB-4851 test method ＞24 h

Surface Resistance: EOS/ESD S.11.11 / 10^6–10^{10} Ω

Adhesive Surface Resistance: ANSI/ESD STM 11.11 / 10^6–10^{10} Ω

Peel-Induced Voltage: <100 V

Static Voltage: <100 V

- 4 °C ~ + 260 °C

Shelf Life: To obtain optimal performance, use this product within one year of the date of manufacture, under storage conditions as defined by FINAT (20–25 °C; 40–50% RH). Prolonged storage outside these conditions may reduce the shelf life.

Warranty: © 2023, DURABLETAG

DURABLETAG products are sold on the understanding that the Buyer will test them under actual conditions of use and determine their suitability for the intended application.

DURABLETAG warrants to the Buyer that its products are free from defects in materials and workmanship. DURABLETAG's obligations under this warranty are limited to replacing products demonstrated to the satisfaction of DURABLETAG to have been defective, provided that the Buyer has complied with the handling, storage and shelf life requirements specified in the applicable DURABLETAG material specifications.
The above warranties extend solely to the Buyer, and all warranty claims must be made by the Buyer. Rework or replacement shall not alter the original warranty period. In all cases, the warranty period shall not exceed thirty (30) days from the date of the original shipment.

THE ABOVE WARRANTIES ARE EXCLUSIVE OF AND IN LIEU OF ALL OTHER WARRANTIES, WRITTEN OR ORAL, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE. NO IMPLIED STATUTORY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE SHALL APPLY. DURABLETAG SHALL NOT BE LIABLE, EITHER IN TORT OR IN CONTRACT, FOR ANY LOSS OR DAMAGE, DIRECT, INCIDENTAL OR CONSEQUENTIAL, ARISING OUT OF THE USE OF OR INABILITY TO USE THE PRODUCT, OR FROM DELAY IN THE REPLACEMENT OR REPAIR OF PRODUCTS UNDER THE ABOVE WARRANTY.

Rev. 02 | 01 Nov 2026

www.durabletag.com