HIGH-TACK
POLYESTER
AIRBAG LABEL

DURABLETAG

PSL 3026

PET50 TOP COAT WHITE SLC-PET75



Product Code: PSL 3026

Product Name: PET50 TOP COAT WHITE SLC-PET75

Facestock: Gloss white polyester film with a smooth, topcoated surface for enhanced ink adhesion.

Basis Weight: 70 g/m² ISO 536

Facestock Caliper: 50 µm

Liner Caliper: 75 µm

Total Caliper, Including Liner: 175 µm ±10%

Adhesive: SLC solvent-based silicone adhesive, designed for strong final adhesion on textured and low-surface-energy substrates.

Liner: A clear polyester liner that provides optimal smoothness to the adhesive layer.

Initial Tack: (25 ±10) N/25 mm — FTM 9, glass

90° Peel Adhesion: (16 ±3) N/25 mm — FTM 2, steel

Service Temperature: -80 °C to +150 °C (-112 °F to +302 °F)

Minimum Application Temperature: +5 °C (+41 °F)

Adhesive Performance: SLC is engineered for creating identification, warning, and tracking labels on challenging surfaces, including siliconized fabrics. It excels in withstanding extreme temperatures, moisture, chemicals, and UV exposure.

Strong Adhesive

Surface : N/25mm	NBR rubber (65° Shore A) : 7.1	Stainless Steel : 19.0
Airbag fabric, siliconised : 4,3	SBR rubber (65° Shore A) : 7.5	Teflon (PTFE) : 7.1
EPDM rubber (Ecolan) : 5,0	Silicone rubber (kSil GP40) : 3.2	FTM1: 180°, 300 mm/min, dwell time: 48 hours
Glass : 19.0	Silicone rubber (kSil GP60) : 3.9	

Shelf Life: To obtain optimal performance, use this product within one year of the date of manufacture, under storage conditions as defined by FINAT (20–25 °C; 40–50% RH). Prolonged storage outside these conditions may reduce the shelf life.

Warranty: © 2023, DURABLETAG

DURABLETAG products are sold on the understanding that the Buyer will test them under actual conditions of use and determine their suitability for the intended application.

DURABLETAG warrants to the Buyer that its products are free from defects in materials and workmanship. DURABLETAG's obligations under this warranty are limited to replacing products demonstrated to the satisfaction of DURABLETAG to have been defective, provided that the Buyer has complied with the handling, storage and shelf life requirements specified in the applicable DURABLETAG material specifications.
The above warranties extend solely to the Buyer, and all warranty claims must be made by the Buyer. Rework or replacement shall not alter the original warranty period. In all cases, the warranty period shall not exceed thirty (30) days from the date of the original shipment.

THE ABOVE WARRANTIES ARE EXCLUSIVE OF AND IN LIEU OF ALL OTHER WARRANTIES, WRITTEN OR ORAL, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE. NO IMPLIED STATUTORY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE SHALL APPLY. DURABLETAG SHALL NOT BE LIABLE, EITHER IN TORT OR IN CONTRACT, FOR ANY LOSS OR DAMAGE, DIRECT, INCIDENTAL OR CONSEQUENTIAL, ARISING OUT OF THE USE OF OR INABILITY TO USE THE PRODUCT, OR FROM DELAY IN THE REPLACEMENT OR REPAIR OF PRODUCTS UNDER THE ABOVE WARRANTY.

Rev. 02 | 01 Nov 2026

www.durabletag.com