HIGH-TEMPERATURE COMPOSITE POLYESTER TAG

DURABLETAG

PST 7030

TTP + PET + TTP 220 WHITE TAG



Product Code: PST 7030

Product Name: TTP + PET + TTP 220 WHITE TAG

Facestock: PST 7030 is a composite tag material comprising thermal transfer paper, polyester and thermal transfer paper. Its surface is treated for thermal transfer printing and ink anchorage. Suitability for elevated temperatures and chemical exposure must be verified with the selected ribbon under the intended application conditions.

Basis Weight: 300 g/m² ±10%

Caliper: 220 µm ±10%

Construction: Non-adhesive tag

Temperature Limits, Including Short-Term Exposure: -4 °C to +300 °C (+24.8 °F to +572 °F)

Short-Term Exposure: (<30 min): +300 °C (+572 °F)

Continuous Operating Upper Limit: +200 °C (+392 °F)

TTP + PET + TTP 220 WHITE TAG is a hang tag label used for identification purposes in the metal industry.

- Labels for thermal transfer printers or manual annotation.
- Material resistant to adverse weather conditions.
- Tags for metal identification and traceability.
- We produce blank labels, in color or pre-printed with your logo and company information.
- Good printing quality for barcodes and QR codes. Wipe-resistant printing.

Up to +200 °C continuous

Up to +300 °C for <30 min

Shelf Life: To obtain optimal performance, use this product within one year of the date of manufacture, under storage conditions as defined by FINAT (20–25 °C; 40–50% RH). Prolonged storage outside these conditions may reduce the shelf life.

Warranty: © 2023, DURABLETAG

DURABLETAG products are sold on the understanding that the Buyer will test them under actual conditions of use and determine their suitability for the intended application.

DURABLETAG warrants to the Buyer that its products are free from defects in materials and workmanship. DURABLETAG's obligations under this warranty are limited to replacing products demonstrated to the satisfaction of DURABLETAG to have been defective, provided that the Buyer has complied with the handling, storage and shelf life requirements specified in the applicable DURABLETAG material specifications.
The above warranties extend solely to the Buyer, and all warranty claims must be made by the Buyer. Rework or replacement shall not alter the original warranty period. In all cases, the warranty period shall not exceed thirty (30) days from the date of the original shipment.

THE ABOVE WARRANTIES ARE EXCLUSIVE OF AND IN LIEU OF ALL OTHER WARRANTIES, WRITTEN OR ORAL, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE. NO IMPLIED STATUTORY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE SHALL APPLY. DURABLETAG SHALL NOT BE LIABLE, EITHER IN TORT OR IN CONTRACT, FOR ANY LOSS OR DAMAGE, DIRECT, INCIDENTAL OR CONSEQUENTIAL, ARISING OUT OF THE USE OF OR INABILITY TO USE THE PRODUCT, OR FROM DELAY IN THE REPLACEMENT OR REPAIR OF PRODUCTS UNDER THE ABOVE WARRANTY.

Rev. 02 | 01 Nov 2026

www.durabletag.com