HIGH-TEMPERATURE STAINLESS STEEL LABEL

DURABLETAG

SCL 6075

LINERLESS STAINLESS STEEL LABEL FOR ROBOTIC APPLICATION



Product Code: SCL 6075

Product Name: LINERLESS STAINLESS STEEL LABEL FOR ROBOTIC APPLICATION

Facestock: Stainless steel with an inorganic coating and a semi-matt, print-receptive topcoat. The smooth surface is specially treated to ensure excellent thermal transfer (TT) printability and strong ink anchorage.

DurableTag SCL 6075 is engineered not only for extreme heat resistance, but also for seamless integration into modern automated steel production systems.

Basis Weight: 117 g/m² ISO 536

Total Caliper: 17 µm ±10%

Total Basis Weight: 134 g/m²

Adhesive: Heat-activated adhesive. Requires pressure against a surface at a minimum temperature of 600 °C for at least 5 seconds to activate bonding.

Total Caliper: 17 µm ±10% / 134 g/m2 ISO 534

Minimum Application Surface Temperature: +600 °C (+1112 °F)
Minimum Pressure Contact Time: 5 seconds

Temperature Range: –4 °C to +1,000 °C (+24.8 °F to +1832 °F)

This product is equipped with a high-temperature activated adhesive and is supplied linerless.

The adhesive is specifically engineered to activate only at elevated temperatures and becomes functional at approximately 600°C. Application at lower temperatures is not possible, as the adhesive system requires high heat to initiate bonding.

– 4 °C ~ + 1,000 °C

Shelf Life: To obtain optimal performance, use this product within one year of the date of manufacture, under storage conditions as defined by FINAT (20–25 °C; 40–50% RH). Prolonged storage outside these conditions may reduce the shelf life.

Warranty: © 2023, DURABLETAG

DURABLETAG products are sold on the understanding that the Buyer will test them under actual conditions of use and determine their suitability for the intended application.

DURABLETAG warrants to the Buyer that its products are free from defects in materials and workmanship. DURABLETAG's obligations under this warranty are limited to replacing products demonstrated to the satisfaction of DURABLETAG to have been defective, provided that the Buyer has complied with the handling, storage and shelf life requirements specified in the applicable DURABLETAG material specifications.
The above warranties extend solely to the Buyer, and all warranty claims must be made by the Buyer. Rework or replacement shall not alter the original warranty period. In all cases, the warranty period shall not exceed thirty (30) days from the date of the original shipment.

THE ABOVE WARRANTIES ARE EXCLUSIVE OF AND IN LIEU OF ALL OTHER WARRANTIES, WRITTEN OR ORAL, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE. NO IMPLIED STATUTORY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE SHALL APPLY. DURABLETAG SHALL NOT BE LIABLE, EITHER IN TORT OR IN CONTRACT, FOR ANY LOSS OR DAMAGE, DIRECT, INCIDENTAL OR CONSEQUENTIAL, ARISING OUT OF THE USE OF OR INABILITY TO USE THE PRODUCT, OR FROM DELAY IN THE REPLACEMENT OR REPAIR OF PRODUCTS UNDER THE ABOVE WARRANTY.

Rev. 02 | 01 Nov 2026

www.durabletag.com