

JavaScript Variables and Data Types Review

Working with HTML, CSS, and JavaScript

While HTML and CSS provide website structure, JavaScript brings interactivity to websites by enabling complex functionality, such as handling user input, animating elements, and even building full web applications.

Data Types in JavaScript

Data types help the program understand the kind of data it's working with, whether it's a number, text, or something else.

- **Number:** A number represents both integers and floating-point values. Examples of integers include 7, 19, and 90.
- **Floating point:** A floating point number is a number with a decimal point. Examples include 3.14, 0.5, and 0.0001.
- **String:** A string is a sequence of characters, or text, enclosed in quotes. `"I like coding"` and `'JavaScript is fun'` are examples of strings.
- **Boolean:** A boolean represents one of two possible values: `true` or `false`. You can use a boolean to represent a condition, such as `isLoggedIn = true`.
- **Undefined and Null:** An `undefined` value is a variable that has been declared but not assigned a value. A `null` value is an empty value, or a variable that has



```
let pet = {  
  name: "Fluffy",  
  age: 3,  
  type: "dog"  
};
```

- **Symbol:** The Symbol data type is a unique and immutable value that may be used as an identifier for object properties.

In this example below, two symbols are created with the same description, but they are not equal.

```
1 const crypticKey1= Symbol("saltNpepper");  
2 const crypticKey2= Symbol("saltNpepper");  
3 console.log(crypticKey1 === crypticKey2); // false
```



- **BigInt:** When the number is too large for the `Number` data type, you can use the `BigInt` data type to represent integers of arbitrary length.

By adding an `n` to the end of the number, you can create a `BigInt`.

```
const veryBigNumber = 1234567890123456789012345678901234567890n;
```

Variables in JavaScript

- Variables can be declared using the `let` keyword.

```
let cityName;
```

- To assign a value to a variable, you can use the assignment operator `=`.

```
cityName = "New York";
```

- Variables declared using `let` can be reassigned a new value.

```
1 let cityName = "New York";
2 cityName = "Los Angeles";
3 console.log(cityName); // Los Angeles
```



- Apart from `let`, you can also use `const` to declare a variable. However, a `const` variable cannot be reassigned a new value.

```
const cityName = "New York";  
cityName = "Los Angeles"; // TypeError: Assignment to constant variable
```

- Variables declared using `const` find uses in declaring constants, that are not allowed to change throughout the code, such as `PI` or `MAX_SIZE`.

Variable Naming Conventions

- Variable names should be descriptive and meaningful.
- Variable names should be camelCase like `cityName`, `isLoggedIn`, and `veryBigNumber`.
- Variable names should not start with a number. They must begin with a letter, `_`, or `$`.
- Variable names should not contain spaces or special characters, except for `_` and `$`.



using single quotes and double quotes.

```
let correctWay = 'This is a string';  
let alsoCorrect = "This is also a string";
```

- Strings are immutable in JavaScript. This means that once a string is created, you cannot change the characters in the string. However, you can still reassign strings to a new value.

```
let firstName = "John";  
firstName = "Jane"; // Reassigning the string to a new value
```

String Concatenation in JavaScript

- Concatenation is the process of joining multiple strings or combining strings with variables that hold text. The `+` operator is one of the simplest and most frequently used methods to concatenate strings.

```
1 let studentName = "Asad";  
2 let studentAge = 25;  
3 let studentInfo = studentName + " is " + studentAge + " y  
4 console.log(studentInfo); // Asad is 25 years old.
```



- If you need to add or append to an existing string, then you can use the `+=` operator. This is helpful when you want to build upon a string by adding more text to it over time.



- Another way you can concatenate strings is to use the `concat( )` method. This method joins two or more strings together.

```
1 let firstName = "John";  
2 let lastName = "Doe";  
3 let fullName = firstName.concat(" ", lastName);  
4 console.log(fullName); // John Doe
```



Logging Messages with `console.log()`

- The `console.log()` method is used to log messages to the console. It's a helpful tool for debugging and testing your code.

```
1 console.log("Hello, World!");  
2 // Output: Hello, World!
```




```
let message = "Hello, World!"; // first statement ends here
let number = 42; // second statement starts here
```

- Semicolons help prevent ambiguities in code execution and ensure that statements are correctly terminated.

Comments in JavaScript

- Any line of code that is commented out is ignored by the JavaScript engine. Comments are used to explain code, make notes, or temporarily disable code.
- Single-line comments are created using `//`.

```
// This is a single-line comment and will be ignored by the JavaScript engine
```

- Multi-line comments are created using `/*` to start the comment and `*/` to end the comment.

```
/*
This is a multi-line comment.
It can span multiple lines.
*/
```

JavaScript as a Dynamically Typed Language



```
let error = 404; // JavaScript treats error as a number  
error = "Not Found"; // JavaScript now treats error as a string
```

- Other languages, like C#, that are not dynamically typed would result in an error:

```
int error = 404; // value must always be an integer  
error = "Not Found"; // This would cause an error in C#
```

Using the `typeof` Operator

- The `typeof` operator is used to check the data type of a variable. It returns a string indicating the type of the variable.

```
1 let age = 25;  
2 console.log(typeof age); // "number"  
3  
4 let isLoggedIn = true;  
5 console.log(typeof isLoggedIn); // "boolean"
```



- However, there's a well-known quirk in JavaScript when it comes to `null`. The `typeof` operator returns `"object"` for `null` values.

```
1 let user = null;  
2 console.log(typeof user); // "object"
```

Assignment



Please complete the assignment

Submit

Ask for Help