**POLITECNICO DI MILANO**
Software Engineering for Geoinformatics

# Software Release Document

## MeteoCity

**City-Level Weather Monitoring using Meteostat**

Academic Year 2025/26
**Group 9**

Authors:
Ayman Abdelgadir
Mobina Faraji
Hangyun Wang

*June 2026*

# Table of Contents


| | |
|---|---|
| **1. Introduction** | **4** |
| 1.1 Purpose | 4 |
| 1.2 Product Overview | 4 |
| 1.3 Release Scope | 4 |
| 1.4 Intended Audience | 4 |
| 1.5 Acronyms and Definitions | 4 |
| **2. Released Software Overview** | **6** |
| 2.1 Release Identification | 6 |
| 2.2 Repository Structure | 6 |
| 2.3 Released Components | 7 |
| **3. System Requirements** | **8** |
| 3.1 Required Software | 8 |
| 3.2 Python Dependencies | 8 |
| 3.3 External Services and Network Access | 8 |
| 3.4 Local Ports and URLs | 9 |
| **4. Installation and Configuration** | **10** |
| 4.1 Clone the Repository | 10 |
| 4.2 Set Up Anaconda Python Environment | 10 |
| 4.3 Install Dependencies | 10 |
| 4.4 Configure the .env File | 10 |
| 4.5 Prepare the PostgreSQL Database | 11 |
| 4.6 Backend Auto-Creates Schema | 11 |
| **5. Data Ingestion** | **12** |
| 5.1 Ingestion Purpose | 12 |
| 5.2 Mock Mode (Default — No API Key) | 12 |
| 5.3 Live Meteostat Mode | 12 |
| 5.4 30-Day Constraint and Synthetic Supplement | 12 |
| **6. Running the Released Software** | **13** |
| 6.1 Recommended Startup Sequence | 13 |
| 6.2 Start the Flask Backend | 13 |
| 6.3 Start the Dashboard | 13 |
| 6.4 Stopping the Services | 13 |
| **7. REST API Reference** | **14** |
| **8. Dashboard User Guide** | **15** |

8.1 Login and Registration 15
8.2 Typical Workflow 15
8.3 Role-Based Access 15
**9. Testing and Release Validation 16**
9.1 Running the Test Suite 16
9.2 Manual Acceptance Checklist 16
**10. Known Limitations and Troubleshooting 18**
10.1 Known Limitations 18
10.2 Troubleshooting Guide 18
**11. Generative AI Usage Declaration 19**
**12. References 20**
**Appendix A — Quick Start Summary 21**
**Appendix B — Environment File Template 21**

# List of Tables

Table 1: Acronyms and Definitions 5
Table 2: Release Identification 6
Table 3: Repository Structure 7
Table 4: Released Components 7
Table 5: Required Software 8
Table 6: Python Dependencies 8
Table 7: Local Ports and URLs 9
Table 8: REST API Endpoints 14
Table 9: Role-Based Access Summary 15
Table 10: Unit Test Cases 16
Table 11: Troubleshooting Guide 18

# 1. Introduction

## 1.1 Purpose

This Software Release Document (SRD) describes how to install, configure, run, test, and maintain the released MeteoCity software. It accompanies the final software release submitted through the group GitHub repository for the MeteoCity project.

The SRD focuses on operational release information. It does not replace the Requirement Analysis and Specification Document (RASD) or the Design Document (DD); it explains how the implemented software can be executed and evaluated by course instructors and teaching assistants.

## 1.2 Product Overview

MeteoCity is a client-server application for city-level weather monitoring. The system retrieves, stores, and exposes historical station-based meteorological observations for Milan and Rome, and provides interactive geographic maps and temporal analysis through a role-based web-based dashboard.

The release follows the three-tier architecture defined in the DD: a PostgreSQL data tier for meteorological storage, a Flask REST API application tier handling authentication and business logic, and an interactive web-based dashboard presentation tier supporting spatial mapping, temporal filters, and analytical charts.

## 1.3 Release Scope

- Selected monitored cities: Milan and Rome.
- Station metadata: station identifiers, names, geographic coordinates, elevation, and city association.
- Hourly meteorological observations: temperature (°C), humidity (%), wind speed (km/h), and weather condition code.
- PostgreSQL database via SQLAlchemy ORM; backend auto-creates schema on first run.
- Flask backend with JWT-based authentication and REST API endpoints.
- Interactive web-based dashboard for map visualisation, filtering, trend analysis, statistics, and CSV export.
- Data ingestion module supporting both RapidAPI/Meteostat live mode and synthetic mock mode.
- Test suite (pytest) for backend API and database validation.

## 1.4 Intended Audience

- Course instructors and teaching assistants evaluating the final project release.
- Group members demonstrating or maintaining the project.
- Future developers who need to understand the release structure and reproduce the local environment.

## 1.5 Acronyms and Definitions

| Term | Definition |
|---|---|
| API | Application Programming Interface. |
| DD | Design Document. |
| FR | Functional Requirement. |
| JWT | JSON Web Token — used for secure session authentication. |

| Term | Definition |
|---|---|
| NFR | Non-Functional Requirement. |
| ORM | Object-Relational Mapper (SQLAlchemy). |
| RASD | Requirement Analysis and Specification Document. |
| REST | Representational State Transfer. |
| SRD | Software Release Document. |
| TR | Technical Requirement. |

*Table 1: Acronyms and Definitions*

# 2. Released Software Overview

## 2.1 Release Identification

| Item | Release Information |
|---|---|
| Product Name | MeteoCity |
| Release Version | 1.0 — Final Academic Release |
| Repository URL | https://github.com/Ayman1017/Software-Engineering-Project-Group_9 |
| Primary Branch | main |
| Release Type | Academic local/development release |
| Target Deployment | Local machine with PostgreSQL, Flask backend, and web-based dashboard |

*Table 2: Release Identification*

## 2.2 Repository Structure

The following table describes the top-level directory and file layout of the Software-Engineering-Project-Group_9 repository as submitted for final evaluation. The structure reflects the actual committed files in the main branch.

```
Software-Engineering-Project-Group_9/
|-- backend/
|   |-- __init__.py
|   |-- app.py            # Flask entry point; auto-creates DB schema
|   |-- config.py         # Environment configuration mapper
|   |-- models.py         # SQLAlchemy ORM table definitions
|   |-- clean_db.py       # Utility to reset the database
|   |-- .env              # Local secrets (gitignored -- NOT committed)
|   |-- .env.example      # Committed template with placeholder values
|   |-- ingestion/
|   |   `-- fetch_hourly.py   # Meteostat hourly observations fetcher
|   `-- routes/
|       |-- auth.py           # Registration and JWT login
|       |-- cities.py         # City resource endpoints
|       |-- stations.py       # Weather station discovery
|       |-- observations.py   # Observation record fetchers
|       |-- statistics.py     # Analytical aggregate routes
|       |-- map_data.py       # Spatial data for map display
|       `-- export.py         # CSV export generator
|-- dashboard/
|   |-- meteocity_dashboard.py   # Interactive web-based dashboard
|   `-- bg.png                   # Dashboard background asset
|-- tests/
|   `-- test_auth.py         # Authentication regression tests
|-- .gitignore
|-- FINAL_VERSION_DD.pdf
|-- FINAL_VERSION_RASD.pdf
|-- project_description_Meteostat.pdf
|-- requirements.txt
`-- README.md
```

| Path / File | Description |
|---|---|
| backend/app.py | Flask application entry point. Auto-creates all database tables on first run via SQLAlchemy db.create_all(). |
| backend/models.py | ORM model definitions for Users, Cities, WeatherStations, Observations, and DataVariables. |
| backend/clean_db.py | Utility script to reset and clean the database during development. |
| backend/.env | Local environment file containing real credentials. Excluded from version control via .gitignore. Must be created manually on each machine. |
| backend/.env.example | Committed placeholder template. Copy to backend/.env and fill in real values before running. |
| backend/ingestion/ | Data ingestion helpers for fetching Meteostat hourly observations. |
| backend/routes/ | Flask Blueprint modules: auth, cities, stations, observations, statistics, map_data, export. |
| dashboard/meteocity_dashboard.py | Interactive web-based dashboard (presentation tier). |
| tests/test_auth.py | Pytest-based authentication regression tests. |
| requirements.txt | All Python package dependencies. |
| README.md | Repository overview and startup instructions. |

*Table 3: Repository Structure*

## 2.3 Released Components

| Component | Implementation | Main Responsibility |
|---|---|---|
| Database Tier | SQLAlchemy models in backend/models.py; PostgreSQL database meteocity. | Stores user accounts, city records, station metadata, hourly observations, and data variable definitions. |
| Backend Layer | Flask application in backend/app.py with route modules under backend/routes/. | Exposes authenticated REST endpoints returning JSON; enforces role-based access control. |
| Data Ingestion | backend/ingestion/fetch_hourly.py, triggered via the dashboard's Show Analysis action. | Fetches real observations from Meteostat/RapidAPI; falls back to synthetic data when no key is configured. |
| Dashboard | dashboard/meteocity_dashboard.py | Interactive web-based interface: maps, filters, charts, statistics, CSV export, role-based views. |
| Test Suite | tests/test_auth.py; pytest framework. | Validates registration, login, JWT issuance, and role-based endpoint access. |

*Table 4: Released Components*

# 3. System Requirements

## 3.1 Required Software

| Software | Version / Notes |
|---|---|
| Operating System | Windows 10/11 (primary development environment). macOS and Linux also supported. |
| Python (Anaconda) | Python 3.10 or later via the Anaconda distribution. Tested and recommended for Windows. |
| PostgreSQL | Version 14 or higher installed locally. Database must be named meteocity (not meteocity_db). |
| PostGIS | PostGIS extension enabled on the meteocity database. Required for the geospatial location column on the weather_stations table. |
| Git | Required to clone the repository from GitHub. |
| Web Browser | Google Chrome, Firefox, or Safari for dashboard access and map tile rendering. |
| RapidAPI Account | Required only for live Meteostat ingestion. Free tier: 500 requests/month. Mock mode works without a key. |

*Table 5: Required Software*

## 3.2 Python Dependencies

All packages are listed in requirements.txt at the repository root. Install them using the command in Section 4.3.

| Package | Version | Purpose |
|---|---|---|
| Flask | 3.0.3 | Lightweight WSGI framework; REST API backend. |
| Flask-JWT-Extended | 4.6.0 | JWT token management with role claims. |
| Flask-SQLAlchemy | 3.1.1 | SQLAlchemy integration for Flask. |
| SQLAlchemy | 2.0.30 | ORM; auto-creates schema; ON CONFLICT upsert support. |
| psycopg2-binary | 2.9.9 | PostgreSQL adapter for Python. |
| python-dotenv | 1.0.1 | Loads environment variables from backend/.env. |
| bcrypt | 4.1.3 | Secure password hashing. |
| requests | 2.32.3 | HTTP client for Meteostat RapidAPI calls. |
| pandas | 2.2.2 | Data manipulation and preprocessing. |
| folium | 0.16.0 | Leaflet.js-backed interactive maps. |
| plotly | 5.22.0 | Interactive time-series and bar charts. |
| Flask-Cors | 4.0.1 | Cross-origin resource sharing. |
| streamlit | 1.35.0 | Web-based dashboard framework. |
| streamlit-folium | 0.21.0 | Folium map integration for the dashboard. |

*Table 6: Python Dependencies*

## 3.3 External Services and Network Access

- Meteostat via RapidAPI (meteostat.p.rapidapi.com): used for live hourly observation ingestion. Requires outbound internet on port 443.
- Map tile providers: internet connection required by the dashboard to resolve OpenStreetMap base tiles via Folium/Leaflet.
- Local loopback: the dashboard communicates with the Flask backend over localhost. Ports 5000 and 8501 must be free.
- Mock ingestion mode populates the database with synthetic data and requires no external network access.

## 3.4 Local Ports and URLs

| Service | Default URL / Port | Purpose |
|---|---|---|
| Flask Backend | http://localhost:5000 | REST API and authentication server. |
| Dashboard | http://localhost:8501 | Interactive web-based dashboard. |
| PostgreSQL | localhost:5432 | Database server. |

*Table 7: Local Ports and URLs*

# 4. Installation and Configuration

Follow these steps sequentially to configure the development stack locally. All commands are shown for Windows (Anaconda). macOS/Linux equivalents are noted where they differ.

## 4.1 Clone the Repository

```
git clone https://github.com/Ayman1017/Software-Engineering-Project-Group_9.git
cd Software-Engineering-Project-Group_9
```

## 4.2 Set Up Anaconda Python Environment

The project is developed and tested using Anaconda Python on Windows. Use the base Anaconda environment or create a dedicated conda environment.

**Option A — Use the base Anaconda environment (simplest):**

```
# Open Anaconda Prompt and navigate to the project
cd Software-Engineering-Project-Group_9
```

**Option B — Create a dedicated conda environment:**

```
conda create -n meteocity python=3.11
conda activate meteocity
```

**macOS/Linux alternative (standard venv):**

```
python3 -m venv venv
source venv/bin/activate
```

## 4.3 Install Dependencies

```
pip install --upgrade pip
pip install -r requirements.txt
```

All packages listed in Section 3.2 will be installed. Ensure requirements.txt has one package per line if pip raises parsing errors.

## 4.4 Configure the .env File

The backend reads all configuration from backend/.env. This file contains database credentials, the JWT secret key, and the RapidAPI key. It is excluded from version control via .gitignore and must be created manually on every new machine.

A committed template backend/.env.example is provided with placeholder values and inline comments. Copy it to backend/.env and fill in your real values:

```
# Windows
copy backend\.env.example backend\.env

# macOS / Linux
cp backend/.env.example backend/.env
```

Then edit backend/.env and set:

```
DATABASE_URL=postgresql://postgres:<your_password>@localhost:5432/meteocity
JWT_SECRET_KEY=<change-this-to-a-long-random-secret>
RAPIDAPI_KEY=<your_rapidapi_key_or_leave_empty_for_mock_mode>
RAPIDAPI_HOST=meteostat.p.rapidapi.com
FLASK_ENV=development
```

The database name must be meteocity (not meteocity_db). If RAPIDAPI_KEY is left empty or set to the placeholder, the system automatically falls back to synthetic mock data.

## 4.5 Prepare the PostgreSQL Database

Create the database named meteocity before starting the backend, then enable the PostGIS extension on it. The weather_stations table uses a PostGIS geometry column for station location, so the backend will fail to create its schema if PostGIS is not enabled.

**Using psql:**

```
psql -U postgres
CREATE DATABASE meteocity;
\c meteocity
CREATE EXTENSION postgis;
\q
```

**Using pgAdmin:**

- Open pgAdmin and connect to your local PostgreSQL server.
- Right-click Databases → Create → Database.
- Enter meteocity as the database name and click Save.
- Open the Query Tool on the new meteocity database and run: CREATE EXTENSION postgis;

**If a database named meteocity already exists:** it can be reused as-is — the backend does not overwrite or drop existing tables, so a meteocity database left over from a previous run is safe to run against again, provided PostGIS is already enabled on it. If a database with this name already exists but contains unrelated content (for example, from a different project or course), drop and recreate it empty before starting the backend, then enable PostGIS on the fresh database:

```
psql -U postgres
DROP DATABASE meteocity;
CREATE DATABASE meteocity;
\c meteocity
CREATE EXTENSION postgis;
\q
```

## 4.6 Backend Auto-Creates Schema

The backend automatically creates all required database tables on first run via SQLAlchemy db.create_all(). No manual migration commands are needed beyond enabling PostGIS (Section 4.5). The meteocity database instance must exist, with PostGIS enabled, before the backend is started.

# 5. Data Ingestion

## 5.1 Ingestion Purpose

The ingestion module populates the database with city records, weather station metadata, data variable definitions, and hourly observation records. Ingestion is triggered automatically when the dashboard calls the /api/observations endpoint after the user clicks Show Analysis.

Four hardcoded Meteostat weather stations are used: Milano Malpensa (16080), Milano Linate (16066), Roma Fiumicino (16242), and Roma Ciampino (16239).

## 5.2 Mock Mode (Default — No API Key)

When RAPIDAPI_KEY is absent, empty, or set to a placeholder value in backend/.env, the system automatically uses mock mode. Synthetic but realistic hourly weather observations are generated for all four stations and stored in the database. This mode is suitable for demonstrations and development testing without consuming RapidAPI quota.

Mock data uses a fixed set of weather condition codes in {1, 2, 3, 4, 5, 21, 61}.

## 5.3 Live Meteostat Mode

When a valid RAPIDAPI_KEY is configured in backend/.env, the system requests real hourly observations from the Meteostat API via RapidAPI. Upsert logic (ON CONFLICT DO NOTHING) ensures real data is never overwritten by subsequent synthetic fallback operations.

The free Meteostat plan via RapidAPI provides 500 requests per month. Manage requests carefully to avoid quota exhaustion.

## 5.4 30-Day Constraint and Synthetic Data Supplement

The Meteostat API enforces a hard 30-day maximum window per request (TR8 in the RASD). For date ranges exceeding 30 days, the system automatically supplements real observations with synthetic values to fill the missing period. Real Meteostat data is only guaranteed for ranges of 30 days or fewer. This is an acknowledged external constraint documented in both the RASD and DD, not a bug.

# 6. Running the Released Software

## 6.1 Recommended Startup Sequence

Launch services in this order to prevent connection errors:

1. Ensure PostgreSQL is running, the meteocity database exists, and PostGIS is enabled on it.
2. Ensure backend/.env is correctly configured (Section 4.4).
3. Open Terminal 1 and start the Flask backend (Section 6.2).
4. Open Terminal 2 and start the dashboard (Section 6.3).
5. Open http://localhost:8501 in a web browser.

## 6.2 Start the Flask Backend

In Terminal 1, from the project root directory:

```
cd backend
python app.py
```

Expected: the backend listens on http://localhost:5000 and logs confirmed table creation on first run. Leave this terminal running.

## 6.3 Start the Dashboard

In Terminal 2, from the project root directory (not backend/):

```
streamlit run dashboard\meteocity_dashboard.py
```

The dashboard opens automatically at http://localhost:8501. The Flask backend must already be running before starting the dashboard.

## 6.4 Stopping the Services

Press Ctrl+C in Terminal 1 to stop the Flask backend. Press Ctrl+C in Terminal 2 to stop the dashboard. If using a conda environment, run conda deactivate when finished.

# 7. REST API Reference

All protected API endpoints require a JWT token in the Authorization header after login:

```
Authorization: Bearer <access_token>
```

| Method | Endpoint | Auth | RASD | Description |
|---|---|---|---|---|
| GET | /health | No | — | Health check; returns {"status":"ok"}. |
| POST | /auth/register | No | FR(Users) | Register a new user (username, password, role). |
| POST | /auth/login | No | FR(Users) | Authenticate user; returns JWT access token. |
| GET | /auth/logout | Yes | FR(Users) | Logs out the current user. |
| GET | /auth/profile | Yes | FR(Users) | Returns current user profile and role. |
| GET | /api/cities | Yes | FR3 | Returns list of monitored cities (Milan, Rome). |
| GET | /api/stations | Yes | FR2, TR5 | Returns station metadata; optional city_name filter. |
| GET | /api/observations | Yes | FR1–FR3 | Returns hourly observations with date/station filters. |
| GET | /api/trend_data | Yes | FR5, FR7 | Returns aggregated time-series for trend visualisation. |
| GET | /api/statistics | Gov | FR5 | Statistical summary (mean, max, min, std). Government only. |
| GET | /api/map_data | Yes | FR4 | Station data for map display with latest observation. |
| GET | /api/export_csv | Yes | TR7 | Exports filtered observations as downloadable CSV. |
| GET | /api/variables | Yes | FR6 | Returns list of available meteorological variables. |

*Table 8: REST API Endpoints*

## Example API Usage

Register a new user:

```
curl -X POST http://localhost:5000/auth/register ^
-H "Content-Type: application/json" ^
-d "{\"username\":\"testuser\",\"password\":\"test123\",\"role\":\"government\"}"
```

Login and retrieve JWT token:

```
curl -X POST http://localhost:5000/auth/login ^
-H "Content-Type: application/json" ^
-d "{\"username\":\"testuser\",\"password\":\"test123\"}"
```

Query stations for Milan:

```
curl -H "Authorization: Bearer <access_token>" ^
"http://localhost:5000/api/stations?city_name=Milan"
```

# 8. Dashboard User Guide

## 8.1 Login and Registration

The dashboard displays a login and registration interface when first launched. New users select a role (Student/Researcher, NGO, or Government Official) and register with a username and password (minimum 6 characters). After logging in, a JWT session token is stored for the duration of the session.

The login screen features MeteoCity branding over a Milan and Rome cityscape background. A role description panel informs new users of available access levels.

## 8.2 Typical Workflow

1. Register or log in via the login/registration screen.
2. Select a city (Milan or Rome) and date range using the sidebar filtering widgets.
3. Select the weather variable (Temperature, Humidity, or Wind Speed).
4. Click Show Analysis; the dashboard queries the REST API and renders colour-coded station markers on the map.
5. Navigate to the Trend Analysis tab for hourly readings with a 24-hour moving average and weekly average bar charts.
6. Navigate to the Statistics tab (Government Official and NGO roles) for descriptive statistics per station.
7. Use the Export CSV tab to download the currently filtered observations.
8. Click Logout to end the session.

## 8.3 Role-Based Access

| Feature | Student/Researcher | NGO | Government Official |
|---|---|---|---|
| Map & Stations | ✓ | ✓ | ✓ |
| Query & Filtering | ✓ | ✓ | ✓ |
| Trend Analysis | ✗ | ✓ | ✓ |
| Statistics Dashboard | ✗ | ✗ | ✓ |
| Export CSV | ✓ | ✓ | ✓ |
| User Registration | ✓ | ✓ | ✓ |
| All API Endpoints | ✗ | ✗ | ✓ |

*Table 9: Role-Based Access Summary*

# 9. Testing and Release Validation

## 9.1 Running the Test Suite

A comprehensive test suite is implemented using the pytest framework. All test files are in the tests/ directory. The Flask backend must be running before executing tests that make HTTP requests.

```
pytest tests/ -v
```

| Test ID | Component | Description | Expected Outcome |
|---|---|---|---|
| UT01 | Backend API | POST /auth/register with valid credentials | 201 Created; user saved in database. |
| UT02 | Backend API | POST /auth/login with correct credentials | 200 OK; JWT token returned. |
| UT03 | Backend API | POST /auth/login with incorrect password | 401 Unauthorized. |
| UT04 | Backend API | GET /api/stations returns station list | 200 OK; JSON array of stations. |
| UT05 | Backend API | GET /api/observations with valid filters | 200 OK; filtered records returned. |
| UT06 | Backend API | GET /api/statistics without government role | 403 Forbidden. |
| UT07 | Backend API | GET /api/export_csv with valid filters | 200 OK; CSV file returned. |
| UT08 | Database | Database connection and table creation | All tables created without error. |
| UT09 | Database | Insert and retrieve WeatherStation record | Record persists and is returned correctly. |
| UT10 | Database | Insert and retrieve Observation with timestamp filter | Correct records returned for date range. |
| UT11 | Database | Duplicate observation insert (upsert logic) | Duplicate skipped; no error raised. |
| UT12 | Meteostat | Fetch hourly observations for valid station and range | Observations returned and stored in database. |

*Table 10: Unit Test Cases*

## 9.2 Manual Acceptance Checklist

Verify the following before final submission and demonstration:

- PostgreSQL is running, the meteocity database exists, and PostGIS is enabled on it.
- backend/.env is correctly configured with DATABASE_URL, JWT_SECRET_KEY, and (optionally) RAPIDAPI_KEY.
- Flask backend starts without errors on http://localhost:5000.
- GET /health returns {"status": "ok"}.
- A user can register with each role (student, ngo, government) and log in successfully.
- Protected endpoints reject requests without a valid JWT token (401 Unauthorized).
- The dashboard connects to localhost:5000 and loads city/station data.
- Map markers are visible and colour-coded for Milan and Rome.
- Observation charts render correctly for selected date ranges.
- Statistics tab is accessible for Government Official and NGO but hidden for Student.

- CSV export downloads a file with the correct columns for the selected variable.
- The GitHub repository contains RASD, DD, SRD, and all source code.

# 10. Known Limitations and Troubleshooting

## 10.1 Known Limitations

- Academic local release: The system is a local/development academic release and is not configured for production deployment or multi-user concurrent access.
- Meteostat 30-day API constraint: The Meteostat API enforces a hard 30-day maximum window per request (TR8 in the RASD). For ranges exceeding 30 days, real observations are supplemented with synthetic data automatically.
- RapidAPI quota: The free Meteostat plan allows 500 requests per month. Repeated live ingestion may exhaust this quota.
- JWT logout blocklist: The JWT blocklist is stored in memory. Revoked tokens are not persisted after backend restart.
- Hardcoded stations and cities: The system uses four hardcoded Meteostat station IDs. Adding new cities or stations requires code changes.
- No real-time data: The system does not provide real-time forecasting, live streaming, predictive modelling, or alerts.
- NGO registration case sensitivity: The frontend sends role value 'NGO' while the backend validates against 'ngo'. If NGO registration fails via the form, register directly via the API with role='ngo' (lowercase).

## 10.2 Troubleshooting Guide

| Problem | Likely Cause | Recommended Solution |
|---|---|---|
| Backend cannot start | DATABASE_URL wrong, PostgreSQL stopped, or database meteocity missing. | Start PostgreSQL, create the meteocity database, and verify DATABASE_URL in backend/.env. |
| 'meteocity_db' not found | Database name mismatch. | Ensure DATABASE_URL uses the name meteocity, not meteocity_db. |
| type "geometry" does not exist | PostGIS extension not enabled on the meteocity database. | Run CREATE EXTENSION postgis; on the meteocity database (Section 4.5), then restart the backend. |
| .env not found / config error | backend/.env does not exist on this machine. | Copy backend/.env.example to backend/.env and fill in real values (Section 4.4). |
| Dashboard cannot connect to Flask | Backend not running on localhost:5000. | Start cd backend && python app.py before launching the dashboard. |
| No observations / empty charts | Ingestion not triggered or date range has no records. | Click Show Analysis; select a date range within the available data window. |
| Statistics returns 403 | User does not have the government role. | Register or log in with role='government'. |
| RapidAPI calls fail | Invalid key, quota reached, or no internet. | Verify RAPIDAPI_KEY and RAPIDAPI_HOST in backend/.env; leave empty to use mock mode. |
| NGO registration fails | Frontend sends 'NGO'; backend expects 'ngo' (case mismatch). | Register via API with role='ngo' (lowercase) using curl or Postman. |

| Problem | Likely Cause | Recommended Solution |
|---|---|---|
| Map tiles do not load | No internet connection. | Ensure internet access is available for OpenStreetMap tiles to render. |

*Table 11: Troubleshooting Guide*

# 11. Generative AI Usage Declaration

In compliance with the Politecnico di Milano Code of Academic Conduct and the guidelines issued by the MeteoCity project for Academic Year 2025/26, Group 9 declares the following use of Generative AI tools during the development of the MeteoCity project.

## Tools Used

- Claude (Anthropic) — used as an AI programming assistant and documentation aid.
- GitHub Copilot — used for code auto-completion suggestions within the VS Code IDE.

## Scope of Use

- Code assistance: AI tools suggested boilerplate code, helped debug syntax errors, and proposed function implementations. All generated code was reviewed, understood, and modified by team members.
- Documentation: AI tools assisted in drafting and refining sections of the RASD, DD, and SRD. All factual content reflects the actual system implemented by the team.
- No AI-generated content was accepted uncritically or without verification.

## Responsibility Statement

All team members take full responsibility for the content of this document and the accompanying software artefacts. The use of Generative AI tools was limited to productivity enhancement and did not substitute for the intellectual contribution, design decisions, or engineering judgement of the team.

# 12. References


1 Meteostat API via RapidAPI. https://rapidapi.com/meteostat/api/meteostat/

2 Flask Documentation. Pallets Projects, 2024. https://flask.palletsprojects.com/

3 SQLAlchemy Documentation. 2024. https://docs.sqlalchemy.org/

4 PostgreSQL Documentation. 2024. https://www.postgresql.org/docs/

5 JWT — JSON Web Tokens. Auth0, 2024. https://jwt.io/introduction

6 Python Software Foundation. Python 3 Documentation, 2024. https://docs.python.org/3/

7 Politecnico di Milano. Software Engineering for Geoinformatics — Project Assignment Specification, Academic Year 2025/26.

8 Group 9. MeteoCity Requirement Analysis and Specification Document (RASD), June 2026. https://github.com/Ayman1017/Software-Engineering-Project-Group_9

9 Group 9. MeteoCity Design Document (DD), June 2026. https://github.com/Ayman1017/Software-Engineering-Project-Group_9

# Appendix A — Quick Start Summary

Complete setup and run sequence for MeteoCity on a clean machine:

```
# 1. Clone the repository
git clone https://github.com/Ayman1017/Software-Engineering-Project-Group_9.git
cd Software-Engineering-Project-Group_9

# 2. Install dependencies (Anaconda environment)
pip install -r requirements.txt

# 3. Create the PostgreSQL database
# In psql: CREATE DATABASE meteocity;
# Then: \c meteocity
# Then: CREATE EXTENSION postgis;
# (If meteocity already exists with unrelated content, drop and recreate it empty first)

# 4. Create backend/.env from the template
copy backend\.env.example backend\.env
# Edit backend/.env: set DATABASE_URL, JWT_SECRET_KEY, RAPIDAPI_KEY

# 5. Terminal 1 -- Start the Flask backend
cd backend
python app.py

# 6. Terminal 2 -- Start the dashboard (from project root)
streamlit run dashboard\meteocity_dashboard.py

# 7. Open browser: http://localhost:8501
```

# Appendix B — Environment File Template

The following is the content of backend/.env.example as committed to the repository. Copy this file to backend/.env and replace all placeholder values with real credentials. Never commit backend/.env to version control.

```
# MeteoCity -- Backend Environment Configuration
# Copy this file to backend/.env and fill in your values.
# NEVER commit backend/.env to GitHub -- it is listed in .gitignore.

# PostgreSQL connection string
# Database name must be 'meteocity' (NOT 'meteocity_db')
DATABASE_URL=postgresql://postgres:<your_password>@localhost:5432/meteocity

# Secret key for JWT token signing -- use a long random string
JWT_SECRET_KEY=change-this-to-a-long-random-secret

# RapidAPI key for live Meteostat data ingestion
# Leave empty or keep placeholder to run in mock (synthetic data) mode
RAPIDAPI_KEY=your-rapidapi-key-here
RAPIDAPI_HOST=meteostat.p.rapidapi.com

# Flask application environment
FLASK_ENV=development
```