Assignment 2:

File   Edit   Options   View   Tools   Extensions   Window   Help

Packet Tracer - Navigate the IOS

Objectives

Part 1: Establish Basic Connections, Access the CLI, and Explore Help

Part 2: Explore EXEC Modes

Part 3: Set the Clock

Background / Scenario

In this activity, you will practice skills necessary for navigating the Cisco IOS, such as different user access modes, various configuration modes, and common commands used on a regular basis. You will also practice accessing the context-sensitive Help by configuring the **clock** command.

Instructions

Part 1: Establish Basic Connections, Access the CLI, and Explore Help

Step 1: Connect PC1 to S1 using a console cable.

a. Click the **Connections** icon (the one that looks like a lightning bolt) in the lower left corner of the Packet Tracer window.

b. Select the light blue Console cable by clicking it. The mouse pointer will change to what appears to be a connector with a cable dangling from it.

c. Click **PC1**. A window displays an option for an RS-232 connection. Connect the cable to the RS-232 port.

d. Drag the other end of the console connection to the S1 switch and click the switch to access the connection list.

e. Select the **Console** port to complete the connection.

Step 2: Establish a terminal session with S1.

a. Click **PC1** and then select the **Desktop** tab.

b. Click the **Terminal** application icon. Verify that the Port Configuration default settings are correct.

What is the setting for bits per second?

c. The screen that appears may have several messages displayed. Somewhere on the screen there should be a **Press RETURN to get started!** message. Press ENTER.

What is the prompt displayed on the screen?

Step 3: Explore the IOS Help.

Terminal Configuration

Port Configuration

Bits Per Second:	9600
Data Bits:	8
Parity:	None
Stop Bits:	1
Flow Control:	None

OK

PC1 — Physical | Desktop | Programming | Attributes

Terminal

```
Importers, exporters, distributors and users are responsible for
compliance with U.S. and local country laws. By using this product you
agree to comply with applicable laws and regulations. If you are unable
to comply with U.S. and local laws, return this product immediately.
A summary of U.S. laws governing Cisco cryptographic products may be found at:
http://www.cisco.com/wwl/export/crypto/tool/stqrg.html
If you require further assistance please contact us by sending email to
export@cisco.com.
cisco WS-C2960-24TT-L (PowerPC405) processor (revision B0) with 65536K bytes of memory.
Processor board ID FOC1010X104
Last reset from power-on
1 Virtual Ethernet interface
24 FastEthernet interfaces
2 Gigabit Ethernet interfaces
The password-recovery mechanism is enabled.
64K bytes of flash-simulated non-volatile configuration memory.
Base ethernet MAC Address       : 00:02:17:14:29:63
Motherboard assembly number     : 73-10390-03
Power supply part number        : 341-0097-02
Motherboard serial number       : FOC10093R12
Power supply serial number      : AZS1007032H
Model revision number           : B0
Motherboard revision number     : B0
Model number                    : WS-C2960-24TT-L
System serial number            : FOC1010X104
Top Assembly Part Number        : 800-27221-02
Top Assembly Revision Number    : A0
Version ID                      : V02
CLEI Code Number                : COM3L00BRA
Hardware Board Revision Number  : 0x01

Switch Ports Model              SW Version        SW Image
------ ----- -----              ----------        --------
*    1 26    WS-C2960-24TT-L    15.0(2)SE4        C2960-LANBASEK9-M

Cisco IOS Software, C2960 Software (C2960-LANBASEK9-M), Version 15.0(2)SE4, RELEASE SOFTWARE (fc1)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2013 by Cisco Systems, Inc.
Compiled Wed 26-Jun-13 02:49 by mnguyen


Press RETURN to get started!

S1>
```

Which command begins with the letter 'C'? -- "Command"

PC1   —   □   X

Physical   Desktop   Programming   Attributes

Terminal   X

```
64K bytes of flash-simulated non-volatile configuration memory.
Base ethernet MAC Address        : 00:02:17:14:29:63
Motherboard assembly number      : 73-10390-03
Power supply part number         : 341-0097-02
Motherboard serial number        : FOC10093R12
Power supply serial number       : AZS1007032H
Model revision number            : B0
Motherboard revision number      : B0
Model number                     : WS-C2960-24TT-L
System serial number             : FOC1010X104
Top Assembly Part Number         : 800-27221-02
Top Assembly Revision Number     : A0
Version ID                       : V02
CLEI Code Number                 : COM3L00BRA
Hardware Board Revision Number   : 0x01

Switch Ports Model              SW Version           SW Image
------ ----- -----             ----------           ----------
*    1 26    WS-C2960-24TT-L    15.0(2)SE4           C2960-LANBASEK9-M

Cisco IOS Software, C2960 Software (C2960-LANBASEK9-M), Version 15.0(2)SE4, RELEASE SOFTWARE (fc1)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2013 by Cisco Systems, Inc.
Compiled Wed 26-Jun-13 02:49 by mnguyen



Press RETURN to get started!



S1>?
Exec commands:
  connect     Open a terminal connection
  disable     Turn off privileged commands
  disconnect  Disconnect an existing network connection
  enable      Turn on privileged commands
  exit        Exit from the EXEC
  logout      Exit from the EXEC
  ping        Send echo messages
  resume      Resume an active network connection
  show        Show running system information
  ssh         Open a secure shell client connection
  telnet      Open a telnet connection
  terminal    Set terminal line parameters
  traceroute  Trace route to destination
S1>
```

Top

PC1

Physical | Desktop | Programming | Attributes

Terminal

```
Motherboard assembly number        : 73-10390-03
Power supply part number           : 341-0097-02
Motherboard serial number          : FOC10093R12
Power supply serial number         : AZS1007032H
Model revision number              : B0
Motherboard revision number        : B0
Model number                       : WS-C2960-24TT-L
System serial number               : FOC1010X104
Top Assembly Part Number           : 800-27221-02
Top Assembly Revision Number       : A0
Version ID                         : V02
CLEI Code Number                   : COM3L00BRA
Hardware Board Revision Number     : 0x01

Switch Ports Model              SW Version          SW Image
------ ----- -----              ----------          ----------
*    1 26    WS-C2960-24TT-L    15.0(2)SE4          C2960-LANBASEK9-M

Cisco IOS Software, C2960 Software (C2960-LANBASEK9-M), Version 15.0(2)SE4, RELEASE SOFTWARE (fc1)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2013 by Cisco Systems, Inc.
Compiled Wed 26-Jun-13 02:49 by mnguyen



Press RETURN to get started!



S1>?
Exec commands:
  connect     Open a terminal connection
  disable     Turn off privileged commands
  disconnect  Disconnect an existing network connection
  enable      Turn on privileged commands
  exit        Exit from the EXEC
  logout      Exit from the EXEC
  ping        Send echo messages
  resume      Resume an active network connection
  show        Show running system information
  ssh         Open a secure shell client connection
  telnet      Open a telnet connection
  terminal    Set terminal line parameters
  traceroute  Trace route to destination
S1>t?
telnet  terminal  traceroute
S1>t
```

Top

PC1

Physical   Desktop   Programming   Attributes

Terminal   X

```
Motherboard serial number       : FOC10093R12
Power supply serial number       : AZS1007032H
Model revision number            : B0
Motherboard revision number      : B0
Model number                     : WS-C2960-24TT-L
System serial number             : FOC1010X104
Top Assembly Part Number         : 800-27221-02
Top Assembly Revision Number     : A0
Version ID                       : V02
CLEI Code Number                 : COM3L00BRA
Hardware Board Revision Number   : 0x01


Switch Ports Model               SW Version           SW Image
------ ----- -----               ----------           ----------
*    1 26    WS-C2960-24TT-L      15.0(2)SE4           C2960-LANBASEK9-M

Cisco IOS Software, C2960 Software (C2960-LANBASEK9-M), Version 15.0(2)SE4, RELEASE SOFTWARE (fc1)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2013 by Cisco Systems, Inc.
Compiled Wed 26-Jun-13 02:49 by mnguyen



Press RETURN to get started!



S1>?
Exec commands:
  connect     Open a terminal connection
  disable     Turn off privileged commands
  disconnect  Disconnect an existing network connection
  enable      Turn on privileged commands
  exit        Exit from the EXEC
  logout      Exit from the EXEC
  ping        Send echo messages
  resume      Resume an active network connection
  show        Show running system information
  ssh         Open a secure shell client connection
  telnet      Open a telnet connection
  terminal    Set terminal line parameters
  traceroute  Trace route to destination
S1>t?
telnet  terminal  traceroute
S1>te?
telnet  terminal
S1>te
```

Top

PART 2:

Step 1:


```
Power supply serial number      : AZS1007032H
Model revision number           : B0
Motherboard revision number     : B0
Model number                    : WS-C2960-24TT-L
System serial number            : FOC1010X104
Top Assembly Part Number        : 800-27221-02
Top Assembly Revision Number    : A0
Version ID                      : V02
CLEI Code Number                : COM3L00BRA
Hardware Board Revision Number  : 0x01

Switch Ports Model              SW Version          SW Image
------ ----- -----              ----------          ----------
*    1 26    WS-C2960-24TT-L    15.0(2)SE4          C2960-LANBASEK9-M

Cisco IOS Software, C2960 Software (C2960-LANBASEK9-M), Version 15.0(2)SE4, RELEASE SOFTWARE (fc1)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2013 by Cisco Systems, Inc.
Compiled Wed 26-Jun-13 02:49 by mnguyen




Press RETURN to get started!




S1>?
Exec commands:
  connect     Open a terminal connection
  disable     Turn off privileged commands
  disconnect  Disconnect an existing network connection
  enable      Turn on privileged commands
  exit        Exit from the EXEC
  logout      Exit from the EXEC
  ping        Send echo messages
  resume      Resume an active network connection
  show        Show running system information
  ssh         Open a secure shell client connection
  telnet      Open a telnet connection
  terminal    Set terminal line parameters
  traceroute  Trace route to destination
S1>t?
telnet  terminal  traceroute
S1>te?
telnet  terminal
S1>en
S1>enable
```

PC1 — □ ✕

Physical   Desktop   Programming   Attributes

Terminal   X

```
Copyright (c) 1986-2013 by Cisco Systems, Inc.
Compiled Wed 26-Jun-13 02:49 by mnguyen



Press RETURN to get started!



S1>?
Exec commands:
  connect     Open a terminal connection
  disable     Turn off privileged commands
  disconnect  Disconnect an existing network connection
  enable      Turn on privileged commands
  exit        Exit from the EXEC
  logout      Exit from the EXEC
  ping        Send echo messages
  resume      Resume an active network connection
  show        Show running system information
  ssh         Open a secure shell client connection
  telnet      Open a telnet connection
  terminal    Set terminal line parameters
  traceroute  Trace route to destination
S1>t?
telnet  terminal  traceroute
S1>te?
telnet  terminal
S1>en
S1>?
Exec commands:
  connect     Open a terminal connection
  disable     Turn off privileged commands
  disconnect  Disconnect an existing network connection
  enable      Turn on privileged commands
  exit        Exit from the EXEC
  logout      Exit from the EXEC
  ping        Send echo messages
  resume      Resume an active network connection
  show        Show running system information
  ssh         Open a secure shell client connection
  telnet      Open a telnet connection
  terminal    Set terminal line parameters
  traceroute  Trace route to destination
S1>en
S1>enable
S1#
```

Top

```
PC1                                                    —   □   X

Physical    Desktop    Programming    Attributes

Terminal                                                          X

S1>te?
telnet  terminal
S1>en
S1>?
Exec commands:
  connect     Open a terminal connection
  disable     Turn off privileged commands
  disconnect  Disconnect an existing network connection
  enable      Turn on privileged commands
  exit        Exit from the EXEC
  logout      Exit from the EXEC
  ping        Send echo messages
  resume      Resume an active network connection
  show        Show running system information
  ssh         Open a secure shell client connection
  telnet      Open a telnet connection
  terminal    Set terminal line parameters
  traceroute  Trace route to destination
S1>en
S1>enable
S1#?
Exec commands:
  clear       Reset functions
  clock       Manage the system clock
  configure   Enter configuration mode
  connect     Open a terminal connection
  copy        Copy from one file to another
  debug       Debugging functions (see also 'undebug')
  delete      Delete a file
  dir         List files on a filesystem
  disable     Turn off privileged commands
  disconnect  Disconnect an existing network connection
  enable      Turn on privileged commands
  erase       Erase a filesystem
  exit        Exit from the EXEC
  logout      Exit from the EXEC
  more        Display the contents of a file
  no          Disable debugging informations
  ping        Send echo messages
  reload      Halt and perform a cold restart
  resume      Resume an active network connection
  setup       Run the SETUP command facility
  show        Show running system information

S1#c?
clear   clock   configure   connect   copy
S1#c

Top
```

Step 2:

PC1   —   □   X

Physical   Desktop   Programming   Attributes

Terminal   X

```
Exec commands:
  connect     Open a terminal connection
  disable     Turn off privileged commands
  disconnect  Disconnect an existing network connection
  enable      Turn on privileged commands
  exit        Exit from the EXEC
  logout      Exit from the EXEC
  ping        Send echo messages
  resume      Resume an active network connection
  show        Show running system information
  ssh         Open a secure shell client connection
  telnet      Open a telnet connection
  terminal    Set terminal line parameters
  traceroute  Trace route to destination
S1>en
S1>enable
S1#?
Exec commands:
  clear       Reset functions
  clock       Manage the system clock
  configure   Enter configuration mode
  connect     Open a terminal connection
  copy        Copy from one file to another
  debug       Debugging functions (see also 'undebug')
  delete      Delete a file
  dir         List files on a filesystem
  disable     Turn off privileged commands
  disconnect  Disconnect an existing network connection
  enable      Turn on privileged commands
  erase       Erase a filesystem
  exit        Exit from the EXEC
  logout      Exit from the EXEC
  more        Display the contents of a file
  no          Disable debugging informations
  ping        Send echo messages
  reload      Halt and perform a cold restart
  resume      Resume an active network connection
  setup       Run the SETUP command facility
  show        Show running system information

S1#c?
clear  clock  configure  connect  copy
S1#confi
S1#configure
Configuring from terminal, memory, or network [terminal]?
Enter configuration commands, one per line.  End with CNTL/Z.
S1(config)#
```

Top

Physical   Desktop   Programming   Attributes

Terminal   X

```
   more        Display the contents of a file
   no          Disable debugging informations
   ping        Send echo messages
   reload      Halt and perform a cold restart
   resume      Resume an active network connection
   setup       Run the SETUP command facility
   show        Show running system information

S1#c?
clear  clock  configure  connect  copy
S1#confi
S1#configure
Configuring from terminal, memory, or network [terminal]?
Enter configuration commands, one per line.  End with CNTL/Z.
S1(config)#end
S1#
%SYS-5-CONFIG_I: Configured from console by console
exit




S1 con0 is now available




Press RETURN to get started.
```

Top

Part 3: Step1:

PC1

Physical | Desktop | Programming | Attributes

Terminal   X

```
S1#c?
clear   clock   configure   connect   copy
S1#confi
S1#configure
Configuring from terminal, memory, or network [terminal]?
Enter configuration commands, one per line.  End with CNTL/Z.
S1(config)#end
S1#
%SYS-5-CONFIG_I: Configured from console by console
exit




S1 con0 is now available




Press RETURN to get started.









S1>enable
S1#show clock
*0:22:22.371 UTC Mon Mar 1 1993
S1#clock?
clock
S1#clock
```

Top

Set date and time.


```
S1>enable
S1#show clock
*0:22:22.371 UTC Mon Mar 1 1993
S1#clock?
clock
S1#clock set?
set
S1#clock set 15:00:00?
hh:mm:ss
S1# Day of the month?
% Unrecognized command
S1# set date?
% Unrecognized command
S1# date?
% Unrecognized command
S1# show clock?
clock
S1# show clock
*0:28:12.279 UTC Mon Mar 1 1993
S1#clock set 15:00:00?
hh:mm:ss
S1#clock set 15:00:00
% Incomplete command.
S1#clock set 15:0:00?
hh:mm:ss
S1#clock set 15:00:00?
hh:mm:ss
S1#clock set 15:00:00<1-31> Day of the month?
% Unrecognized command
S1#clock set 15:00:00<1-31> Day of the month
                    ^
% Invalid input detected at '^' marker.

S1#clock set 15:00:00?
hh:mm:ss
S1#clock set 15:00:00 15?
<1-31>
S1#clock set 15:00:00 15 Feb?
MONTH
S1#clock set 15:00:00 15 Feb 2035?
<1993-2035>
S1#clock set 15:00:00 15 Feb 2035
S1#show clock
15:0:12.411 UTC Thu Feb 15 2035
S1#
```

Top