

Focus search box

[array_push »](#)

[« array_pop](#)

- [Manual de PHP](#)
- [Referencia de funciones](#)
- [Extensiones relacionadas con variable y tipo](#)
- [Arrays](#)
- [Funciones de Arrays](#)

Change language: Spanish ▼

[Submit a Pull Request](#) [Report a Bug](#)

array_product

(PHP 5 >= 5.1.0, PHP 7, PHP 8)

array_product — Calcula el producto de los valores de un array

Descripción ¶

array_product(array \$array): number

array_product() devuelve el producto de valores de un array.

Parámetros ¶

array

El array.

Valores devueltos ¶

Devuelve el producto como integer o float.

Historial de cambios ¶

Versión	Descripción
5.3.6	El producto de un array vacío ahora es 1, mientras que antes esta función devolvía 0 para un array vacío.

Ejemplos ¶

Ejemplo #1 Ejemplo de array_product()

```
<?php
```

```
$a = array(2, 4, 6, 8);  
echo "producto(a) = " . array_product($a) . "\n";  
echo "producto(array()) = " . array_product(array()) . "\n";
```

```
?>
```

El resultado del ejemplo sería:

```
producto(a) = 384
producto(array()) = 1
```

[+ add a note](#)

User Contributed Notes 6 notes

[up](#)
[down](#)

29

[Andre D.](#)

16 years ago

This function can be used to test if all values in an array of booleans are TRUE.

Consider:

```
<?php
```

```
function outbool($test)
{
    return (bool) $test;
}
```

```
$check[] = outbool(TRUE);
$check[] = outbool(1);
$check[] = outbool(FALSE);
$check[] = outbool(0);
```

```
$result = (bool) array_product($check);
// $result is set to FALSE because only two of the four values evaluated to TRUE
```

```
?>
```

The above is equivalent to:

```
<?php
```

```
$check1 = outbool(TRUE);
$check2 = outbool(1);
$check3 = outbool(FALSE);
$check4 = outbool(0);
```

```
$result = ($check1 && $check2 && $check3 && $check4);
```

```
?>
```

This use of array_product is especially useful when testing an indefinite number of booleans and is easy to construct in a loop.

[up](#)
[down](#)

10

[bsr dot anwar at gmail dot com](#)

5 years ago

Here's how you can find a factorial of a any given number with help of range and array_product functions.

```
function factorial($num) {
    return array_product(range(1, $num));
}
```

}

```
printf("%d", factorial(5)); //120
```

[up](#)[down](#)

0

[biziclop ¶](#)**17 days ago**

You can use `array_product()` to calculate the geometric mean of an array of numbers:

```
<?php
$a = [ 1, 10, 100 ];
$geom_avg = pow( array_product( $a ), 1 / count( $a ));
// = 9.999999999999998 ≈ 10
?>
```

[up](#)[down](#)

-1

[Marcel G ¶](#)**12 years ago**

You can use `array_product` to calculate the factorial of `n`:

```
<?php
function factorial( $n )
{
    if( $n < 1 ) $n = 1;
    return array_product( range( 1, $n ));
}
?>
```

If you need the factorial without having `array_product` available, here is one:

```
<?php
function factorial( $n )
{
    if( $n < 1 ) $n = 1;
    for( $p++; $n; ) $p *= $n--;
    return $p;
}
?>
```

[up](#)[down](#)

-2

[Jimmy PHP ¶](#)**8 years ago**

`array_product()` can be used to implement a simple boolean AND search

```
<?php
$args = array('first_name'=>'Bill','last_name'=>'Buzzard');
$values[] = array('first_name'=>'Brenda','last_name'=>'Buzzard');
$values[] = array('first_name'=>'Victor','last_name'=>'Vulture');
$values[] = array('first_name'=>'Bill','last_name'=>'Blue Jay');
$values[] = array('first_name'=>'Bill','last_name'=>'Buzzard');
```

```
$result = search_for($values,$args);
var_dump($result);exit;
```

```
function search_for($array,$args) {
    $results = array();
    foreach ($array as $row) {
```

```

    $found = false;
    $hits = array();
    foreach ($row as $k => $v) {
        if (array_key_exists($k,$args)) $hits[$k] = ($args[$k] == $v);
    }

    $found = array_product($hits);
    if (!in_array($row,$results) && true == $found) $results[] = $row;
}

return $results;
}
?>

```

Output:

```

array (size=1)
  0 =>
    array (size=2)
      'first_name' => string 'Bill' (length=4)
      'last_name' => string 'Buzzard' (length=7)

```

[up](#)
[down](#)

-7

[pqppq at wanadoo dot nl](#)

15 years ago

An observation about the `_use_` of `array_product` with primes:

```

$a=$arrayOfSomePrimes=(2,3,11);
    // 2 being the first prime (these days)

$codeNum=array_product($a); // gives 66 (== 2*3*11)

echo "unique product(\$a) = " . array_product($a) . "\n";

```

The 66 can (only) be split into its original primes, which can be transformed into their place in the row of primes (2,3,5,7,11,13,17,19...) giving (1,2,3,4,5,6,7,8...)

The 66 gives the places {1,2,5} in the row of primes. The number "66" is unique as a code for {1,2,5}

So you can define the combination of table-columns {1,2,5} in "66". The bigger the combination, the more efficient in memory/transmission, the less in calculation.

[+ add a note](#)

- [Funciones de Arrays](#)
 - [array_change_key_case](#)
 - [array_chunk](#)
 - [array_column](#)
 - [array_combine](#)
 - [array_count_values](#)
 - [array_diff_assoc](#)
 - [array_diff_key](#)
 - [array_diff_uassoc](#)
 - [array_diff_ukey](#)
 - [array_diff](#)
 - [array_fill_keys](#)

- [array_fill](#)
- [array_filter](#)
- [array_flip](#)
- [array_intersect_assoc](#)
- [array_intersect_key](#)
- [array_intersect_uassoc](#)
- [array_intersect_ukey](#)
- [array_intersect](#)
- [array_is_list](#)
- [array_key_exists](#)
- [array_key_first](#)
- [array_key_last](#)
- [array_keys](#)
- [array_map](#)
- [array_merge_recursive](#)
- [array_merge](#)
- [array_multisort](#)
- [array_pad](#)
- [array_pop](#)
- [array_product](#)
- [array_push](#)
- [array_rand](#)
- [array_reduce](#)
- [array_replace_recursive](#)
- [array_replace](#)
- [array_reverse](#)
- [array_search](#)
- [array_shift](#)
- [array_slice](#)
- [array_splice](#)
- [array_sum](#)
- [array_udiff_assoc](#)
- [array_udiff_uassoc](#)
- [array_udiff](#)
- [array_uintersect_assoc](#)
- [array_uintersect_uassoc](#)
- [array_uintersect](#)
- [array_unique](#)
- [array_unshift](#)
- [array_values](#)
- [array_walk_recursive](#)
- [array_walk](#)
- [array](#)
- [arsort](#)
- [asort](#)
- [compact](#)
- [count](#)
- [current](#)
- [end](#)
- [extract](#)
- [in_array](#)
- [key_exists](#)
- [key](#)
- [krsort](#)
- [ksort](#)
- [list](#)
- [natcasesort](#)
- [natsort](#)

- [next](#)
 - [pos](#)
 - [prev](#)
 - [range](#)
 - [reset](#)
 - [rsort](#)
 - [shuffle](#)
 - [sizeof](#)
 - [sort](#)
 - [uasort](#)
 - [uksort](#)
 - [usort](#)
- Deprecated
 - [each](#)
- [Copyright © 2001-2022 The PHP Group](#)
- [My PHP.net](#)
- [Contact](#)
- [Other PHP.net sites](#)
- [Privacy policy](#)
- [View Source](#)

