



Inspire...Educate...Transform.

4. Link Analysis Algorithms

Dr. Manish Gupta

Sr. Mentor – Academics, INSOF

Adapted from <http://infolab.stanford.edu/~ullman/mining/2009/PageRank.ppt>

Course Content

- Collection of three main topics of high recent interest.
 - Search engines (Crawling, Indexing, Ranking)
 - Language Modeling
 - Text Indexing and Crawling
 - Relevance Ranking
 - **Link Analysis Algorithms**
 - Text Processing (NLP, NER, Sentiments)
 - Natural Language Processing
 - Named Entity Recognition
 - Sentiment Analysis
 - Summarization
 - Social networks (Properties, Influence Propagation)
 - Social Network Analysis
 - Influence Propagation in Social Networks


Today's Agenda

- PageRank

Ranking Web Pages

- Web pages are not equally “important”
 - www.joe-schmoe.com vs www.stanford.edu
- Inlinks as votes
 - www.stanford.edu has 23,400 inlinks
 - www.joe-schmoe.com has 1 inlink
- Are all inlinks equal?
 - Recursive question
 - Each link’s vote is proportional to the **importance** of its source page
 - If page **P** with importance **x** has **n** outlinks, each link gets x/n votes
 - Page **P**’s own importance is the sum of the votes on its inlinks

Simple “Flow” Model



$$y = y/2 + a/2$$

$$a = y/2 + m$$

$$m = a/2$$


Solving the Flow Equations

- 3 equations, 3 unknowns, no constants
 - No unique solution
 - All solutions equivalent modulo scale factor
- Additional constraint forces uniqueness
 - $y+a+m = 1$
 - $y = 2/5, a = 2/5, m = 1/5$
- Gaussian elimination method works for small examples, but we need a better method for large graphs

Matrix Formulation

Suppose page j links to 3 pages, including i

M =web linkage matrix
 r =rank vector



$$y = y/2 + a/2$$

$$a = y/2 + m$$

$$m = a/2$$


$$\begin{bmatrix} y \\ a \\ m \end{bmatrix} = \begin{bmatrix} 1/2 & 1/2 & 0 \\ 1/2 & 0 & 1 \\ 0 & 1/2 & 0 \end{bmatrix} \begin{bmatrix} y \\ a \\ m \end{bmatrix}$$

r is the principal eigen-vector of M

Power Iteration Method

- Simple iterative scheme
- Suppose there are N web pages
- Initialize: $\mathbf{r}^0 = [1/N, \dots, 1/N]^T$
- Iterate: $\mathbf{r}^{k+1} = \mathbf{M}\mathbf{r}^k$
- Stop when $\|\mathbf{r}^{k+1} - \mathbf{r}^k\|_1 < \varepsilon$
 - $\|\mathbf{x}\|_1 = \sum_{1 \leq i \leq N} |x_i|$ is the L1 norm
 - Can use any other vector norm e.g., Euclidean

Power Iteration Example



	y	a	m
y	1/2	1/2	0
a	1/2	0	1
m	0	1/2	0

y		1/3	1/3	5/12	3/8		2/5
a	=	1/3	1/2	1/3	11/24	...	2/5
m		1/3	1/6	1/4	1/6		1/5


Random Walk Interpretation

- Imagine a **random web surfer**
 - At any time t , surfer is on some page P
 - At time $t+1$, the surfer follows an outlink from P uniformly at random
 - Ends up on some page Q linked from P
 - Process repeats indefinitely
- Let $\mathbf{p}(t)$ be a vector whose i^{th} component is the probability that the surfer is at page i at time t
 - $\mathbf{p}(t)$ is a probability distribution on pages

The Stationary Distribution

- Where is the surfer at time $t+1$?
 - Follows a link uniformly at random
 - $\mathbf{p}(t+1) = \mathbf{M}\mathbf{p}(t)$
- Suppose the random walk reaches a state such that $\mathbf{p}(t+1) = \mathbf{M}\mathbf{p}(t) = \mathbf{p}(t)$
 - Then $\mathbf{p}(t)$ is called a **stationary distribution** for the random walk
- Our rank vector \mathbf{r} satisfies $\mathbf{r} = \mathbf{M}\mathbf{r}$
 - So it is a stationary distribution for the random surfer

Bow-tie Structure of the Web




Spider Traps

- A group of pages is a **spider trap** if there are no links from within the group to outside the group
 - Random surfer gets trapped
- Spider traps violate the conditions needed for the random walk theorem

Random Teleports

- Solution for spider traps
- At each time step, the random surfer has two options:
 - With probability β , follow a link at random
 - With probability $1-\beta$, jump to some page uniformly at random
 - Common values for β are in the range 0.8 to 0.9
- Surfer will teleport out of spider trap within a few time steps

Random Teleports ($\beta = 0.8$)




$$\begin{array}{c} y \\ a \\ m \end{array} \begin{array}{c} y \\ 1/2 \\ 1/2 \\ 0 \end{array} \quad 0.8 * \begin{array}{c} y \\ 1/2 \\ 1/2 \\ 0 \end{array} + 0.2 * \begin{array}{c} y \\ 1/3 \\ 1/3 \\ 1/3 \end{array}$$

$$\begin{array}{c} 1/2 \ 1/2 \ 0 \\ 1/2 \ 0 \ 0 \\ 0 \ 1/2 \ 1 \end{array} \quad + 0.2 \begin{array}{c} 1/3 \ 1/3 \ 1/3 \\ 1/3 \ 1/3 \ 1/3 \\ 1/3 \ 1/3 \ 1/3 \end{array}$$

$$\begin{array}{c} y \\ a \\ m \end{array} \begin{array}{ccc} 7/15 & 7/15 & 1/15 \\ 7/15 & 1/15 & 1/15 \\ 1/15 & 7/15 & 13/15 \end{array}$$

Random Teleports ($\beta = 0.8$)



$$0.8 \begin{bmatrix} 1/2 & 1/2 & 0 \\ 1/2 & 0 & 0 \\ 0 & 1/2 & 1 \end{bmatrix} + 0.2 \begin{bmatrix} 1/3 & 1/3 & 1/3 \\ 1/3 & 1/3 & 1/3 \\ 1/3 & 1/3 & 1/3 \end{bmatrix}$$

$$\begin{matrix} y \\ a \\ m \end{matrix} \begin{bmatrix} 7/15 & 7/15 & 1/15 \\ 7/15 & 1/15 & 1/15 \\ 1/15 & 7/15 & 13/15 \end{bmatrix}$$

$$\begin{matrix} y \\ a \\ m \end{matrix} = \begin{matrix} 1 & 1.00 & 0.84 & 0.776 & 7/11 \\ 1 & 0.60 & 0.60 & 0.536 & 5/11 \\ 1 & 1.40 & 1.56 & 1.688 & 21/11 \end{matrix}$$

The **PageRank vector** \mathbf{r} is the stationary distribution of the random walk with teleports

Dealing with Dead-ends

- Pages with no outlinks are “dead ends” for the random surfer
- Teleport
 - Follow random teleport links with probability 1.0 from dead-ends
 - Adjust matrix accordingly
- Prune and propagate
 - Preprocess the graph to eliminate dead-ends
 - Might require multiple passes
 - Compute PageRank on reduced graph
 - Approximate values for deadends by propagating values from reduced graph

Today's Agenda

- PageRank
- Topic-Specific PageRank

Topic-sensitive PageRank

- $r = \beta Mr + (1-\beta)p$
- **Conventional PageRank:** p is a uniform vector with values $1/N$
- Topic-sensitive PageRank uses a **non-uniform** personalization vector p
- Not simply a post-processing step of the PageRank computation
- Personalization vector p introduces bias in all iterations of the iterative computation of the PageRank vector

Personalization Vector

Topic-sensitive PageRank: Overall Approach

- Preprocessing
 - Fix a set of k topics
 - For each topic c_j compute the PageRank scores of page u wrt to the j -th topic: $r(u,j)$
- Query-time processing:
 - For query q compute the total score of page u wrt q as $\text{score}(u,q) = \sum_{j=1 \dots k} \text{Pr}(c_j|q) r(u,j)$

Topic-sensitive PageRank: Preprocessing

- Create k different biased PageRank vectors using some pre-defined set of k categories (c_1, \dots, c_k)
 - E.g., Open Directory (DMOZ)'s 16 top level categories like sports, medicine, etc.
- T_j : set of URLs in the j -th category
- Use non-uniform personalization vector p_j such that:

$$p_j(v) = \begin{cases} \frac{1}{T_j} & \dots v \in T_j \\ 0 & \dots \text{otherwise} \end{cases}$$

Topic-sensitive PageRank: Query Processing

- $\text{score}(u, q) = \sum_{j=1 \dots k} \text{Pr}(c_j | q) r(u, j)$

$$\text{Pr}(c_j | q) = \frac{\text{Pr}(c_j) \text{Pr}(q | c_j)}{\text{Pr}(q)} \propto \text{Pr}(c_j) \prod_i \text{Pr}(q_i | c_j)$$

- How can we compute $\text{Pr}(c_j)$?
 - Can be fixed as uniform
 - Can be biased to a particular set of categories if we have that information about the user
- How can we compute $\text{Pr}(q | c_j)$?
 - Estimated using n-gram model from set of URLs in j-th category.

Take-away Messages

- Linkage on the web is an important phenomena
- Links contain a lot of knowledge
- Knowledge in the link structure can be used to rank webpages
 - Using PageRank
 - Using Topic Sensitive PageRank

Further Reading

- [A nice summary of link analysis algorithms from John Kleinberg](#)
 - <http://dl.acm.org/citation.cfm?id=345982>
- Chapter 5: "Link Analysis" from [Mining of Massive Datasets](#)
 - <http://infolab.stanford.edu/~ullman/mmds.html>
- Chapter 7 (Social Network Analysis) from [Mining the Web](#)
 - <http://www.cse.iitb.ac.in/soumen/mining-the-web/>
- J.M. Kleinberg: Authoritative Sources in a Hyperlinked Environment, JACM 46(5), 1999
- S Brin, L. Page: The Anatomy of a Large-Scale Hypertextual Web Search Engine, WWW 1998
- M. Najork, H. Zaragoza, M. Taylor: HITS on the Web: How does it Compare?, SIGIR 2007
- R. Lempel, S. Moran: SALSA: The Stochastic Approach for Link-Structure Analysis, ACM TOIS 19(2), 2001.
- G. Jeh, J. Widom: SimRank: a Measure of Structural-Context Similarity, KDD 2002
- Taher Haveliwala: Topic-Sensitive PageRank: A Context-Sensitive Ranking Algorithm for Web Search, IEEE Trans. on Knowledge and Data Engineering, 2003.
- G. Jeh, J. Widom: Scaling personalized web search, WWW 2003.
- D. Fogaras, B. Racz, K. Csalogany, A. Benczur: Towards Scaling Fully Personalized PageRank: Algorithms, Lower Bounds, and Experiments, Internet Mathematics 2(3): 333-358, 2006.

International School of Engineering

Plot 63/A, 1st Floor, Road # 13, Film Nagar, Jubilee Hills, Hyderabad - 500 033

For Individuals: +91-9502334561/63 or 040-65743991

For Corporates: +91-9618483483

Web: <http://www.insofe.edu.in>

Facebook: <https://www.facebook.com/insofe>

Twitter: <https://twitter.com/Insofeedu>

YouTube: <http://www.youtube.com/InsofeVideos>

SlideShare: <http://www.slideshare.net/INSOFE>

LinkedIn: <http://www.linkedin.com/company/international-school-of-engineering>

This presentation may contain references to findings of various reports available in the public domain. INSOF makes no representation as to their accuracy or that the organization subscribes to those findings.