Governance memo GM-VDL-26: reduction, adjustment and rate parameters for campaign VDL-26
Issued by the geodetic quality board. Tables marked IN FORCE govern the recomputation.
Tables marked WITHDRAWN or SUPERSEDED are kept for audit history only.
The errata at the end of this memo amend the tables they cite and take precedence over the printed values.

Table T-0: Double-run tolerances, 2019 issue [SUPERSEDED]

class	section mm per sqrt km	loop mm per sqrt km
I	4.0	5.0
II	6.0	7.0
III	8.0	10.0

Table T-1: Double-run and loop tolerances [IN FORCE]

class	section mm per sqrt km	loop mm per sqrt km
I	3.0	4.0
II	4.5	6.0
III	6.0	8.0

Table K-1: Observation precision and data snooping [IN FORCE]

parameter	value
sigma class I mm per sqrt km	0.70
sigma class II mm per sqrt km	1.00
sigma class III mm per sqrt km	1.50
critical value of w	3.29
minimum redundancy after a removal	2
maximum removals per component	3

Table I-1: Instrument acceptance and refraction [IN FORCE]

parameter	value
collimation limit mm per 100 m	3.000
refraction coefficient	0.13

Table A-1: Rod types [IN FORCE]

rod type	graduation	alpha ppm per degC
INV-B	FULL	0.60
INV-F	FULL	0.80
INV-H	HALF	1.10

Table R-1: Rate classification [IN FORCE]

parameter	value
alert rate mm per yr	-8.00
significance factor	2.00

Table C-1: Control heights, adjustment VDH-2023 [WITHDRAWN]

mark	height m
VD-0005	0.91383
VD-0023	2.10668
VD-0045	9.39508
VD-0072	9.21357
VD-0081	5.48368
VD-0151	8.35950
VD-0152	9.09258
VD-0157	5.35417
VD-0164	6.68070
VD-0180	5.48262
VD-0196	3.16905
VD-0211	0.32183
VD-0263	4.63551
VD-0285	5.79347
VD-0335	9.11309
VD-0336	10.60335
VD-0448	6.32727
VD-0505	6.16505
VD-0535	9.63411
VD-0558	2.61364
VD-0559	5.98756
VD-0702	0.50341
VD-0733	0.73053
VD-0749	2.10924
VD-0778	10.85024
VD-0819	3.59108
VD-0835	8.36484
VD-0840	6.11667

Table C-1 (continued): Control heights, adjustment VDH-2023 [WITHDRAWN]

mark	height m
VD-0841	1.56129
VD-0860	5.87977
VD-0867	4.24770
VD-0925	3.66259
VD-0953	7.97925
VD-1064	4.25795
VD-1090	2.44824
VD-1108	4.76068
VD-1144	2.55581
VD-1159	2.82602
VD-1209	3.32219
VD-1228	2.96286
VD-1349	7.00405
VD-1361	6.20498
VD-1363	3.80800
VD-1392	5.82748
VD-1394	5.98344
VD-1481	5.89508
VD-1571	4.69498
VD-1572	3.19875
VD-1596	3.37558
VD-1608	3.64496
VD-1614	4.82606
VD-1633	5.53834
VD-1644	4.11538
VD-1902	2.86263
VD-1928	2.77580
VD-1947	3.03474
VD-1948	4.91531
VD-1961	5.02288

Table C-2: Control heights, adjustment VDH-2025 [IN FORCE]

mark	height m
VD-0005	0.90883
VD-0019	1.75582
VD-0023	2.09968
VD-0045	9.40108
VD-0072	9.20957
VD-0081	5.48968
VD-0151	8.36450
VD-0152	9.09958
VD-0157	5.36117
VD-0164	6.67870
VD-0172	10.35001
VD-0196	3.16305
VD-0211	0.31983
VD-0263	4.63351
VD-0284	8.01728
VD-0285	5.79547
VD-0335	9.10709
VD-0336	10.60135
VD-0437	10.03761
VD-0448	6.33027
VD-0475	7.76130
VD-0505	6.16305
VD-0535	9.63011
VD-0558	2.60764
VD-0559	5.99056
VD-0702	0.50141
VD-0733	0.73253
VD-0749	2.11324
VD-0778	10.84524
VD-0819	3.58408
VD-0835	8.36884
VD-0840	6.11167
VD-0841	1.55529
VD-0850	5.37152
VD-0860	5.87677
VD-0867	4.25270
VD-0912	3.40280

Table C-2 (continued): Control heights, adjustment VDH-2025 [IN FORCE]

mark	height m
VD-0925	3.65659
VD-0953	7.97525
VD-1011	2.61900
VD-1058	4.44748
VD-1064	4.26495
VD-1090	2.45024
VD-1108	4.76468
VD-1115	5.56728
VD-1144	2.56081
VD-1159	2.81902
VD-1209	3.32619
VD-1228	2.95986
VD-1349	7.01005
VD-1361	6.20098
VD-1363	3.81400
VD-1392	5.83348
VD-1394	5.97844
VD-1481	5.90208
VD-1514	3.90311
VD-1571	4.68998
VD-1572	3.19175
VD-1596	3.38058
VD-1608	3.65196
VD-1614	4.81806
VD-1633	5.53634
VD-1644	4.12338
VD-1839	3.69578
VD-1902	2.86863
VD-1928	2.78080
VD-1947	3.03174
VD-1948	4.91301
VD-1961	5.01888
VD-1970	5.84606

Table X-2: Chi-square bounds for the global test [IN FORCE]

degrees of freedom	lower 2.5 percent	upper 97.5 percent
1	0.001	5.024
2	0.051	7.378
3	0.216	9.348
4	0.484	11.143
5	0.831	12.833
6	1.237	14.449
7	1.690	16.013
8	2.180	17.535
9	2.700	19.023
10	3.247	20.483
11	3.816	21.920
12	4.404	23.337
13	5.009	24.736
14	5.629	26.119
15	6.262	27.488
16	6.908	28.845
17	7.564	30.191
18	8.231	31.526
19	8.907	32.852
20	9.591	34.170
21	10.283	35.479
22	10.982	36.781
23	11.689	38.076
24	12.401	39.364
25	13.120	40.646
26	13.844	41.923
27	14.573	43.195
28	15.308	44.461
29	16.047	45.722
30	16.791	46.979
31	17.539	48.232
32	18.291	49.480
33	19.047	50.725
34	19.806	51.966

Table X-2 (continued): Chi-square bounds for the global test [IN FORCE]

degrees of freedom	lower 2.5 percent	upper 97.5 percent
35	20.569	53.203
36	21.336	54.437
37	22.106	55.668
38	22.878	56.896
39	23.654	58.120
40	24.433	59.342
41	25.215	60.561
42	25.999	61.777
43	26.785	62.990
44	27.575	64.201
45	28.366	65.410
46	29.160	66.617
47	29.956	67.821
48	30.755	69.023
49	31.555	70.222
50	32.357	71.420
51	33.162	72.616
52	33.968	73.810
53	34.776	75.002
54	35.586	76.192
55	36.398	77.380
56	37.212	78.567
57	38.027	79.752
58	38.844	80.936
59	39.662	82.117
60	40.482	83.298
61	41.303	84.476
62	42.126	85.654
63	42.950	86.830
64	43.776	88.004
65	44.603	89.177
66	45.431	90.349
67	46.261	91.519
68	47.092	92.689
69	47.924	93.856
70	48.758	95.023
71	49.592	96.189
72	50.428	97.353
73	51.265	98.516
74	52.103	99.678
75	52.942	100.839
76	53.782	101.999
77	54.623	103.158
78	55.466	104.316
79	56.309	105.473
80	57.153	106.629

Table J-0: Run and section rulings, first issue [WITHDRAWN]

ruling	target	action	effective
J-26-90	R-26-8884	REJECT_RUN	2026-09-23
J-26-91	R-26-0192	REJECT_RUN	2026-10-01
J-26-92	R-26-4342	REJECT_RUN	2026-10-05
J-26-93	R-26-3200	REJECT_RUN	2026-09-22
J-26-94	R-26-2994	REJECT_RUN	2026-09-22
J-26-95	R-26-8997	REJECT_RUN	2026-09-24
J-26-96	R-26-4513	REJECT_RUN	2026-10-01
J-26-97	S-0329	REJECT_SECTION	2026-09-12
J-26-98	R-26-8497	REJECT_RUN	2026-10-02

Table J-1: Run and section rulings [IN FORCE]

ruling	target	action	effective	note
J-26-01	R-26-3520	REJECT_RUN	2026-09-12	rod support settled during run
J-26-02	R-26-7363	REJECT_RUN	2026-09-12	rod support settled during run
J-26-03	R-26-3913	REJECT_RUN	2026-09-16	suspected rod swap
J-26-04	S-0290	REJECT_SECTION	2026-09-09	mark suspected loose

Errata

Erratum E-1: Table K-1 heading, for per km read per square root km

Erratum E-2: Table C-2, mark VD-1948: for 4.91301 read 4.91031

Erratum E-3: Table T-1, class II, section column: for 4.5 read 5.0