

Eco-Loop Building Agents: Autonomous HVAC Control & Energy Optimization

A Hybrid 7-Tier Architecture for Intelligent Building Energy Management powered by Open-Source LLMs and Native EnergyPlus 26.1 Co-Simulation.

PROBLEM STATEMENT ID

HW-2026-HVAC

THEME & CATEGORY

Smart Buildings (Software)

TEAM NAME

Eco-Loop Autonomous Team

CORE TECHNOLOGY

LLM + EnergyPlus Co-Sim

Proposed Solution & Innovation

Core Architecture

Autonomous Hybrid 7-Tier System

Combines deterministic thermal physics, multi-agent domain expertise, and real-time EnergyPlus 26.1 co-simulation to optimize HVAC setpoints autonomously.

- **Static BEMS Elimination:** Replaces rigid 24/7 fixed setpoints with real-time responsive AI control.
- **Multi-Objective Balance:** Simultaneously handles peak power tariffs (\$0.45/kWh), high carbon grid windows (\$430g/kWh), and CO2 spikes.
- **Guaranteed Safety:** Physical validator prevents unconstrained LLM risks and equipment damage.

Unique Selling Proposition

Innovation & Uniqueness

Industry-first closed-loop supervisory controller linking local LLM orchestrator directly to native building thermodynamics engines.

- **Native EnergyPlus Co-Simulation:** Direct closed-loop telemetry feedback via SQLite (`eplusout.sql`).
- **Deterministic Safety Net:** Dual-layer rule-based fallback executes automatically if LLM latency exceeds bounds.
- **Policy-Driven Resolution:** Strict rules (D1-D4) govern trade-offs between occupant comfort and grid energy cost.



Unconstrained LLM Safety Guard

Unconstrained AI models writing raw HVAC commands present catastrophic physical risks. Eco-Loop solves this by isolating LLM decisions inside deterministic safety boundaries (Rate limit $\leq 2.0^{\circ}\text{C}/\text{step}$, Deadband $\geq 1.0^{\circ}\text{C}$).

Technical Approach & Architecture

HYBRID 7-TIER LAYERED EXECUTION PIPELINE



</> Technology Stack & Tooling

- **Simulation Engine:** Native EnergyPlus 26.1 binary with DOE/NREL baseline building models (``baseline_building.idf``).
- **Language & Runtime:** Python 3.11 with SQLite3 runtime feedback extraction (``eplusout.sql``).
- **Model Context Protocol (MCP):** Custom tools (``get_building_telemetry``, ``extract_runtime_errors``, ``apply_hvac_setpoints``).
- **LLM Framework:** Centralized LLM client resolving multi-agent recommendations under policy constraints.

🤖 Tier 4: Specialized Domain Agents

- **Comfort Agent:** Enforces ASHRAE-55 PMV comfort limits [-0.5, +0.5].
- **Energy Agent:** Curtails kW power draw during peak electricity pricing.
- **Carbon Agent:** Shifts loads away from high grid emission windows (430g CO2e/kWh).
- **Air Quality Agent:** Boosts ventilation during indoor CO2 spikes (> 1000 PPM).
- **Demand Response Agent:** Relaxes setpoints in unoccupied zones (``board_room``).

Feasibility & Risk Management

Technical Feasibility

Designed for immediate deployment in commercial real estate equipped with modern Building Automation Systems (BAS) or BACnet gateways.

- **Deterministic Core:** 100% Python-based state modeling, ASHRAE-55 thermal score generation, and safety boundary enforcement.
- **Low Compute Overhead:** Micro-agent evaluations run in < 50ms; central LLM invocation is required only on detected event changes.
- **Zero Disruptive Retrofit:** Seamlessly injects supervisory setpoint schedules into existing HVAC controllers.

Risks & Mitigation Strategies

Comprehensive fail-safe design preventing system downtime or hardware damage.

- **Risk: LLM Hallucination / Out-of-Bound Setpoints**
Mitigation: Tier 6 Physical Safety Validator strictly forces setpoint changes $\leq 2.0^{\circ}\text{C}$ per step and deadbands $\geq 1.0^{\circ}\text{C}$.
- **Risk: LLM Latency or Network Timeout**
Mitigation: Automatic deterministic Rule-Based Fallback Engine takes control instantly.
- **Risk: Large Simulation Context Window Overflow**
Mitigation: MCP regex tail filtering extracts only critical runtime errors (``eplusout.err``).

Governing Policy Matrix (D1 – D4 Policy Rules)

D1 Vector Align: Combines harmonious agent setpoint directives in occupied spaces.

D2 Fan Override: High-density room CO2 needs override floor fan reductions.

D3 Priority Hierarchy: Strict decision rule: Health > Comfort > Energy > Carbon.

D4 Density Floor: Non-negotiable comfort constraints when zone occupancy > 10.

| System Artifacts & Results

42.4% – 47.1%

Energy Reduction (kWh)

+0.59 PMV

ASHRAE-55 Comfort Level

100%

Safety Rule Compliance (0 Violations)

☰ Closed-Loop Trajectory (5 Cycles)

Cycle	Detected Event	AI Control Directive	Outcome / Metric
Cycle 1	CO2 Spike (1150 PPM)	Max Damper + Fan Boost	CO2 diluted < 1000 PPM
Cycle 2-3	Peak Tariff Window	Setpoint adjusted to 22.5°C	kW Draw reduced 38%
Cycle 4-5	Board Room Unoccupied	Relaxed setpoint to 26.0°C	PMV restored to +0.59

🖥️ Live Telemetry Dashboard



| Research, References & Code

Academic & Industry Standards

- **ASHRAE Standard 55-2023:** Thermal Environmental Conditions for Human Occupancy (PMV/PPD thermal comfort indices).
- **DOE & NREL Commercial Building Benchmarks:** Baseline Building Energy Models utilized in EnergyPlus 26.1 physics calculations.
- **Model Context Protocol (MCP):** Open standard for secure tool integration between autonomous agents and runtime simulation binaries.

Project Deliverables & Repository

Full implementation source code, simulation input files (IDF), and orchestration scripts are open-source and ready for evaluation.

 <https://github.com/Ayush99392003/agenthc-hvac-optimization.git>

Autonomous Self-Correcting HVAC Control

Delivering up to 47.1% verified energy savings with 100% physical safety guarantees for commercial building operations.

 Honeywell Hackathon 2026 |  Open for Questions & Answers

| Image Sources



<https://www.smorescience.com/wp-content/uploads/2024/03/Featured-Images-74.jpg>

Source: www.smorescience.com



https://transform.octanecd.com/crop/1600x650/https://octanecd.com/moodyheatingandaircom/moodyheatingandaircom_135425094.jpg

Source: moodyheatingandair.com