

Mphasis-PreAssessment-Java

33% (5/15)



```
1. public abstract class Shape {  
    private int x;  
    private int y;  
    public abstract void draw();  
    public void setAnchor(int x, int y) {  
        this.x = x;  
        this.y = y;  
    }  
}
```

Which two classes use the Shape class correctly? (Choose two.)

- ☐ A public class Circle implements Shape {
 private int radius;
}
- ☒ B public abstract class Circle extends Shape {
 private int radius;
}
- ☐ C public class Circle extends Shape {
 private int radius;
 public void draw();
}
- ☐ D public abstract class Circle implements Shape {
 private int radius;
 public void draw();
}
- ☒ E public class Circle extends Shape {
 private int radius;
 public void draw() { /* code here */ }
}
- ☐ F public abstract class Circle implements Shape {
 private int radius;
 public void draw() { /* code here */ }
}

✗ 2. Which statement is true about the classes and interfaces in the exhibit?

```
01. public interface A {  
02.     public void doSomething(String thing);  
03. }  
01. public class AImpl implements A {  
02.     public void doSomething(String msg) {}  
03. }  
01. public class B {  
02.     public A doit(){  
03.         //more code here  
04.     }  
05.     public String execute(){  
06.         //more code here  
07.     }  
08. }  
01. public class C extends B {  
02.     public AImpl doit(){  
03.         //more code here  
04.     }  
05.     public Object execute() {  
06.         //more code here  
07.     }  
08. }  
09. }
```

- ☐ (A) Compilation will succeed for all classes and interfaces.
- ☒ (B) Compilation of class C will fail because of an error in line 2.
- ☐ (C) Compilation of class C will fail because of an error in line 6.
- ☐ (D) Compilation of class AImpl will fail because of an error in line 2.

✓ 3. Given:

```
public static void parse(String str) {  
    try {  
        float f = Float.parseFloat(str);  
    } catch (NumberFormatException nfe) {  
        f = 0;  
    } finally {  
        System.out.println(f);  
    }  
}  
  
public static void main(String[] args) {  
    parse("invalid");  
}
```

What is the result?

- ☐ (A) 0.0
- ☒ (B) Compilation fails.
- ☐ (C) A ParseException is thrown by the parse method at runtime.
- ☐ (D) A NumberFormatException is thrown by the parse method at runtime.

- ✗ 4. Given:
- ```
01. public class Blip {
02. protected int blipvert(int x) { return 0; }
03. }
04. class Vert extends Blip {
05. // insert code here
06. }
```
- Which five methods, inserted independently at line 5, will compile? (Choose five.)

- ☒ A public int blipvert(int x) { return 0; }
- ☒ B private int blipvert(int x) { return 0; }
- ☒ C private int blipvert(long x) { return 0; }
- ☒ D protected long blipvert(int x) { return 0; }
- ☐ E protected int blipvert(long x) { return 0; }
- ☒ F protected long blipvert(long x) { return 0; }
- ☐ G protected long blipvert(int x, int y) { return 0; }

- ✗ 5. 

```
public class TestString1 {
 public static void main(String[] args) {
 String str = "420";
 str += 42;
 System.out.print(str);
 }
}
```
- What is the output?

- ☐ A 42
- ☐ B 420
- ☐ C 462
- ☐ D 42042
- ☒ E Compilation fails.
- ☐ F An exception is thrown at runtime.

✗ 6. Given:  
23. Object [] myObjects = {  
24. new Integer(12),  
25. new String("foo"),  
26. new Integer(5),  
27. new Boolean(true)  
28. };  
29. Arrays.sort(myObjects);  
30. for(int i=0; i<myObjects.length; i++) {  
31. System.out.print(myObjects[i].toString());  
32. System.out.print(" ");  
33. }  
What is the result?

- ☐ (A) Compilation fails due to an error in line 23.
- ☐ (B) Compilation fails due to an error in line 29.
- ☐ (C) A ClassCastException occurs in line 29.
- ☒ (D) A ClassCastException occurs in line 31.
- ☐ (E) The value of all four objects prints in natural order.

✗ 7. Which statement is true?

- ☐ (A) A class's finalize() method CANNOT be invoked explicitly.
- ☒ (B) super.finalize() is called implicitly by any overriding finalize() method.
- ☐ (C) The finalize() method for a given object is called no more than once by the garbage collector.
- ☐ (D) The order in which finalize() is called on two objects is based on the order in which the two objects became finalizable.

✓ 8. package com;

```
public class Test {

 private int empId;
 private String empName;
 public String designation;
 public int getEmpId() {
 return empId;
 }
 public void setEmpId(int empId) {
 this.empId = empId;
 }
 public String getEmpName() {
 return empName;
 }
 public void setEmpName(String empName) {
 this.empName = empName;
 }
 public String getDesignation() {
 return designation;
 }
 public void setDesignation(String designation) {
```

```
this.designation = designation;
}
}
```

**Above defined class is not fully encapsulated. why?**

- ☐ A all methods defined as public
- ☐ B all properties defined as private
- ☒ C designation property is defined as public
- ☐ D Test class is defined as public

✗ 9. 

```
class Employee{
@Override
public void finalize(){
System.out.println("Finallize method got called");
}
}
class Test{
@Override
public void finalize(){
System.out.println("Finallize method got called");
}
public static void main(String[] args){

Employee emp=new Employee();
String str=new String("Abc");
System.gc();
}
}
```

**Select One correct option**

- ☐ A Finalize method of Employee executed
- ☐ B Finalize method of Test executed
- ☐ C None of classes Finalize method gets called
- ☒ D Finalize method cannot be overridden in Test class. Because Test is not sub class of Employee

✗ 10. interface DoStuff2 {  
float getRange(int low, int high);  
}  
interface DoMore {  
float getAvg(int a, int b, int c);  
}  
abstract class DoAbstract implements DoStuff2, DoMore {  
}  
06. class DoStuff implements DoStuff2 {  
07. public float getRange(int x, int y) {  
08. return 3.14f;  
09. }  
10. }  
11.  
12. interface DoAll extends DoMore {  
13. float getAvg(int a, int b, int c, int d);  
14. }  
What is the result?

- ☐ A The file will compile without error.
- ☐ B Compilation fails. Only line 7 contains an error.
- ☐ C Compilation fails. Only line 12 contains an error.
- ☒ D Compilation fails. Only line 13 contains an error.
- ☐ E Compilation fails. Only lines 7 and 12 contain errors.

✓ 11. What is displayed on the console when running the following program?

```
class Test {
```

```
 public static void main(String[] args) {
 try {
 method();
 System.out.println("After the method call");
 }
 catch (NumberFormatException ex) {
 System.out.println("NumberFormatException");
 }
 catch (RuntimeException ex) {
 System.out.println("RuntimeException");
 }
 }
}
```

```

}
}
static void method() {
String s = "5.6";
Integer.parseInt(s); // Cause a NumberFormatException
int i = 0;
int y = 2 / i;
System.out.println("Welcome to Java");
}
}

```

- ☒ A The program displays NumberFormatException.
- ☐ B The program displays NumberFormatException followed by After the method call.
- ☐ C The program has a compilation error.
- ☐ D The program displays RuntimeException.

✗ 12. 

```

public class BuildStuff {
public static void main(String[] args) {
Boolean test = new Boolean(true);
Integer x = 343;
Integer y = new BuildStuff().go(test, x);
System.out.println(y);
}
int go(Boolean b, int i) {
if(b) return (i/7);
return (i/49);
}
}

```

What is the result?

- ☐ A 7
- ☐ B 49
- ☐ C 343
- ☒ D Compilation fails.
- ☐ E An exception is thrown at runtime.

✗ 13. Given:

```
import java.io.*;
public class Forest implements Serializable {
 private Tree tree = new Tree();
 public static void main(String [] args) {
 Forest f = new Forest();
 try {
 FileOutputStream fs = new FileOutputStream("Forest.ser");
 ObjectOutputStream os = new ObjectOutputStream(fs);
 os.writeObject(f); os.close();
 } catch (Exception ex) { ex.printStackTrace(); }
 }
}
class Tree {
```

What is the result?

- ☐ (A) Compilation fails.
- ☐ (B) An exception is thrown at runtime.
- ☒ (C) An instance of Forest is serialized.
- ☐ (D) An instance of Forest and an instance of Tree are both serialized.

✓ 14. C1,C2 and C3 classes defined in various packages as below declaration

```
package p1;
public class C1{
```

```
}
package p1.p2;
public class C2{
```

```
}
package p1.p2.p3;
class C3{
```

what is the correct statement to import class C3?

- ☐ (A) import p1.\*;
- ☐ (B) import p3.\*;
- ☐ (C) import p1.p2.\*;
- ☐ (D) import p1.p3.p2.\*;
- ☒ (E) import p1.p2.p3.\*;



✗ 15. Analyze the following code:

```
class Test {
 public static void main(String[] args) {
 try {
 String s = "5.6";
 Integer.parseInt(s); // Cause a NumberFormatException

 int i = 0;
 int y = 2 / i;
 }
 catch (Exception ex) {
 System.out.println("NumberFormatException");
 }
 catch (RuntimeException ex) {
 System.out.println("RuntimeException");
 }
 }
}
```

- ☒ A The program displays NumberFormatException.
- ☐ B The program displays RuntimeException.
- ☐ C The program displays NumberFormatException followed by RuntimeException.
- ☐ D The program has a compilation error.