Road conflict screening summary

Coverage

- Sources: clip-01
- Track observations: 8654
- Road-user observations by group: {'pedestrian': 285, 'vehicle': 8369}
- Unique road users: 678
- Observed time span: 20.26 seconds
- Candidate events: 0

Ranked hotspots

No candidate events were observed in the supplied tracks.

Conflict patterns

No candidate conflict patterns were observed.

Validation summary

- Seed/reference event count: 0
- video: recall None; spurious events 0
- SUMO SSM encounters available: 0
- TTC/PET agreement summary: {'TTC': None, 'PET': None}

Engineering review prompts

Review crossing visibility, signal phasing, refuge provision, and approach-speed management where th
e mapped data and local context support it.

Method and limitations

TTC is estimated from observed positions using a short constant-velocity prediction and buffered roa
d-user footprints. Results are screening indicators for engineering review, not crash probabilities
or legal findings.

Coordinates are assumed to be calibrated metres in one shared road-plane coordinate system. Hotspots
 are metric grid cells and are not yet snapped to road segments. Data gaps, detector errors, and inc
omplete observation coverage can hide conflicts; ?none observed? does not mean a location is safe.
Threshold defaults are TTC < 3 s, PET < 2 s, and DRAC > 3 m/s?, following [SUMO SSM defaults](https:
//sumo.dlr.de/docs/Simulation/Output/SSM_Device.html). Treat these as configurable screening values,
 not universal cutoffs.