Road conflict screening summary

Coverage

- Sources: sumo-control-42
- Track observations: 3750
- Road-user observations by group: {'pedestrian': 2020, 'vehicle': 1730}
- Unique road users: 22
- Observed time span: 174.80 seconds
- Candidate events: 3

Ranked hotspots

1. Metric grid cell (29, 18): 3 candidate event(s); minimum indicator 1.06 s; rate per 1,000 users 1
36.36363636363637; main pattern other; pair pedestrian / pedestrian; coverage flags none.

Conflict patterns

- Other: 3

Validation summary

- Seed/reference event count: 3
- SUMO SSM encounters available: 0
- TTC/PET agreement summary: {'TTC': None, 'PET': None}

Engineering review prompts

Review crossing visibility, signal phasing, refuge provision, and approach-speed management where th
e mapped data and local context support it.

Method and limitations

TTC is estimated from observed positions using a short constant-velocity prediction and buffered roa
d-user footprints. Results are screening indicators for engineering review, not crash probabilities
or legal findings.

Coordinates are assumed to be calibrated metres in one shared road-plane coordinate system. Hotspots
 are metric grid cells and are not yet snapped to road segments. Data gaps, detector errors, and inc
omplete observation coverage can hide conflicts; ?none observed? does not mean a location is safe.
Threshold defaults are TTC < 3 s, PET < 2 s, and DRAC > 3 m/s?, following [SUMO SSM defaults](https:
//sumo.dlr.de/docs/Simulation/Output/SSM_Device.html). Treat these as configurable screening values,
 not universal cutoffs.