#### Vue 3 is officially released. Learn it now with a 30% discount

#### Claim Offer

Vue mastery

#### $\underline{\textbf{Courses}} \\ \textbf{PricingBlogConference VideosSearch}$

Sign UpLogin

# Intro to Vue 3

5. List Rendering

Lessons
1. Intro to Vue 3
2:22
2. Creating the Vue App
6:56
3. Attribute Binding
3:53
4. Conditional Rendering
5:11

### Forms & v-model

In this lesson, we're going to look at the concept of attribute binding. If you're coding along with the repo, you can checkout the L11-start branch or the starting code on Codepen.

### **Our Goal**

Create a form for users to add product reviews.

## Introducing v-model

At the beginning of this course, we learned about v-bind, which creates a one-way binding, from the data to the template. When working with forms, however, this one way binding isn't enough. We also need to be binding from the template to the data.

For example, when a user inputs their name into an input field, we want to record and store that value in our data. The v-model directive helps us achieve this, creating two-way data binding.

```
Joe Smith

app.component('v-model-demo', {
   template: `<input v-model="name"/>`,
   data() {
      return {
        name:'Joe Smith'
      }
   }
})
```

To see this all in action, we're going to create a new reviewform component.

### The review-form component

We'll add a new **ReviewForm.js** file into our components folder, and scaffold out the component.

#### components/ReviewForm.js

```
app.component('review-form', {
  template:
  /*html*/
  `<form class="review-form">
   <h3>Leave a review</h3>
    <label for="name">Name:</label>
    <input id="name">
    <label for="review">Review:</label>
    <textarea id="review"></textarea>
    <label for="rating">Rating:</label>
    <select id="rating">
      <option>5</option>
     <option>4</option>
     <option>3</option>
      <option>2</option>
      <option>1</option>
    </select>
    <input class="button" type="submit" value="Submit">
  </form>`,
  data() {
     name: '',
     review: '',
     rating: null
```

Inside of our template, notice these elements:

- <input id="name">
- <textarea id="review">

<select id="rating">

We want to bind these input fields to their respective data properties so that when the user fills out the form, we store their data locally.

```
data() {
   return {
     name: '',
     review: '',
     rating: null
   }
}
```

We'll achieve this by adding the v-model directive to each of those input elements.

#### components/ReviewForm.js

```
app.component('review-form', {
  template:
  /*html*/
  `<form class="review-form">
    <h3>Leave a review</h3>
    <label for="name">Name:</label>
    <input id="name" v-model="name">
    <label for="review">Review:</label>
    <textarea id="review" v-model="review"></textarea>
    <label for="rating">Rating:</label>
    <select id="rating" v-model.number="rating">
      <option>5</option>
      <option>4</option>
      <option>3</option>
      <option>2</option>
      <option>1</option>
    </select>
    <input class="button" type="submit" value="Submit">
  </form>`,
  data() {
    return {
```

```
name: '',
    review: '',
    rating: null
}
```

Notice how on the <select> element, we used v-model.number,
this is a modifier that typecasts the value as a number.

### **Submitting the Review Form**

In order to submit this form, we'll add a listener at the top:

#### components/ReviewForm.js

```
app.component('review-form', {
   template:
    /*html*/
   `<form class="review-form"
@submit.prevent="onSubmit">
        ...
        <input class="button" type="submit" value="Submit">
        </form>`
        ...
})
```

We're using another modifier, @submit.prevent="onSubmit" to prevent the default behavior (a browser refresh). When this form is submitted, it will trigger the <code>onSubmit()</code> method, which we'll write now:

#### components/ReviewForm.js

```
data() {
  return {
   name: '',
   review: '',
   rating: null
```

```
}
},
methods: {
  onSubmit() {
    let productReview = {
      name: this.name,
      review: this.review,
      rating: this.rating,
    }
    this.$emit('review-submitted', productReview)

    this.name = ''
    this.review = ''
    this.rating = null
  }
}
...
```

That method will create a productReview object, containing the name, review and rating from our data. It will then Semit a review-submitted event, sending that productReview along as the payload.

Finally, we're clearing out the data fields.

### **Using the Review Form**

Now that our review form is created, we can import it within **index.html**.

#### **∏index.html**


```
<!-- Import Components -->
...
<script src="./components/ReviewForm.js"></script>
...
```

Then we'll head into product-display, and actually use the component within its template, below the "product-container".

#### components/ProductDisplay.js

```
template:
   /*html*/
   `<div class="product-display">
        <div class="product-container">
        ...
        </div>
        <review-form></review-form>
        </div>
     })
```

Now in the browser, we can see the review form.



It looks like it's working... except when we click the submit button, we're emitting the event, but we haven't listened for it anywhere. Like we learned in the previous lesson, we need to listen for the review-submitted event in the parent scope (in product-display).

When the event is "heard", we'll add the productReview payload to the product-display component's data.

### **Adding product reviews**

We'll add the event listener here on the review-form, where it's being used:

### components/ProductDisplay.js

When the event happens, we'll trigger a new addReview() method. This will add product reviews to our product-display component, which means that component needs a new reviews array in its data.

#### components/ProductDisplay.js

```
data() {
   return {
        ...
        reviews: []
   }
}
```

Now let's flesh out the addReview() method:

#### components/ProductDisplay.js

```
data() {
  return {
          reviews: []
      }
},
methods: {
      ...
      addReview(review) {
          this.reviews.push(review)
      }
},
```

As you can see, it which takes in the review that we got from the review-submitted event payload, and pushes it into the reviews array.

# Displaying the reviews

Now that we've implemented the ability to add reviews, we need to be displaying those reviews. Let's create a new component to do that. That component will be called review-list, which we'll scaffold out like this:

#### components/ReviewList.js

```
app.component('review-list', {
  props: {
    reviews: {
      type: Array,
      required: true
    }
  },
  template:
```

It will have a prop so that it can receive the reviews and print them out in the template using v-for, including the index, so that we can bind the index attribute to it.

Now we can import this component inside **index.html**:

#### index.html

```
<!-- Import Components -->
...
<script src="./components/ReviewList.js"></script>
...
```


Then add it within product-display, right above the review-form:

#### components/ProductDisplay.js

```
template:
   /*html*/
   `<div class="product-display">
        <div class="product-container">
        ...
        </div>
        <review-list :reviews="reviews"></review-list>
```

Notice how we've added :reviews="reviews" so we can pass the reviews that live on product-display into the review-list.

Checking this out in the browser, we'll add a new review, click submit, and see the review is being displayed.



So far so good, but when we refresh (and there are no reviews) we still see an empty box because the review-list component is still being rendered with no reviews to print out. Let's fix that,

and only render that component when we have reviews to display.

#### components/ProductDisplay.js

In other words, if the reviews array is empty, we will not show the review-list component.

With a refresh, it looks like it's working, and the component only shows up after we've added a review.

### **Basic Form Validation**

To finish out this lesson, we're going to add some very basic validation to our review-form.

#### components/ReviewForm.js

```
methods: {
  onSubmit() {
    if (this.name === '' || this.review === '' ||
  this.rating === null) {
     alert('Review is incomplete. Please fill out
  every field.')
     return
  }
  ...
}
```

Before we create a productReview, we'll check if this.name or this.review or this.rating are empty. If any of these things are the case, we will show an alert, which says: 'Review is incomplete. Please fill out every field.' And then return out of the method.

This is an overly simplified method of form validation. If you're interested in learning more production-level form validation practices, check out our lessons on Vuelidate in our <u>Next-Level Vue</u> course.

## **Congratulations!**

You've made it to the end of the Intro to Vue 3 course and completed your first step on your path to Vue Mastery. To continue learning, I invite you to check out our <u>library of Vue.js</u> <u>courses</u>, which cover all the topics you'll need to succeed as a Vue developer.

If you're seeking a more guided and hands-on learning experience, we recommend checking out this <u>Vue Training</u> by our partner Jeffrey Biles, who will serve as your mentor through his 8-week training.

# **Coding Challenge**

For your final coding challenge:

# Add a question to the review-form: 'Would you recommend this product?'

# Record and emit the response, and display it within review-

As a reminder, if you're coding along with our repo, you can check out L11-end branch, and you can view the solution code on Codepen.

**Download Video** 

**Share Lesson** 

#### **Lesson Resources**

- Starting Code
- Ending Code

<u>Discuss in our Facebook Group</u> Send us Feedback

Previous LessonNext Lesson



As the ultimate resource for Vue.js developers, Vue Mastery produces weekly lessons so you can learn what you need to succeed as a Vue.js Developer.

#### **VUE MASTERY**

•

•

•

•

•

•

•

•

#### **ABOUT US**

•

•

•

•