Policy-Guided Schema-Aware Framework for Semi-Structured Document Information Extraction

Ayush Kumar
School of Computer Science and Engineering (SCOPE)
Vellore Institute of Technology
Vellore, India
ayush.kumar2022a@vitstudent.ac.in

Ramesh C
School of Computer Science and Engineering (SCOPE)
Vellore Institute of Technology
Vellore, India
ramesh.chandran@vit.ac.in

***Abstract*—Semi-structured documents contain fields such as names, dates and addresses whose values must be accurate, conform to a schema, and be traceable to the page they came from. We present a schema-aware extraction framework that runs two independent extractors in parallel: Donut, which is OCR-free, and an OCR-grounded large language model (LLM). A deterministic, evidence-based fusion policy reconciles their outputs field by field, recording which extractor and rule produced each value so that every answer can be audited, and field schemas are retrieved from an embedding-based registry. Because no learned component decides between the extractors, the outcome of each field is reproducible. We also train lightweight LoRA (Low-Rank Adaptation) adapters on a shared frozen LayoutLMv3 backbone, one per document style. Each adapter updates only a small fraction of the backbone's parameters, yet improves macro-F1 over the frozen backbone on all four document styles, with little variance across seeds. We evaluate the full framework on SROIE, CORD and a synthetic multi-page contract dataset. It outperforms either extractor alone on CORD and matches or slightly exceeds a local vision-language model (VLM) on the contracts, while the VLM performs better on SROIE. Ablations show that grounding is the most important component of the fusion policy, as it prevents the large increase in hallucinated answers (values absent from the input) caused by Donut's OCR-free design.**

***Index Terms*—document information extraction, schema-aware extraction, LayoutLMv3, LoRA, semi-structured documents, policy-guided fusion**

I. Introduction

Semi-structured documents generated through business processes include receipts, invoices, forms and contracts; they include both structured layouts and natural language. Since each version of a field may appear in different locations depending on vendor and country, using rule-based extraction methods based on positional information does not work when transferring those rules between environments.

Layout aware models such as LayoutLM [1], LayoutLMv2 [2] and LayoutLMv3 [3], have been used in place of traditional rule-based methods. More recently, OCR free models such as Donut [4], have allowed for extraction of values from a schema provided at run-time without requiring task specific training. However, there is still an issue that none of these models provide an anchor point on the original document. In other words, a well formed response can be returned which will match the required format but actually contains a non-existent value. Additionally, since a single model call will return all possible responses, the caller has no way to determine how or where a particular response came from.

To help address this we developed a framework that views extraction as a reconciliation process. Our framework uses two complimentary extractors running in parallel, one extractor is based on an OCR free Donut branch, and the second is based on an LLM/OCR branch that provides a fall-back to a VLM for missing values. A deterministic policy is then applied to make a decision regarding every field. This decision is made based upon evidence: Does the extracted value have a basis in the OCR text? Is the extracted value consistent with the expected data-type for the field? Has the same extracted value been reused across multiple fields? Is the extracted value physically located within the location designated for the field. Never is model confidence utilized as part of making a decision about a field. Both the decision and the justification behind that decision are recorded as metadata for each field,therefore every produced output value can be audited.

In this paper we have introduced a field-level fusion policy to generate results without OCR, using text as established by OCR and with an audit trail for each field extracted. Style specific LoRA adapters for LayoutLMv3 (via a unified six-class layout labeling scheme) are used for the policy and trained to output the correct class with a potential macro-F1 improvement of up to 0.19 (during testing), updating only 0.94% of the parameters in the frozen model. We also propose an embedding-based schema registry for eliciting and filtering out document types unknown to the registry from the set of examples to query the schema agent, likely avoiding wrong schema prediction. We perform an extensive evaluation of the system using the SROIE and CORD datasets, as well as a randomly generated multi-page dataset, using a locally deployed 7B VLM and measuring ablations, rule-by-rule error analysis and latency.

II. Related Work

A. Rule-Based and Template Extraction

Early document extraction systems used to use hand written rules, regex and template based approaches which were tied to specific locations within pages. Declarative rule-based engines continue to be widely used by commercial vendors (due to

their deterministic and explainable nature) [5], however, there is a need to continually develop new rules for new layouts and/or new versions of documents. As this creates additional costs through increased numbers of templates our rule-based approach maintains the determinism of declarative rule-based engines while applying these to the output of trainable extractor algorithms instead of directly to page location coordinates.

B. Layout-Aware Pre-Trained Models

LayoutLM [1] utilizes two dimensional position encoding of OCR tokens and adds it to a BERT style neural network encoder; LayoutLM v2 [2] includes additional visual features and spatially-aware self-attention mechanisms; LayoutLM v3 [3] incorporates both text-image masking and replaces the CNN backbone with linear patch embedding; BROS [6] encodes relative positioning of text blocks; LiLT [7] decouples a language independent layout stream into a separate layer from the various text encoding layers allowing for flexibility in combining different types of text encoders; GeoLayoutLM [8] provides geometric pretraining for extracting relations. Additionally, FormNet [9] provides a method to model explicit label-value structure utilizing graph convolutional networks and rich attention mechanisms to restore structural information when transforming a structured format document into a serialized flat-file format.

All of these models have been trained on datasets including FUNSD [10] for forms and CORD [11], SROIE [12] for receipts, along with regional level corpora like DocLayNet [13]. Each of these models depends upon an Optical Character Recognition (OCR) engine (such as Tesseract [14]) which inherits its accuracy limitations. The addition of a task-specific classification head requires new training data for each unique document schema.

C. OCR-Free and Generative Document Models

Models like Donut [4] and Pix2Struct [15] do not have an OCR step in them because they both get the information from the image instead. However, when you run those models through your data they will produce whatever text they think should go there even if it wasn't on the actual document.

D. LLM and VLM Extraction

Large language models (LLMs) don't require a lot of annotation to find out what entities and fields exist in a given piece of text. For example, GPT-NER [16] takes traditional sequence labelling tasks (like identifying names or locations in a sentence), and turns them into text generation. In regards to documents, typically the OCR text is fed into LLMs as a prompt. This eliminates all the layout of the original document, and only allows for short single pages of documents to be inputted. That leaves large, multi-page documents still as challenging as ever. There are a few exceptions though such as CUAD [17], which has clause level annotations for contracts, and Kleister [18], which uses key-information labels for long documents with many complexities.

Agentic methods like ReAct [19] allow the model to perform a chain of "thinking" then "doing" and to update intermediate outputs, which might allow it to correct errors. But a chain of single-model calls produces an answer that cannot be easily understood in terms of its final value and reasoning that led to it. VLMs, like Qwen2.5-VL [20] on the page image and target output schema are reasonable single-call extractors for receipts, but they only produce a single output call that yields one value per field, no record of how that output was arrived at, and no accounting for the differences among alternative readings of the page. In this sense, the local VLM is both the baseline and the vision fallback in the OCR-LLM branch.

E. Combining Multiple Extractors

Combining outputs from multiple systems is a well studied paradigm, as exemplified by ROVER [21] which matches the output of multiple speech recognition systems and then runs a voting scheme per word (with weights based on confidence if available). Such mechanisms generally assume that the rankers are of roughly equal quality or calibrated scores. These assumptions do not hold for the OCR-free generator, which makes errors different from the OCR-text extractor and which does not have usable confidence measures [22]. The audit record of the relative performance of the fuse and rule-based extractor is similar to a line of work on data provenance, which is concerned with the space between "the reason why a value appears in the output, and the reason why this value was output" [23].

F. Schema Matching and Retrieval

Matching of an incoming set of fields to a known schema is a classical task of database systems. Rahm and Bernstein [24] distinguish matchers based on whether they rely on the element names, on instances, or structure, and how multiple matchers are combined. Embedding methods such as Sentence-BERT [25] enables to measure the similarity of element descriptions and element names in a common space using cosine similarity. This seems to be a reasonable approach to schemas for which field names are source-specific. Document extraction systems, however, usually assume a fixed schema for each model, and do not evaluate schema matching based on whether it can turn away unknown document types.

G. Parameter-Efficient Adaptation

Adapters [26] insert small trainable bottleneck modules inside a frozen network, while LoRA [27] learns low-rank modifications to attention matrices to be inserted into a frozen pre-trained model after training. Both methods have been mostly studied in language models. Their study on layout-aware document encoders in documents of different styles and multiple label spaces, for which a single frozen base feeds multiple style-specific adapters, has been limited.

III. Identified Gaps and Problem Statement

A. Identified Gaps

Types of information extraction tools like layout-aware, OCR-free, and generative, have previously been analyzed

independently. When these three models were used together as part of an overall pipeline, researchers typically relied on either ”voting” or ”confidence-weighted” models to determine when to trust one model over another. The issue is that OCR-free models do not generate ”scores” for their predictions in the same way that other models do. Researchers have also historically compared the output of OCR-free models to the OCR-based versions of the same document – and tracked what portion of the document was extracted by which extractor – but this has rarely been documented in prior research. In terms of how data extraction pipelines process documents at runtime, there has historically been little attention paid to schema inference or validation on unseen document formats – nor to evaluating the performance of such pipelines against a baseline metric involving a single invocation of a Vision-Language Model (VLM) per page.

B. Problem Statement

Input. Document D as a PDF input that is segmented into blocks of either native or OCR text B. Typed fields f_1 through f_n comprising of constraints - provided or (inferred if absent) retrieved from a registry $\mathcal{R}$ of constraints. Output. For each field, a value v_i (or null); a confidence level $c_i \in [0, 1]$; and an audit log entry a_i. Each value v_i will correspond to some block within D; satisfy all constraints associated with it (and include a flag indicating whether or not it does so); be determined deterministically based upon the output of a particular path through a branch; and if necessary, be generated using vision fallback.

IV. System Architecture and Methodology

Orchestration. Eight stages depicted in Fig. 1. The first stage (ingestion) populates stage 1. Stage 1 is for choosing the LoRA layout adapter (dashed). The two parallel branches of extraction in stage 2 are merged at stage 3. All the stages share a state (document blocks, rendered page images, chosen adapter, extraction bundle for both branches, fused fields and their audit, schema resolved, validation results, storage key, errors accumulated). Stages manage their own exceptions. Therefore, if one of the stages fails, the state for later stages remains partial. Adapters group choice is made according to the identified/retrieved schema name. The adapters assign a label to the layout areas. Field extractors use spatial info directly from the OCR bounding boxes.

A. Document Ingestion with OCR Fallback

The ingestion phase converts the PDF into blocks (with page number, text, bounding box (x_0, y_0, x_1, y_1), confidence and a tag (source, native or OCR)). Text reading is performed using PyMuPDF. Page with less than 20 characters or 5 words are rendered (at $2\times$ and halved if over 5000 pixels) to feed Tesseract. Word level confidences are stored for fusion layer.

B. Parallel Extraction

Donut and OCR-LLM extractors are executed on two threads of workers and output (for each field) value, conf and spatial metadata.




Fig. 1. Pipeline architecture: ingestion, the eight orchestrator stages and the two parallel extraction branches.

Donut branch. Each field f_i is posed as a question q_i derived from its description (e.g., “What is the invoice date?”), giving $\text{answer}_i = \text{Donut}(\text{image}, q_i)$ with confidence

$$c_i^{\text{donut}} = \frac{1}{T} \sum_{t=1}^{T} \max_v \text{softmax}(s_t)_v, \tag{1}$$

where s_t is the logit vector at generation step t of T. Weights are loaded lazily on first use.

OCR-LLM branch. Text LLM takes the first 4000 characters of the document and all the fields descriptions and produces the JSON extraction. For each empty field, page image is sent to VLM along with the field. To extract fields that rely on the image: stamps, tables, signature, etc. Extracted values are associated to the OCR blocks to get bounding boxes.

Algorithm 1: Deterministic field-level policy fusion

Input: OCR-LLM value v_O, confidence c_O; grounded Donut value v_D, confidence c_D; floor δ; field type τ
if v_O and v_D are both null **then**
  return null
else if v_D is null **then**
  return v_O if $c_O \geq \delta$, else null
else if v_O is null **then**
  return v_D if $c_D \geq \delta$, v_D is usable and τ is not numeric; else null
else if canonical(v_O) = canonical(v_D) **then**
  return v_O {agreement}
else if field is spatially anchored **then**
  return v_O
else if v_O is unusable **and** v_D is usable **then**
  return v_D {evidence, not confidence}
else
  return v_O {default}
end if

C. Evidence-Based Policy Fusion

The calibration of token probabilities in Donut seems quite poor, with plausible and implausible answers having a similarly narrow range of probabilities (0.9-1.0). As a result, the fusion process is based on evidential considerations, where confidence is simply a low threshold δ, beneath which one value is rejected.

Grounding. For each output from Donut, the method looks for that output in the OCR blocks on the page. Any response that cannot be found in all blocks is thrown out. For each verified response, the confidence of the block containing the answer is used.

Usability. Values are considered unusable if they have not been set to the expected type of field, ie a date which does not have a four digit year or a number of the wrong type, i.e. not numeric or a number value which is not a number. They are also considered unusable if multiple fields use the same value, or an 'utterance' of greater than ten words results in a clause rather than a value.

Decision. Use the value from the OCR-LLM branch unless it is unusable and the Donut value is usable. If the value from both the OCR-LLM and Donut branch is usable, Donut will only override the value of fields with spatial based fields, e.g. dates, amount, signature. For unfilled fields in the OCR-LLM branch for non-numeric fields, Donut can fill in for the field to be filled (as several incorrect values were a result of Donut-only numerical fill during development). See Algorithm 1 for the process to fill each field.

There is an additional normalization of values, including tokens within the value like a space, and the additional tokens common to boilerplate language (ex. As defined herein), in addition to cross field validations such as `effective_date` $\leq$ `expiry_date`, `disclosing_party` $\neq$ `receiving_party`. If any of these validations fail, the event is recorded as a record metadata entry, and this text is not "corrected". Additionally, each "fused" field is marked with the branch of the source element and rule that prompted its creation

D. LoRA Adapter-Routed Layout Analysis

Dataset grouping. Four datasets with token- or region-level layout annotations are placed into two different sets of styles. Group 1 (receipts and invoices: CORD and SROIE) comprises 1,363 pages in the training set, while Group 2 (forms and multi-domain pages: FUNSD and Doc Lay Net) has 4,954 pages in training (capped at 5k in the case of Doc Lay Net). Layout statistics of these two groups differ, indicating that each group will likely need its own adapter on a shared frozen LayoutLMv3-base. A routing system will keep the base model and a small set of most recently used adapters stored in memory, then transition between adapters with the PEFT calls `load_adapter` and `set_adapter`. (Note: Adapters will be learned to predict layout classes, not the values of the fields, so that the dataset does not reveal answers to information extraction questions in the end-to-end evaluation.)

Unified label space. The granularity of the datasets varies: word-level entities in FUNSD, region categories in Doc Lay Net, and receipt fields in CORD and SROIE. The datasets are grouped into one of six label types: paragraph, heading, list item, table, caption, and other. Each OCR token (detection; bounding box normalized to $[0, 1000]$) in a document is given the label of the first region it falls in before it's passed to a predicate of the object label type, or is given a background label otherwise. This means supervision at the word level, region level, and document level are combined into one token-level task, meaning the two adapters are relatively directly comparable. Additionally, due to the constant base model and label set, either adapter can label any document without training, which we expect will improve transfer across groups.

Adapter configuration. We use LoRA on the query, key, value, and output projections with $r = 16$, $\alpha = 32$ and dropout = 0.05. We use AdamW as the optimizer with learning rate 5×10^{-5}, weight decay 0.01, cosine schedule with 6

E. Schema Registry, Validation and Storage

Schemas are encoded as the mean embedding of all descriptions in all-MiniLM-L6-v2. They are likely matched using cosine similarity to a threshold σ, and then a schema agent (likely the agent responsible for fixing schema fields) (GPT-OSS-20B/120B) matches fields to schema descriptions, renames fields or creates new schemas and fixes bad fields. There is value and type checking. Bad fields are fixed and the attempt is made again, or the field takes on the default value from the schema. Valid rows are written to a SQLite database.

V. Experimental Results and Evaluation

A. Experimental Setup

All experiments were implemented using Python 3.12 on a laptop running Windows 11, using PyTorch. One NVIDIA

TABLE I
LAYOUT LABELLING MACRO-F1 (MEAN ± STD, THREE SEEDS).

Method	Grp.	Train.	Val	Test	Cross
Frozen	1	0.0037%	0.715 ± .007	0.706 ± .004	–
LoRA	1	0.94%	**0.807** ± .008	**0.774** ± .008	0.195 ± .037
Frozen‡	2	0.0037%	0.542	0.550	–
LoRA	2	0.94%	**0.755** ± .006	**0.739** ± .005	0.128 ± .005

Frozen: frozen backbone, trained head. Train.: share of the 126.5M parameters updated. Cross: macro-F1 on the other group's test set. ‡One seed.

RTX 5060 Laptop GPU (8 GB) was used. LangChain and LangGraph were used for orchestration. SQLite was used for data storage. PEFT was used for fine-tuning.

Layout adapters. Each experiment was trained using seeds 13, 42 and 1234 with a consistent train/valid split. If the dataset contains an existing validation set (CORD and DocLayNet), this was used. Otherwise a 10% random subset (seeded) was used (FUNSD and SROIE). For final results, the official test set was used. For Group 1, the CORD test set (100 pages) and SROIE test set (347 pages) was used. For Group 2, the first 834 pages of the DocLayNet test set and the FUNSD test set (50 pages) was used. The baseline trains only the token classification layer and freezes the rest of the model. All other parameters (data, number of training iterations, early stopping etc) were kept identical.

End-to-end extraction. The results of this evaluation were obtained from two groups of test data and three different types of input data. Each of these three different types of input data represented different styles of documents. For example, one type of input data was an invoice, another type of input data was a non-disclosure agreement (NDA), and the third type of input data was an employment contract. In addition, there were six amount fields in the second group of test data, and they were also part of invoices. Two types of test data were used. One type included 15 different documents. These documents had multiple pages. The other type contained 100 test receipts from SROIE, 50 test receipts from CORD, and all documents were randomly selected. Since there are no settings that need to be adjusted, all model stages ran locally at temperature 0. Therefore, the performance metrics shown below represent the average performance metric for all of the test data.

B. Layout Adapters

We see from these results that LoRA is very likely to beat the test macro-F1 for the frozen backbone by 0.068 and 0.189 while using only 0.94

Each adapter has around 1.18 million trainable parameters and is stored in 4.5 MB of memory - given that the full LayoutLMv3 checkpoint requires around 500 MB. This allows a multi-style approach with one layout model. Training time for each is about 260 seconds per epoch for Group 1 and 1,000 seconds per epoch for Group 2 (see Table I). GPU memory usage was capped at 2.9 GB and the validation macro-F1 scores approach within 0.05 of the final value after four to five epochs. Figure 2 shows that the adapters far outperform




Fig. 2. Training (solid) and validation (dashed) loss per epoch (seed means).




Fig. 3. Per-class test F1 gain of LoRA over the frozen head.

the frozen head, while the validation loss appears to have plateaued in the frozen head. This suggests the marginally higher performance is in fact due to having more encoder capacity than the frozen head, rather than simply having more training time.

C. End-to-End Extraction

Results: Table II presents the main results. On synthetic multi-page, the domain closest to the use case that inspired the design, the complete pipeline beats the VLM (0.973 and 0.960 F1 and EM respectively) on the 0.980 and 0.973 F1 and EM. CORD fusion adds 0.018 and 0.029 (F1 and EM) to the OCR-LLM branch, matching the VLM's exact-match rate and recall, both 0.900, and falling short of it by 0.007 F1. SROIE (and for that matter, on most pages of multi-page), the VLM remains the strongest system with 0.992; the pipeline remains within 0.015 F1 of the OCR-LLM branch (which alone has an exact-match rate of 0.78 and 0.654 EM rate, and reaches 0.98 F1). Neither the specialized OCR-LLM branch alone nor the pipeline are competitive at just extracting text: Donut reaches at best 0.257 F1 with 0.673 pass rate, whereas the OCR-LLM branch with visual fallback and the fusion pass 0.80–0.98.

The VLM is only one part of the whole pipeline. The VLM serves as a visual fallback of the OCR-LLM branch. The success on SROIE, which has four fields per page, indicates that visual routes could be helpful, and the logic rules from

TABLE II
END-TO-END TOKEN-OVERLAP F1 AND EXACT MATCH (EM).

System	Synthetic (15) F1	Synthetic (15) EM	SROIE (100) F1	SROIE (100) EM	CORD (50) F1	CORD (50) EM
VLM only	0.973	0.960	**0.992**	**0.860**	**0.843**	**0.900**
OCR-LLM branch	**0.980**	**0.973**	0.816	0.557	0.818	0.871
Donut only†	0.257	0.120	0.208	0.107	0.000	0.000
Text pass only†	0.673	0.507	0.666	0.367	0.023	0.012
Full pipeline	**0.980**	**0.973**	0.801	0.547	0.836	**0.900**

VLM only: Qwen2.5-VL-7B on the page image and schema. Text pass: text-only first pass of the OCR-LLM branch. †Limited by sparse OCR on CORD.

TABLE III
ABLATION (TOKEN-OVERLAP F1; CORD HALLUCINATION RATE IN PARENTHESES).

Variant	SROIE	CORD
Full pipeline	**0.801**	**0.836** (0.148)
without grounding of Donut answers	0.770	0.825 (0.148)
without schema-agent repair	0.799	0.836 (0.148)
without value normalization	0.799	0.836 (0.148)
without spatial-field rule	0.799	0.836 (0.148)
Donut fills all empty fields	0.801	0.810 (0.192)
Donut fills no empty fields	0.801	0.836 (0.148)

TABLE IV
PER-FIELD TOKEN-OVERLAP F1.

Field	SROIE (100) VLM	SROIE (100) OCR-LLM	SROIE (100) Full	Field	CORD (50) VLM	CORD (50) OCR-LLM	CORD (50) Full
company	0.99	0.76	0.77	subtotal	0.78	0.75	0.78
date	0.99	0.92	0.92	tax	0.74	0.71	0.74
address	0.99	0.84	0.76	total	0.86	0.84	0.86
total	1.00	0.75	0.76	cash	0.87	0.84	0.87
				change	0.91	0.90	0.90
				credit c.	1.00	0.89	0.89




Fig. 4. CORD: predicted values where the gold value is empty.

Algorithm 1 could also be used on the output of the VLM, which is the third source of evidence.

D. Ablation

For each of the variants in the synthetic set, F1 is identical to running the full pipeline: 0.980. These figures are used to generate the all-variant results in Table III for the SROIE and CORD data sets. Grounding is probably the biggest factor; when absent, it reduces F1 by 0.031 and 0.011 on the SROIE and CORD data respectively. For SROIE, the median per-receipt F1 falls from 0.850 to 0.788; 8% of receipts have an F1 at or below 0.5, roughly doubling hallucination rate from 0.148 to 0.192. Defaulting to filling all fields in the table that are empty by default can statistically significantly lower Donut's F1 on CORD from 0.862 to 0.810, and increase the hallucination rate from 0.148 to 0.192; this default was used before the first test iteration. Schema-agent repair, normalization, and spatial rule can cause maximum differences of 0.002, 0.004, and 0.002 respectively over these short receipts, although these can be relevant and desirable for longer documents where normalization and cross-field check are more critical.

E. Audit Trail and Error Attribution

Since every fused value is recorded along with its selection rule, the difference between the pipeline and its OCR-LLM branch can be directly measured with respect to that rule. The per-field F1 scores for each document, averaged as in Table II, are displayed in Table IV. On CORD, the fused pipeline outperforms or matches its branch on every field, matching the VLM on fields such as subtotal, tax, total, and cash. The policy only changes 6 values, 5 of which were improved (including 1 cash amount and 4 filled amounts) with no incorrect changes. On SROIE, 21 of 400 values are changed, 6 are improved (3 company names, 2 totals, 1 address), and 1 does not change the score. 14 are addresses, each of the 15 address overrides was of the same rule: Malaysian addresses are sometimes longer than 10 words, so the clause test fails on the correct value, which is replaced by the fragment of the short Donut, resulting in a difference of a single rule between the pipeline and its branch. This can be fixed by filtering the clause test to only clause-type fields, which is implemented in the policy as it was before this paper was written.

Figure 4 shows the composition of CORD hallucination rate is similar between all systems (0.148 pipeline, 0.151 OCR-LLM branch, 0.135 VLM). We hypothesize that this is an annotation effect: each system emits 18 values for subtotal, five for tax, and two for total; change and credit-card values emit 1 value for the VLM and 4 for the others. For the VLM, 16 of the 18 emitted subtotals duplicate a gold field from the same receipt, generally the total and especially on receipts where there is no printed subtotal line. Removing subtotals reduces the hallucination rate for the VLM to 5.6%. CORD illustrates the dependence of grounding on OCR coverage: the Tesseract OCR produces 11 text blocks per CORD receipt, compared to 29.5 on SROIE. Accordingly, grounding removes near-all of Donut answers (6 per receipt before grounding), and the Donut-only and text-pass rows in Table II are an orthogonal measure of OCR coverage rather than performance; an OCR engine with greater coverage should preserve information via grounding.

F. Latency

Timing analysis was performed for 15 documents, five from each set after the initial warm-up was thrown away, with




Fig. 5. Median seconds per document by stage, against a standalone VLM call.




Fig. 6. Schema retrieval precision and recall against threshold σ.

response caching disabled. Each stage was run sequentially, and the median result plotted in Figure 5. Timing analysis of CORD VLM was omitted as Ollama seemed to have answered from its prompt cache. Fusion takes under 3 ms to complete, with OCR taking about 1.2 seconds. In addition, on the SROIE set, where the text pass saturates all fields, the entire pipeline takes 14.3 s per receipt versus 19.5 s for a single VLM call, and, on CORD set, where the text pass only fills sparse fields so vision fallback is required, the median timing of the entire pipeline is 29.7 seconds. For synthetic multi-page documents, the median timing is 24.4 seconds, 17 seconds of which is the Donut component. Running both the two branches in parallel during deployment likely restricts the extraction time to that of the slower branch rather than summing the time of the two branches.

G. Schema Registry Retrieval

The registry contains 8 schemas (4 synthetic document types, SROIE and CORD receipts, purchase orders and forms) and the query set 50 labelled field-name sets; 40 labelled sets describe a registered schema (exact name, two synonym renames, two subsets and two subsets with unrelated additional fields per schema) and therefore must be accepted; 10 describe an unregistered document type and must be rejected. At the operating point of $\sigma = 0.70$ (Fig. 6), where 10 of the 50 queries are rejected to the schemas agent, precision is 1.00 and no unregistered documents are accepted, with recall at 0.575. When queries with σ below this threshold are rejected to the schemas agent, no false acceptances are made. Precision is maintained at high levels throughout, for example at $\sigma = 0.45$ precision is 0.889 with recall 0.800, with no false acceptances; false acceptances only happen at $\sigma = 0.40$, and in a deployment where the agent need only call the schemas agent infrequently, could be significantly reduced further.

VI. Conclusion

The schema aware framework introduced here integrates both an OCR free extractor and an OCR grounded extractor in a deterministic evidence based field by field way. The approach contains embedding based schema registry with style dependent LoRA layout adapters. Given that each style documented has enough to avoid document routing, the approach seems to have a test macro F1 of 0.774/0.739 with trainable parameters of 0.94/4.5 MB. End to end pipeline gives test F1 of 0.980 for a multi-page synthetic set that outperforms 7B VLM. CORD strongest branch maximizes performance and all three improve on exact match rate and matches VLM. Amazingly the most effective way to avoid hallucination of values is to ground the OCR free answer in page text. At operational threshold for schema registry none of the unregistered document style will be accepted. Usual error analysis is converted into rule analysis with field by field audit record. And the analysis to bridge the gap from strongest branch on SROIE is boiled down to one clause length and form rule and this can be found in log in less than 15 minutes of experimental work.

VII. Limitations

In terms of public benchmark, we have a receipt data which are usual 100/50 document public benchmarks and we run them once each for each configuration. So we cannot test the F1 difference of 0.02. There might be some disadvantages of multi-page set. Small synthetic written by the authors. We are limited in terms of grounding by output range of the OCR engine. The most obvious is in CORD data where the output of tesseract is very sparse. We manually set policy rule, threshold for development documents which we need to re-tune in case of any new domain. E.g. in case of clause test for longer address. We are experimenting with layout adapters in isolation, we don't yet plug them into field extractors.

VIII. Future Work

The VLM is current fallback for OCR-LLM branch. We can plug it into policy as 3rd evidence with comparable grounding, usability tests. We might be able to avoid regression on SROIE with clause test limited to clause type fields. We might also be able to pass region labels from layout adapters to field extractors to limit region for grounding to field region. Also better OCR engine will save more Donut output for grounding. Also we will do more experiments with bigger multi-page documents with public annotations e.g. Kleister [18], CUAD [17].

References

[1] Y. Xu, M. Li, L. Cui, S. Huang, F. Wei, and M. Zhou, "LayoutLM: Pre-training of text and layout for document image understanding," in *Proc. 26th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD)*, 2020, pp. 1192–1200.

[2] Y. Xu, Y. Xu, T. Lv, L. Cui, F. Wei, G. Wang, Y. Lu, D. Florencio, C. Zhang, W. Che, M. Zhang, and L. Zhou, "LayoutLMv2: Multi-modal pre-training for visually-rich document understanding," in *Proc. 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (ACL-IJCNLP)*, 2021, pp. 2579–2591.

[3] Y. Huang, T. Lv, L. Cui, Y. Lu, and F. Wei, "LayoutLMv3: Pre-training for document AI with unified text and image masking," in *Proc. 30th ACM International Conference on Multimedia (ACM MM)*, 2022, pp. 4083–4091.

[4] G. Kim, T. Hong, M. Yim, J. Nam, J. Park, J. Yim, W. Hwang, S. Yun, D. Han, and S. Park, "OCR-free document understanding transformer," in *Proc. European Conference on Computer Vision (ECCV)*, 2022, pp. 498–517.

[5] L. Chiticariu, Y. Li, and F. R. Reiss, "Rule-based information extraction is dead! Long live rule-based information extraction systems!" in *Proc. 2013 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2013, pp. 827–832.

[6] T. Hong, D. Kim, M. Ji, W. Hwang, D. Nam, and S. Park, "BROS: A pre-trained language model focusing on text and layout for better key information extraction from documents," in *Proc. AAAI Conference on Artificial Intelligence*, vol. 36, no. 10, 2022, pp. 10767–10775.

[7] J. Wang, L. Jin, and K. Ding, "LiLT: A simple yet effective language-independent layout transformer for structured document understanding," in *Proc. 60th Annual Meeting of the Association for Computational Linguistics (ACL)*, 2022, pp. 7747–7757.

[8] C. Luo, C. Cheng, Q. Zheng, and C. Yao, "GeoLayoutLM: Geometric pre-training for visual information extraction," in *Proc. IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2023, pp. 7092–7101.

[9] C.-Y. Lee, C.-L. Li, T. Dozat, V. Perot, G. Su, N. Hua, J. Ainslie, R. Wang, Y. Fujii, and T. Pfister, "FormNet: Structural encoding beyond sequential modeling in form document information extraction," in *Proc. 60th Annual Meeting of the Association for Computational Linguistics (ACL)*, 2022, pp. 3735–3754.

[10] G. Jaume, H. K. Ekenel, and J.-P. Thiran, "FUNSD: A dataset for form understanding in noisy scanned documents," in *Proc. ICDAR Workshops*, 2019, pp. 1–6.

[11] S. Park, S. Shin, B. Lee, J. Lee, J. Surh, M. Seo, and H. Lee, "CORD: A consolidated receipt dataset for post-OCR parsing," in *NeurIPS 2019 Workshop on Document Intelligence*, 2019.

[12] Z. Huang, K. Chen, J. He, X. Bai, D. Karatzas, S. Lu, and C. V. Jawahar, "ICDAR2019 competition on scanned receipt OCR and information extraction," in *Proc. International Conference on Document Analysis and Recognition (ICDAR)*, 2019, pp. 1516–1520.

[13] B. Pfitzmann, C. Auer, M. Dolfi, A. S. Nassar, and P. Staar, "DocLayNet: A large human-annotated dataset for document-layout segmentation," in *Proc. 28th ACM SIGKDD Conference on Knowledge Discovery and Data Mining (KDD)*, 2022, pp. 3743–3751.

[14] R. Smith, "An overview of the Tesseract OCR engine," in *Proc. 9th International Conference on Document Analysis and Recognition (ICDAR)*, 2007, pp. 629–633.

[15] K. Lee, M. Joshi, I. R. Turc, H. Hu, F. Liu, J. M. Eisenschlos, U. Khandelwal, P. Shaw, M.-W. Chang, and K. Toutanova, "Pix2Struct: Screenshot parsing as pretraining for visual language understanding," in *Proc. 40th International Conference on Machine Learning (ICML)*, PMLR vol. 202, 2023, pp. 18893–18912.

[16] S. Wang, X. Sun, X. Li, R. Ouyang, F. Wu, T. Zhang, J. Li, G. Wang, and C. Guo, "GPT-NER: Named entity recognition via large language models," in *Findings of the Association for Computational Linguistics: NAACL 2025*, 2025, pp. 4257–4275.

[17] D. Hendrycks, C. Burns, A. Chen, and S. Ball, "CUAD: An expert-annotated NLP dataset for legal contract review," in *Proc. Neural Information Processing Systems Track on Datasets and Benchmarks*, vol. 1, 2021.

[18] T. Stanisławek, F. Graliński, A. Wróblewska, D. Lipiński, A. Kaliska, P. Rosalska, B. Topolski, and P. Biecek, "Kleister: Key information extraction datasets involving long documents with complex layouts," in *Proc. International Conference on Document Analysis and Recognition (ICDAR)*, LNCS vol. 12821, 2021, pp. 564–579.

[19] S. Yao, J. Zhao, D. Yu, N. Du, I. Shafran, K. Narasimhan, and Y. Cao, "ReAct: Synergizing reasoning and acting in language models," in *Proc. International Conference on Learning Representations (ICLR)*, 2023.

[20] S. Bai, K. Chen, X. Liu, J. Wang, W. Ge, S. Song, K. Dang, P. Wang, S. Wang, J. Tang, H. Zhong, Y. Zhu, M. Yang, Z. Li, J. Wan, P. Wang, W. Ding, Z. Fu, Y. Xu, J. Ye, X. Zhang, T. Xie, Z. Cheng, H. Zhang, Z. Yang, H. Xu, and J. Lin, "Qwen2.5-VL technical report," *arXiv preprint arXiv:2502.13923*, 2025.

[21] J. G. Fiscus, "A post-processing system to yield reduced word error rates: Recognizer output voting error reduction (ROVER)," in *Proc. IEEE Workshop on Automatic Speech Recognition and Understanding (ASRU)*, 1997, pp. 347–354.

[22] C. Guo, G. Pleiss, Y. Sun, and K. Q. Weinberger, "On calibration of modern neural networks," in *Proc. 34th International Conference on Machine Learning (ICML)*, PMLR vol. 70, 2017, pp. 1321–1330.

[23] P. Buneman, S. Khanna, and W.-C. Tan, "Why and where: A characterization of data provenance," in *Proc. 8th International Conference on Database Theory (ICDT)*, LNCS vol. 1973, 2001, pp. 316–330.

[24] E. Rahm and P. A. Bernstein, "A survey of approaches to automatic schema matching," *The VLDB Journal*, vol. 10, no. 4, pp. 334–350, 2001.

[25] N. Reimers and I. Gurevych, "Sentence-BERT: Sentence embeddings using Siamese BERT-networks," in *Proc. 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, 2019, pp. 3982–3992.

[26] N. Houlsby, A. Giurgiu, S. Jastrzebski, B. Morrone, Q. de Laroussilhe, A. Gesmundo, M. Attariyan, and S. Gelly, "Parameter-efficient transfer learning for NLP," in *Proc. 36th International Conference on Machine Learning (ICML)*, PMLR vol. 97, 2019, pp. 2790–2799.

[27] E. J. Hu, Y. Shen, P. Wallis, Z. Allen-Zhu, Y. Li, S. Wang, L. Wang, and W. Chen, "LoRA: Low-rank adaptation of large language models," in *Proc. International Conference on Learning Representations (ICLR)*, 2022.