Response to the Reviewers

CICT-2026 — "Web2Music: Page-Conditioned Music Generation with a Disclosure-Aware Classifier Cascade"

We thank both reviewers for a careful reading and for recommending acceptance after minor revision. Each comment is answered below with what changed in the manuscript and where. Locations refer to section and table titles in the revised paper. Every number quoted here is produced by a script in the released repository from a result file that is committed alongside it.

Two requests could not be met in full in the revision window: we ran **no human listening study**, and we could **not recruit independent annotators**. For each we explain what we did instead and how the claims were narrowed. Two studies are still running and are marked **Pending** below: the held-out test set for the cascade (R4 #1, R3 W3) and the real black-box set for the sensitive-page detector (R4 #3). Their placeholders remain in the manuscript and will be filled before the camera-ready version.

Summary of the main changes

- **Real end-to-end latency on a consumer GPU.** The built extension was measured with the real embedding model, classifier and generator (110 page loads per setup). Generation was measured on an RTX 5060 laptop GPU (33 cold requests per clip length), on the same machine with the GPU disabled, and on an Apple M4.
- **How often generated audio is heard.** A browsing simulation now uses measured generation times and the cache hit rate measured on real page profiles. With a cold cache, page-level audio is heard on 52% of visits on the GPU, 48% on the M4 and 34% on the CPU (15 s clips, median dwell 30 s).
- **Objective conditioning fidelity**, in place of a listening study: 702 clips for 234 pages compared against shuffled-mood controls on three scorers. The effect is significant but small, and the paper says so.
- **Loops.** A fresh seeded study of 220 clips at the shipped crossfade, objective gapless verification (30 of 30), and seam size relative to each clip's own variation.
- **Generator comparison** against MusicGen-medium and AudioLDM2-music.
- **Network-level privacy audit** of the built extension, and a switch that makes the fully local configuration (A6) send no LLM request at all.
- **Prompt ablation** rerun with fixed seeds and paired tests. The earlier "template wins" reading did not reproduce and was replaced by the null result.

Requests we could not meet in full

Listening study (R3 W1/R1; R4 #2). We could not run a human listening study within the revision period, so we: (i) removed every claim that the music is perceived as fitting the page; (ii) added objective tests of conditioning fidelity; and (iii) separated *gapless* playback, which we now verify from rendered output, from *perceptual* seamlessness, which we do not claim.

The fidelity tests use audio valence/arousal regressors, a mood tagger and CLAP retrieval. Each compares page-matched against shuffled-mood clips over 234 pages × 3 seeds. The protocol and instruments for a within-subjects listening study are released for follow-up work.

Independent annotators (R3 W3/R3; R4 #1). We could not recruit independent annotators. The revised protocol:

- labelling is blind to the collection category, to system outputs and to the other labellers, under guidelines frozen before the test set is labelled;
- all cascade thresholds are chosen on the 255-page development set only;
- LLMs are kept out of page selection, labelling and judging, and the LLM stage is frozen, with its raw answers cached for replay;
- every claim that depends on mood labels is removed, since mood is no longer an evaluated target;
- author annotation is stated as a limitation.

Pending: the held-out test set itself (pages captured after the freeze, blind labels and test-set agreement) is being collected; its numbers will be added to the test table and the abstract.

Reviewer 3

#	Comment	What we did	Where
W1 / R1	Fit to the page is never evaluated with listeners	Narrowed the claim to music *conditioned on* the page, and removed "suits the page" wording, including from the abstract. Added objective conditioning-fidelity measures (702 clips, matched against shuffled-mood controls): • matched clips are closer to the intended valence–arousal by 0.050 [0.026, 0.076]; • the intended mood is in the top-5 tags 7.5 points more often [1.3, 13.8]; • CLAP page-text similarity is higher by 0.023 [0.014, 0.033]; • valence and arousal track the targets ($\rho = 0.40$ and 0.51). The effect is small: CLAP picks a page's own clip among ten in 12.5% of cases against 10% chance. We report it as a tendency. Listening protocol released.	Abstract; Introduction; Results: Conditioning fidelity (Table "Conditioning fidelity"); Limitations
W2 / R2	"36 ms" is the fallback clip, and users mostly hear the fallback	Restated the claim as three levels of conditioning: L1 mood-level, L2 profile-level from the cache, L3 page-level. Measured cold generation on a consumer GPU: a median of 13.3 s for a 15 s clip and 24.3 s for a 28 s clip (real-time factor 0.87–0.91 end to end, $n = 33$ per length). Simulated how often each level is heard, with a cold per-session cache and the pre-warm-grid hit rate measured on real profiles (0 of 235). At 15 s clips and a median dwell of 30 s: • L3 is heard on 52% of visits on the GPU, 48% on the M4 and 34% on the CPU; • L3 is 75% of listening time on the GPU; • the results are stratified by page type, with a dwell sweep from 10 to 120 s and two stated bounds (an assumed 50% grid hit, and a cache persisting across sessions).	Abstract; Introduction; Results: Generation latency, How often generated audio is heard (Table "Exposure", Eq. 4)
W3 / R3	Labels come from the authors; α below threshold; mood $\alpha = 0.195$	Partly addressed (see above): blind labelling under frozen guidelines; mood is no longer an evaluated target; author labelling stated as a limitation. **Pending:** held-out test set and test-set α for category and sensitivity.	Results: Evaluation design, Annotation agreement; Limitations
W4	Headline latencies come from stubbed benchmarks	Re-measured end to end with the real embedding model, classifier and generator: 110 page loads per setup, all of which became audible, with none timed out. • With the LLM stage off, the first sound is heard at a median of 7.7 s (p95 12.1 s), and the generated clip takes over by p95 37.6 s. • Descriptor cost with the real, warm embedding model: median 360 ms (p95 519 ms) on 166 live sites. The stubbed figures remain only where labelled as such.	Abstract; Introduction; Results: Descriptor cost, Generation latency (Table "Latency")

#	Comment	What we did	Where
R4 (clarity)	Garbled sentences; "bart-large-mini"; dense notation	Rewrote the abstract, introduction and the architecture sections in plain language. The models are named `bart-large-mnli` and `nli-deberta-v3-xsmall` throughout. Four numbered equations (gate rule, disclosure, seam cost, exposure) are each explained in words, and terms (macro-F1, NLI, off-device rate, RTF, LUFS, α) are defined at first use.	Throughout

Reviewer 4

#	Comment	What we did	Where
1	Independent held-out corpus and annotators; tune thresholds on a separate set	Gates are chosen on the 255-page development set only, and the test protocol scores every configuration once with those gates. Independent annotators: not possible, mitigated as above. **Pending:** held-out test results (macro-F1 with CIs, off-device rate, accuracy by deciding stage, post-cutoff split).	Results: Evaluation design, Classification and disclosure (Table "Held-out test set")
2	Listening study for fit and gapless loops	A listening study was not possible. Instead: • **Gapless playback, verified objectively:** rendering clips through the browser's decoder for 10 loop cycles, 30 of 30 show no inserted silence and are sample-identical from cycle to cycle. • **Seam size relative to each clip's own variation:** the spectral-centroid change at the seam is within the clip's 95th percentile in 91.4% [87.7, 95.0] of 220 clips. The energy share (100%) is reported as circular, because the selector minimises it. "Seamless" and "inaudible" are not claimed.	Results: Loop quality
3	Improve and re-measure the sensitive detector, including the on-device model	Added an "unrelated" hypothesis (three-way entailment) and an on-device back end. Gates are chosen on the hand-written slice only. **Pending:** evaluation on the real black-box crisis/support pages and benign pages (recall and false-alarm rate with Wilson CIs, latency).	Results: Restraint (Table "Sensitive-page detection")
4	Real end-to-end latency; enough runs for p95; CPU-only case	See R3 W4. • **Enough runs for p95:** each cold-generation cell has 33 requests, and each end-to-end setup 110 loads. • **CPU-only:** the GPU host with the GPU disabled generates a 10 s clip in a median of 38.5 s and a 15 s clip in 62.2 s (12 per length, none timed out). The simulation shows page-level audio on 34% of visits in this configuration.	Results: Generation latency (Table "Latency", Fig. "Cold generation"); How often generated audio is heard

#	Comment	What we did	Where
5	Seeds and intervals for prompt and loop studies; compare another generator	Fixed seed lists, paired tests and bootstrap CIs: • **Loop study:** 220 clips, 176 scoreable, with the two exclusion reasons stated. The share of seams above 1 dB falls from 72.7% to 8.5% (McNemar $p = 2 \times 10^{-34}$). • **Prompt study:** 165 clips. The earlier difference does not reproduce (engineered minus template 0.00 dB [−0.10, 0.04], $p = 0.88$), and the paper now reports a null result. • **Generator comparison:** MusicGen-small, MusicGen-medium and AudioLDM2-music, 55 clips each, reporting RTF, seam, loop retention, CLAP-space FAD and Audiobox quality.	Results: Loop quality, Prompt ablation, Generator comparison (Table "Generators")
6	Rewrite abstract and intro; define terms; release code and data	Rewritten, and terms defined. Code, URLs, result files and the raw LLM responses are released (page text withheld for copyright). **Pending:** archive DOI.	Abstract; Introduction; repository release
7	Mathematical modelling, annotation reliability, privacy validation, perception, clarity	**Modelling and annotation:** four numbered equations (gate rule, disclosure, seam cost, exposure), and α reported on the development set. **Privacy validation:** a network-level audit of the built extension. • In the fully local configuration (A6) no request body carries page text. • In the default (A6b) page text goes only to the LLM proxy. • No telemetry leaves the browser, and every request to the generation service carries only the music profile. • URL hashes in telemetry now use a keyed HMAC. **Perception:** handled as above.	System architecture; Results: Annotation agreement, Restraint (network audit)
W	Limited comparison with alternatives	Generator comparison added. The cascade table's seven configurations, from keyword-only to LLM-only, are the baselines and are now named as such.	Table "Cascade configurations"; Table "Generators"

Other corrections found during the revision

- **The shipped build now matches the evaluated system.** The on-device zero-shot middle stage and the measured-seam loop selector are the defaults.
- **Crossfade.** The paper previously described a 50 ms default crossfade; the shipped default is 250 ms, and the text now says so.
- **The fully local configuration (A6) previously still attempted LLM requests.** It sent them to the local proxy address and they failed when the proxy was down. The network audit exposed this. A6 is now an explicit setting under which no LLM request is made, and the audit and the A6 latency run were repeated with it.
- **The exposure simulation earlier assumed that half of all pages hit the pre-warm cache.** Replaying real page profiles gives 0 of 235, because cache keys include the exact style string. The simulation now uses the measured value, and the assumed value is reported only as a bound.
- **Real-time factors.** They are now reported end to end (0.87–0.91), with the generator-only figure (0.83–0.85) stated separately.
- **The descriptor-cost benchmark previously timed the embedding model's download and load on every page.** It now times per-page inference with the model loaded once, as in the extension.
- **Batching.** Concurrent generation requests were measured to give no throughput gain on the GPU (speedup

1.01–1.02× at 2–8 concurrent requests, five repeats), and the paper says so.

- **Disclosure.** AI-assisted language editing is disclosed in the acknowledgments.