Agenda: ↗ stability

→ Radix Sorting } Poll
→ Sorting Review }

→ Balanced Trees!
  → problem w/ BST (insert order)
    4 motivation?

BST Problems

Best Case:
"balanced"



height: $\Theta(\log n)$

worst case:
"spindly"



height: $\Theta(n)$ → Linked List!

→ height grows linearly OR better!

Insert Order

Create an insert order for 1, 2, 3, 4, 5, 6, 7
to make the tree

1.) Spindly

→ add(1)
→ add(2)
⋮
→ add(7)



2.) Balanced

add(4), add(2), 1, 3, 6, 5, 7



→ How do we ensure trees are bushy?

B-trees

→ 2-3 trees

→ problem is in adding leaves ← that's what increases height

↳ Sol : stack new items at leaves



Solution: set limit, say L = 3

→ if node # > 3, give node to parent

→ arbitrarily left middle (makes most sense)





New problem : 16 > 17 ?

→ solution : size 2 node has 3 children ← max k+1 children

⇒ size k node has k+1 children (true for k = 1)

⇒

Do Prob 2, Do Prob 3

Problem: 2-3 hard to implement → not very easy to "send nodes up"

→ Left Leaning Red Black Trees! → use Rotations instead!

Rotation:

- note diff tree BST depending on insertion order
- You can get from one BST shape to another!





Rotate Left (G)

→ temp. merge

→ send down ≠ L





Rotate Right (P)

→ temp merge

→ send down ≠ R



Test:



Rotate Right (3)



Rotate Left (1)



Do Animation

Why Rotations? ← our goal

→ easy to implement → can result in Balanced Trees

LLRBs - like 2-3 (but) easier to implement

- any 2-3 tree can be converted to an LLRB (vice versa!)



→



→ store smaller item off to left (left leaning)

→ just convenient book keeping (code: store a marker on each edge)



→



Rules:

Problems: Must Always agree w/ 2-3 structure (1-1 correspondence)



→



↳ "four node" (2-3-4 ✓) we want 2-3

Rule 1: Two Red nodes cannot appear in a row

Fix: Rotate!



RotateRight(c) →



→

Rule 2: No Right Red Links!

→ push red link up

⇒



same





Not valid
⇒ not balanced

→ 1 link to A
→ 2 to C
→ 1 to x

} Not allowed

Rule 3: Root to all leaves must have same # of black links

Summary : LLRBs

1.) LLRB 1-1 correspondence w/ 2-3 trees

2.) One node cannot have 2 red links  → violates 2-3 property

3.) No Right Red Links 

4.) Every path from Root to leaf has same # of black links → ensure balance

5.) Always insert using Red Link → merge into 2-3 tree leaf