

OOP CODE 3

```
#include <iostream>

using namespace std;

void readArray(int arr[], int size) {
    cout << "Enter " << size << " numbers:\n";
    for (int i = 0; i < size; i++) {
        cin >> arr[i];
    }
}

void displayArray(const int arr[], int size) {
    for (int i = 0; i < size; i++) {
        cout << arr[i] << " ";
    }
    cout << endl;
}

void swapNumbers(int &a, int &b) {
    int temp = a;
    a = b;
    b = temp;
}

void sortArray(int arr[], int size) {
    for (int i = 0; i < size - 1; i++) {
        for (int j = 0; j < size - i - 1; j++) {
            if (arr[j] > arr[j + 1]) {
                swapNumbers(arr[j], arr[j + 1]);
            }
        }
    }
}

int main() {
```

```
int n;
cout << "Enter the size of the array: ";
cin >> n;

int arr[n];
readArray(arr, n);

cout << "Original array: ";
displayArray(arr, n);

sortArray(arr, n);
cout << "Sorted array: ";

displayArray(arr, n);

return 0;

}
```

OUTPUT:

```
Output
Enter the size of the array: 3
Enter 3 numbers:
30
478
93
Original array: 30 478 93
Sorted array: 30 93 478

=== Code Execution Successful ===
```