

Practical Assignment 09: K-Nearest Neighbors (KNN) on Iris Dataset

Submission Details

Field	Details
Name	Ayushkar Pau
ID	GF202343142
Subject	Statistical Foundation of Data Science (CSU1658)
Date	December 10, 2025
Repo	View My Repository

Objective

The goal of this assignment is to implement the **K-Nearest Neighbors (KNN)** algorithm to classify Iris flowers based on their physical measurements. We will perform Exploratory Data Analysis (EDA), standardize the features, tune the hyperparameter K by analyzing error rates, and visualize the decision boundaries.

Environment Setup and Dependencies

Start by importing all the required libraries and setting up the environment for analysis.

```
# --- 0. Environment Setup ---
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.datasets import load_iris
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import StandardScaler
from sklearn.neighbors import KNeighborsClassifier
from sklearn.metrics import classification_report, confusion_matrix, accuracy_score
from matplotlib.colors import ListedColormap

# Configure plotting
plt.rcParams['figure.figsize'] = (10, 6)
sns.set_style("whitegrid")
```

```
print("Environment setup complete.")
```

Environment setup complete.

Step 1: Exploratory Data Analysis (EDA)

Instruction: Perform `head()`, `describe()`, and `groupby()`.

Approach

We load the dataset into a `DataFrame` and inspect its structure.

- `head()` shows the first few rows.
- `describe()` provides statistical summaries (mean, std, quartiles).
- `groupby()` allows us to see the average measurements for each flower species.

```
# --- Step 1: EDA ---
```

```
# Load Data
```

```
iris = load_iris()
```

```
df = pd.DataFrame(data=iris.data, columns=iris.feature_names)
```

```
df['species'] = iris.target # 0: Setosa, 1: Versicolor, 2: Virginica
```

```
print("--- 1. First 5 Rows (head) ---")
```

```
display(df.head())
```

```
print("\n--- 2. Statistical Summary (describe) ---")
```

```
display(df.describe())
```

```
print("\n--- 3. Grouped by Species (mean) ---")
```

```
# We group by species to see the average size differences
```

```
display(df.groupby('species').mean())
```

```
--- 1. First 5 Rows (head) ---
```

	sepal length (cm)	sepal width (cm)	petal length (cm)	petal width
0	5.1	3.5	1.4	
0.2				
1	4.9	3.0	1.4	
0.2				
2	4.7	3.2	1.3	
0.2				
3	4.6	3.1	1.5	
0.2				
4	5.0	3.6	1.4	
0.2				
species				
0	0			

1	0
2	0
3	0
4	0

--- 2. Statistical Summary (describe) ---

	sepal length (cm)	sepal width (cm)	petal length (cm)	\
count	150.000000	150.000000	150.000000	
mean	5.843333	3.057333	3.758000	
std	0.828066	0.435866	1.765298	
min	4.300000	2.000000	1.000000	
25%	5.100000	2.800000	1.600000	
50%	5.800000	3.000000	4.350000	
75%	6.400000	3.300000	5.100000	
max	7.900000	4.400000	6.900000	

	petal width (cm)	species
count	150.000000	150.000000
mean	1.199333	1.000000
std	0.762238	0.819232
min	0.100000	0.000000
25%	0.300000	0.000000
50%	1.300000	1.000000
75%	1.800000	2.000000
max	2.500000	2.000000

--- 3. Grouped by Species (mean) ---

	sepal length (cm)	sepal width (cm)	petal length (cm)	\
species				
0	5.006	3.428	1.462	
1	5.936	2.770	4.260	
2	6.588	2.974	5.552	

	petal width (cm)
species	
0	0.246
1	1.326
2	2.026

Step 2: Feature Scaling

Instruction: Feature scaling.

Approach

KNN calculates distance (Euclidean) between points. If one feature has a large range (e.g., 1000-2000) and another has a small range (e.g., 0.1-1.0), the large feature will dominate the distance

calculation. We use `StandardScaler` to transform all features to have a mean of 0 and variance of 1.

```
# --- Step 2: Feature Scaling ---

# Define Features (X) and Target (y)
X = df.drop('species', axis=1)
y = df['species']

# Split the dataset (80% Train, 20% Test) BEFORE scaling to prevent data leakage
X_train, X_test, y_train, y_test = train_test_split(X, y,
test_size=0.2, random_state=42)

# Scale the features
scaler = StandardScaler()
X_train_scaled = scaler.fit_transform(X_train)
X_test_scaled = scaler.transform(X_test)

print("Data scaled successfully.")
print(f"Training Data Shape: {X_train_scaled.shape}")
print(f"Test Data Shape: {X_test_scaled.shape}")

Data scaled successfully.
Training Data Shape: (120, 4)
Test Data Shape: (30, 4)
```

Step 3: Training the K-NN Model

Instruction: Training the K-NN model on the Training set.

Approach

We initialize the `KNeighborsClassifier`. We will start with a default value of $K=5$ (analyzing 5 nearest neighbors) and the 'minkowski' metric (standard Euclidean distance).

```
# --- Step 3: Train KNN Model ---

# Initialize KNN with K=5
classifier = KNeighborsClassifier(n_neighbors=5, metric='minkowski',
p=2)

# Train on scaled data
classifier.fit(X_train_scaled, y_train)

print("KNN model (K=5) trained successfully.")

KNN model (K=5) trained successfully.
```

Step 4 & 5: Evaluation

Instruction: Making the Confusion Matrix, Predicting Accuracy Score, and Classification Report.

Approach

We use the trained model to predict species for the test set. We then evaluate performance using:

- **Confusion Matrix:** To see where the model confused one species for another.
- **Accuracy Score:** Overall percentage of correct predictions.
- **Classification Report:** Precision, Recall, and F1-Score for each class.

```
# --- Step 4 & 5: Evaluation ---

# Predict
y_pred = classifier.predict(X_test_scaled)

# Confusion Matrix
cm = confusion_matrix(y_test, y_pred)
print("--- Confusion Matrix ---")
print(cm)

# Accuracy
accuracy = accuracy_score(y_test, y_pred)
print(f"\n--- Accuracy Score: {accuracy*100:.2f}% ---")

# Classification Report
print("\n--- Classification Report ---")
print(classification_report(y_test, y_pred,
target_names=iris.target_names))

--- Confusion Matrix ---
[[10  0  0]
 [ 0  9  0]
 [ 0  0 11]]

--- Accuracy Score: 100.00% ---

--- Classification Report ---
              precision    recall  f1-score   support

   setosa         1.00        1.00        1.00         10
  versicolor      1.00        1.00        1.00          9
   virginica      1.00        1.00        1.00         11

   accuracy                1.00          30
  macro avg         1.00        1.00        1.00          30
 weighted avg         1.00        1.00        1.00          30
```

Step 6, 7 & 8: Finding the Best K

Instruction: Comparing Error Rate with K Value, Plotting, and Finding Best K.

Approach

Choosing the right K is critical.

- **Small K:** Sensitive to noise (overfitting).
- **Large K:** Smoothes boundaries too much (underfitting).

We will loop through K values from 1 to 40, calculate the **Mean Error Rate** (average of incorrect predictions) for each, and plot the results to find the "elbow" or minimum error point.

```
# --- Step 6, 7 & 8: Elbow Method to find Best K ---


error_rate = []

# Loop through K values from 1 to 40
for i in range(1, 41):
    knn = KNeighborsClassifier(n_neighbors=i)
    knn.fit(X_train_scaled, y_train)
    pred_i = knn.predict(X_test_scaled)

    # Calculate average error (mean of where prediction != actual)
    error_rate.append(np.mean(pred_i != y_test))

# Plot Error Rate vs K Value
plt.figure(figsize=(10, 6))
plt.plot(range(1, 41), error_rate, color='blue', linestyle='dashed',
         marker='o',
         markerfacecolor='red', markersize=10)
plt.title('Error Rate vs. K Value')
plt.xlabel('K')
plt.ylabel('Error Rate')
plt.show()

# Find best K (minimum error)
min_error = min(error_rate)
best_k = error_rate.index(min_error) + 1
print(f"Minimum Error Rate: {min_error:.4f}")
print(f"Best K value: {best_k}")
```



Minimum Error Rate: 0.0000
Best K value: 1

Step 9: Visualize Test Result of KNN

Instruction: Visualize Test Result of KNN.

Approach

Visualizing a 4-dimensional dataset (4 features) is difficult. To show the **Decision Boundaries**, we will retrain a model using only the first two features (Sepal Length and Sepal Width). This allows us to plot a 2D map showing how the KNN algorithm divides the space between the three flower species.

```
# --- Step 9: Visualization (Using 2 Features) ---

# Re-train on just first two features for 2D plotting
X_vis = X.to_numpy()[ :, :2] # Sepal Length, Sepal Width
y_vis = y.to_numpy()

# Split and Scale again for this visualization subset
X_train_v, X_test_v, y_train_v, y_test_v = train_test_split(X_vis,
y_vis, test_size=0.2, random_state=42)
scaler_v = StandardScaler()
X_train_v = scaler_v.fit_transform(X_train_v)
```

```

X_test_v = scaler_v.transform(X_test_v)

# Train KNN (using Best K found above, typically 1 or 3 for this
dataset)
# We use a fixed K=5 here for clear visualization standard
knn_vis = KNeighborsClassifier(n_neighbors=5)
knn_vis.fit(X_train_v, y_train_v)

# Create a mesh grid
X_set, y_set = X_test_v, y_test_v
X1, X2 = np.meshgrid(np.arange(start=X_set[:, 0].min() - 1,
stop=X_set[:, 0].max() + 1, step=0.01),
                    np.arange(start=X_set[:, 1].min() - 1,
stop=X_set[:, 1].max() + 1, step=0.01))


plt.figure(figsize=(10, 6))
plt.contourf(X1, X2, knn_vis.predict(np.array([X1.ravel(),
X2.ravel()]).T).reshape(X1.shape),
            alpha=0.3, cmap=ListedColormap(('red', 'green', 'blue')))
plt.xlim(X1.min(), X1.max())
plt.ylim(X2.min(), X2.max())

# Scatter plot of Test Data
for i, j in enumerate(np.unique(y_set)):
    plt.scatter(X_set[y_set == j, 0], X_set[y_set == j, 1],
                c=ListedColormap(('red', 'green', 'blue'))(i),
                label=iris.target_names[j])

plt.title('KNN Decision Boundary (Test Set)')
plt.xlabel('Sepal Length (Scaled)')
plt.ylabel('Sepal Width (Scaled)')
plt.legend()
plt.show()

/tmp/ipykernel_98573/2681138395.py:31: UserWarning: *c* argument looks
like a single numeric RGB or RGBA sequence, which should be avoided as
value-mapping will have precedence in case its length matches with *x*
& *y*. Please use the *color* keyword-argument or provide a 2D array
with a single row if you intend to specify the same RGB or RGBA value
for all points.
    plt.scatter(X_set[y_set == j, 0], X_set[y_set == j, 1],

```

Final Summary and Conclusions

This notebook successfully implemented the K-Nearest Neighbors (KNN) algorithm to classify Iris flower species, covering the complete machine learning pipeline.

Summary of Tasks Completed:

- **1. Exploratory Data Analysis:** We examined the dataset structure and statistical properties, observing distinct measurements for different species.
- **2. Data Preprocessing:** We applied **Standard Scaling** to normalize feature values, ensuring that distance calculations were not biased by feature magnitude.
- **3. Model Training & Evaluation:** We trained a KNN classifier and evaluated its performance using a Confusion Matrix and Classification Report, achieving high accuracy.
- **4. Hyperparameter Tuning:** We utilized the **Elbow Method** by plotting Error Rate vs. K Value. We observed that while small K values (like 1) gave low error, slightly larger values (like 5-10) often generalize better.
- **5. Visualization:** We visualized the decision boundaries in 2D space, clearly showing how the algorithm partitions the feature space to separate the three classes.

Key Learnings:

- **Feature Scaling is Critical:** Since KNN relies on Euclidean distance, unscaled data can lead to poor performance. Standardizing inputs is a mandatory step.

- **Choosing K:** The choice of K involves a bias-variance trade-off. A very small K captures noise (overfitting), while a very large K smooths out boundaries too much (underfitting). The error rate plot is an effective tool for finding the optimal balance.

This completes the requirements for Practical Assignment 09.