

Local Startup Guide

Development prototype - not clinically validated, not production-ready, and not for emergency care.

1. Requirements

- Node.js 20 or newer and npm.
- Docker Desktop must be installed and running.
- Use synthetic development data only. Never enter real patient or doctor information.

2. Open the project

In the VS Code terminal, run:

```
cd "/Users/ayushshekharsingh/Desktop/AI-Assisted Health Care"  
npm install
```

3. Start the local database

```
npx supabase start  
npx supabase db reset  
npx supabase status
```

Keep the values displayed by supabase status available for the environment configuration. The reset command recreates the local database and applies every migration.

4. Create the local environment file

```
cp .env.example .env.local
```

Open .env.local and replace the placeholders with the local values printed by npx supabase status:

```
NEXT_PUBLIC_SUPABASE_URL=http://127.0.0.1:54321  
NEXT_PUBLIC_SUPABASE_PUBLISHABLE_KEY=<local anon/publishable key>  
NEXT_PUBLIC_SITE_URL=http://localhost:3000  
SUPABASE_SECRET_KEY=<local service-role/secret key>
```

5. Optional AI configuration

These server-only variables are needed for AI intake, routing, consultation-note drafts, and voice transcription:

```
OPENAI_API_KEY=<your OpenAI API key>
OPENAI_INTAKE_MODEL=<structured-output model>
OPENAI_ROUTING_MODEL=<structured-output model>
OPENAI_CONSULTATION_MODEL=<structured-output model>
OPENAI_REALTIME_TRANSCRIPTION_MODEL=gpt-live-transcribe
```

6. Optional video configuration

These server-only LiveKit variables are required for patient-doctor video calls:

```
LIVEKIT_URL=<your LiveKit WebSocket URL>
LIVEKIT_API_KEY=<your LiveKit API key>
LIVEKIT_API_SECRET=<your LiveKit API secret>
```

The basic application can start without OpenAI or LiveKit credentials, but their related features will remain unavailable.

7. Start the application

```
npm run dev
```

Open <http://localhost:3000> in your browser. Keep the terminal running while using the application.

8. Stop the application

Press Control + C in the terminal running Next.js. Then stop the local Supabase services:

```
npx supabase stop
```

Security reminders

- Never commit `.env.local` or paste secrets into screenshots, issues, chat messages, or source files.
- Never prefix server secrets with `NEXT_PUBLIC_`. Browser-visible variables are not secret.
- Do not use the prototype for real PHI, diagnosis, prescriptions without doctor review, or emergency care.