

Development Doctor Testing Guide

Development use only. Use synthetic identities and local Supabase data. Never use real doctor, patient, registration, contact, or clinical information. Never put a password, Supabase key, or other secret in this document or in SQL history.

Prerequisites

- Application: <http://localhost:3000>
- Local Supabase Studio: <http://127.0.0.1:54323>
- Local Supabase and the Next.js application must be running.
- Public application sign-up creates patients only. Doctor and operations accounts must be provisioned through trusted local administration.

1. Create and provision a synthetic doctor

In Supabase Studio, open Authentication > Users > Add user. Create and auto-confirm a new account using a synthetic email such as `doctor.dev@example.test` and a unique development-only password of at least 12 characters.

Do not complete patient onboarding with this account. In Studio's SQL Editor, run:

SQL

```
do $$
declare
doctor_auth_user_id uuid;
doctor_profile_id uuid;
begin
select id
into doctor_auth_user_id
from auth.users
where lower(email) = lower('doctor.dev@example.test');

if doctor_auth_user_id is null then
raise exception 'Synthetic doctor auth user not found';
end if;

select id
into doctor_profile_id
from public.profiles
where auth_user_id = doctor_auth_user_id
for update;

if exists (
select 1
from public.patients
where profile_id = doctor_profile_id
and onboarding_completed_at is not null
) then
raise exception 'Do not convert an onboarded patient account';
end if;

delete from public.patients
where profile_id = doctor_profile_id;

update public.profiles
set role = 'doctor', display_name = null
where id = doctor_profile_id;

insert into public.doctors (profile_id)
values (doctor_profile_id);
end;
```

\$\$;

Sign in at <http://localhost:3000/auth/login>. Open

<http://localhost:3000/doctor/onboarding> and submit clearly synthetic professional details. Suggested development values:

- Name: Dr Synthetic One
- Qualification: MBBS Test Credential
- Registration number: DEV-REG-001
- Council: Synthetic Medical Council
- State: Synthetic State
- Specialty: GENERAL_MEDICINE
- Languages: English and/or Hindi
- Fee: 500.00 INR
- City: Synthetic City

The account must remain pending_verification and non-bookable after submission.

2. Create and provision a synthetic operations account

In Supabase Studio, create and auto-confirm another new account such as `operations.dev@example.test`. Do not complete patient onboarding. Run this in the SQL Editor:

SQL

```
do $$
declare
operations_auth_user_id uuid;
operations_profile_id uuid;
begin
select id
into operations_auth_user_id
from auth.users
where lower(email) = lower('operations.dev@example.test');

if operations_auth_user_id is null then
raise exception 'Synthetic operations auth user not found';
end if;

select id
into operations_profile_id
from public.profiles
where auth_user_id = operations_auth_user_id
for update;

if exists (
select 1
from public.patients
where profile_id = operations_profile_id
and onboarding_completed_at is not null
) then
raise exception 'Do not convert an onboarded patient account';
end if;

delete from public.patients
where profile_id = operations_profile_id;

update public.profiles
set role = 'operations', display_name = null
where id = operations_profile_id;
end;
$$;
```

3. Verify the doctor

1. Sign out of the doctor account.

2. Sign in as the operations account at <http://localhost:3000/auth/login>.

3. Open <http://localhost:3000/admin/doctors>.

4. Find the pending synthetic doctor.

5. Approve it with a reason such as Synthetic credentials approved for local testing only.

Approval must set the doctor to verified, make the doctor bookable, record the decision actor and timestamp, and add a content-free audit event. A doctor cannot verify itself.

4. Test the doctor dashboard and appointment workflow

1. Sign in as the doctor at <http://localhost:3000/auth/login>.

2. Open the dashboard at <http://localhost:3000/doctor>.

3. Open <http://localhost:3000/doctor/availability> and add a future 30-minute slot.

4. In a separate browser profile or private window, create a synthetic patient through

<http://localhost:3000/auth/sign-up>.

5. Complete patient onboarding using synthetic data.

6. Optionally complete an intake before booking so its structured result is attached to the appointment.

7. As the patient, open <http://localhost:3000/patient/appointments> and request the doctor's slot.

8. Return to the doctor browser and refresh <http://localhost:3000/doctor>.

9. Use Today for a slot today or Upcoming after today for a later slot.

10. Select View appointment details to test the assigned-doctor detail workflow.

The appointment initially has status REQUESTED. The current UI does not yet expose a dedicated confirmation control, although authorized status-transition logic exists at the service and database layers. Dashboard and assigned appointment-detail testing work with a requested appointment.

Safety notes

- These SQL commands are for trusted local development administration only.
- Never expose role selection or these operations through an unauthenticated browser action.
- Never convert an account that has completed patient onboarding or contains patient data.
- Never use production credentials, production database exports, or real registration numbers.
- Keep .env.local, passwords, Supabase secret keys, and service-role keys out of Git and PDFs.