

# iOS mOcean SDK Developer Guide

---

For iOS Version 2.6

# Table of Contents

---

System Requirements.....	5
Feature list.....	6
Installing the Ad SDK.....	7
Add the Latest version of SDK library project to your app.....	7
Add Frameworks and libraries to your project .....	8
Set Target Dependencies.....	9
Install Documentation .....	10
Simple AdView integration .....	11
Simple AdInterstitialView integration .....	12
Customize AdView.....	13
Customize view appearance.....	13
Customize content.....	13
Customize AdInterstitialView .....	14
Customize view appearance.....	14
Customize content.....	14
Troubleshooting .....	15
Duplicate symbol compile error .....	15
Remove 3 <sup>rd</sup> party library from SDK.....	16
<b>Overview .....</b>	<b>Ошибка! Закладка не определена.</b>
<b>Tasks .....</b>	<b>Ошибка! Закладка не определена.</b>
Initializing an AdView Object .....	Ошибка! Закладка не определена.
Configuring the AdView .....	Ошибка! Закладка не определена.
Loading the AdView Content .....	Ошибка! Закладка не определена.
Filtering the AdView Content .....	Ошибка! Закладка не определена.
Install Notification.....	Ошибка! Закладка не определена.
Debug the AdView.....	Ошибка! Закладка не определена.
Setting the Delegate.....	Ошибка! Закладка не определена.
<b>Properties .....</b>	<b>Ошибка! Закладка не определена.</b>
adServerUrl .....	Ошибка! Закладка не определена.

additionalParameters .....	Ошибка! Закладка не определена.
adsType .....	Ошибка! Закладка не определена.
advertiserId .....	Ошибка! Закладка не определена.
animateMode .....	Ошибка! Закладка не определена.
area .....	Ошибка! Закладка не определена.
carrier .....	Ошибка! Закладка не определена.
city .....	Ошибка! Закладка не определена.
contentAlignment .....	Ошибка! Закладка не определена.
contentSize .....	Ошибка! Закладка не определена.
country .....	Ошибка! Закладка не определена.
defaultImage .....	Ошибка! Закладка не определена.
delegate .....	Ошибка! Закладка не определена.
groupCode .....	Ошибка! Закладка не определена.
internalOpenMode .....	Ошибка! Закладка не определена.
isLoading .....	Ошибка! Закладка не определена.
keywords .....	Ошибка! Закладка не определена.
latitude .....	Ошибка! Закладка не определена.
logMode .....	Ошибка! Закладка не определена.
longitude .....	Ошибка! Закладка не определена.
maxSize .....	Ошибка! Закладка не определена.
metro .....	Ошибка! Закладка не определена.
minSize .....	Ошибка! Закладка не определена.
premium .....	Ошибка! Закладка не определена.
region .....	Ошибка! Закладка не определена.
site .....	Ошибка! Закладка не определена.
testMode .....	Ошибка! Закладка не определена.
textColor .....	Ошибка! Закладка не определена.
updateTimeInterval .....	Ошибка! Закладка не определена.
zip .....	Ошибка! Закладка не определена.
zone .....	Ошибка! Закладка не определена.
<b>Instance Methods</b> .....	Ошибка! Закладка не определена.
initWithFrame:site:zone: .....	Ошибка! Закладка не определена.
update .....	Ошибка! Закладка не определена.

AdInterstitialView Class Reference .....	Ошибка! Закладка не определена.
Overview .....	Ошибка! Закладка не определена.
Tasks .....	Ошибка! Закладка не определена.
Customizing AdInterstitialView Closing.....	Ошибка! Закладка не определена.
Setting the Delegate.....	Ошибка! Закладка не определена.
Properties .....	Ошибка! Закладка не определена.
autocloseInterstitialTime .....	Ошибка! Закладка не определена.
closeButton .....	Ошибка! Закладка не определена.
delegate .....	Ошибка! Закладка не определена.
showCloseButtonTime .....	Ошибка! Закладка не определена.
AdViewDelegate Protocol Reference .....	Ошибка! Закладка не определена.
Overview .....	Ошибка! Закладка не определена.
Tasks .....	Ошибка! Закладка не определена.
Instance Methods.....	Ошибка! Закладка не определена.
adDidEndFullScreen: .....	Ошибка! Закладка не определена.
adShouldOpen:withUrl: .....	Ошибка! Закладка не определена.
adWillStartFullScreen: .....	Ошибка! Закладка не определена.
didFailToReceiveAd:withError: .....	Ошибка! Закладка не определена.
didReceiveAd: .....	Ошибка! Закладка не определена.
willReceiveAd: .....	Ошибка! Закладка не определена.
AdInterstitialViewDelegate Protocol Reference .....	Ошибка! Закладка не определена.
Overview .....	Ошибка! Закладка не определена.
Tasks .....	Ошибка! Закладка не определена.
Instance Methods.....	Ошибка! Закладка не определена.
didClosedInterstitialAd:usageTimeInterval: .....	Ошибка! Закладка не определена.

## System Requirements

---

- Intel based Mac
- iOS 4.0 - 5.0 SDK
- XCode 4

## Feature list

---


- **HTML / JS ads**  
SDK support displaying web ads using UIWebView component.
- **Video ads**  
SDK support playing video ads in clickable MPMoviePlayerController component.
- **Location auto detect**  
SDK could automatically detecting user location
- **User-Agent auto detect**  
SDK automatically detects device User-Agent
- **Ad visibility tracking**  
SDK automatically detects ads visibility for controlling updates and video playback
- **Logging**  
SDK support logging.
- **Content caching**  
All content cached
- **Internal browser**  
SDK contains built-in browser for displaying ads in application
- **Millennial 3<sup>rd</sup> party**  
SDK includes Millennial library. [See more.](#)
- **Google AdMob 3<sup>rd</sup> party**  
SDK includes AdMob library. [See more.](#)
- **Rhythm 3<sup>rd</sup> party**  
SDK includes Rhythm library. [See more.](#)
- **Greystripe 3<sup>rd</sup> party**  
SDK includes Greystripe library. [See more.](#)
- **iAd 3<sup>rd</sup> party**  
SDK support iAd framework. [See more.](#)
- **iVdopia 3<sup>rd</sup> party**  
SDK includes iVdopia library. [See more.](#)
- **SmartAdServer 3<sup>rd</sup> party**  
SDK includes SmartAdServer library. [See more.](#)
- **ORMMA level 1,2,3**  
SDK support all ORMMA levels. [See more.](#)

## Installing the Ad SDK

### Add the Latest version of SDK library project to your app

Add the AdView.h, AdInterstitialView.h, AdDelegate.h header files from Public folder in SDK sources and library project.

Select Classes, then right-click and select Add Files to “Project Name”...




## Add Frameworks and libraries to your project

Add following frameworks and libraries to you project:

- **libAdMobileSDK.a**
- AudioToolbox
- AVFoundation
- CFNetwork
- CoreGraphics
- CoreMotion
- CoreTelephony
- iAd
- libsqlite3.0
- libz.1
- MediaPlayer
- MessageUI
- QuartzCore
- SystemConfiguration


Select Project, Target, Build Phases, then add frameworks in “Link Binary With Libraries” section





## Set Target Dependencies

Select Project, Target, Build Phases, then add AdMobileSDK target in “Target Dependencies” section.



## Install Documentation

SDK includes XCode documentation in “Documentation\Reference” folder.

Run installdocset.sh script in Terminal.app to copy documentation to XCode or you can use web based version of documentation in html folder

## Simple AdView integration

---

To add AdView into your application just import AdView.h

```
#import "AdView.h"
```

And put initialize code in (void)viewDidLoad method

```
- (void)viewDidLoad {  
    AdView *adView = [[AdView alloc] initWithFrame:CGRectMake(0, 0, 320, 50) site:8061  
zone:20249];  
    [self.view addSubview:adView];  
    [adView release];  
  
    [super viewDidLoad];  
}
```

See Also:

- For more code samples see AdMobileSamples application.

## Simple AdInterstitialView integration

---

To add AdInterstitialView into your application just import AdInterstitialView.h

```
#import "AdInterstitialView.h"
```

And put initialize code in (void)viewDidLoad method

```
- (void)viewDidLoad {  
    AdInterstitialView *adView = [[AdInterstitialView alloc] initWithFrame:CGRectMake(0, 20, 320,  
460) site:8061 zone:16112];  
    adView.minSize = CGSizeMake(320, 460);  
  
    [self.navigationController.view addSubview:adView];  
    [adView release];  
  
    [super viewDidLoad];  
}
```

For more customization you can set custom close button, delay for showing button or auto close interstitial time.

See Also:

- For more code samples see AdMobileSamples application.

## Customize AdView

---

### Customize view appearance.

1. By default in AdView enabled animation and internalOpenMode.

To disable default animation set animateMode property to NO. **Important:** you need to disable animation if you specify your own.

2. Also you can set defaultImage property to show image while ad loading.
3. Set contentAlignment property to enable auto alignment content in center vertically and horizontally.
4. Also you can apply default UIView customization such as animation, background color, support different orientations and so on.

### Customize content.

1. By default in SDK disabled location auto detect. If you want to filter content by user location set latitude and longitude property of AdView.

Also you could enable auto detect location by replacing “#undef INCLUDE\_LOCATION\_MANAGER” with «#define INCLUDE\_LOCATION\_MANAGER” in AdView.h and adding CoreLocation framework.

**Important:** However do not use Core Location just for advertising, make sure it is used for more beneficial reasons as well. It is both a good idea and part of Apple's guidelines.

2. For Rhythm SDK support CoreLocation framework is required. So by default it is disabled: “#undef INCLUDE\_RHYTHM” in AdView.h file. To enable Rhythm SDK support add CoreLocation framework to your project and replace “#undef INCLUDE\_RHYTHM” with “#define INCLUDE\_RHYTHM”.
3. To add additionally filtration you can set keywords, city, carrier, metro, etc.

## Customize AdInterstitialView

---

### Customize view appearance.

1. By default for interstitial created rounded white close button. You can customize button by setting your own.
2. To enable auto close interstitial timer set time interval `autoCloseInterstitial` property, in seconds.
3. You can delay close button displaying by setting `showCloseButtonTime` property.

### Customize content.

See customize section of `AdView`

# Troubleshooting

---

## Duplicate symbol compile error

If you got compile error like this:

```
/Users/william/Library/Developer/Xcode/DerivedData/theScoreMobile-  
testApp/Build/Products/Debug-iphoneos/libAdMobileSDK.a(SBJSON.o)"
```


It means that your project and SDK contains files with same name. In most cases this error due to duplication some framework. In this case – SBJSON.

To solve this problem you need to remove .m files for all files than cause this error. In this case – keep SBJSON.h and remove SBJSON.m and so on...


## Remove 3<sup>rd</sup> party library from SDK

To remove any 3<sup>rd</sup> party SDK follow steps below. Here example how to remove Google AdMob SDK.

1. Replace `"#define INCLUDE_ADMOB"` with `"#undef INCLUDE_ADMOB"` in AdView.h file



2. Remove .a files from Google AdMob SDK in AdMobileSDK project. You can keep files and remove reference only. It's also minimize application binary size.





# AdView Class Reference

---

**Inherits from**    [UIView](#)

---

**Declared in**    [AdView.h](#)

---

## Overview

---

You use the [AdView](#) class to embed advertisement content in your application. To do so, you simply create an [AdView](#) object and add it to a [UIView](#). An instance of [AdView](#) (or simply, an ad) is a means for displaying advertisement information from ad publisher [site](#). To choose ad publisher [site](#) set parameters in the ad initialization method [initWithFrame:site:zone:](#) or use the properties [site](#) and [zone](#). Use the [adServerUrl](#) property to choose ad publisher server.

Ad handles the rendering of any content in its area: HTML, Video, Gif animation or JavaScript. Ad also handles any interactions with that content. So you can link from the banner to ad publisher [site](#). Use the [internalOpenMode](#) property to set open mode for ad publisher [site](#). To control all interactions implement [AdViewDelegate](#) protocol.

Ad always tries to load the content after creation. The time interval between load requests is managed using the property [updateTimeInterval](#). Also you can [update](#) ad content immediately using the [update](#) method. Use the [isLoading](#) property to find out if ad is in the process of loading.

To configure ad visual appearance use the properties [defaultImage](#), [textColor](#) or [contentAlignment](#). To manage the ad animation use the property [animateMode](#).

Advanced ad customization is supported. So you can filter the ad content using the [premium](#) property. Use the properties [minSize](#) and [maxSize](#) to configure ad content size in server response. Also you can set the search parameters or any other parameters using the properties [keywords](#) and [additionalParameters](#) accordingly.

To debug ad behavior use the properties [testMode](#) and [logMode](#).

Set the [delegate](#) property to an object conforming to the [AdViewDelegate](#) protocol if you want to track the processing of ad content.

## Tasks

---

### Initializing an AdView Object

- [- initWithFrame:site:zone:](#)

### Configuring the AdView

- [site](#) property
- [zone](#) property

- [\\_\\_adServerUrl](#) *property*
- [\\_\\_defaultImage](#) *property*
- [\\_\\_animateMode](#) *property*
- [\\_\\_contentAlignment](#) *property*
- [\\_\\_internalOpenMode](#) *property*
- [\\_\\_textColor](#) *property*

## Loading the AdView Content

- [\\_\\_isLoading](#) *property*
- [\\_\\_updateTimeInterval](#) *property*
- [- update](#)
- [\\_\\_contentSize](#) *property*

## Filtering the AdView Content

- [\\_\\_premium](#) *property*
- [\\_\\_adsType](#) *property*
- [\\_\\_type](#) *property*
- [\\_\\_keywords](#) *property*
- [\\_\\_minSize](#) *property*
- [\\_\\_maxSize](#) *property*
- [\\_\\_additionalParameters](#) *property*
- [\\_\\_latitude](#) *property*
- [\\_\\_longitude](#) *property*
- [\\_\\_country](#) *property*
- [\\_\\_region](#) *property*
- [\\_\\_city](#) *property*
- [\\_\\_area](#) *property*
- [\\_\\_metro](#) *property*
- [\\_\\_zip](#) *property*
- [\\_\\_carrier](#) *property*

## Install Notification

- [\\_\\_advertiserId](#) *property*
- [\\_\\_groupCode](#) *property*

## Debug the AdView

- [\\_\\_testMode](#) *property*
- [\\_\\_logMode](#) *property*

## Setting the Delegate

- [\\_\\_delegate](#) *property*

## Properties

---

### adServerUrl

Publisher server url.

```
@property (retain) NSString *adServerUrl
```

#### **Discussion**

Publisher server url.

The default value is <http://ads.AdMobile.mobi/ad>.

#### **Declared In**

AdView.h

### additionalParameters

Custom request parameters.

```
@property (retain) NSDictionary *additionalParameters
```

#### **Discussion**

Custom request parameters.

Use this property to add custom request parameters.

The default value is nil.

**Note:** All keys and objects is need to be kind of NSString Class. For example:

```
[NSDictionary dictionaryWithObject:@"value" forKey:@"key"]
```

#### **Declared In**

AdView.h

### adsType

Ad [type](#) filter.

```
@property AdsType adsType
```

#### **Discussion**

Ad [type](#) filter.

```
typedef enum {  
    AdsTypeTextOnly = 1,  
    AdsTypeImagesOnly = 2,  
    AdsTypeImagesAndText = 3,  
    AdsTypeSMS = 6,  
}
```

```
} AdsType;
```

Deprecated! Use [type](#) property instead.

The default value is `AdsTypeImagesAndText`.

### **Declared In**

AdView.h

## advertiserId

Id of the advertiser for install notification.

```
@property (assign) NSInteger advertiserId
```

### **Discussion**

Id of the advertiser for install notification.

**Note:** Install notification enabled only if [advertiserId](#) and [groupCode](#) are specified.

### **Declared In**

AdView.h

## animateMode

A Boolean value that determines whether ad animate mode is enabled.

```
@property BOOL animateMode
```

### **Discussion**

A Boolean value that determines whether ad animate mode is enabled.

Setting the value of this property to YES enables ad animate mode and setting it to NO disables this mode.

The default value is YES.

### **Declared In**

AdView.h

## area

Area code of a user. For US only.

```
@property (retain) NSString *area
```

### **Discussion**

Area code of a user. For US only.

The default value is nil.

### **Declared In**

AdView.h

## **carrier**

User [carrier](#).

```
@property (retain) NSString *carrier
```

### **Discussion**

User [carrier](#).

The default value is nil.

### **Declared In**

AdView.h

## **city**

City of the device user (with state). For US only.

```
@property (retain) NSString *city
```

### **Discussion**

City of the device user (with state). For US only.

The default value is nil.

### **Declared In**

AdView.h

## **contentAlignment**

A Boolean value that determines whether content alignment center vertically and horizontally.

```
@property BOOL contentAlignment
```

### **Discussion**

A Boolean value that determines whether content alignment center vertically and horizontally.

Setting the value of this property to YES enables auto wrapping server response content in HTML table with alignment

The default value is NO.

**Important:** You need to disable animation if you specify your own.

### **Declared In**

AdView.h

## contentSize

Size of the ad content to be shown.

```
@property (readonly) CGSize contentSize
```

### **Discussion**

Size of the ad content to be shown.

Use this property to get the actual size of the ad content. Property value updated after ad content downloaded.

**Note:** If size unavailable (Millennial, Greystripe, iVdopia and other 3rd party SDKs) property returns CGRectZero.

### **Declared In**

AdView.h

## country

Country of visitor. It overrides [country](#) detected by IP. It is ISO 3166 to be used for specifying [country](#) code.

```
@property (retain) NSString *country
```

### **Discussion**

Country of visitor. It overrides [country](#) detected by IP. It is ISO 3166 to be used for specifying [country](#) code.

The default value is nil.

### **Declared In**

AdView.h

## defaultImage

Image for unloaded ad state.

```
@property (retain) UIImage *defaultImage
```

### **Discussion**

Image for unloaded ad state.

Settings the value of this property determines ad default image for unloaded state. In this state the content of ad is invisible and ad default image is displayed. Without connection to the internet default image also will be displayed.

The default value is nil.

### **Declared In**

AdView.h

## delegate

The receiver's [delegate](#).

```
@property (assign) id<AdViewDelegate> delegate
```

### Discussion

The receiver's [delegate](#).

The [AdView](#) is sent messages when content is processing. The [delegate](#) must adopt the [AdViewDelegate](#) protocol. The [delegate](#) is not retained.

**Important:** Before releasing an instance of [AdView](#) for which you have set a [delegate](#), you must first set its [delegate](#) property to nil. This can be done, for example, in your dealloc method.

### See Also

- [AdViewDelegate](#) Protocol Reference for the optional methods this [@property delegate](#) may implement.

### Declared In

AdView.h

## groupCode

Group code for install notification.

```
@property (retain) NSString *groupCode
```

### Discussion

Group code for install notification.

**Note:** Install notification enabled only if [advertiserId](#) and [groupCode](#) are specified.

### Declared In

AdView.h

## internalOpenMode

A Boolean value that determines whether ad internal browser is enabled.

```
@property BOOL internalOpenMode
```

### Discussion

A Boolean value that determines whether ad internal browser is enabled.

Setting the value of this property to NO disables internal browser, so after linking from the banner the ad publisher [site](#) will be opened in Safari.

To handle opening/closing internal browser use [AdView delegate](#) or `viewWillAppear/viewWillDisappear` methods of `UIViewController`.

The default value is YES.

### **Declared In**

AdView.h

## isLoading

A Boolean value that determines whether ad is in the process of loading.

```
@property (readonly) BOOL isLoading
```

### **Discussion**

A Boolean value that determines whether ad is in the process of loading.

### **Declared In**

AdView.h

## keywords

Keywords for search ads.

```
@property (retain) NSString *keywords
```

### **Discussion**

Keywords for search ads.

Use this property to search ads. The values are delimited by commas.

The default value is nil.

### **Declared In**

AdView.h

## latitude

User location [latitude](#) value.

```
@property (retain) NSString *latitude
```

### **Discussion**

User location [latitude](#) value.

Use this property to set [latitude](#). The value @"" will stop coordinates auto-detection and coordinates will not be sent to server. Any other values also will stop coordinates auto-detection but coordinates will be sent to server.

The default value is auto-detected by locationManager and sent to server.

### **Declared In**

AdView.h



## logMode

AdLogMode value that determines log level.

```
@property AdLogMode logMode
```

### **Discussion**

AdLogMode value that determines log level.

```
typedef enum {  
    AdLogModeNone = 0,  
    AdLogModeErrorsOnly = 1,  
    AdLogModeAll = 2,  
} AdLogMode;
```

Setting the value of this property to AdLogModeNone disables ads logging. AdLogModeErrorsOnly – enables logging errors only. AdLogModeAll – enables logging errors and infos.

The default value is AdLogModeErrorsOnly.

### **Declared In**

AdView.h

## longitude

User location [longitude](#) value.

```
@property (retain) NSString *longitude
```

### **Discussion**

User location [longitude](#) value.

Use this property to set [longitude](#). The value @" " will stop coordinates auto-detection and coordinates will not be sent to server. Any other values also will stop coordinates auto-detection but coordinates will be sent to server.

The default value is auto-detected by locationManager and sent to server.

### **Declared In**

AdView.h

## maxSize

Maximal size of the ad content to be shown.

```
@property CGSize maxSize
```

### **Discussion**

Maximal size of the ad content to be shown.

Use this property to set the maximal size of the ad content and server response will be close to this size.

### **Declared In**

AdView.h

## metro

Metro code of a user. For US only.

```
@property (retain) NSString *metro
```

### **Discussion**

Metro code of a user. For US only.

The default value is nil.

### **Declared In**

AdView.h

## minSize

Minimal size of the ad content to be shown.

```
@property CGSize minSize
```

### **Discussion**

Minimal size of the ad content to be shown.

Use this property to set the minimal size of the ad content and server response will be close to this size.

### **Declared In**

AdView.h

## premium

Ad [premium](#) filter.

```
@property AdPremium premium
```

### **Discussion**

Ad [premium](#) filter.

```
typedef enum {  
    AdPremiumNonPremium = 0,  
    AdPremiumPremium,  
    AdPremiumBoth,  
} AdPremium;
```

Use this property to filter the content of ad by [premium](#) status.

The default value is AdPremiumNonPremium.

### **Declared In**

AdView.h

## region

Region of visitor. ISO 3166-2 is used for United States and Canada and FIBS 10-4 is used for other countries.

```
@property (retain) NSString *region
```

### **Discussion**

Region of visitor. ISO 3166-2 is used for United States and Canada and FIBS 10-4 is used for other countries.

The default value is nil.

### **Declared In**

AdView.h

## site

Id of the publisher [site](#).

```
@property (assign) NSInteger site
```

### **Discussion**

Id of the publisher [site](#).

Settings the value of this property determines the id of the publisher [site](#), so switching between publisher sites is possible. The default value is copied from parameter [site](#) of ad initialization method.

### **Declared In**

AdView.h

## testMode

A Boolean value that determines whether ads test mode is enabled. Setting the value of this property to YES enables ads test mode and setting it to NO disables ads test mode.

```
@property BOOL testMode
```

### **Discussion**

A Boolean value that determines whether ads test mode is enabled. Setting the value of this property to YES enables ads test mode and setting it to NO disables ads test mode.

The default value is NO.

### **Declared In**

AdView.h

## textColor

Color of ad text links.

```
@property (retain) UIColor *textColor
```

### **Discussion**

Color of ad text links.

The default value is nil.

**Note:** Alpha value ignored.

### **Declared In**

AdView.h

## type

Ad [type](#) filter.

```
@property AdType type
```

### **Discussion**

Ad [type](#) filter.

```
typedef enum {  
    AdTypeTextOnly = 1,  
    AdTypeImagesOnly = 2,  
    AdTypeImagesAndText = 3,  
    AdTypeRichmedia = 4,  
    AdTypeRichmediaAndText = 5,  
    AdTypeRichmediaAndImages = 6,  
    AdTypeAll = 7,  
} AdType;
```

Use this property to filter the content of ad by [type](#).

The default value is AdTypeImagesAndText.

### **Declared In**

AdView.h

## updateTimeInterval

Update time interval, in seconds.

```
@property NSTimeInterval updateTimeInterval
```

### **Discussion**

Update time interval, in seconds.

The value of this property determines time interval between ads updating. This interval is counted after finish loading content, so the ad will start updating only after loading is finished and time interval is passed.

Setting value in range from 0 to 5 will apply 5 seconds to prevent too fast ad updates.

Setting to 0 will stop updates. All positive values enable updates.

The default value is 120.

### **Declared In**

AdView.h

## zip

Zip/Postal code of user (note: parameter is all caps). For US only.

```
@property (retain) NSString *zip
```

### **Discussion**

Zip/Postal code of user (note: parameter is all caps). For US only.

The default value is nil.

### **Declared In**

AdView.h

## zone

Id of the publisher [zone](#).

```
@property (assign) NSInteger zone
```

### **Discussion**

Id of the publisher [zone](#).

Settings the value of this property determines the id of the publisher [zone](#), so switching between publisher zones is possible. The default value is copied from parameter [zone](#) of ad initialization method.

### **Declared In**

AdView.h

## Instance Methods

---

### initWithFrame:site:zone:

Initializes and returns an [AdView](#) object having the given frame, [site](#) and [zone](#).

–

```
(id)initWithFrame:(CGRect) frame site:(NSInteger) site zone:(NSInteger) zone
```

## Parameters

*frame*

A rectangle specifying the initial location and size of the ad view in its superview's coordinates.

*site*

A value that specifies the id of ad publisher [site](#).

*zone*

A value that specifies the id of ad publisher [zone](#).

## Return Value

Returns an initialized [AdView](#) object or nil if the object could not be successfully initialized.

## Discussion

Initializes and returns an [AdView](#) object having the given frame, [site](#) and [zone](#).

## Declared In

AdView.h

## update

Starts to [update](#) the ad content immediately.

- (void)update

## Discussion

Starts to [update](#) the ad content immediately.

Call this method if you want [update](#) the ad content immediately (for example, after setting [site](#) and [zone](#) or changing [adServerUrl](#)). If ad is in the process of loading it will be interrupted.

## Declared In

AdView.h

# AdInterstitialView Class Reference

---

Inherits from [AdView](#) : UIView

---

Declared in AdInterstitialView.h

---

## Overview

---

The [AdInterstitialView](#) class is subclassing of [AdView](#) with advanced customization parameters. An instance of [AdInterstitialView](#) is a means for full-screen displaying ads with specific closing.

## Tasks

---

### Customizing AdInterstitialView Closing

- [showCloseButtonTime](#) *property*
- [autocloseInterstitialTime](#) *property*
- [closeButton](#) *property*

### Setting the Delegate

- [delegate](#) *property*

## Properties

---

### autocloseInterstitialTime

Auto close interstitial time interval, in seconds.

```
@property NSTimeInterval autocloseInterstitialTime
```

#### **Discussion**

Auto close interstitial time interval, in seconds.

Setting to 0 will disable auto closing interstitial.

The default value is 0.

#### **Declared In**

AdInterstitialView.h

## closeButton

Interstitial close button.

```
@property (retain) UIButton *closeButton
```

### Discussion

Interstitial close button.

Set this value to customize close button appearance.

### Declared In

AdInterstitialView.h

## delegate

The receiver's [delegate](#).

```
@property (assign) id<AdInterstitialViewDelegate> delegate
```

### Discussion

The receiver's [delegate](#).

The [AdInterstitialView](#) is sent messages when content is processing. The [delegate](#) must adopt the [AdInterstitialViewDelegate](#) protocol. The [delegate](#) is not retained.

**Important:** Before releasing an instance of [AdInterstitialView](#) for which you have set a [delegate](#), you must first set its [delegate](#) property to nil. This can be done, for example, in your dealloc method.

### See Also

- [AdInterstitialViewDelegate](#) Protocol Reference for the optional methods `this@property delegate` may implement.

### Declared In

AdInterstitialView.h

## showCloseButtonTime

Show close button delay time interval, in seconds.

```
@property NSTimeInterval showCloseButtonTime
```

### Discussion

Show close button delay time interval, in seconds.

Setting to 0 will show close button immediately.

The default value is 0.

### Declared In

AdInterstitialView.h



# AdViewDelegate Protocol Reference

---

**Conforms to**    NSObject

---

**Declared in**    AppDelegate.h

---

## Overview

---

The [AdViewDelegate](#) protocol defines methods that a delegate of a [AdView](#) object can optionally implement to receive notifications from ad.

## Tasks

---

- [- willReceiveAd:](#)
- [- didReceiveAd:](#)
- [- didFailToReceiveAd:withError:](#)
- [- adWillStartFullScreen:](#)
- [- adDidEndFullScreen:](#)
- [- adShouldOpen:withUrl:](#)

## Instance Methods

---

### adDidEndFullScreen:

Sent after an ad view finished displaying internal browser.

– (void)adDidEndFullScreen:(id) *sender*

#### **Parameters**

*sender*

The ad view has finished displaying internal browser.

#### **Discussion**

Sent after an ad view finished displaying internal browser.

#### **Declared In**

AppDelegate.h

## adShouldOpen:withUrl:

Sent before an ad view will start to open URL.

```
- (BOOL)adShouldOpen:(id) sender withUrl:(NSURL *) url
```

### Parameters

*sender*

The ad view that is about to open URL.

*url*

The URL that should be opened in internal or external browser.

### Return Value

Returns YES to allow SDK open browser otherwise returns NO.

### Discussion

Sent before an ad view will start to open URL.

Implement this method with return NO value if you want to control opening ads by your self.

This method is optional. If you do not implement this method, the SDK accept YES as return value.

**Important:** This method may not calling on 3rd party SDKs (Millennial, Greystripe, ivdopia, ...)

### Declared In

AdDelegate.h

## adWillStartFullScreen:

Sent before an ad view will start to display internal browser.

```
- (void)adWillStartFullScreen:(id) sender
```

### Parameters

*sender*

The ad view that is about to display internal browser.

### Discussion

Sent before an ad view will start to display internal browser.

**Important:** This method called after [adShouldOpen:withUrl:](#) returns YES or not implemented.

**Important:** This method is not called on opening ads in Safari (internalOpenMode set to NO). To handle this behaviour implement UIApplicationDelegate protocol

### Declared In

AdDelegate.h

## didFailToReceiveAd:withError:

Sent if an ad view failed to load ad content.

```
- (void)didFailToReceiveAd:(id) sender withError:(NSError *) error
```

### **Parameters**

*sender*

The ad view that failed to load ad content.

*error*

The error that occurred during loading.

### **Discussion**

Sent if an ad view failed to load ad content.

The same method can be invoked if the server does not currently advertising.

### **Declared In**

AdDelegate.h

## didReceiveAd:

Sent after an ad view finished loading ad content.

```
- (void)didReceiveAd:(id) sender
```

### **Parameters**

*sender*

The ad view has finished loading.

### **Discussion**

Sent after an ad view finished loading ad content.

### **Declared In**

AdDelegate.h

## willReceiveAd:

Sent before an ad view will begin loading ad content.

```
- (void)willReceiveAd:(id) sender
```

### **Parameters**

*sender*

The ad view that is about to load ad content.

***Discussion***

Sent before an ad view will begin loading ad content.

***Declared In***

AdDelegate.h

# AdInterstitialViewDelegate Protocol

## Reference

---

Conforms to [AdViewDelegate](#)

---

Declared in AdDelegate.h

---

## Overview

---

The [AdInterstitialViewDelegate](#) protocol defines methods that a delegate of a [AdInterstitialView](#) object can optionally implement to receive notifications from ad.

## Tasks

---

- [- didClosedInterstitialAd:usageTimeInterval:](#)

## Instance Methods

---

### didClosedInterstitialAd:usageTimeInterval:

Sent after an ad interstitial view closed and tracks the usage time of ad interstitial view.

–

```
(void) didClosedInterstitialAd: (id) sender usageTimeInterval: (NSTimeInterval) usageTimeInterval
```

#### **Parameters**

*sender*

The ad interstitial view was closed.

*usageTimeInterval*

The usage time interval of ad interstitial view.

#### **Discussion**

Sent after an ad interstitial view closed and tracks the usage time of ad interstitial view.

#### **Declared In**

AdDelegate.h