

Dual-Band Bandpass Filter using Coupled Lines

23BEC0362 – K AZAAN AHAMED

INTRODUCTION:

The ongoing growth of wireless technology requires advanced filtering components capable of efficiently managing multiple radio standards simultaneously. Modern communication systems frequently operate on two primary spectrums: a lower communication frequency and a higher communication frequency. A Dual-Band Bandpass Filter is a vital solution, enabling a single circuit to select signals from both channels while rigorously rejecting all unwanted noise. The utilization of Coupled Lines in a planar microstrip format is chosen due to its low-cost fabrication, minimal cost, and relatively simple integration into printed circuit boards.

Problem Statement

The core engineering difficulty is designing a single structure that produces two clean, low-loss passbands that are completely separate from one another. Since coupled-line filters inherently generate unwanted responses at harmonic frequencies, there is a risk of these spurious signals interfering with the operation of the upper communication band. This study addresses the necessity of designing a coupled-line filter that establishes two distinct, highly isolated frequency channels.

Study Goal


The purpose is to analyze the design and performance characteristics of a specific Coupled Line Dual-Band Bandpass Filter topology. The goal is to validate its dual-band operation, confirm its key performance metrics such as low signal loss and high channel isolation, and establish a framework for design improvement, thereby placing the design within the larger context of established microstrip filter theory.

Analysis


The analysis compares the filter's performance characteristics, obtained from the simulation of the coupled-line structure, with the theoretical expectations and benchmarks established in the literature review. The functional success of the dual-band filter is validated by interpreting its S-parameters (transmission and reflection data) across the frequency spectrum. The analysis first confirms that the two peaks in the transmission response (S_{21}) are precisely aligned with the target lower communication frequency and upper communication frequency, which validates the design's achievement of dual-mode operation necessary for the system. This alignment is further supported by comparing the measured frequencies against the theoretical predictions dictated by the

filter's geometry, with any minor deviation allowing for cautious conjecture regarding parasitic effects from the circuit's complex coupled bends or other non-idealities. The filter's efficiency is subsequently assessed by its Insertion Loss; a minimal loss value for both the first and second passbands is crucial as it indicates the achievement of critical coupling, the ideal state for maximizing power transfer. Concurrently, high Return Loss ($S(1,1)$) at both centers confirms that the filter is well-matched to the standard fifty Ohm ports. The most critical aspect of the dual-band validation is the measurement of Inter-Band Isolation, which must be high, confirming the successful generation of a transmission zero in the frequency region between the two passbands, thereby guaranteeing channel separation. Furthermore, the relationship between the peak frequency and the filter's Bandwidth establishes the Quality Factor, which serves as the ultimate measure of the device's frequency selectivity and is compared against standard coupled-line performance. Finally, the analysis must examine the spectrum beyond the upper band to evaluate any unwanted spurious passbands (harmonics) characteristic of periodic coupled-line structures, and cautious conjecture is applied to explain any observed differences in performance, such as a potentially higher signal loss in the upper band due to the frequency-dependent nature of the substrate material.

CIRCUIT:



RESULT:



Conclusions and Recommendations

The study concludes that the Dual-Band Bandpass Filter, utilizing a specialized coupled-line resonator architecture, successfully fulfills its primary design objective by establishing dual-mode frequency selectivity and producing two distinct passbands at the lower communication frequency and the upper communication frequency. This operational success is characterized by low Insertion Loss and, critically, excellent inter-band isolation, which validates the viability of using advanced coupled-line topologies for compact, high-efficiency, multi-channel wireless systems. Flowing directly from the analysis, three specific recommendations are proposed to enhance the filter's performance and manufacturability: first, a detailed parametric study of the coupling gap is essential to minimize Insertion Loss for both passbands simultaneously, aiming for critical coupling; second, it is recommended to investigate and implement methods for harmonic suppression, such as integrating precisely calculated open-circuited stubs into the feed lines, to block unwanted spurious passbands and significantly improve the filter's spectral purity; and third, future research should explore advanced structures that permit the center frequency and bandwidth of the two communication bands to be adjusted independently, enhancing the filter's flexibility for practical system integration.