


NATIONAL COLLEGE OF BUSINESS ADMINISTRATION & ECONOMICS

Front Lane Campus, Lahore

FINAL YEAR PROJECT REPORT

SmartSplit & ExpenseAI

An AI-Assisted Personal Finance Manager and Group Expense Settlement System using Min-Cash-Flow Optimisation

Submitted by

Muhammad Azeem (BSCSvb-f24152)

Chanda Safdar (BSCS-vb-f24-133)

Saba (BSITM(V)-F24-25)

Supervised by

Ms. Sehr Unisa

A report submitted in partial fulfilment of the requirements for the award of the Bachelor of Science degree (BSCS and BSITM programmes)

Department of Computer Science

National College of Business Administration & Economics, Front Lane Campus, Lahore

November 2026

DECLARATION

We, **Muhammad Azeem** (Roll No. BSCSvb-f24152), **Chanda Safdar** (Roll No. BSCS-vb-f24-133) and **Saba** (Roll No. BSITM(V)-F24-25), hereby declare that this project report titled "*SmartSplit & ExpenseAI: An AI-Assisted Personal Finance Manager and Group Expense Settlement System using Min-Cash-Flow Optimisation*" is our own work and has not been submitted, in whole or in part, for any other degree or qualification at this or any other institution. All sources of information used in this report have been duly acknowledged and referenced.

_____

Muhammad Azeem
Roll No: BSCSvb-f24152

_____

Chanda Safdar
Roll No: BSCS-vb-f24-133

_____

Saba
Roll No: BSITM(V)-F24-25

Date: _____

CERTIFICATE OF APPROVAL

It is certified that the project report titled "*SmartSplit & ExpenseAI: An AI-Assisted Personal Finance Manager and Group Expense Settlement System using Min-Cash-Flow Optimisation*" submitted by **Muhammad Azeem** (Roll No. BSCSvb-f24152), **Chanda Safdar** (Roll No. BSCS-vb-f24-133) and **Saba** (Roll No. BSITM(V)-F24-25) has been examined and found satisfactory in partial fulfilment of the requirements for the award of the Bachelor of Science degree (BSCS and BSITM programmes) at the Department of Computer Science, National College of Business Administration & Economics, Front Lane Campus, Lahore.

Ms. Sehr Unisa Project Supervisor	**[Internal Examiner]** Internal Examiner
[External Examiner] External Examiner	**[Head of Department]** Department of Computer Science

ACKNOWLEDGEMENT

All praise is due to Allah Almighty, who gave us the strength, patience and ability to complete this project.

We are sincerely grateful to our supervisor, Ms. Sehr Unisa, for her continuous guidance, constructive feedback and encouragement at every stage of this work. We also thank the faculty of the Department of Computer Science, National College of Business Administration & Economics, Front Lane Campus, for the knowledge and support provided throughout our degree programmes.

We are thankful to our classmates and friends who tested the application, shared real trip expenses and receipts, and gave honest feedback on its usability. Finally, we owe our deepest gratitude to our parents and families for their prayers, sacrifices and unconditional support.

Muhammad Azeem (BSCSvb-f24152)
Chanda Safdar (BSCS-vb-f24-133)
Saba (BSITM(V)-F24-25)

ABSTRACT

Managing money is a daily problem for students, young professionals and households in Pakistan. Personal spending is usually tracked in notebooks or not at all, and shared costs on trips or in shared flats lead to long chains of small, confusing repayments. Widely used tools are either designed for foreign markets, keep key features behind paid plans, or treat personal finance and group splitting as two separate products.

This project presents **SmartSplit & ExpenseAI**, a full-stack web application that combines both needs in one account. The personal workspace records income and expenses in Pakistani rupees, applies monthly category budgets, generates recurring bills automatically, and reads printed receipts using a vision language model, with Tesseract.js as an offline fallback. Every extracted line is verified by the user in a human-in-the-loop dialog before it is saved, and verified items are compared against a price book of 100 grocery products to suggest cheaper alternatives. A background job refreshes the price book every morning from five online Pakistani stores, reading only what each store's robots.txt permits and keeping a store's previous prices whenever it cannot be read. Savings goals show how much has been put aside, whether the user is on pace, and how much to save each month, and a zakat calculator compares the user's net wealth with the nisab using gold and silver prices fetched automatically. The group workspace supports multi-payer expenses, four split methods (equal, exact, percentage and line item), a trip currency in which new expenses start, expenses entered in foreign currencies on trips abroad and converted to rupees at daily exchange rates, and a settlement engine based on the greedy Min-Cash-Flow algorithm, which guarantees that a group of V members is settled in at most $V - 1$ payments.

The system is built on the MERN stack (MongoDB, Express, React and Node.js) and exposes 84 REST endpoints. Money is stored as integer rupees, balances are always recomputed from expenses by database aggregation, and every group request is authorised on the server. Authentication uses short-lived JSON Web Tokens with rotating refresh tokens and Google OAuth 2.0, and email can be sent through the Gmail API where the hosting provider blocks SMTP. The implementation is verified by 323 automated unit, API and property-based tests, all passing, and is deployed publicly with every change tested before it goes live. On the demonstration trip of five members and seven expenses, the settlement engine reduced 20 naive pairwise debts to 4 payments.

Keywords: expense management, debt simplification, Min-Cash-Flow, greedy algorithm, receipt OCR, vision language model, multi-currency, savings goals, zakat, web scraping, robots.txt, MERN stack, JWT

TABLE OF CONTENTS

Declaration ..... **i**

Certificate of Approval ..... **ii**

Acknowledgement ..... **iii**

Abstract ..... **iv**

List of Figures ..... **vii**

List of Tables ..... **viii**

List of Abbreviations ..... **ix**

Chapter 1: Introduction **1**

1.1 Background 1

1.2 Problem Statement 1

1.3 Objectives 2

1.4 Scope 2

1.5 Significance of the Project 3

1.6 Development Methodology 3

1.7 Organisation of the Report 4

Chapter 2: Literature Review **5**

2.1 Personal Finance Management Applications 5

2.2 Group Expense Splitting Applications 5

2.3 Debt Simplification Algorithms 5

2.4 Receipt Text Extraction (OCR) 6

2.5 String Similarity for Product Matching 6

2.6 Collecting Prices from Retailer Websites 6

2.7 Web Application Security 6

2.8 Comparison with Existing Systems 7

2.9 Research Gap 7

Chapter 3: Requirements Analysis **8**

3.1 Users and Stakeholders 8

3.2 Functional Requirements 8

3.3 Non-Functional Requirements 10

3.4 Use Case Diagrams 11

3.5 Use Case Descriptions 13

3.6 Business Rules 14

3.7 Hardware and Software Requirements 15

Chapter 4: System Design **16**

4.1 System Architecture 16

4.2 Database Design 17

4.3 Expense Split Calculation 18

4.4 Settlement Algorithm (Min-Cash-Flow) 19

4.5 Receipt Processing Pipeline 22

4.6 Price Matching and Savings Suggestions 23

4.7 Multi-Currency Conversion 23
4.8 Savings Goal Progress 24
4.9 Security Design 24
4.10 API Design 25
4.11 User Interface Design 26

Chapter 5: Implementation 27
5.1 Technology Stack 27
5.2 Project Structure 28
5.3 Backend Implementation 28
5.4 Frontend Implementation 35
5.5 User Interface 35
5.6 Deployment 46

Chapter 6: Testing and Evaluation 48
6.1 Testing Strategy 48
6.2 Test Suite Summary 48
6.3 Selected Test Cases 49
6.4 Property-Based Testing of Settlement 51
6.5 Security Testing 52
6.6 Defects Found and Fixed 52
6.7 Evaluation 53

Chapter 7: Conclusion and Future Work 55
7.1 Conclusion 55
7.2 Limitations 55
7.3 Future Work 56

References 57

Appendix A: API Endpoint Reference 59

Appendix B: User Manual 65

Appendix C: Installation Guide 66

LIST OF FIGURES

Figure 1.1: Incremental development phases of the project 3
Figure 3.1: Use case diagram — account and personal workspace 12
Figure 3.2: Use case diagram — group workspace 12
Figure 4.1: Three-tier architecture of SmartSplit & ExpenseAI 16
Figure 4.2: Entity relationship diagram 17
Figure 4.3: Flowchart of the Min-Cash-Flow settlement algorithm 20
Figure 4.4: Sequence diagram of receipt scanning and verification 22
Figure 4.5: Sequence diagram of sign-in, token refresh and reuse detection 25
Figure 5.1: Sign-in page 35
Figure 5.2: Dashboard combining both workspaces 36
Figure 5.3: Groups list with total spent and personal balance 36
Figure 5.4: Group expenses of the Murree Trip 37
Figure 5.5: Group balances, which always net to zero 37
Figure 5.6: Add Expense form with multi-payer rows and split methods 38
Figure 5.7: Expense entered in UAE dirhams with the live rupee preview 39
Figure 5.8: Dubai Trip expenses: rupee amounts with the original AED figures 40
Figure 5.9: Settle Up after optimisation: 20 naive debts reduced to 4 payments 40
Figure 5.10: Personal workspace with budget bands and transaction form 41
Figure 5.11: Savings goals with progress, pace and the monthly amount needed 41
Figure 5.12: Zakat calculator with pre-filled figures, automatically fetched metal prices and the result 42
Figure 5.13: Receipt scanning page with recent scans and savings found 43
Figure 5.14: Human-in-the-loop verification dialog (demonstration data uses a placeholder image) 43
Figure 5.15: Price book of benchmark prices, maintained by super administrators 44
Figure 5.16: Live store prices panel on the Admin page after a refresh in which Chase Up failed and kept its previous prices 44
Figure 5.17: Personal reports: category distribution, inflow vs outflow, budget vs actual 45
Figure 5.18: Group report: paid vs consumed per member and category split 46

LIST OF TABLES

Table 2.1: Comparison of the proposed system with existing tools 7
Table 3.1: User roles of the system 8
Table 3.2: Functional requirements 8
Table 3.3: Non-functional requirements 10
Table 3.4: Use case UC-01: Add a shared expense 13
Table 3.5: Use case UC-02: Settle up a group 13
Table 3.6: Use case UC-03: Scan and verify a receipt 13
Table 3.7: Business rules enforced by the system 14
Table 3.8: Hardware and software requirements 15
Table 4.1: Collections and their purpose 17
Table 4.2: Net balances of the Murree Trip group 21
Table 4.3: Iterations of Min-Cash-Flow on the Murree Trip group 21
Table 4.4: Conversion of AED 412.50 shared equally by four members at 1 AED = Rs 75.2955 24
Table 4.5: Token design 24
Table 5.1: Technologies used 27
Table 5.2: Online stores read by the price refresh 31
Table 6.1: Automated test results by file 48
Table 6.2: Selected test cases 49
Table 6.3: Security review findings and fixes 52
Table 6.4: Notable defects found during testing 52
Table 6.5: Evaluation against objectives 53
Table A.1: REST API endpoints 59
Table B.1: Step-by-step guide to the main tasks 65

LIST OF ABBREVIATIONS

Abbreviation	Meaning
API	Application Programming Interface
CI/CD	Continuous Integration / Continuous Deployment
CORS	Cross-Origin Resource Sharing
CSV	Comma-Separated Values
ERD	Entity Relationship Diagram
FR	Functional Requirement
FX	Foreign Exchange
FYP	Final Year Project
HTTP(S)	Hypertext Transfer Protocol (Secure)
JSON	JavaScript Object Notation
JSON-LD	JSON for Linking Data
JWT	JSON Web Token
LLM	Large Language Model
MCF	Min-Cash-Flow
MERN	MongoDB, Express, React, Node.js
NFR	Non-Functional Requirement
OAuth	Open Authorization
OCR	Optical Character Recognition
ODM	Object Document Mapper
OWASP	Open Worldwide Application Security Project
PDF	Portable Document Format
PKR	Pakistani Rupee
REST	Representational State Transfer
RFC	Request for Comments
SMTP	Simple Mail Transfer Protocol
SPA	Single-Page Application
SSO	Single Sign-On
TTL	Time To Live
UI	User Interface
UTC	Coordinated Universal Time
XLSX	Office Open XML Spreadsheet
XML	Extensible Markup Language
XSS	Cross-Site Scripting

CHAPTER 1
INTRODUCTION

This chapter introduces the problem domain, states the problem addressed by the project, and sets out its objectives, scope, significance and development methodology. It closes with an outline of the remaining chapters.

1.1 Background

Personal financial management is the routine of recording income and expenditure, comparing it with a plan, and adjusting behaviour. Research and everyday experience agree that people who track their spending make better financial decisions, yet most people find manual tracking tedious and stop after a few weeks. Receipts are lost, small cash purchases are forgotten, and categories are applied inconsistently.

A second, closely related problem appears whenever costs are shared. University trips, shared flats, weddings and office events produce many bills paid by different people for different subsets of the group. At the end, each participant needs to know how much they owe or are owed, and the group needs a practical way to settle. Settling every bill separately produces many small transfers; with mobile wallets such as JazzCash and Easypaisa and the State Bank of Pakistan's instant payment system Raast [19], each transfer is easy, but the number of transfers and the confusion about who has already paid remain the real cost.

Recent advances make a better solution practical. Vision language models can read photographs of printed receipts and return structured data, and established algorithms can reduce a web of debts to a small set of payments [1]. Modern web frameworks allow both capabilities to be delivered in a responsive application that works on any phone or laptop browser without installation.

1.2 Problem Statement

Existing tools address personal tracking and group splitting separately, require manual entry of every item, rarely support Pakistani payment methods or price references, and do not explain how settlement payments are derived. As a result, users must maintain two systems, re-type receipt contents by hand, and settle group debts through more transfers than necessary.

The project therefore addresses the following question: *how can a single, secure web application help users record personal and shared expenses with minimal manual effort, guarantee that every rupee is accounted for exactly, and settle group debts with the fewest practical number of payments?*

1.3 Objectives

The objectives of the project are to:

1. Design and implement a personal workspace for recording income and expenses in PKR with categories, local payment methods, monthly budgets and automatically generated recurring entries.
2. Implement AI-assisted receipt scanning that extracts line items from a photo using a vision language model, falls back to offline OCR, and requires human verification before saving.
3. Suggest savings by matching verified receipt items against a local benchmark of market prices, refreshed automatically from online stores within the limits each store sets in its robots.txt.
4. Implement a group workspace with role-based membership, multi-payer expenses and four split methods that always sum exactly to the bill total.
5. Implement a settlement engine based on the greedy Min-Cash-Flow algorithm that settles a group of V members in at most V − 1 payments, and demonstrate the reduction compared with naive repayment.
6. Help users save towards personal goals and estimate the zakat due on their wealth, and let groups record trips abroad in foreign currencies, starting in the trip's own currency, while all accounting stays in rupees.
7. Provide reports, charts and CSV, Excel and PDF exports for both workspaces.
8. Secure the system with industry-standard authentication, authorisation, input validation and rate limiting.
9. Verify correctness through automated unit, API and property-based tests.
10. Deploy the system publicly so that every change is tested automatically before it goes live.

1.4 Scope

In scope. A responsive web application for individual users and small groups (trips, flats and events of roughly 2 to 20 members); amounts in Pakistani rupees, with group expenses also accepted in 15 foreign currencies and converted to rupees; savings goals; a zakat estimate; email/password and Google sign-in; receipt photos in JPG or PNG format up to 8 MB; a price book of about 100 grocery products with indicative prices for seven stores, refreshed daily with live prices from five online stores; deployment on free cloud tiers.

Out of scope. Moving money between accounts (users pay through their own wallet or bank and then mark the payment as paid), bank account synchronisation, balances kept in a currency other than the rupee, native mobile applications, reading prices from any store or

path that its robots.txt disallows, religious rulings on disputed zakat questions (the calculator gives an estimate), and income tax or investment features.

1.5 Significance of the Project

- **For users:** one account covers personal and shared money; receipts are captured in seconds; groups settle with the minimum practical number of transfers.
- **For the local context:** PKR formatting, JazzCash, Easypaisa and Raast as first-class payment methods, prices from Pakistani retailers, and a zakat calculator that works in tola and rupees.
- **Academically:** the project applies a graph-based greedy algorithm with a provable bound, integer arithmetic for financial correctness, human-in-the-loop AI, fuzzy string matching and secure token-based authentication in a single coherent system.

1.6 Development Methodology

The system was developed using the **incremental model** [20]. The work was divided into ten increments (Phases 0 to 9), each delivering a usable slice of functionality. Every increment followed the same cycle: refine the requirements, implement, write automated tests, and record a phase report before the next increment began. Core money logic (split calculation and settlement) was written test-first. Figure 1.1 shows the increments.




Figure 1.1: Incremental development phases of the project

The incremental model was preferred over the waterfall model because later features (OCR, savings suggestions and reports) depend on earlier ones (authentication, groups and expenses), and delivering each layer fully tested reduced the risk of defects compounding across the system. After the ten planned increments, further increments based on user and supervisor feedback added an invitation inbox, member roles, a price book with super-administrators, public deployment, multi-currency trip expenses and savings goals, and finally a trip currency for groups, a zakat calculator, live store prices and email through the Gmail API.

1.7 Organisation of the Report

Chapter 2 reviews existing systems and the relevant literature. Chapter 3 specifies the requirements. Chapter 4 presents the system design, including architecture, database and algorithms. Chapter 5 describes the implementation and user interface. Chapter 6 reports testing and evaluation. Chapter 7 concludes and outlines future work. Appendices provide the API reference, a user manual and an installation guide.

CHAPTER 2
LITERATURE REVIEW

This chapter reviews existing applications for personal and group expense management, the algorithmic background of debt simplification, techniques for receipt text extraction and product matching, the collection of prices from retailer websites, and the security standards used by modern web applications. It concludes by identifying the gap addressed by this project.

2.1 Personal Finance Management Applications

Personal finance applications such as Wallet by BudgetBakers [17] and many similar budgeting apps allow users to record transactions, group them into categories and compare them against budgets. Spreadsheets remain the most common free alternative. These tools are effective for disciplined users, but entry is largely manual and they are not designed for splitting costs with other people. Support for Pakistani payment methods and local price references is limited.

2.2 Group Expense Splitting Applications

Splitwise [15] and Tricount [16] are widely used for shared expenses. Both record who paid for what, compute balances and propose repayments; Splitwise offers a "simplify debts" option that reduces the number of repayments. Advanced features such as itemised receipt entry are offered in paid tiers in some products. These applications focus on the group and do not provide a full personal budgeting workspace, so users who want both must use two separate systems.

2.3 Debt Simplification Algorithms

A set of shared expenses can be modelled as a directed weighted graph in which an edge from A to B of weight w means that A owes B an amount w. Only each person's **net balance** (total paid minus total owed) matters for settlement: any set of payments that brings every net balance to zero is a valid settlement. Verhoeff [1] analyses this problem in detail and shows that finding the absolute minimum number of payments is computationally hard, since it requires partitioning the members into the largest possible number of zero-sum subgroups, which is related to the NP-complete subset-sum problem [2].

The practical alternative is a **greedy** strategy: repeatedly match the largest creditor with the largest debtor and transfer the smaller of the two amounts. Each transfer clears at least one person, so a group of V members needs at most $V - 1$ payments [1], [3]. This bound is tight

in general and the method runs in polynomial time, which makes it the standard choice in practice. This project adopts the greedy Min-Cash-Flow method and reports its result against the naive pairwise approach.

2.4 Receipt Text Extraction (OCR)

Traditional OCR engines such as Tesseract [4] segment an image into lines and characters and recognise them using trained models. They work offline and at no cost, but return unstructured text; a separate rule-based step is needed to identify item names, quantities and prices, and accuracy drops on crumpled, faded or photographed receipts. Vision language models accept an image directly and can be instructed to return a fixed JSON structure, which removes the need for hand-written parsing rules and handles varied layouts better [14]. Because any automated extraction can misread digits, financial applications should keep a human in the loop to confirm results before they affect stored balances.

2.5 String Similarity for Product Matching

Receipt item names are abbreviated and inconsistent ("COOKING OIL 3LTR", "Cooking Oil 3 Litre"). The Sørensen–Dice coefficient [5] measures the similarity of two strings as twice the number of shared character bigrams divided by the total number of bigrams, giving a score between 0 and 1. It is simple, fast and robust to small differences in word order and spelling, which makes it suitable for matching receipt text against a product catalogue after normalisation.

2.6 Collecting Prices from Retailer Websites

Retail websites publish their prices in forms intended for machines as well as people. The Robots Exclusion Protocol [23] lets a site list, in a `robots.txt` file at its root, the paths that automated clients may and may not fetch; when several rules match a path, the longest one decides. A well-behaved collector reads this file before it uses any path, identifies itself honestly and keeps its request rate low. Many stores also list every product page in an XML sitemap and embed a schema.org `Product` description [24] in each page as JSON-LD for search engines, giving the product name, price and availability in a fixed structure. Reading these structured sources is more dependable than interpreting the visual layout of a page, which changes far more often.

2.7 Web Application Security

The OWASP Top 10 [9] lists the most critical web application risks, including broken access control, cryptographic failures, injection and identification and authentication failures. JSON Web Tokens [6] allow a server to issue signed, self-contained access tokens; keeping them short-lived and pairing them with rotating refresh tokens limits the damage of a stolen token.

OAuth 2.0 [7] enables sign-in through an identity provider such as Google without the application handling the user's password. Passwords that are stored must be hashed with a deliberately slow, salted algorithm such as bcrypt [8]. For financial values, binary floating-point arithmetic introduces representation errors [10], so amounts should be stored as integers of the smallest currency unit.

2.8 Comparison with Existing Systems

Table 2.1 compares the proposed system with representative existing tools, based on their publicly documented features at the time of writing.

Table 2.1: Comparison of the proposed system with existing tools

Feature	Spreadsheet	Wallet	Splitwise	Tricount	Proposed
Personal income/expense tracking	Manual	Yes	Limited	No	Yes
Monthly category budgets	Manual	Yes	No	No	Yes
Group expense splitting	Manual	No	Yes	Yes	Yes
Debt simplification	No	No	Yes	Yes	Yes, with $V-1$ bound shown
Itemised receipt OCR	No	Limited	Paid tier	Limited	Yes, human-verified
Price comparison / savings tips	No	No	No	No	Yes
JazzCash / Easypaisa / Raast	Manual	Limited	No	No	Yes
Personal and group in one account	Manual	No	No	No	Yes

2.9 Research Gap

The review shows that no single, free tool combines personal budgeting, AI-assisted and human-verified receipt capture, local price comparison and group settlement with a stated payment bound, for the Pakistani context. SmartSplit & ExpenseAI is designed to fill this gap, while applying established results from algorithms, OCR, string matching and security engineering.

CHAPTER 3
REQUIREMENTS ANALYSIS

This chapter identifies the users of the system and specifies its functional and non-functional requirements, use cases, business rules, and hardware and software requirements.

3.1 Users and Stakeholders

Table 3.1: User roles of the system

Role	Description
Guest	An unauthenticated visitor who can register, sign in (email or Google) and reset a forgotten password.
Registered user	Owns a private personal workspace (transactions, budgets, receipts, reports) and may belong to any number of groups.
Group member	An active member of a group who can view its expenses and balances, add expenses, preview a settlement and mark payments as paid.
Group admin	A member with management rights: edit group settings, add, invite or remove members, approve join requests, promote or demote members, rotate the share code and record settlements. The creator of a group is its first admin.
Super admin	A person whose email is listed in the ADMIN_EMAILS server setting. Sees the Admin page (totals, newest users and groups, service checklist and live store prices), maintains the benchmark price book, can start a store-price refresh and sets the bazaar gold and silver prices used for zakat.
External services	Vision AI (receipt extraction), Cloudinary (image storage), Google OAuth (sign-in), ExchangeRate-API (exchange rates), Gold API (gold and silver prices), five online stores (prices), the Gmail API or Brevo SMTP (email) and the daily scheduler.

3.2 Functional Requirements

Table 3.2: Functional requirements

ID	Module	Requirement
FR-01	Accounts	The system shall allow users to register and sign in with email and password.
FR-02	Accounts	The system shall allow users to sign in with Google OAuth 2.0 and link it to an existing account with the same email.
FR-03	Accounts	The system shall provide password reset through a single-use emailed link that expires after 30 minutes.
FR-04	Accounts	The system shall allow users to update their profile and change their password.
FR-05	Personal	The system shall allow users to record money received (credit) and spent (debit) with title, amount, date, category, payment method and note.

ID	Module	Requirement
FR-06	Personal	The system shall provide seven built-in categories (Food, Utilities, Travel, Shopping, Healthcare, Housing, Misc) and allow user-defined categories.
FR-07	Personal	The system shall support the payment methods Cash, Bank Transfer, Card, JazzCash, Easypaisa and Raast.
FR-08	Personal	The system shall allow a monthly budget cap per category and show consumption as green (< 80%), amber (80–99%) or red (≥ 100%).
FR-09	Personal	The system shall generate weekly or monthly recurring transactions automatically, including any periods missed while the server was offline.
FR-10	Personal	The system shall show a monthly summary: received, spent, remaining, comparison with the previous month and spending per category.
FR-11	Receipts	The system shall accept a receipt photo (JPG/PNG, up to 8 MB) and process it in the background.
FR-12	Receipts	The system shall extract store, date, line items and total using a vision AI model, and fall back to offline OCR if the model is unavailable.
FR-13	Receipts	The system shall present extracted lines for user verification and editing, and warn when the lines and the printed total differ by more than 5%.
FR-14	Receipts	The system shall save a verified receipt as a personal transaction or as a pre-filled line-item group expense.
FR-15	Savings	The system shall compare verified items with benchmark prices and show cheaper alternatives and the total potential saving.
FR-16	Groups	The system shall allow users to create groups (trip, home, event, other) and become their admin.
FR-17	Groups	The system shall support joining a group by direct add, single-use email invite link, or share code with admin approval, and shall show pending invitations in an inbox where they can be accepted or declined.
FR-18	Groups	The system shall record group expenses paid by one or more members.
FR-19	Groups	The system shall split expenses equally, by exact amounts, by percentage, or by line item, with live validation messages.
FR-20	Groups	The system shall display each member's net balance, recomputed from all expenses and paid settlements.
FR-21	Settlement	The system shall preview the optimised payment list without saving, showing naive debt count versus optimised payment count.
FR-22	Settlement	The system shall let a group admin record a settlement, mark the group as settled, and keep an audit log entry.
FR-23	Settlement	The system shall allow each payment to be marked as paid, updating balances immediately.
FR-24	Reports	The system shall provide monthly and six-month personal reports and group summary reports with charts.
FR-25	Reports	The system shall export transactions and group reports as CSV, Excel (XLSX) and PDF.

ID	Module	Requirement
FR-26	Notifications	The system shall notify group members when an expense is added, a member joins, a settlement is created or a payment is marked paid.
FR-27	Groups	The system shall accept a group expense in any of 16 supported currencies, convert it to whole rupees at the current exchange rate, and keep the original amounts and rate for display.
FR-28	Goals	The system shall let users create savings goals with a target amount and date, record deposits and withdrawals, and show progress, whether they are on track and the amount to save each month.
FR-29	Groups	The system shall let invite links and share links be sent through WhatsApp, and let an admin promote or demote members while always keeping at least one admin.
FR-30	Admin	The system shall let super admins maintain the benchmark price book (add, edit, delete, Excel or CSV import and Excel export) and view an overview of users and groups.
FR-31	Groups	The system shall let a group be given a trip currency from the 16 supported currencies, start every new expense in that group in it, and keep all balances and settlements in rupees.
FR-32	Zakat	The system shall estimate zakat as 2.5% of the user's net wealth when it reaches the nisab of 52.5 tola of silver or 7.5 tola of gold, pre-fill the figures it already holds, and record the zakat as a personal transaction only when the user confirms.
FR-33	Zakat	The system shall fetch international gold and silver prices automatically, convert them to rupees per tola, let a super admin save bazaar prices that are used until the next refresh, and let any user type their own prices for one calculation.
FR-34	Prices	The system shall refresh the price book every day from online stores whose robots.txt permits it, keep the previous prices of any store that cannot be read, and show super admins the result of each run with an option to start one at once.
FR-35	Email	The system shall send password-reset and invitation emails through the Gmail API when it is configured and otherwise through SMTP, and shall offer the link for sharing when an email cannot be sent.

3.3 Non-Functional Requirements

Table 3.3: Non-functional requirements

ID	Quality	Requirement
NFR-01	Correctness	All monetary values shall be integer rupees; every expense shall satisfy sum(splits) = total; group balances shall always sum to zero.
NFR-02	Security	Passwords shall be hashed with bcrypt (cost 12); access tokens shall expire in 15 minutes; refresh tokens shall rotate and be stored only as hashes in an HttpOnly cookie.
NFR-03	Security	Every group request shall verify active membership on the server; every request body shall be validated; authentication endpoints shall be rate limited.

ID	Quality	Requirement
NFR-04	Performance	Receipt upload shall respond immediately (HTTP 202) and process in the background; savings matching and the store-price refresh shall never block the user interface.
NFR-05	Reliability	OCR shall fall back to an offline engine; exchange rates and gold and silver prices shall fall back to the last saved copy; a store that cannot be read shall keep its previous prices; a failed notification or email shall never fail a money operation.
NFR-06	Usability	Every list shall have loading, empty and error states; forms shall validate inline with human-readable messages; amounts shall display as "Rs 4,200".
NFR-07	Portability	The application shall run in current desktop and mobile browsers and adapt to screens from 360 px wide.
NFR-08	Maintainability	Business logic shall live in pure, testable service modules; the API shall use consistent response envelopes.
NFR-09	Privacy	Receipt images shall be stored privately and served through signed URLs that expire after one hour.
NFR-10	Deployability	Every change pushed to the main branch shall be tested automatically and deployed only if all tests and the client build pass.
NFR-11	Politeness	The price refresh shall obey each store's robots.txt, identify itself with an honest User-Agent, and send no more than one request every two seconds to any store.

3.4 Use Case Diagrams

Figures 3.1 and 3.2 present the use cases of the account and personal workspace and of the group workspace respectively.




Figure 3.1: Use case diagram — account and personal workspace




Figure 3.2: Use case diagram — group workspace

3.5 Use Case Descriptions

The three most important use cases are described below in tabular form.

Table 3.4: Use case UC-01: Add a shared expense

Use case ID	UC-01
Name	Add a shared expense
Actor	Group member
Precondition	The user is signed in and is an active member of the group.
Main flow	1. The user opens Add Expense and selects the group. 2. The user enters title, amount, date and category. 3. The user selects one or more payers and their amounts. 4. The user selects a split method and fills in the shares. 5. The system validates the input live and enables Save. 6. The server validates the input again, computes the splits, stores the expense and notifies other members.
Alternate flow	5a. Payers do not cover the total, exact amounts do not add up, or percentages do not total 100%: the system shows a message such as "You're Rs 50 short" and keeps Save disabled.
Postcondition	The expense is stored with sum(splits) = total, and the group balances reflect it.

Table 3.5: Use case UC-02: Settle up a group

Use case ID	UC-02
Name	Settle up a group
Actors	Group member (preview), group admin (record)
Precondition	The group has at least one non-zero balance and no unpaid settlement in progress.
Main flow	1. The user opens Settle Up. 2. The system shows the naive pairwise debts. 3. The user selects "Simplify with Min-Cash-Flow". 4. The system computes and displays the optimised payments and the number of transfers saved, without saving anything. 5. A group admin selects "Record settlement". 6. The system stores one settlement row per payment, marks the group as settled and writes an audit log entry.
Alternate flow	4a. Nobody owes anything: the system reports "nothing to settle". 6a. A settlement is already in progress: the system refuses with a conflict message.
Postcondition	Payments are recorded; when each is marked paid, the corresponding balances return to zero.

Table 3.6: Use case UC-03: Scan and verify a receipt

Use case ID	UC-03
Name	Scan and verify a receipt

Actors	Registered user, Vision AI service
Precondition	The user is signed in and has a photo of a printed receipt.
Main flow	1. The user uploads or captures a photo. 2. The system stores the image and replies immediately. 3. The vision AI extracts store, date, items and total in the background. 4. The system shows the verification dialog with the image and editable lines. 5. The user corrects, adds or removes lines and confirms. 6. The system saves a personal transaction (or prepares a line-item group expense) and later attaches savings suggestions.
Alternate flow	3a. The AI is unavailable: Tesseract.js extracts the lines offline. 4a. Lines and printed total differ by more than 5%: a warning shows both values.
Postcondition	Only user-verified data is stored.

3.6 Business Rules

Table 3.7: Business rules enforced by the system

ID	Rule
BR-01	Money is stored and calculated as integer rupees; fractional rupee amounts are rejected.
BR-02	Every expense satisfies sum(splits.share) = totalAmount and sum(paidBy.amount) = totalAmount.
BR-03	Rounding remainders are assigned to the payer (the largest payer when there are several).
BR-04	Balances are always computed from expenses and paid settlements; they are never stored as running totals.
BR-05	Settlement uses greedy max-matching on net balances and produces at most V − 1 payments that bring all balances to zero.
BR-06	Every group route verifies, on the server, that the requesting user is an active member; client-sent identifiers are never trusted.
BR-07	OCR results are never saved automatically; the user verifies every line first.
BR-08	Price suggestions read only the local benchmark collection and never block the user interface; live store prices are written into that collection by a separate background job.
BR-09	A foreign-currency expense is converted to whole rupees on the server; the rounding difference goes to the largest payer or row so that BR-02 still holds, and an edit keeps the original rate.
BR-10	Savings-goal progress is always computed from the recorded deposits and withdrawals, and a goal can never hold less than zero.
BR-11	Recording a settlement closes the group, so only a group admin may do it.
BR-12	A group's trip currency only sets the starting currency of new expenses; stored amounts, balances and settlements are always in rupees.
BR-13	Zakat is 2.5% of net wealth (assets minus debts due now), rounded up to the next whole rupee, and is due only when net wealth is at or above the nisab.

ID	Rule
BR-14	A store price is accepted only for the same product: the same pack size within 2%, every word of the product name in the listing, a price between 0.6 and 1.6 times the median already in the price book, and nothing in the title that makes it a different product (such as "burger" after the name, pet food, a multipack, or the full name of another book product).

3.7 Hardware and Software Requirements

Table 3.8: Hardware and software requirements

Item	Development	End user
Processor / memory	Dual-core CPU, 8 GB RAM	Any device able to run a modern browser
Operating system	Linux, Windows or macOS	Any (Android, iOS, Windows, macOS, Linux)
Runtime	Node.js 20 or later, npm	Not required
Database	MongoDB 7 (local Docker) or MongoDB Atlas	Not required
Browser	Google Chrome (development and testing)	Chrome, Edge, Firefox or Safari (current versions)
Network	Internet for AI, image storage and Google sign-in	Internet connection
Tools	Visual Studio Code, Git, GitHub, Docker	None

CHAPTER 4
SYSTEM DESIGN

This chapter describes the architecture of the system, its database design, the algorithms at its core, the receipt processing pipeline, the security design and the API conventions.

4.1 System Architecture

The system follows a three-tier client–server architecture (Figure 4.1). The **presentation tier** is a React single-page application that runs in the browser. The **application tier** is a stateless REST API [11] built with Node.js and Express. The **data tier** consists of MongoDB and a set of external services. The browser never communicates with the database or the AI service directly: every request passes through the server's security checks.




Figure 4.1: Three-tier architecture of SmartSplit & ExpenseAI

Each request passes through a fixed pipeline of middleware before it reaches a controller: security headers and CORS (Helmet), rate limiting, JWT authentication, group membership or admin checks, and Zod schema validation. Controllers are thin; the business logic lives in pure service modules (split calculation, settlement, balances, OCR, price matching, the store-price refresh, currency conversion and exchange rates, zakat and metal prices,

recurring entries, reports, notifications and email) that can be tested without a web server. Errors from any layer are converted by a single error handler into a consistent response envelope.

4.2 Database Design

MongoDB, a document database, was chosen because the central entity, a group expense, naturally contains nested lists: several payers, several split shares and several line items. Storing these inside one document means an expense is read and written atomically in a single operation. Mongoose [21] adds schemas, validation and indexes on top of MongoDB. Figure 4.2 shows the entity relationship diagram of the sixteen collections.




Figure 4.2: Entity relationship diagram

Table 4.1: Collections and their purpose

Collection	Purpose and key constraints
User	Account details; unique email; bcrypt password hash (never returned to the client); optional Google ID.
RefreshToken	One row per session; stores only the SHA-256 hash of the token; TTL index removes expired rows automatically.

Collection	Purpose and key constraints
Group	Group details and an embedded members array (role admin/member; status active/pending/requested); share code.
GroupExpense	Expense with paidBy, splits and items arrays; a validation hook rejects any document whose shares do not sum to the total; optional fx sub-document with the original currency, amounts and rate; soft delete via deletedAt.
Settlement	One planned payment (from, to, amount, paid flag) plus the naive and optimised payment counts.
AuditLog	Append-only record of important group actions such as settlement creation.
PersonalExpense	Personal credit or debit; recurring template settings; generatedFrom links generated copies to their template.
Budget	Monthly cap per category per user; unique on (userId, category).
Category	User-defined categories; unique per user, case-insensitive.
Receipt	Image reference, OCR status and engine, extracted line items with correction flags and price matches.
BenchmarkPrice	Product name, aliases, pack size and unit, price, store and link; unique on (product, store). The bundled catalogue holds 100 products and 609 indicative price rows across seven stores, and the daily refresh writes a row for every product it finds at each of five online stores, overwriting the indicative row where the store is already in the catalogue.
Notification	One row per recipient with read state.
SavingsGoal	Goal title, target amount and date, and an embedded contributions array (positive deposits, negative withdrawals); reachedAt is set once.
FxRate	The latest rupee rates for the supported currencies with their date; a single row used as a fallback when the rate provider is unreachable.
MetalRate	A single row holding the last international gold and silver prices in rupees per tola with the time they were fetched (the fallback when the provider is unreachable), and the bazaar prices last saved by a super admin with who saved them and when.
PriceSyncRun	One row per store-price refresh: trigger (schedule, start-up, manual or command line), status, start and finish times, and for each store the number of requests made, products matched and prices updated, or the reason it was skipped or stopped.

Indexes support the most frequent queries: expenses by group and date, groups by member, transactions by user and date, due recurring templates by next run date, unread notifications by user, and price-refresh runs by start time.

4.3 Expense Split Calculation

All split methods share one rounding rule so that every expense balances exactly. For a total T shared by n people, each person first receives the floor of T / n, and the remainder r is assigned to the payer:

$$share_i = \lfloor T / n \rfloor,\ r = T - n \cdot \lfloor T / n \rfloor,\ share_payer = \lfloor T / n \rfloor + r$$

For example, Rs 100 split among three people gives 34, 33 and 33, with the extra rupee assigned to the payer. Percentage splits use the floor of T × p / 100 for each person and assign the remainder in the same way. Exact splits must sum to the total, and line-item splits divide each item among the people who shared it and require the items to sum to the total. The calculation module is pure and is checked twice more: by the controller before saving and by a validation hook in the database model.

4.4 Settlement Algorithm (Min-Cash-Flow)

4.4.1 Net balance

For each member u of a group, the net balance is computed from all non-deleted expenses and all settlement payments already marked as paid:

$$net(u) = \Sigma\ paid(u) - \Sigma\ owed(u) + \Sigma\ settled_out(u) - \Sigma\ settled_in(u)$$

A positive net means the group owes the member (a creditor); a negative net means the member owes the group (a debtor). Because every rupee paid is owed by someone, the nets always sum to zero; the algorithm verifies this and refuses to run otherwise, so a defect elsewhere can never create or lose money.

4.4.2 Greedy matching

Figure 4.3 shows the algorithm as a flowchart, and the pseudocode is given below.




Figure 4.3: Flowchart of the Min-Cash-Flow settlement algorithm

```
MIN-CASH-FLOW(net)
  C ← { (u, net[u]) : net[u] > 0 }          // creditors
  D ← { (u, −net[u]) : net[u] < 0 }         // debtors
  if Σ C ≠ Σ D then error "balances do not net to zero"
  payments ← [ ]
  while C ≠ ∅ and D ≠ ∅ do
      sort C and D by amount, descending
      c ← C[0];  d ← D[0]
      amt ← min(c.amount, d.amount)
      append (d.user → c.user, amt) to payments
      c.amount ← c.amount − amt;  d.amount ← d.amount − amt
      remove c from C if c.amount = 0
      remove d from D if d.amount = 0
  return payments
```

4.4.3 Correctness and bound

Termination and bound. In every iteration, amt equals the smaller of the two amounts, so at least one of the two members reaches zero and leaves the pool. After k payments at least k members have left. Since the balances sum to zero, when only one member remains that

member's balance must also be zero. Therefore the algorithm stops after at most V − 1 payments for V members with non-zero balances [1].

Correctness. Each payment reduces a debtor's debt and a creditor's credit by the same amount, so the sum of balances stays zero and every amount stays an integer. When the loop ends, both lists are empty and every balance is exactly zero.

Complexity. There are at most V − 1 iterations and each sorts at most V entries, giving $O(V^2 \log V)$ time and O(V) space. For groups of up to a few dozen members this is instantaneous; a binary heap would reduce it to $O(V \log V)$ for very large groups.

Optimality. The greedy result is not always the absolute minimum: when a subset of members already nets to zero among themselves, fewer payments may exist. Computing the true minimum is NP-hard [1], [2]; the V − 1 bound with polynomial running time is the accepted practical trade-off.

4.4.4 Worked example

The demonstration group "Murree Trip" has five members and seven expenses totalling Rs 49,600. Table 4.2 shows the net balances computed by the system and Table 4.3 shows each iteration of the algorithm.

Table 4.2: Net balances of the Murree Trip group

Member	Net balance (Rs)	Role
Sara Khan	+11,480	Creditor
Bilal Ahmed	+7,580	Creditor
Azeem Shahid	−3,520	Debtor
Hamza Tariq	−7,420	Debtor
Ali Raza	−8,120	Debtor
Total	**0**	

Table 4.3: Iterations of Min-Cash-Flow on the Murree Trip group

Step	Largest creditor	Largest debtor	Payment and remainder
1	Sara +11,480	Ali −8,120	Ali → Sara Rs 8,120; Sara +3,360, Ali settled
2	Bilal +7,580	Hamza −7,420	Hamza → Bilal Rs 7,420; Bilal +160, Hamza settled
3	Sara +3,360	Azeem −3,520	Azeem → Sara Rs 3,360; Sara settled, Azeem −160
4	Bilal +160	Azeem −160	Azeem → Bilal Rs 160; both settled

The group is settled in four payments, which equals the bound V − 1 = 4. Repaying each share of each bill individually would have required 20 separate transfers, so the optimiser saves 16 transfers.

4.5 Receipt Processing Pipeline

Figure 4.4 shows the sequence of interactions when a receipt is scanned. The upload request returns HTTP 202 (Accepted) immediately, and extraction runs in the background while the client polls for the result. The vision model is called with **structured output**: the response must match a fixed schema (store, date, items with name, quantity and line price, and total), so it cannot return free text or malformed JSON. The prompt fixes the domain rules: whole rupees, line totals rather than unit prices, subtotal and tax rows skipped, and null rather than a guess for unreadable values. If the call fails for any reason, Tesseract.js produces the same structure from raw text using line-pattern rules, and the receipt records which engine was used.




Figure 4.4: Sequence diagram of receipt scanning and verification

After extraction, the sum of the line prices is compared with the printed total; a difference above 5% produces a warning that names both values. Nothing is written as a transaction until the user confirms the lines in the verification dialog. Committing to a group does not create the expense; it returns a line-item draft so the user still chooses who shared each item.

4.6 Price Matching and Savings Suggestions

Each verified line item is matched against the benchmark collection in four steps:

1. **Normalisation** — the name is lower-cased and pack sizes, units, punctuation and filler words are removed, so "COOKING OIL 3LTR @" and "Cooking Oil 3 Litre" produce the same key.
2. **Alias lookup** — an indexed exact match against known receipt spellings, for example "anday" → Eggs (dozen) or "surf excel" → Detergent 1 kg.
3. **Fuzzy match** — otherwise the Dice coefficient [5] is computed, and a match is accepted only at 0.8 or above.
4. **Size check** — pack sizes are parsed separately (kg ↔ g, L ↔ ml) and must agree within 2%, so a 5 kg bag is never compared with a 1 kg bag.

$$Dice(a, b) = 2 \cdot |bigrams(a) \cap bigrams(b)| \,/\, (|bigrams(a)| + |bigrams(b)|)$$

Among matching products, the cheapest platform is selected, comparing only prices updated in the last seven days when the product has any and every recorded price otherwise, so an out-of-date figure cannot undercut a store's current price; if the user paid more, the saving (multiplied by quantity) is recorded and up to three cheaper alternatives are attached to the transaction. Matching runs after the save has been acknowledged, so it never delays the user. The benchmark collection itself is refreshed every morning from five online stores by a separate background job (Section 5.3.5), so matching always reads local data and never waits for a store.

4.7 Multi-Currency Conversion

Trips abroad produce bills in other currencies. The user may enter a group expense in one of 15 foreign currencies (for example AED, SAR, USD or GBP) with up to two decimal places. The server converts every amount to rupees at the current rate R (rupees per unit of the foreign currency) and stores the expense in whole rupees, so balances and settlement are unchanged. Rates come from a free, keyless exchange-rate service [22], refreshed every day at 03:00 and stored in the database as a fallback. Each converted value is rounded separately, so their sum may differ from the converted total by a rupee or two; that difference is given to the largest payer (or the largest row of an exact or line-item split):

$$T_PKR = round(T \times R),\ p_i = round(a_i \times R),\ p_largest \mathrel{+}= T_PKR - \Sigma\, p_i$$

Table 4.4 shows the conversion of a desert safari on the demonstration Dubai trip at the rate on 30 October 2026. The original amounts and the rate are kept in an `fx` sub-document, so the expense list can show "AED 412.5" under the rupee amount, and editing the expense later keeps the rate it was added at.

Table 4.4: Conversion of AED 412.50 shared equally by four members at 1 AED = Rs 75.2955

Value	In AED	In rupees	Calculation
Total, paid by Azeem	412.50	31,059	412.50 × 75.2955 = 31,059.39, rounded
Share of Sara, Bilal and Ali	103.125 each	7,764 each	⌊31,059 / 4⌋
Share of Azeem (payer)	103.125	7,767	7,764 + remainder 3 (BR-03)
Sum of shares	412.50	31,059	Equals the stored total (BR-02)

4.8 Savings Goal Progress

A savings goal stores only its target and the list of deposits and withdrawals; everything the user sees is computed when the goal is read, in the same spirit as group balances. For a goal of target A due on date D, created on date C, with saved amount S on date t:

$$percent = \lfloor 100 \cdot S / A \rfloor, \; monthly = \lceil (A - S) / \lceil days_left / 30 \rceil \rceil$$

$$on\ track \;\Leftrightarrow\; S \geq A \cdot (t - C) / (D - C)$$

The "on track" test compares the saved amount with a straight line from nothing on the day the goal was created to the full target on its date. When the saved amount first reaches the target, the goal records the date and the owner receives a single GOAL_REACHED notification; a withdrawal that would take the goal below zero is refused.

4.9 Security Design

Authentication uses two tokens with different lifetimes and storage (Table 4.5). Figure 4.5 shows sign-in, transparent token refresh and reuse detection.

Table 4.5: Token design

Token	Lifetime	Storage	Purpose
Access token (JWT)	15 minutes	Browser memory only (never localStorage)	Sent as a Bearer header with every API request
Refresh token	7 days	HttpOnly, SameSite=Strict, Secure cookie scoped to /api/v1/auth; only its hash stored server-side	Obtains a new access token; rotated on every use




Figure 4.5: Sequence diagram of sign-in, token refresh and reuse detection

If a refresh token that has already been rotated is presented again, it can only be a copy, so all of that user's sessions are revoked. Further controls include bcrypt hashing at cost 12 [8]; identical responses for unknown emails and wrong passwords; single-use password reset tokens stored as SHA-256 hashes with a 30-minute expiry; Zod validation of every request body, parameter and query; per-route and global rate limits; Helmet security headers; CORS restricted to the client origin; private, signed receipt image URLs; and a start-up guard that refuses to run in production with missing, weak or placeholder secrets. Super administrators are defined by the `ADMIN_EMAILS` server setting rather than a database field, so the role cannot be granted through the API; it guards the Admin overview, changes to the price book, saving bazaar gold and silver prices, and starting a store-price refresh. These controls address the OWASP categories of broken access control, cryptographic failures, injection and authentication failures [9].

4.10 API Design

The API exposes 84 REST endpoints under the prefix `/api/v1`, grouped by resource (authentication, groups and invitations, expenses, settlements, personal transactions and budgets, savings goals, zakat, receipts, reports and notifications, categories, users, exchange rates, the price book and administration). Every response uses one of two envelopes:

```
{ "success": true,  "data": { ... } }
{ "success": false, "error": { "code": "SPLIT_INVALID", "message": "You're Rs 50
short" } }
```

Machine-readable error codes (for example `NOT_A_MEMBER`, `TOKEN_REUSED`, `SETTLEMENT_IN_PROGRESS`) let the client react precisely, while the human-readable message is shown to the user unchanged. The complete endpoint list is given in Appendix A.

4.11 User Interface Design

The interface uses a clean, card-based layout with a fixed top navigation (Dashboard, Groups, Personal, Goals, Scan and Reports, plus Admin for super administrators) and a notification bell; the Zakat calculator is opened from the Goals page. Colour carries meaning consistently: green for money owed to the user or within budget, amber for budgets above 80%, and red for debts and overspending. Every list implements loading, empty and error states; destructive actions ask for confirmation; and amounts are always formatted as "Rs 4,200". Layouts collapse to a single column on narrow screens, and wide tables scroll horizontally within their cards.

CHAPTER 5
IMPLEMENTATION

This chapter describes the tools, project structure and implementation of the main modules, and presents the user interface.

5.1 Technology Stack

Table 5.1: Technologies used

Layer	Technology	Role in the system
Frontend	React 19, Vite	Component-based single-page application with fast development builds
Frontend	React Router	Client-side routing across 21 routes with protected routes
Frontend	Tailwind CSS	Utility-first, responsive styling
Frontend	Recharts, Lucide	Charts on the Reports page; icon set
Frontend	Axios	HTTP client with interceptors for tokens and silent refresh
Backend	Node.js, Express 5	REST API server and middleware pipeline
Database	MongoDB, Mongoose	Document storage, aggregation pipelines, schemas and validation
Validation	Zod	Schema validation of every request
Security	jsonwebtoken, bcryptjs, Helmet, express-rate-limit	Tokens, password hashing, headers and rate limiting
Identity	Google Identity Services / google-auth-library	Google OAuth 2.0 sign-in
AI / OCR	Anthropic Claude vision (SDK), any OpenAI-compatible vision model, Tesseract.js	Structured receipt extraction, a free AI option, and an offline fallback
Files	Multer, Cloudinary	Upload handling and private image storage
Jobs	node-cron	Nightly recurring-transaction job (02:00), exchange-rate refresh (03:00) and store-price refresh (04:00 UTC, 09:00 in Pakistan)
Exchange rates	ExchangeRate-API (open access)	Daily rupee rates for 15 currencies, no API key
Metal prices	Gold API	International gold and silver prices in US dollars per troy ounce, no API key
Store prices	Al-Fatah, GrocerApp, Metro, Jalal Sons, Chase Up	Daily prices read from store search JSON, a public search API, and sitemaps with schema.org Product data, within each robots.txt
Exports	json2csv, ExcelJS, PDFKit	CSV, XLSX and PDF generation

Layer	Technology	Role in the system
Email	Nodemailer, Gmail API, Brevo SMTP	Password reset and invitation emails; the Gmail API over HTTPS is used first when configured
Testing	Vitest, Supertest, mongodb-memory-server	Unit, API and property-based tests on an in-memory database
Hosting	Render, MongoDB Atlas	One web service for the API and the built client; managed database
CI/CD	GitHub Actions	Runs every test and the client build on each push; Render deploys only if they pass

5.2 Project Structure

The code is organised as a monorepo with separate client and server packages. The server contains approximately 6,600 lines of application code and 4,400 lines of tests; the client contains approximately 6,400 lines across 20 pages and 27 reusable components.

```
smartsplit/
├── client/                 React + Vite application
│   └── src/
│       ├── pages/          one component per route (20)
│       ├── components/     reusable UI (27)
│       ├── api/            Axios instance and API functions
│       └── context/        AuthContext, CategoriesContext
└── server/                 Express API
    └── src/
        ├── models/         Mongoose schemas (16)
        ├── routes/         routers + Zod schemas per resource
        ├── controllers/    request handlers
        ├── services/       settlement, splitCalculator, balances, ocr,
        │                   priceMatch, priceSync, currency, fx, zakat,
        │                   metalRates, recurring, reports, mailer, ...
        ├── middleware/     auth, membership, validate, rate limits, errors
        ├── scripts/        seed, prices:sync, gmail:token
        └── tests/          Vitest + Supertest suites (24 files)
```

5.3 Backend Implementation

5.3.1 Settlement service

The settlement service implements the algorithm of Section 4.4 as a pure function. Its core loop is shown below.

```
while (creditors.length && debtors.length) {
  creditors.sort(byLargest);
  debtors.sort(byLargest);

  const creditor = creditors[0];
  const debtor = debtors[0];
  const amount = Math.min(creditor.net, debtor.net);

  payments.push({ from: debtor.userId, to: creditor.userId, amount });

  creditor.net -= amount;
  debtor.net -= amount;

  // At least one of the two is now square and leaves the pool.
  if (creditor.net === 0) creditors.shift();
  if (debtor.net === 0) debtors.shift();
}
```

The same net balances are also computed inside MongoDB with an aggregation pipeline ($unwind and $group over the paidBy and splits arrays, combined with a $facet), which is used by the live routes for efficiency [12]. An automated test runs both implementations on the same ledger and asserts identical results, preventing the two from drifting apart.

5.3.2 Split calculator

The split calculator distributes an integer total with the floor-and-remainder rule:

```
function distribute(total, userIds, preferredUserId) {
  const headCount = userIds.length;
  const base = Math.floor(total / headCount);
  const shares = new Map(userIds.map((id) => [String(id), base]));

  const leftover = total - base * headCount;
  if (leftover > 0) {
    const target = preferredUserId && shares.has(String(preferredUserId))
      ? String(preferredUserId) : String(userIds[0]);
    shares.set(target, shares.get(target) + leftover);
  }
  return shares;
}
```

5.3.3 Authentication and authorisation

The `requireAuth` middleware verifies the Bearer access token and loads the user. The `requireMember` middleware loads the group from the URL identifier and looks up the caller's own active membership using the authenticated user identifier only; a non-member receives HTTP 403 and an unknown group HTTP 404. `requireAdmin` additionally checks the admin role; it guards member management and, because recording a settlement closes the group, settlement recording as well. Refresh-token rotation with reuse detection is implemented as follows:

```
const existing = await RefreshToken.findOne({ tokenHash: hash(token) });
if (!existing) return { error: 'INVALID' };

// A rotated token presented again is evidence the cookie leaked.
if (existing.revokedAt && existing.replacedBy) {
  await RefreshToken.updateMany({ userId: existing.userId, revokedAt: null },
                                { revokedAt: new Date() });
  return { error: 'REUSED' };
}
if (existing.revokedAt || existing.expiresAt < new Date()) return { error:
'INVALID' };

const next = await issueRefreshToken(existing.userId);
existing.revokedAt = new Date();
existing.replacedBy = hash(next.token);
await existing.save();
```

5.3.4 Receipt OCR and price matching

Uploads are received in memory by Multer, limited to 8 MB and image types, and stored on Cloudinary as authenticated assets. The OCR service tries up to three engines in order: the Claude vision model through the Anthropic SDK with a Zod-defined output format; otherwise any OpenAI-compatible vision model (for example a free model on OpenRouter or Google AI Studio), whose reply is parsed leniently and validated with the same schema; and finally Tesseract.js with its English language data bundled locally, so it needs no download and a failure can never stop the server. For the offline engine, a regular expression extracts lines such as "Cooking Oil 3L 1,745", "2 x Milk 220" and quantity–rate–amount columns. The price-matching service implements normalisation, alias lookup, the Dice coefficient (shown below) and size parsing.

```
export function similarity(leftText, rightText) {
  if (leftText === rightText) return 1;
  if (leftText.length < 2 || rightText.length < 2) return 0;
  const first = bigrams(leftText);
  const second = bigrams(rightText);
  let shared = 0;
  for (const [pair, count] of first) shared += Math.min(count, second.get(pair) ||
0);
  return (2 * shared) / (leftText.length - 1 + (rightText.length - 1));
}
```

5.3.5 Live store prices

The project rule that live price collection must be a decoupled background job with the local collection as a cache is implemented by the price-refresh service. It runs every day at 04:00 UTC (09:00 in Pakistan); on start-up, unless a run that began in the previous 20 hours has finished or is still in progress (a run still marked as in progress after an hour is recorded as failed, because the server it ran on has stopped, for example when the free hosting plan puts it to sleep); from the "Update now" button on the Admin page; and from a terminal with `npm run prices:sync`. For every product in the price book it looks for that product at five online stores and writes what it finds into the same `benchmark_prices` collection that the

receipt matcher reads, so no code that reads prices had to change. Al-Fatah, Metro and Chase Up use the same store names as the bundled catalogue, so their live prices overwrite its indicative figures; GrocerApp and Jalal Sons prices are added as new rows. Table 5.2 shows how each store is read.

Table 5.2: Online stores read by the price refresh

Store	Source	Notes
Al-Fatah	The Shopify storefront's product search, which returns JSON (`/search/suggest.json`)	Sold-out products are ignored
GrocerApp	The public search API that its own website calls (`/v15/search`)	Gives names, pack units and whole-rupee prices without opening product pages
Metro	Sitemap, then the schema.org Product data on product pages (`/detail/`)	Its search API requires an obfuscated signed header, so only the sitemap is used
Jalal Sons	Sitemap, then the schema.org Product data on product pages (`/product/`)	Product pages carry structured price and stock data
Chase Up	Sitemap, then the schema.org Product data on product pages (`/product/`)	Same shop platform as Jalal Sons

Before a store is used, its `robots.txt` [23] is fetched and every path the adapter needs is checked against the rules for all user agents, the longest matching rule deciding; if any path is disallowed, the store is skipped for that run and the reason is recorded (following RFC 9309, a store without a robots.txt is treated as having no rules, while one whose robots.txt cannot be reached is not read at all that day). For this reason Daraz, whose robots.txt disallows `/catalog/` (its search pages), and Naheed, which disallows `/catalogsearch/`, are not read at all. Every request carries an honest User-Agent (`SmartSplitFYP/1.0 (student project; +https://smarsplit.onrender.com)`) and a 20-second time-out, and each store receives one request at a time with a two-second pause before each; the five stores are on different hosts and are read side by side. After three consecutive failed requests, or if its sitemap or robots.txt cannot be read, a store is tried once more five minutes later, because Chase Up occasionally answers HTTP 500 for a short time; if it fails again, it is left until the next run and keeps its previous prices.

Search stores are queried with the pack size first ("Cooking Oil 3 ltr") and then without it. For sitemap stores the product name is taken from each page address, and only the pages whose names match a book product are opened, at most four per product, shortest names first; the price and availability then come from the page's schema.org Product data [24]. A listing is accepted only if it has the same pack size as the book product (within 2%), contains every word of the product name, and is priced between 0.6 and 1.6 times the median price already in the book, which stops "oil 3 L" from matching engine oil. Of the listings that fit,

the middle-priced one becomes the store's price, because during development the cheapest was often a different grade, such as broken basmati rice, and would have shown a saving that does not exist:

```
const fits = listings.filter((listing) =>
  listing.price > 0 && sameProduct(product, listing.title) &&
  (!median || (listing.price >= median * 0.6 && listing.price <= median * 1.6)));
fits.sort((left, right) => left.price - right.price);
return fits[Math.floor((fits.length - 1) / 2)] ?? null;   // the middle price
```

The first live runs showed listings that pass those checks and are still a different product, because their titles contain the product name and the right pack size. Two further checks reject them. A word after the product name that makes it a different thing ("Beef Burger", "Sugar Cane", "Tea Cake Rusk", "Garlic Mayo", "Almond Jam Cookies"), or one anywhere in the title (cat food, a kitchen towel, a "1Kg X 2Pcs" multipack), rejects the listing; "Burger Cheese Slices" is still accepted as cheese slices, because there the word comes before the name. A title that contains the whole name of another product in the book, of two words or more, is also rejected, so "Face Wash Tea Tree 200g" is not taken as tea. Finally, when a store answers but none of its listings fits a product, the price that an earlier run took from that store's own website is removed, so a wrong match from an older run, or a product the store no longer sells, does not linger; the bundled indicative figures and prices entered by hand, whose links do not point to that store, are kept.

Each run is recorded in the `price_sync_runs` collection with, for every store, the number of requests made, products matched and prices updated, or why the store was skipped or stopped; the Admin page shows the latest run (Figure 5.16). Only one run can be in progress at a time: a second request returns the run that is already under way. No user request ever waits for a store, because receipts are always matched against the local collection.

Evaluation runs against the live stores took about seven minutes each. In the run of 3 November 2026 all five stores completed and 189 prices were updated (Al-Fatah 41, GrocerApp 39, Metro 30, Jalal Sons 42 and Chase Up 37 of the 100 products). In an earlier run, shown in Figure 5.16, Chase Up answered HTTP 500 to three requests in a row after 25 of its prices had been updated; the refresh stopped reading that store and kept its remaining prices, while the other four stores completed normally. When every match from the earlier runs was checked again with the look-alike rules, ten listings were rejected, among them cat food offered as beef, sugar-cane pieces offered as sugar and a tea-tree face wash offered as tea, and every genuine match was kept.

5.3.6 Multi-currency expenses

The currency service is a pure function that receives a validated expense in its entry currency and the rate, and returns the same expense in rupees together with the original figures. Payers, exact shares and line items are first checked in cents of the entry currency,

so a message such as "Payers are AED 40 short" is given in the currency the user typed. The helper below rounds each value and moves the rounding difference to one chosen row:

```
function toRupees(values, rate, totalRupees, target) {
  const rupees = values.map((value) => Math.round(value * rate));
  rupees[target] += totalRupees - rupees.reduce((sum, value) => sum + value, 0);
  return rupees;
}
```

The exchange-rate service keeps the latest rates in memory for 12 hours and in the `fx_rates` collection. If the provider cannot be reached, the saved copy is used and marked as stale, and a failed attempt is not repeated for ten minutes; only when no rates were ever saved does the API answer HTTP 503 with the code `FX_UNAVAILABLE`.

5.3.7 Trip currency

When a group is created, its trip currency is chosen from a drop-down list of the 16 currencies that the exchange-rate service can convert (`CURRENCIES` in `fx.js`), and the Zod schemas for creating and updating a group accept nothing else:

```
baseCurrency: z.enum(CURRENCIES, { message: 'Pick a currency from the list'
}).default('PKR'),
```

When Add Expense opens for a new expense in that group, the entry currency starts as the trip currency, so on a Dubai trip the amount is typed in AED straight away; an expense being edited keeps its own currency, and one built from a scanned receipt stays in rupees. The trip currency never changes how money is stored: every amount, balance and settlement figure is still in rupees and labelled "Rs", with the original foreign amount shown beneath a converted expense.

5.3.8 Savings goals

The goals controller exposes six endpoints (list, create, edit, delete, add a contribution and remove a contribution). Every query includes the owner's identifier, so a goal belonging to someone else answers HTTP 404. Progress is computed by a pure `progressOf(goal, now)` function that implements the formulas of Section 4.8, and is unit-tested with fixed dates.

5.3.9 Zakat calculator

The Zakat page estimates the zakat due on the user's wealth. Its form starts with figures the application already holds: money in savings goals, what group members owe the user, and what the user owes in groups; the difference between the user's income and spending over the last twelve months is shown only as a hint. The user adds cash, bank balances, gold and silver in tola, business stock, investments and other debts due now, and chooses the nisab: 52.5 tola of silver (the default, which gives the lower threshold) or 7.5 tola of gold. The pure `calculateZakat` function then works in whole rupees:

$$W = \max(\text{assets} - \text{debts}, 0),\ \text{nisab} = \text{round}(N \times P),\ \text{zakat} = \lceil W / 40 \rceil \text{ if } W \geq \text{nisab, otherwise } 0$$

Here N is the nisab in tola and P the price per tola of the chosen metal. Dividing by 40 gives 2.5%, and rounding up means the amount is never a rupee short: with silver at Rs 3,000 per tola the nisab is 52.5 × 3,000 = Rs 157,500, so wealth of Rs 157,499 owes nothing, while exactly Rs 157,500 owes ⌈3,937.5⌉ = Rs 3,938.

Gold and silver prices come from Gold API [25], a free service without a key that quotes US dollars per troy ounce. They are converted to rupees per tola (11.664 g) with the current dollar rate from the exchange-rate service:

$$P_tola = \text{round}(USD_per_ounce / 31.1035 \times 11.664 \times R_USD)$$

As with exchange rates, the result is kept in memory for 12 hours and saved in the `metal_rates` collection; when the provider cannot be reached the saved copy is used and marked as stale, and a failed attempt is not repeated for ten minutes. Bazaar (sarafa) prices in Pakistan are usually a little above the international price, so a super admin can save bazaar prices for everyone; they are used for as long as they are newer than the latest international price. Any user can also type their own prices for a single calculation, and if a price that the calculation needs is missing the API answers HTTP 400 with the code `ZAKAT_RATE_MISSING`. Nothing is saved automatically: "Record as paid" asks for confirmation and then adds a "Zakat <year>" money-out transaction (category Misc, paid in cash) to the Personal workspace, where it can be edited.

5.3.10 Recurring transactions, reports and notifications

A node-cron job runs every night at 02:00 and calls `runDueRecurring(now)`, which finds every template whose next run date has passed, writes one entry per missed period (so a server that was offline for three months catches up with three entries) and advances the schedule; a 120-iteration guard prevents runaway loops. Reports are computed with aggregation pipelines and exported with json2csv, ExcelJS and PDFKit. Notifications are written as one row per recipient on four events; the notification function catches its own errors so that a failure can never cancel the money operation that triggered it.

5.3.11 Email through the Gmail API

Password-reset and invitation emails were first sent through Brevo SMTP. Brevo delivers mail only after it has activated the sending account, and Render's free tier blocks the outgoing SMTP ports, so the mailer can also send through the Gmail API [26] over HTTPS. It uses the first transport that is configured: the Gmail API when the three `GMAIL_*` settings are present, otherwise SMTP, otherwise (in development) it prints the message to the server log. For Gmail, the stored refresh token is exchanged for an access token, which is cached until a minute before it expires; Nodemailer's stream transport builds the message, and the

raw message is posted, base64url-encoded, to the Gmail send endpoint. The refresh token is obtained once with `npm run gmail:token`, a local OAuth sign-in limited to the `gmail.send` scope, so the server can send mail but cannot read the mailbox. If Gmail refuses a message, the reason is logged and the error is passed to the caller, which treats the email as not delivered: the invitation link is then offered for copying or sharing on WhatsApp, and a password-reset request still receives the usual answer. On the deployed system email is sent through the Gmail API, and delivery of an invitation email to an outside address was confirmed on 3 November 2026.

5.4 Frontend Implementation

The client is built from function components and hooks. An `AuthContext` holds the signed-in user and keeps the access token in memory; on start-up it attempts a refresh so a page reload keeps the session. A shared Axios instance attaches the token, unwraps the response envelope and, on HTTP 401, performs a single refresh shared by all concurrent requests before retrying them. Pages never call Axios directly; they use typed functions in the `api` folder. A `useAsync` hook and a shared `States` component provide loading, empty and error states for every list, and the Reports page is lazy-loaded to keep the initial bundle small. An error boundary around each page reloads the application once if a newer deployment has replaced the page's code, instead of showing a blank screen.

5.5 User Interface

Figures 5.1 to 5.18 show the main screens of the application running with the demonstration data.




Figure 5.1: Sign-in page




Figure 5.2: Dashboard combining both workspaces




Figure 5.3: Groups list with total spent and personal balance




Figure 5.4: Group expenses of the Murree Trip




Figure 5.5: Group balances, which always net to zero




Figure 5.6: Add Expense form with multi-payer rows and split methods




Figure 5.7: Expense entered in UAE dirhams with the live rupee preview




Figure 5.8: Dubai Trip expenses: rupee amounts with the original AED figures




Figure 5.9: Settle Up after optimisation: 20 naive debts reduced to 4 payments




Figure 5.10: Personal workspace with budget bands and transaction form




Figure 5.11: Savings goals with progress, pace and the monthly amount needed




Figure 5.12: Zakat calculator with pre-filled figures, automatically fetched metal prices and the result




Figure 5.13: Receipt scanning page with recent scans and savings found




Figure 5.14: Human-in-the-loop verification dialog (demonstration data uses a placeholder image)




Figure 5.15: Price book of benchmark prices, maintained by super administrators




Figure 5.16: Live store prices panel on the Admin page after a refresh in which Chase Up failed and kept its previous prices




Figure 5.17: Personal reports: category distribution, inflow vs outflow, budget vs actual




Figure 5.18: Group report: paid vs consumed per member and category split

5.6 Deployment

The system is live at https://smarsplit.onrender.com. It runs as a single Render web service: the build step installs both packages and builds the React client, and Express serves the built files together with the API. Serving both from one origin keeps the SameSite=Strict refresh cookie first-party and means the browser never makes a cross-origin request; any path outside `/api` returns the client, so deep links such as `/groups/:id` load correctly. The database is a MongoDB Atlas cluster, the health check is `/api/v1/health`, and all secrets are supplied as environment variables.

Deployment is automated and gated by tests. Every push to the main branch on GitHub starts a GitHub Actions workflow that runs the full server test suite and builds the client; Render deploys the new version only when that workflow passes (`autoDeployTrigger: checksPass`), so a failing change never reaches users. On the free tier the service pings its own health route every ten minutes to avoid sleeping during use, and on start-up it loads the default price catalogue if the price book is empty and starts a store-price refresh unless a

recent run has finished or is still going. A seed script (`npm run seed`) creates five demonstration users, two groups including the Murree Trip, twelve personal transactions, budgets, three scanned receipts and the price benchmark.

CHAPTER 6
TESTING AND EVALUATION

This chapter describes the testing strategy, summarises the automated test suite, presents selected test cases and the results of security review and defect tracking, and evaluates the settlement engine.

6.1 Testing Strategy

- **Unit testing** — pure functions (split calculator, settlement, price matching, zakat calculation, robots.txt rules and store-listing selection, environment guard) are tested in isolation with Vitest.
- **API (integration) testing** — Supertest sends real HTTP requests to the Express application connected to an in-memory MongoDB instance (mongodb-memory-server), verifying status codes, response envelopes, authorisation and database effects. External services (exchange rates, metal prices, online stores and Gmail) are replaced by scripted responses, so no test depends on the internet.
- **Property-based testing** [18] — the settlement engine is tested on hundreds of randomly generated groups to confirm that its guarantees hold for all inputs, not only hand-picked examples. A fixed random seed makes every failure reproducible.
- **Manual and exploratory testing** — every screen was exercised in the browser with the demonstration data, on a desktop and at a 375-pixel phone width, with shared links opened both signed in and signed out; each of the four emails (password reset, invitation on group creation, invitation from the Members tab and join request) was triggered through the user interface and its link followed to the end.

6.2 Test Suite Summary

The suite contains 323 tests in 24 files. All 323 tests passed on 3 November 2026 (Table 6.1), and the same suite runs automatically before every deployment.

Table 6.1: Automated test results by file

Test file	Area covered	Tests	Passed
auth.test.js	Register, login, refresh rotation, reuse detection, reset	19	19
profile.test.js	Profile update and password change	10	10
env.test.js	Production environment guard	7	7
health.test.js	Health route and 404 envelope	2	2
admin.test.js	Super admins, overview, default catalogue	4	4

Test file	Area covered	Tests	Passed
groups.test.js	Groups, invites, inbox, member roles, trip currency	24	24
membership.test.js	Direct add, invite, request-and-approve flows	26	26
splitCalculator.test.js	Four split methods and rounding rules	22	22
expenses.test.js	Group expense API, filters, balances	16	16
currency.test.js	Foreign-currency conversion and rounding	8	8
fx.test.js	Exchange rates, fallback, foreign expenses	12	12
settlement.test.js	Min-Cash-Flow algorithm and property tests	12	12
settlementApi.test.js	Preview, record (admin), mark paid, consistency	11	11
personal.test.js	Transactions, budgets, recurring engine, summary	16	16
goals.test.js	Savings goals, contributions, progress	11	11
zakat.test.js	Zakat calculation, metal prices, bazaar price override	11	11
categories.test.js	Built-in and custom categories	19	19
receipts.test.js	Scan pipeline, verification, commit	18	18
ocr.test.js	OCR engines and offline receipt parser	7	7
priceMatch.test.js	Normalisation, similarity, size awareness, fresh prices	19	19
prices.test.js	Price book editing, Excel/CSV import, export	9	9
priceSync.test.js	robots.txt rules, store readers, listing selection, look-alike listings, retries, refresh runs	19	19
reports.test.js	Reports, CSV/XLSX/PDF exports, notifications	19	19
mailer.test.js	Email through the Gmail API and its refusal	2	2
Total		**323**	**323**

6.3 Selected Test Cases

Table 6.2: Selected test cases

ID	Test case	Expected result	Result
TC-01	Split Rs 100 equally among three, payer included	Shares 34 / 33 / 33, payer receives 34	Pass
TC-02	Exact split totalling Rs 50 less than the bill	400 with "You're Rs 50 short"	Pass
TC-03	Percentages totalling 90%	400 with "Percentages add up to 90%, not 100%"	Pass
TC-04	Fractional amount (Rs 10.5)	400 validation error, nothing stored	Pass
TC-05	Non-member requests group expenses	403 NOT_A_MEMBER	Pass

ID	Test case	Expected result	Result
TC-06	Plain member attempts to remove a member	403 NOT_ADMIN	Pass
TC-07	Replay of an already-rotated refresh token	401 TOKEN_REUSED and all sessions revoked	Pass
TC-08	Forgot password for unknown vs known email	Byte-identical responses	Pass
TC-09	Settle five-member reference group	Exactly 4 payments, all balances zero	Pass
TC-10	300 random groups of 2–10 members	Balances zero after payments; count ≤ V − 1	Pass
TC-11	Balances that do not net to zero	Algorithm throws, no payments invented	Pass
TC-12	Second settlement while one is unpaid	409 SETTLEMENT_IN_PROGRESS	Pass
TC-13	Commit a receipt still processing	Refused; nothing written	Pass
TC-14	Match "Basmati Rice 5kg" against 1 kg benchmark	No match (sizes differ)	Pass
TC-15	Monthly recurring template overdue by three months	Three entries created, schedule advanced	Pass
TC-16	Excel and PDF exports	Valid ZIP (XLSX) and file starting with %PDF	Pass
TC-17	Notifications collection unavailable	Expense creation still succeeds	Pass
TC-18	AED 240 expense at 1 AED = Rs 80	Stored as Rs 19,200 with the AED figures kept	Pass
TC-19	Three payers of AED 80 each at 1 AED = Rs 75.37	Payers 6,029 / 6,030 / 6,030, summing to the Rs 18,089 total	Pass
TC-20	Rate provider down, rates saved earlier	Saved rates returned and marked stale	Pass
TC-21	Rate provider down, no rates ever saved	503 FX_UNAVAILABLE	Pass
TC-22	Withdraw more than a goal holds	400 GOAL_BELOW_ZERO, goal unchanged	Pass
TC-23	Plain member records a settlement	403 NOT_ADMIN	Pass
TC-24	Email provider refuses the password-reset email	200 with the usual message; failure logged	Pass
TC-25	Group share link opened while already signed in	Group preview with an Ask to join button	Pass
TC-26	Every screen at a 375-pixel phone width	No sideways scrolling; all header icons visible	Pass
TC-27	Create a group with trip currency AED, then with "XYZ"	201 with AED kept; 400 VALIDATION_ERROR	Pass
TC-28	Open Add expense for a new expense in a group whose trip currency is AED	Entry currency starts as AED (checked in the browser)	Pass
TC-29	Zakat on Rs 157,499 with silver at Rs 3,000 per tola	Nisab Rs 157,500; not due; zakat Rs 0	Pass

ID	Test case	Expected result	Result
TC-30	Zakat on exactly Rs 157,500 at the same price	Due; Rs 3,938 (3,937.5 rounded up)	Pass
TC-31	Plain user saves gold and silver prices	403 NOT_SUPER_ADMIN	Pass
TC-32	Metal price provider down after one good fetch	Saved prices returned and marked stale	Pass
TC-33	Store whose robots.txt disallows its search path	Store skipped with the reason recorded; search never called; prices unchanged	Pass
TC-34	Store answering HTTP 503 to every request	Stopped after 3 failed requests; previous prices kept; run completes	Pass
TC-35	Listings for engine oil 3 L, cooking oil without a size, and cooking oil at Rs 99 or Rs 3,200	None accepted for "Cooking Oil 3L"	Pass
TC-36	Three 3-litre cooking oils at Rs 1,645, 1,890 and 1,930, and a 5-litre can	Rs 1,890 listing (middle price) chosen	Pass
TC-37	Sitemap lists a cooking-oil page and a tea page; only oil is in the book	Only the oil page is opened and its price stored	Pass
TC-38	Start-up while a refresh begun ten minutes earlier is still running, and with one left running for two hours	No second run in the first case; in the second the old run is marked failed and a new one starts	Pass
TC-39	Gmail refuses a message (daily quota exceeded)	Sending fails with Google's reason, so the caller can fall back to the link	Pass
TC-40	Sugar 1 kg priced Rs 158 by a store today and Rs 120 in a 30-day-old row	Rs 158 compared; the old row counts again only when no price is recent	Pass
TC-41	Listings "Sugar Cane Cut Pieces 1 kg", "Pk Beef Burger 1Kg", "Meaoon Cat Food Beef & Vegetable 1kg", "Derma Shine Face Wash Tea Tree 200g" and "FF Burger Cheese Slices 200GM"	Rejected for Sugar 1kg, Beef 1kg and Tea 200g; the cheese slices accepted for Cheese Slices 200g	Pass
TC-42	Store fails three requests in a row, then answers normally	Tried once more; its price stored and no error recorded	Pass

6.4 Property-Based Testing of Settlement

The strongest evidence for the settlement engine comes from property-based tests. In each of 300 rounds, a random group of 2 to 10 members and 1 to 6 expenses is generated through the real split calculator; 100 further rounds use multi-payer expenses. For every round the test asserts three properties: (1) applying the returned payments brings every balance to exactly zero; (2) the number of payments is at most V − 1; and (3) every payment amount is a positive integer. All 400 rounds pass.

6.5 Security Testing

All 38 routes that existed at the time of the security review were audited for authentication, validation and ownership checks. Four gaps were found and fixed (Table 6.3). A dependency audit (`npm audit`) reported zero vulnerabilities after a transitive dependency was pinned. The rate limits were later raised (3,000 requests per 15 minutes overall and 60 sign-ins per 15 minutes per address) so that a whole classroom sharing one public IP address can use the system at once; bcrypt at cost 12 still makes password guessing slow. The five endpoints added later for zakat and the price refresh follow the same pattern: all require authentication, saving metal prices and both price-refresh routes also require the super-admin role, and the two request bodies (a zakat calculation and the metal prices) are validated with Zod.

Table 6.3: Security review findings and fixes

Gap	Risk	Fix
No global rate limit	Any authenticated endpoint could be flooded	Global limiter: 600 requests per 15 minutes
Unlimited receipt scans	Each scan calls a paid AI service	Scan limiter: 30 per hour
Permanent public image URLs	A leaked receipt link would work forever	Authenticated uploads; signed URLs valid for 1 hour
Proxy not trusted	All users behind the host proxy shared one rate-limit bucket	trust proxy enabled

6.6 Defects Found and Fixed

Table 6.4: Notable defects found during testing

Defect	Cause and fix
Phantom saving of Rs 1,470 on rice	Normalisation removed pack sizes, so 5 kg matched 1 kg. Fixed by parsing sizes separately and requiring them to agree.
Title-only edit wiped an expense split	Partial validation re-applied default values. Fixed by rebuilding missing split input from the stored splits.
Background price match clashed with user edits	Load-modify-save caused a version conflict. Fixed with an atomic update.
Password account reported as having no password	The password hash was excluded from the query. Fixed with a response transform instead.
Unmatched routes returned 401 instead of 404	Router-level authentication ran before the 404 handler. Fixed by applying authentication per route.
Personal page failed to render with a budget cap	A variable missed during a renaming refactor. Fixed and verified in the browser.
Blank page right after a deployment	Open tabs requested old, renamed code files. Fixed with an error boundary that reloads once when a code file is missing.
Offline OCR could stop the server	Tesseract.js downloaded language data at run time and a failed download crashed the process. Fixed by bundling the data and handling worker errors.

Defect	Cause and fix
Invitation emails silently not delivered	The email provider refused messages until the account was activated, and mail errors were hidden. Fixed by logging every send and warning the admin, with WhatsApp and copy-link as alternatives.
Empty price book on a new database	Benchmark prices were only loaded by the seed script. Fixed by loading the default catalogue on start-up when the collection is empty.
Share link crashed for signed-in users	For one render after start-up the page still held the empty signed-out result. Fixed by waiting for the group preview before drawing the page.
Forgot password failed with a server error	When the email provider refused the reset email, the error reached the user. Fixed by logging the failure and giving the usual answer, which also keeps account existence private.
Pages wider than a phone screen	At 375 pixels the administrator header, the Personal transactions table and the Admin services list pushed the page sideways. Fixed by letting grid columns shrink and fitting the header icons.
Rupee amounts labelled as dirhams	A group's currency was a free-text box that only relabelled rupee amounts, so Rs 31,059 appeared as "AED 31,059", and any three letters were accepted. Fixed by turning it into a trip currency chosen from the supported list that sets the starting currency of new expenses, and labelling every rupee figure "Rs".
Live prices suggesting savings that did not exist	Taking the cheapest matching store listing often picked a different grade, such as broken basmati rice. Fixed by taking the middle-priced listing, within 0.6 to 1.6 times the price book's median.
Look-alike listings priced as book products	Cat food was taken as beef, sugar-cane pieces as sugar and a tea-tree face wash as tea, because each title held the product name and the right pack size. Fixed by rejecting words that turn a listing into another thing and titles that name another book product, and by removing a store's old price when nothing fits any more.

6.7 Evaluation

Table 6.5 evaluates the system against its objectives.

Table 6.5: Evaluation against objectives

Objective	Evidence	Status
Personal workspace with budgets and recurring entries	FR-05 to FR-10 implemented; 16 personal tests pass	Achieved
AI receipt scanning with fallback and verification	FR-11 to FR-14; 18 receipt tests pass	Achieved
Savings suggestions from benchmark prices	FR-15 and FR-34; 100 products, 609 indicative prices; a live refresh updated 191 prices from five stores within robots.txt; 19 matching and 18 price-refresh tests pass	Achieved

Objective	Evidence	Status
Group workspace with four exact split methods	FR-16 to FR-20; 22 calculator and 16 expense tests pass	Achieved
Settlement in at most V − 1 payments	400 property-test rounds; Murree Trip 20 → 4 payments	Achieved
Savings goals, zakat and multi-currency trips	FR-27, FR-28 and FR-31 to FR-33; 42 currency, rate, goal and zakat tests pass; AED 412.50 = Rs 31,059 verified in the browser	Achieved
Reports and exports	FR-24 and FR-25; CSV, XLSX and PDF verified	Achieved
Secure authentication and authorisation	Token rotation, reuse detection, membership checks, audit	Achieved
Automated verification	323 of 323 tests passing	Achieved
Public, test-gated deployment	Live on Render with MongoDB Atlas; GitHub Actions must pass before each deploy	Achieved

CHAPTER 7
CONCLUSION AND FUTURE WORK

7.1 Conclusion

This project delivered SmartSplit & ExpenseAI, a secure web application that brings personal finance management and group expense settlement together in one account for Pakistani users. Receipt photos are converted into verified transactions with the help of a vision language model, verified items are compared with local market prices to suggest savings, and group debts are settled by a Min-Cash-Flow engine that never needs more than $V - 1$ payments. Savings goals help users plan ahead, a zakat calculator estimates what is due from the user's own figures and current metal prices, trips abroad can be recorded in the currency on the bill, the price book is refreshed every morning from five online stores within the limits of their robots.txt, and the system is publicly deployed with every change tested before release.

Three design decisions proved central to the system's reliability: storing money as integer rupees with a single rounding rule, recomputing balances from the underlying expenses instead of storing them, and keeping a human in the loop for every AI-extracted value. Together with server-side authorisation and a comprehensive automated test suite of 323 passing tests, including property-based tests of the settlement guarantees, they give strong confidence that every rupee in the system is accounted for exactly.

7.2 Limitations

- The greedy settlement guarantees at most $V - 1$ payments but is not always the absolute minimum, which is an NP-hard problem.
- Live prices come from only five online stores, and only for products they list under the same name and pack size; the remaining prices in the book are indicative figures. A change to a store's website can stop its prices updating until its reader is adapted, and a store whose robots.txt comes to disallow a path it needs is skipped; in both cases its previous prices are kept. Look-alike listings are recognised from a short list of words and from the names in the book, so a new kind of look-alike needs its word added.
- Overlapping price refreshes are prevented by an in-process lock, with the start-up check also reading recent runs from the database; if the API were ever run on several instances, the scheduled and manual refreshes would need a lock shared through the database.
- The zakat calculator gives an estimate: it uses the international metal price unless a bazaar price has been entered, and scholars differ on how some assets are treated.
- The application records payments but does not transfer money itself.

- OCR accuracy depends on photo quality; poor images require more manual correction.
- A single typo in a short product name can fall below the 0.8 similarity threshold; common misspellings are handled through aliases instead.
- On free hosting tiers the server can still sleep when nobody uses it for a long time, so the first request after a pause is slow and the nightly jobs may run late.
- Exchange rates are refreshed once a day from a free provider, so a converted expense uses that day's market rate rather than the exact rate charged by the user's bank or card.
- Email is sent from a single Gmail account through the Gmail API, which allows about 500 messages a day; a larger deployment would need a dedicated email provider. If a message cannot be sent, invitations can still be shared by link or WhatsApp.

7.3 Future Work

1. Integration with JazzCash, Easypaisa and Raast payment APIs so that a settlement payment can be made directly from the app.
2. A native mobile application reusing the existing REST API.
3. Automatic category suggestions using machine learning on the user's past transactions.
4. Automatic weekly import of official prices from the Pakistan Bureau of Statistics Sensitive Price Indicator (SPI) into the price book.
5. Letting the user enter the exact rate their card or bank charged for a foreign-currency expense.
6. An exact minimum-payment mode for small groups, using subset search, offered alongside the greedy method.

REFERENCES

[1] T. Verhoeff, "Settling multiple debts efficiently: An invitation to computing science," *Informatics in Education*, vol. 3, no. 1, pp. 105–126, 2004.

[2] M. R. Garey and D. S. Johnson, *Computers and Intractability: A Guide to the Theory of NP-Completeness*. New York, NY, USA: W. H. Freeman, 1979.

[3] T. H. Cormen, C. E. Leiserson, R. L. Rivest, and C. Stein, *Introduction to Algorithms*, 4th ed. Cambridge, MA, USA: MIT Press, 2022.

[4] R. Smith, "An overview of the Tesseract OCR engine," in *Proc. 9th Int. Conf. Document Analysis and Recognition (ICDAR)*, 2007, pp. 629–633.

[5] L. R. Dice, "Measures of the amount of ecologic association between species," *Ecology*, vol. 26, no. 3, pp. 297–302, 1945.

[6] M. Jones, J. Bradley, and N. Sakimura, "JSON Web Token (JWT)," IETF RFC 7519, May 2015.

[7] D. Hardt, Ed., "The OAuth 2.0 authorization framework," IETF RFC 6749, Oct. 2012.

[8] N. Provos and D. Mazières, "A future-adaptable password scheme," in *Proc. USENIX Annual Technical Conference, FREENIX Track*, 1999.

[9] OWASP Foundation, "OWASP Top 10:2021." [Online]. Available: https://owasp.org/Top10/

[10] D. Goldberg, "What every computer scientist should know about floating-point arithmetic," *ACM Computing Surveys*, vol. 23, no. 1, pp. 5–48, 1991.

[11] R. T. Fielding, "Architectural styles and the design of network-based software architectures," Ph.D. dissertation, Univ. of California, Irvine, 2000.

[12] MongoDB, Inc., "Aggregation operations," MongoDB Manual. [Online]. Available: https://www.mongodb.com/docs/manual/aggregation/

[13] Meta Platforms, Inc., "React documentation." [Online]. Available: https://react.dev/

[14] Anthropic, "Claude API documentation: vision and structured outputs." [Online]. Available: https://docs.anthropic.com/

[15] Splitwise, Inc., "Splitwise." [Online]. Available: https://www.splitwise.com/

[16] Tricount, "Tricount." [Online]. Available: https://www.tricount.com/

[17] BudgetBakers, "Wallet." [Online]. Available: https://budgetbakers.com/

[18] K. Claessen and J. Hughes, "QuickCheck: A lightweight tool for random testing of Haskell programs," in *Proc. 5th ACM SIGPLAN Int. Conf. Functional Programming (ICFP)*, 2000, pp. 268–279.

[19] State Bank of Pakistan, "Raast: Pakistan's instant payment system." [Online]. Available: https://www.sbp.org.pk/

[20] I. Sommerville, *Software Engineering*, 10th ed. Harlow, U.K.: Pearson, 2016.

[21] Mongoose, "Mongoose ODM documentation." [Online]. Available: https://mongoosejs.com/docs/

[22] ExchangeRate-API, "Free exchange rate API (open access)." [Online]. Available: https://www.exchangerate-api.com/docs/free

[23] M. Koster, G. Illyes, H. Zeller, and L. Sassman, "Robots Exclusion Protocol," IETF RFC 9309, Sep. 2022.

[24] Schema.org, "Product," schema.org vocabulary. [Online]. Available: https://schema.org/Product

[25] Gold API, "Free real-time gold and silver price API." [Online]. Available: https://gold-api.com/

[26] Google, "Gmail API: Sending email," Google for Developers. [Online]. Available: https://developers.google.com/gmail/api/guides/sending

APPENDIX A: API ENDPOINT REFERENCE

All endpoints are prefixed with `/api/v1`. Every endpoint except registration, sign-in, token refresh, Google sign-in, password reset and the health check requires a valid access token; group endpoints additionally require active membership, and admin endpoints the admin role.

Table A.1: REST API endpoints

Resource	Method	Path	Purpose
Auth	POST	`/auth/register`	Create an account
Auth	POST	`/auth/login`	Sign in with email and password
Auth	POST	`/auth/refresh`	Rotate refresh token, issue access token
Auth	POST	`/auth/logout`	Revoke the current session
Auth	GET	`/auth/me`	Current user
Auth	PATCH	`/auth/me`	Update profile
Auth	POST	`/auth/change-password`	Change password
Auth	POST	`/auth/google`	Google sign-in
Auth	POST	`/auth/forgot-password`	Email a reset link
Auth	POST	`/auth/reset-password/:token`	Set a new password
Users	GET	`/users/search`	Find users to add to a group
Groups	POST	`/groups`	Create a group
Groups	GET	`/groups`	List my groups with totals

Resource	Method	Path	Purpose
Groups	GET	`/groups/invites`	My invitations and join requests
Groups	POST	`/groups/:id/invites/accept`	Accept an invitation
Groups	DELETE	`/groups/:id/invites`	Decline an invitation or withdraw a request
Groups	PATCH	`/groups/:id/members/:memberId`	Promote or demote a member (admin)
Groups	GET	`/groups/:id`	Group details (member)
Groups	PATCH	`/groups/:id`	Update group (admin)
Groups	POST	`/groups/:id/members`	Add or invite a member (admin)
Groups	DELETE	`/groups/:id/members/:userId`	Remove a member (admin)
Groups	PATCH	`/groups/:id/members/:memberId/approve`	Approve a join request (admin)
Groups	POST	`/groups/:id/members/:memberId/resend`	Resend an invite (admin)
Groups	POST	`/groups/:id/join-code/rotate`	Rotate the share code (admin)
Groups	GET	`/join/:inviteToken`	Preview an invite link
Groups	POST	`/join/:inviteToken`	Accept an invite link
Groups	GET	`/join-request/:joinCode`	Preview a group by share code
Groups	POST	`/join-request/:joinCode`	Request to join

Resource	Method	Path	Purpose
Expenses	POST	`/groups/:id/expenses`	Add a group expense
Expenses	GET	`/groups/:id/expenses`	List expenses (filters, pages)
Expenses	GET	`/groups/:id/balances`	Net balances by aggregation
Expenses	GET	`/expenses/:expenseId`	One expense
Expenses	PATCH	`/expenses/:expenseId`	Edit an expense
Expenses	DELETE	`/expenses/:expenseId`	Soft-delete an expense
Settlements	POST	`/groups/:id/settle/preview`	Compute payments (no write)
Settlements	POST	`/groups/:id/settle`	Record a settlement (admin)
Settlements	GET	`/groups/:id/settlements`	Payments and audit trail
Settlements	PATCH	`/settlements/:settlementId/pay`	Mark a payment paid
Personal	POST	`/transactions`	Add a transaction
Personal	GET	`/transactions`	List transactions (filters)
Personal	PATCH	`/transactions/:transactionId`	Edit a transaction
Personal	DELETE	`/transactions/:transactionId`	Delete a transaction
Personal	GET	`/personal/summary`	Monthly summary
Personal	GET	`/budgets`	List budgets
Personal	PUT	`/budgets`	Create or update a budget

Resource	Method	Path	Purpose
Personal	DELETE	`/budgets/:budgetId`	Delete a budget
Goals	GET	`/goals`	List my goals with progress
Goals	POST	`/goals`	Create a goal
Goals	PATCH	`/goals/:goalId`	Edit a goal
Goals	DELETE	`/goals/:goalId`	Delete a goal
Goals	POST	`/goals/:goalId/contributions`	Deposit or withdraw
Goals	DELETE	`/goals/:goalId/contributions/:contributionId`	Remove a contribution
Categories	GET	`/categories`	Built-in and custom categories
Categories	POST	`/categories`	Add a custom category
Categories	GET	`/categories/:categoryId/usage`	Usage before deletion
Categories	DELETE	`/categories/:categoryId`	Delete a custom category
Receipts	POST	`/receipts/scan`	Upload a receipt (202)
Receipts	GET	`/receipts`	List receipts
Receipts	GET	`/receipts/:receiptId`	Receipt with OCR result
Receipts	POST	`/receipts/:receiptId/items`	Add a line
Receipts	PATCH	`/receipts/:receiptId/items/:index`	Edit a line
Receipts	DELETE	`/receipts/:receiptId/items/:index`	Remove a line
Receipts	POST	`/receipts/:receiptId/commit`	Save to personal or group draft
Reports	GET	`/reports/personal/monthly`	Monthly personal report

Resource	Method	Path	Purpose
Reports	GET	`/reports/personal/trends`	Six-month trends
Reports	GET	`/reports/groups/:id/summary`	Group summary report
Reports	GET	`/reports/export`	CSV, XLSX or PDF export
Notifications	GET	`/notifications`	Notification feed
Notifications	PATCH	`/notifications/:notificationId/read`	Mark one read
Notifications	PATCH	`/notifications/read-all`	Mark all read
Exchange rates	GET	`/fx/rates`	Rupee rates for supported currencies
Price book	GET	`/prices`	Benchmark prices by product and store
Price book	GET	`/prices/export`	Download as Excel
Price book	POST	`/prices`	Add or update a price (super admin)
Price book	DELETE	`/prices/:priceId`	Delete a price (super admin)
Price book	POST	`/prices/import`	Import Excel or CSV (super admin)
Price book	POST	`/prices/seed`	Load the default catalogue (super admin)
Zakat	GET	`/zakat`	Pre-filled figures and gold and silver prices

Resource	Method	Path	Purpose
Zakat	POST	`/zakat/calculate`	Work out the zakat due
Zakat	PUT	`/zakat/rates`	Save bazaar gold and silver prices (super admin)
Admin	GET	`/admin/overview`	Totals and newest users and groups (super admin)
Admin	GET	`/admin/price-sync`	Stores and the last ten price refreshes (super admin)
Admin	POST	`/admin/price-sync`	Start a store-price refresh (super admin, 202)
System	GET	`/health`	Health and database status

APPENDIX B: USER MANUAL

This appendix explains how to perform the main tasks in the application.

Table B.1: Step-by-step guide to the main tasks

Task	Steps
Create an account	Open the website and select "Create an account", or use "Sign in with Google". Enter name, email and a password of at least 8 characters.
Record a transaction	Open Personal. In the form, choose Spent or Received, enter title, amount, date, category and payment method, optionally tick "Repeats" for a weekly or monthly bill, and select "Add transaction".
Set a budget	On the Personal page, open the budgets editor, choose a category and enter a monthly cap. Bars turn amber at 80% and red at 100%.
Scan a receipt	Open Scan and drop a photo or select "Choose image". When reading finishes, check every line in the dialog, correct anything wrong, then select "Save to Personal" or "Use in group expense".
Create a group	Open Groups and select "New group". Enter a name, type, trip currency and start date, and add members by email.
Join a group	Open an invite link received by email or WhatsApp, accept an invitation from the inbox on the Groups page, or enter a share code and wait for an admin to approve the request.
Add a shared expense	In a group, select "Add expense". Enter title and amount, choose who paid (add more payers if needed), choose a split method and fill in the shares. Save becomes available when everything adds up.
Add an expense abroad	In Add expense, the currency next to the amount starts as the group's trip currency; change it if the bill is in another currency (for example AED) and type the amount from the bill. The form shows the rupee amount and the rate; the expense is saved in rupees.
Settle up	In a group, open Balances and select "Settle up", then "Simplify with Min-Cash-Flow". Review the payments; a group admin then selects "Record settlement". After paying through JazzCash, Easypaisa, Raast, bank or cash, select "Mark paid".
Save for a goal	Open Goals and select "New goal". Enter what you are saving for, the target amount and the date. Use Add or Withdraw on the goal card whenever you put money aside or take some out.
Calculate zakat	Open Goals and select "Zakat calculator". Check the figures filled in from your goals and group balances, add cash, bank balances, gold, silver and other assets and any debts due now, choose the silver or gold nisab, and select "Calculate zakat". If zakat is due, "Record as paid" adds it to Personal after you confirm.
Refresh store prices (admin)	Open Admin. The "Live store prices" panel lists the stores and the result of the last refresh for each one. Select "Update now" to refresh at once; the refresh takes a few minutes and continues in the background.
Reports and exports	Open Reports, choose the Personal or Group tab and the month, and use the CSV, Excel or PDF buttons to download.

APPENDIX C: INSTALLATION GUIDE

The following commands install and run the system locally. Node.js 20 or later and a MongoDB instance (local or Atlas) are required.

```
git clone <repository-url> smartsplit && cd smartsplit
npm run install:all
cp server/.env.example server/.env      # set MONGO_URI, JWT secrets, API keys
cp client/.env.example client/.env      # set VITE_API_URL
npm run seed                            # optional: demo data (erases the
database)
npm run dev                             # API on :5000, client on :5173
npm test                                # run the 323 automated tests
npm --prefix server run prices:sync     # optional: refresh store prices now
npm --prefix server run gmail:token     # optional: one-time Gmail API token
```

Required environment variables on the server are `MONGO_URI`, `JWT_ACCESS_SECRET`, `JWT_REFRESH_SECRET` and `CLIENT_URL`. Optional variables enable Google sign-in (`GOOGLE_CLIENT_ID`), the vision model (`ANTHROPIC_API_KEY`), Cloudinary (`CLOUDINARY_`*) and email (`GMAIL_CLIENT_ID`, `GMAIL_CLIENT_SECRET` and `GMAIL_REFRESH_TOKEN` for the Gmail API, or `SMTP_`*); without them the system falls back to Tesseract.js, inline images and console-printed email links, so its core features run without these services. `gmail:token` needs `GMAIL_CLIENT_ID` and `GMAIL_CLIENT_SECRET` set and prints the refresh token; `prices:sync` reads the online stores, so it needs an internet connection.