

-
- Review
 - Pointers and Memory Addresses
 - Physical and Virtual Memory
 - Addressing and Indirection
 - Functions with Multiple Outputs
 - Arrays and Pointer Arithmetic
 - Strings
 - String Utility Functions
 - Searching and Sorting Algorithms
 - Linear Search
 - A Simple Sort
 - Faster Sorting
 - Binary Search

Review: Unconditional jumps

- **goto** keyword: jump somewhere else in the same function
- Position identified using labels
- Example (**for** loop) using **goto**:

```
{  
    int i = 0, n = 20; /* initialization */  
    goto loop_cond;  
loop_body:  
    /* body of loop here */  
    i++;  
loop_cond:  
    if (i < n) /* loop condition */  
        goto loop_body;  
}
```

- Excessive use of **goto** results in “spaghetti” code

Review: I/O Functions

- I/O provided by `stdio.h`, not language itself
- Character I/O: `putchar()`, `getchar()`, `getc()`, `putc()`, etc.
- String I/O: `puts()`, `gets()`, `fgets()`, `fputs()`, etc.
- Formatted I/O: `fprintf()`, `fscanf()`, etc.
- Open and close files: `fopen()`, `fclose()`
- File read/write position: `feof()`, `fseek()`, `ftell()`, etc.
- ...

Review: `printf()` and `scanf()`

- Formatted output:

`int` `printf` (`char` `format[]`, `arg1`, `arg2`, ...)

- Takes variable number of arguments
- Format specification:

`%[flags][width][.precision][length]<type>`

- types: `d`, `i` (int), `u`, `o`, `x`, `X` (unsigned int), `e`, `E`, `f`, `F`, `g`, `G` (double), `c` (char), `s` (string)
 - flags, width, precision, length - modify meaning and number of characters printed
- Formatted input: `scanf()` - similar form, takes pointers to arguments (except strings), ignores whitespace in input

Review: Strings and character arrays

- Strings represented in C as an array of characters (`char []`)
- String must be null-terminated (`'\0'` at end)
- Declaration:
`char str[] = "I am a string.";` or
`char str[20] = "I am a string.";`
- `strcpy()` - function for copying one string to another
- More about strings and string functions today...

-
- Review
 - **Pointers and Memory Addresses**
 - Physical and Virtual Memory
 - Addressing and Indirection
 - Functions with Multiple Outputs
 - Arrays and Pointer Arithmetic
 - Strings
 - String Utility Functions
 - Searching and Sorting Algorithms
 - Linear Search
 - A Simple Sort
 - Faster Sorting
 - Binary Search

Pointers and addresses

- Pointer: memory address of a variable
- Address can be used to access/modify a variable from anywhere
- Extremely useful, especially for data structures
- Well known for obfuscating code

Physical and virtual memory

- Physical memory: physical resources where data can be stored and accessed by your computer
 - cache
 - RAM
 - hard disk
 - removable storage
- Virtual memory: abstraction by OS, addressable space accessible by your code

Physical memory considerations

- Different sizes and access speeds
- Memory management – major function of OS
- Optimization – to ensure your code makes the best use of physical memory available
- OS moves around data in physical memory during execution
- Embedded processors – may be very limited

Virtual memory

- How much physical memory do I have?
Answer: 2 MB (cache) + 2 GB (RAM) + 100 GB (hard drive) + ...
- How much virtual memory do I have?
Answer: <4 GB (32-bit OS), typically 2 GB for Windows, 3-4 GB for linux
- Virtual memory maps to different parts of physical memory
- Usable parts of virtual memory: *stack* and *heap*
 - stack: where declared variables go
 - heap: where dynamic memory goes

Addressing variables

- Every variable residing in memory has an address!
- What doesn't have an address?
 - register variables
 - constants/literals/preprocessor defines
 - expressions (unless result is a variable)
- How to find an address of a variable? The `&` operator

```
int n = 4;  
double pi = 3.14159;  
int *pn = &n; /* address of integer n */  
double *ppi = &pi; /* address of double pi */
```

- Address of a variable of type t has type t^*

Dereferencing pointers

- I have a pointer – now what?
- Accessing/modifying addressed variable:
dereferencing/indirection operator *

```
/* prints "pi = 3.14159\n" */  
printf("pi = %g\n",*ppi);
```

```
/* pi now equals 7.14159 */  
*ppi = *ppi + *pn;
```

- Dereferenced pointer like any other variable
- null pointer, *i.e.* 0 (NULL): pointer that does not reference anything

Casting pointers

- Can explicitly cast any pointer type to any other pointer type

```
ppi = (double *)pn; /* pn originally of type (int *) */
```

- Implicit cast to/from `void *` also possible (more next week...)
- Dereferenced pointer has new type, regardless of real type of data
- Possible to cause segmentation faults, other difficult-to-identify errors
 - What happens if we dereference `ppi` now?

Functions with multiple outputs

- Consider the Extended Euclidean algorithm
`ext_euclid(a, b)` function from Wednesday's lecture
 - Returns $\gcd(a, b)$, x and y s.t. $ax + by = \gcd(a, b)$
 - Used global variables for x and y
 - Can use pointers to pass back multiple outputs:
- ```
int ext_euclid(int a, int b, int *x, int *y);
```
- Calling `ext_euclid()`, pass pointers to variables to receive  $x$  and  $y$ :

```
int x, y, g;
/* assume a, b declared previously */
g = ext_euclid(a, b, &x, &y);
```

- Warning about  $x$  and  $y$  being used before initialized

# Accessing caller's variables

---

- Want to write function to swap two integers
- Need to modify variables in caller to swap them
- Pointers to variables as arguments

```
void swap(int *x, int *y) {
 int temp = *x;
 *x = *y;
 *y = temp;
}
```

- Calling `swap()` function:

```
int a = 5, b = 7;
swap(&a, &b);
/* now, a = 7, b = 5 */
```

# Variables passing out of scope

---

- What is wrong with this code?

```
#include <stdio.h>
```

```
char * get_message() {
 char msg[] = "Aren't pointers fun?";
 return msg;
}
```

```
int main(void) {
 char * string = get_message();
 puts(string);
 return 0;
}
```



# Variables passing out of scope

---

- What is wrong with this code?

```
#include <stdio.h>
```

```
char * get_message() {
 char msg[] = "Aren't pointers fun?";
 return msg;
}
```

```
int main(void) {
 char * string = get_message();
 puts(string);
 return 0;
}
```

- Pointer invalid after variable passes out of scope

- 
- Review
  - Pointers and Memory Addresses
    - Physical and Virtual Memory
    - Addressing and Indirection
    - Functions with Multiple Outputs
  - **Arrays and Pointer Arithmetic**
  - Strings
    - String Utility Functions
  - Searching and Sorting Algorithms
    - Linear Search
    - A Simple Sort
    - Faster Sorting
    - Binary Search

# Arrays and pointers

---

- Primitive arrays implemented in C using pointer to block of contiguous memory
- Consider array of 8 ints:  
`int arr[8];`
- Accessing `arr` using array entry operator:  
`int a = arr[0];`
- `arr` is like a pointer to element 0 of the array:  
`int *pa = arr; ⇔ int *pa = &arr[0];`
- Not modifiable/reassignable like a pointer

# The `sizeof()` operator

---

- For primitive types/variables, size of type in bytes:

```
int s = sizeof(char); /* == 1 */
```

```
double f; /* sizeof(f) == 8 */ (64-bit OS)
```

- For primitive arrays, size of array in bytes:

```
int arr[8]; /* sizeof(arr) == 32 */ (64-bit OS)
```

```
long arr[5]; /* sizeof(arr) == 40 */ (64-bit OS)
```

- Array length:

```
/* needs to be on one line when implemented */
#define array_length(arr) (sizeof(arr) == 0 ?
 0 : sizeof(arr)/sizeof((arr)[0]))
```

- More about `sizeof()` next week...

# Pointer arithmetic

---

- Suppose `int *pa = arr;`
- Pointer not an `int`, but can add or subtract an `int` from a pointer:  
`pa + i` points to `arr[i]`
- Address value increments by  $i$  times size of data type  
Suppose `arr[0]` has address 100. Then `arr[3]` has address 112.
- Suppose `char *pc = (char *)pa;` What value of  $i$  satisfies `(int *)(pc+i) == pa + 3`?

# Pointer arithmetic

---

- Suppose `int *pa = arr;`
- Pointer not an `int`, but can add or subtract an `int` from a pointer:  
`pa + i` points to `arr[i]`
- Address value increments by  $i$  times size of data type  
Suppose `arr[0]` has address 100. Then `arr[3]` has address 112.
- Suppose `char *pc = (char *)pa;` What value of  $i$  satisfies `(int *)(pc+i) == pa + 3`?
  - $i = 12$

- 
- Review
  - Pointers and Memory Addresses
    - Physical and Virtual Memory
    - Addressing and Indirection
    - Functions with Multiple Outputs
  - Arrays and Pointer Arithmetic
  - **Strings**
    - **String Utility Functions**
  - Searching and Sorting Algorithms
    - Linear Search
    - A Simple Sort
    - Faster Sorting
    - Binary Search

# Strings as arrays

---

- Strings stored as null-terminated character arrays (last character == `'\0'`)
- Suppose `char str[] = "This is a string.";` and  
`char * pc = str;`
- Manipulate string as you would an array  
`*(pc+10) = 'S';`  
`puts(str); /* prints "This is a String." */`



# String utility functions

---

- String functions in standard header `string.h`
- Copy functions: `strcpy()`, `strncpy()`  
`char * strcpy( strto , strfrom );` – copy *strfrom* to *strto*  
`char * strncpy( strto , strfrom, n );` – copy *n* chars from *strfrom* to *strto*
- Comparison functions: `strcmp()`, `strncmp()`  
`int strcmp(str1, str2);` – compare *str1*, *str2*; return 0 if equal, positive if *str1* > *str2*, negative if *str1* < *str2*  
`int strncmp(str1, str2, n);` – compare first *n* chars of *str1* and *str2*
- String length: `strlen()`  
`int strlen( str );` – get length of *str*

## More string utility functions

---

- Concatenation functions: `strcat()`, `strncat()`  
`char * strcat ( strto , strfrom );` – add *strfrom* to end of *strto*  
`char * strncat ( strto , strfrom , n );` – add *n* chars from *strfrom* to end of *strto*
- Search functions: `strchr()`, `strrchr()`  
`char * strchr ( str , c );` – find char *c* in *str*, return pointer to first occurrence, or NULL if not found  
`char * strrchr ( str , c );` – find char *c* in *str*, return pointer to last occurrence, or NULL if not found
- Many other utility functions exist. . .

- 
- Review
  - Pointers and Memory Addresses
    - Physical and Virtual Memory
    - Addressing and Indirection
    - Functions with Multiple Outputs
  - Arrays and Pointer Arithmetic
  - Strings
    - String Utility Functions
  - Searching and Sorting Algorithms
    - Linear Search
    - A Simple Sort
    - Faster Sorting
    - Binary Search

# Searching and sorting

---

- Basic algorithms
- Can make good use of pointers
- Just a few examples; not a course in algorithms
- Big-O notation

# Searching an array

---

- Suppose we have an array of `int`'s

```
int arr[100]; /* array to search */
```

- Let's write a simple search function:

```
int * linear_search(int val) {
 int * parr, * parrend = arr + array_length(arr);
 for (parr = arr; parr < parrend; parr++) {
 if (*parr == val)
 return parr;
 }
 return NULL;
}
```

# A simple sort

---

- A simple insertion sort:  $O(n^2)$ 
  - iterate through array until an out-of-order element found
  - insert out-of-order element into correct location
  - repeat until end of array reached
- Split into two functions for ease-of-use

```
int arr[100]; /* array to sort */

void shift_element(unsigned int i) {
 /* do insertion of out-of-order element */
}

void insertion_sort() {
 /* main insertion sort loop */
 /* call shift_element() for
 each out-of-order element */
}
```

# Shifting out-of-order elements

---

- Code for shifting the element

```
/* move previous elements down until
 insertion point reached */
void shift_element(unsigned int i) {
 int ival;
 /* guard against going outside array */
 for (ival = arr[i]; i && arr[i-1] > ival; i--)
 arr[i] = arr[i-1]; /* move element down */
 arr[i] = ival; /* insert element */
}
```

# Insertion sort

---

- Main insertion sort loop

```
/* iterate until out-of-order element found;
 shift the element, and continue iterating */
void insertion_sort(void) {
 unsigned int i, len = array_length(arr);
 for (i = 1; i < len; i++)
 if (arr[i] < arr[i-1])
 shift_element(i);
}
```

- Can you rewrite using pointer arithmetic instead of indexing?



# Quicksort

---

- Many faster sorts available (shellsort, mergesort, quicksort, ...)
- Quicksort:  $O(n \log n)$  average;  $O(n^2)$  worst case
  - choose a pivot element
  - move all elements less than pivot to one side, all elements greater than pivot to other
  - sort sides individually (recursive algorithm)
- Implemented in C standard library as `qsort()` in `stdlib.h`

# Quicksort implementation

---

- Select the pivot; separate the sides:

```
void quick_sort(unsigned int left ,
 unsigned int right) {
 unsigned int i , mid;
 int pivot;
 if (left >= right)
 return; /* nothing to sort */
 /* pivot is midpoint; move to left side */
 swap(arr+left , arr + (left+right)/2);
 pivot = arr[mid = left];
 /* separate into side < pivot (left+1 to mid)
 and side >= pivot (mid+1 to right) */
 for (i = left+1; i <= right; i++)
 if (arr[i] < pivot)
 swap(arr + ++mid , arr + i);
```

[Kernighan and Ritchie. The C Programming Language. 2nd ed. Prentice Hall, 1988.]

© Prentice Hall. All rights reserved. This content is excluded from our Creative Commons license.  
For more information, see <http://ocw.mit.edu/fairuse>.

# Quicksort implementation

---

- Restore the pivot; sort the sides separately:

```
/* restore pivot position */
swap(arr+left , arr+mid);
/* sort two sides */
if (mid > left)
 quick_sort(left , mid-1);
if (mid < right)
 quick_sort(mid+1, right);
}
```

- Starting the recursion:

```
quick_sort(0, array_length(arr) - 1);
```

[Kernighan and Ritchie. The C Programming Language. 2nd ed. Prentice Hall, 1988.]

# Discussion of quicksort

---

- Not *stable* (equal-valued elements can get switched) in present form
- Can sort *in-place* – especially desirable for low-memory environments
- Choice of pivot influences performance; can use random pivot
- Divide and conquer algorithm; easily parallelizeable
- Recursive; in worst case, can cause stack overflow on large array

# Searching a sorted array

---

- Searching an arbitrary list requires visiting half the elements on average
- Suppose list is sorted; can make use of sorting information:
  - if desired value greater than value and current index, only need to search after index
  - each comparison can split list into two pieces
  - solution: compare against middle of current piece; then new piece guaranteed to be half the size
  - divide and conquer!
- More searching next week. . .

# Binary search

---

- Binary search:  $O(\log n)$  average, worst case:

```
int * binary_search(int val) {
 unsigned int L = 0, R = array_length(arr), M;
 while (L < R) {
 M = (L+R-1)/2;
 if (val == arr[M])
 return arr+M; /* found */
 else if (val < arr[M])
 R = M; /* in first half */
 else
 L = M+1; /* in second half */
 }
 return NULL; /* not found */
}
```

# Binary search

---

- Worst case: logarithmic time
- Requires random access to array memory
  - on sequential data, like hard drive, can be slow
  - seeking back and forth in sequential memory is wasteful
  - better off doing linear search in some cases
- Implemented in C standard library as `bsearch()` in `stdlib.h`

# Summary

---

Topics covered:

- Pointers: addresses to memory
  - physical and virtual memory
  - arrays and strings
  - pointer arithmetic
- Algorithms
  - searching: linear, binary
  - sorting: insertion, quick